

SAFETY DATA SHEET

Product and Company Identification

SERVPRO Product Number and Name: 490 Stainless Steel Cleaner

Manufacturer Product Identifier: 490 Stainless Steel 222000005-20AR

Distributor Company Name: Servpro Professional Cleaning Products, LLC.
801 Industrial Blvd.
Gallatin, TN 37066

Safety Data Sheet
490 Stainless Steel

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: 490 Stainless Steel
PRODUCT CODE: 222000005-20AR
RECOMMENDED USE: Stainless Steel Polish
RESTRICTIONS ON USE: None Known
COMPANY NAME: Servpro Industries
COMPANY ADDRESS: 801 Industrial Drive, Gallatin, TN 37066
COMPANY PHONE: 615-451-0200
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 2
Liquefied Gas
Eye Irritant: Category 2B
Aspiration Hazard

HAZARD STATEMENT(S): **DANGER:** Flammable Aerosol Contains gas under pressure; May explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 6%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Distillates (petroleum), hydrotreated light	64742-47-8	10-30%
Propane/n-Butane	68476-86-8	10-30%

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eye: stinging, tearing, redness

Oral: Aspiration risk

CHRONIC HEALTH HAZARDS: None known

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Safety Data Sheet
490 Stainless Steel

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Stop leak if you can do so without risk. Move the cylinder/can to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent spill from entering sewers, storm drains, and natural waterways. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Strong oxidizers, Alkalies, Acids

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Distillates (petroleum), hydrotreated light	400 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation adequate.

RESPIRATORY PROTECTION: Not required with normal use.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White Foam

ODOR: Lemon scent

ODOR THRESHOLD: N/D

pH: 6 - 7

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: > 200°F (93°C)

EVAPORATION RATE: Slow

FLAMMABILITY(solid/gas): Flammable Aerosol

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H2O=1): 0.93 - 0.97

Safety Data Sheet
490 Stainless Steel

SOLUBILITY(IES): 77%
PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None Known
CHEMICAL STABILITY: Stable
POSSIBLE HAZARDOUS REACTIONS: None Known
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.
INCOMPATIBLE MATERIALS: Strong oxidizers, Alkalies, Acids
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Isoparaffinic Hydrocarbon (64742-47-8) LD₅₀ (Oral, Rat) >5000 mg/kg; LD₅₀ (Dermal, Rabbit) >2000 mg/kg
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: May cause irritation.
INGESTION: May cause gastric discomfort and nausea. No hazard by this route in normal use.
INHALATION: No hazards under normal use due to its low volatility. If vapor is present in high concentrations, irritation to upper respiratory tract may occur.
SKIN: May cause irritation, localized defatting, dermatitis, with prolonged or repeated contact.
MEDICAL CONDITION AGGRAVATED: None known
ACUTE HEALTH HAZARDS: Eye: stinging, tearing, redness
Oral: Aspiration risk
CHRONIC HEALTH HAZARDS: None known
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Isoparaffinic Hydrocarbon (64742-47-8) Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms.
PERSISTENCE AND DEGRADABILITY: This product is biodegradable.
BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.
MOBILITY IN SOIL: This product is mobile in soil.
OTHER ADVERSE EFFECTS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.
RCRA STATUS: Product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: None

SHIPPING BY WATER:

Safety Data Sheet
490 Stainless Steel

VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: None
ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None
SARA 311/312 HAZARD CATEGORIES: None
SARA 313 REPORTABLE INGREDIENTS: None
STATE REGULATIONS: California Proposition 65: None
INTERNATIONAL REGULATIONS: Isoparaffinic Hydrocarbon (64742-47-8)
VOLATILE ORGANIC COMPOUNDS (VOC): 15%

NFPA HEALTH:	1	HMIS HEALTH:	1
NFPA FLAMMABILITY:	1	HMIS FLAMMABILITY:	1
NFPA REACTIVITY:	0	HMIS REACTIVITY:	0
NFPA OTHER:	None	HMIS PROTECTION:	A

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Andrew Bach
DATE PREPARED: 12/17/2013
REVISION DATE: 02/04/2021

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.