



Issue date 09-Nov-2016

Safety Data Sheet

Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON ACRYLIC MATTE FINISH
Chemical name 6-5911-3

Other means of identification

Product code FG 499-0531-1
Synonyms Spray Paint

Recommended use of the chemical and restrictions on use

Recommended Use Interior/exterior enamel.
Uses advised against Do not use on surfaces that come in contact with food.

Details of the supplier of the safety data sheet

| Supplier Address | Manufacturer Address |
|-------------------------|-----------------------------|
| Chase Products Co. | Chase Products Co. |
| 2727 Gardner Road | 2727 Gardner Road |
| Broadview, IL 60155 | Broadview, IL 60155 |
| 708-273-1121 | 708-273-1121 |

Emergency Telephone Number

| | |
|---------------------------------------|------------------------|
| Company Phone Number | 708-865-1000 |
| 24 Hour Emergency Phone Number | 1-800-255-3924 |
| Emergency telephone | ChemTel 1-800-255-3924 |

2. Hazards Identification

Classification

| | |
|--|---------------|
| Acute toxicity - Inhalation (Gases) | Category 3 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 1B |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| FLAMMABLE AEROSOLS | Category 1 |
| Gases Under Pressure | liquefied gas |

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

Toxic if inhaled
CAUSES SKIN IRRITATION
Causes serious eye irritation
Suspected of causing cancer
May damage fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
EXTREMELY FLAMMABLE AEROSOL

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

Contains gas under pressure; may explode if heated



Appearance Clear, viscous liquid.

Physical State Aerosol

Odor Characteristic odor of paint.

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves, protective clothing, eye protection and face protection.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe fumes, mist, vapors or spray.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment: See additional cautionary statements on this label.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Protect from sunlight

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

• Toxic to aquatic life with long lasting effects

• Toxic to aquatic life

10.948% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/information on Ingredients

Synonyms

Spray Paint.

Chemical Family

MIXTURES.

Formula

6-5911-3

| Chemical name | CAS No | weight-% | Trade secret |
|-----------------|----------|----------|--------------|
| Acetone | 67-64-1 | 30-40 | * |
| Propane | 74-98-6 | 15-20 | * |
| N-Butane | 106-97-8 | 10-15 | * |
| n-Butyl acetate | 123-86-4 | 5-10 | * |

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

| | | | |
|-------------------------------------|------------|------|---|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 5-10 | * |
| Toluene | 108-88-3 | 5-10 | * |
| Magnesium Silicate | 14807-96-6 | 1-5 | * |
| Ethylbenzene | 100-41-4 | 1-5 | * |
| Naphtha (petroleum), heavy aromatic | 64742-94-5 | 1-5 | * |
| Butyl benzyl phthalate | 85-68-7 | <1 | * |

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact

Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise.

Inhalation

If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

Ingestion

Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms

Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO₂ or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure. This product is extremely flammable. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

For emergency responders

Remove all sources of ignition.

Environmental precautions

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Methods for cleaning up

Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling

Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B)**.

Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines

See occupational exposure limits listed below.

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--------------------|--|---|--|
| Acetone 67-64-1 | STEL: 500 ppm TWA: 250 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| Propane 74-98-6 | : See Appendix F: Minimal Oxygen Content | TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ | IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ |

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

| | | | |
|---|--|--|--|
| N-Butane 106-97-8 | STEL: 1000 ppm | (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | TWA: 800 ppm TWA: 1900 mg/m ³ |
| n-Butyl acetate 123-86-4 | STEL: 200 ppm TWA: 150 ppm | TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³ | IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³ |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³ | - |
| Toluene 108-88-3 | TWA: 20 ppm | TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| Magnesium Silicate 14807-96-6 | TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction | (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit | IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust |
| Ethylbenzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³ | IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³ |

Appropriate engineering controls

Engineering controls Use with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Chemical resistant gloves required.

Respiratory protection Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

General hygiene considerations Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

| | | | |
|------------------------------|------------------------|--------------------------|-------------------------------|
| Physical State | Aerosol | Odor | Characteristic odor of paint. |
| Appearance | Clear, viscous liquid. | Odor threshold | No information available |
| Color | Colorless | | |
| Property | Values | Remarks • Method | |
| pH | Not applicable | Solvent-based product. | |
| Melting point/freezing point | Not applicable | No information available | |

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

| | | |
|-------------------------------------|---|--------------------------|
| Boiling point/boiling range | Acetone 133 F/56.29 C | No information available |
| Flash Point | Not available. This is an aerosol product with a Flame Projection of 18 in. with 3 in. flashback. Temperatures above 120 F may cause cans to burst. | No information available |
| Evaporation Rate | Faster than butyl acetate | No information available |
| Flammability (solid, gas) | | No information available |
| Flammability Limits in Air | | No information available |
| Upper flammability limits | Not available | No information available |
| Lower Flammability Limit | Not available | No information available |
| Vapor pressure | | No information available |
| Vapor Density | | No information available |
| Relative Density | 0.886 concentrate | No information available |
| Water solubility | Insoluble in water | No information available |
| Solubility in other solvents | | No information available |
| Partition coefficient | | No information available |
| Autoignition Temperature | | No information available |
| Decomposition temperature | | No information available |
| Kinematic viscosity | | No information available |
| Dynamic viscosity | | No information available |
| Explosive properties | No information available | No information available |
| Oxidizing properties | No information available | No information available |

Other Information

| | |
|-------------------------|--------------------------|
| Softening point | No information available |
| Molecular weight | No information available |
| VOC content (%) | 53.2% |
| Density | 7.37 lb/gal concentrate |
| Bulk Density | No information available |

10. Stability and Reactivity

Reactivity

Not applicable No data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

Hazardous decomposition products

Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information

This product has not been tested as whole. See below for information on ingredients.

Inhalation No data available.

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

| | |
|---------------------|--------------------|
| Eye Contact | No data available. |
| Skin contact | No data available. |
| Ingestion | No data available. |

| Chemical name | Oral LD50 | dermal LD50 | Inhalation LC50 |
|---|-----------------------|---|---|
| Acetone 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| Propane 74-98-6 | - | - | = 658 mg/L (Rat) 4 h |
| N-Butane 106-97-8 | - | - | = 658 g/m ³ (Rat) 4 h |
| n-Butyl acetate 123-86-4 | = 10768 mg/kg (Rat) | > 17600 mg/kg (Rabbit) | = 390 ppm (Rat) 4 h |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | = 3500 mg/kg (Rat) | > 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h |
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| Ethylbenzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.2 mg/L (Rat) 4 h |
| Naphtha (petroleum), heavy aromatic 64742-94-5 | > 5000 mg/kg (Rat) | > 2 mL/kg (Rabbit) | > 590 mg/m ³ (Rat) 4 h |
| Butyl benzyl phthalate 85-68-7 | = 2330 mg/kg (Rat) | = 6700 mg/kg (Rat) | > 6.7 mg/L (Rat) 4 h |

Information on toxicological effects

| | |
|-----------------|--|
| Symptoms | Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. |
|-----------------|--|

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|--|--|
| Skin corrosion/irritation | May cause skin irritation and reddening after prolonged or repeated contact with skin. |
| Serious eye damage/eye irritation | Irritating to eyes. |
| irritation | May cause skin and eye irritation. |
| corrosivity | Not applicable. |
| sensitization | No information available. |
| Germ cell mutagenicity | See Section 2 of this SDS. |
| Carcinogenicity | The table below indicates whether each agency has listed any ingredient as a carcinogen. |

| Chemical name | ACGIH | IARC | NTP | OSHA |
|---|-------|----------|-----|------|
| Xylenes (o-, m-, p- isomers) 1330-20-7 | | Group 3 | | |
| Toluene 108-88-3 | | Group 3 | | |
| Magnesium Silicate 14807-96-6 | | Group 3 | | |
| Ethylbenzene 100-41-4 | A3 | Group 2B | | X |
| Butyl benzyl phthalate 85-68-7 | | Group 3 | | |

| | |
|---------------------------------|----------------------------|
| Reproductive toxicity | See Section 2 of this SDS. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Aspiration Hazard | No information available. |

Numerical measures of toxicity - Product Information

Unknown acute toxicity 10.948% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

| | |
|-----------------|-------------|
| ATEmix (oral) | 21118 mg/kg |
| ATEmix (dermal) | 31293 mg/kg |

ATEmix (inhalation-gas) 15680 mg/l
 ATEmix (inhalation-dust/mist) 15.9 mg/l
 ATEmix (inhalation-vapor) 840 mg/l

12. Ecological Information

This product contains chemicals which are listed as a marine pollutants according to DOT.

ecotoxicity

36.708% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical name | Algae/aquatic plants | Fish | Toxicity to Microorganisms | Crustacea |
|---|---|---|--|--|
| Acetone 67-64-1 | | 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static | EC50 = 14500 mg/L 15 min | 12600 - 12700: 48 h Daphnia magna mg/L EC50 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static |
| n-Butyl acetate 123-86-4 | 674.7: 72 h Desmodesmus subspicatus mg/L EC50 | 62: 96 h Leuciscus idus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static | EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min | 72.8: 24 h Daphnia magna mg/L EC50 |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | | 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 | EC50 = 0.0084 mg/L 24 h | 3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50 |
| Toluene 108-88-3 | 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 12.6: 96 h Pimephales promelas mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static | EC50 = 19.7 mg/L 30 min | 11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static |

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

| | | | | |
|--|--|--|--|---|
| Magnesium Silicate 14807-96-6 | | 100: 96 h Brachydanio rerio g/L LC50 semi-static | | |
| Ethylbenzene 100-41-4 | 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 | 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static | EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h | 1.8 - 2.4: 48 h Daphnia magna mg/L EC50 |
| Naphtha (petroleum), heavy aromatic 64742-94-5 | 2.5: 72 h Skeletonema costatum mg/L EC50 | 41: 96 h Pimephales promelas mg/L LC50 45: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static | | 0.95: 48 h Daphnia magna mg/L EC50 |
| Butyl benzyl phthalate 85-68-7 | 0.02 - 0.25: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.2 - 28.2: 72 h Pseudokirchneriella subcapitata mg/L EC50 | 1.0 - 10.0: 96 h Oncorhynchus mykiss mg/L LC50 static 0.82: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.78: 96 h Pimephales promelas mg/L LC50 static 1.39 - 3.88: 96 h Pimephales promelas mg/L LC50 flow-through 1.0 - 10.0: 96 h Lepomis macrochirus mg/L LC50 static | | 0.97: 48 h Daphnia magna mg/L EC50 0.9 - 1.1: 48 h Daphnia magna mg/L EC50 Static 1.28: 48 h Daphnia magna mg/L EC50 semi-static 0.76: 48 h Daphnia magna mg/L EC50 Flow through |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical name | Partition coefficient |
|---|-----------------------|
| Acetone 67-64-1 | -0.24 |
| Propane 74-98-6 | 2.3 |
| N-Butane 106-97-8 | 2.89 |
| n-Butyl acetate 123-86-4 | 1.81 |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | 2.77 - 3.15 |
| Toluene 108-88-3 | 2.65 |
| Ethylbenzene 100-41-4 | 3.118 |
| Naphtha (petroleum), heavy aromatic 64742-94-5 | 2.9 - 6.1 |
| Butyl benzyl phthalate 85-68-7 | 3.57 - 4.91 |

Other adverse effects

No information available

13. Disposal Considerations

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

Waste treatment methods

| | |
|-------------------------------|--|
| Disposal of wastes | Dispose of in accordance with federal, state and local regulations. |
| Contaminated packaging | Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. |

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---|------|--|------------------------|------------------------|
| Acetone 67-64-1 | | Included in waste stream: F039 | | U002 |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | | Included in waste stream: F039 | | U239 |
| Toluene 108-88-3 | U220 | Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151 | | U220 |
| Ethylbenzene 100-41-4 | | Included in waste stream: F039 | | |
| Butyl benzyl phthalate 85-68-7 | | Included in waste stream: F039 | | |

| Chemical name | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|--|------------------------|
| Toluene 108-88-3 | | | Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution. | |

| Chemical name | California Hazardous Waste Status |
|---|-----------------------------------|
| Acetone 67-64-1 | Ignitable |
| n-Butyl acetate 123-86-4 | Toxic |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | Toxic Ignitable |
| Toluene 108-88-3 | Toxic Ignitable |
| Ethylbenzene 100-41-4 | Toxic Ignitable |

14. Transport Information

DOT

| | |
|-----------------------------|---|
| UN/ID no | Limited Quantity |
| Proper Shipping Name | Consumer Commodity |
| Hazard Class | ORM-D |
| Marine pollutant | This product contains chemicals which are listed as a marine pollutants according to DOT. |

15. Regulatory information

International Inventories

TSCA

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

DSL

All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - *United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL - *Canadian Domestic Substances List/Non-Domestic Substances List*

US Federal Regulations

SARA 313

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

| Chemical name | CAS No | weight-% | SARA 313 - Threshold Values % |
|--|-----------|----------|-------------------------------|
| Xylenes (o-, m-, p- isomers) - 1330-20-7 | 1330-20-7 | 5-10 | 1.0 |
| Toluene - 108-88-3 | 108-88-3 | 5-10 | 1.0 |
| Ethylbenzene - 100-41-4 | 100-41-4 | 1-5 | 0.1 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | yes |
| Chronic Health Hazard | yes |
| Fire Hazard | yes |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---|-----------------------------|------------------------|---------------------------|----------------------------|
| n-Butyl acetate 123-86-4 | 5000 lb | | | X |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | 100 lb | | | X |
| Toluene 108-88-3 | 1000 lb | X | X | X |
| Ethylbenzene 100-41-4 | 1000 lb | X | X | X |
| Butyl benzyl phthalate 85-68-7 | | X | X | |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---|--------------------------|----------------|--|
| Acetone 67-64-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| n-Butyl acetate 123-86-4 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |
| Toluene | 1000 lb 1 lb | | RQ 1000 lb final RQ |

FG 499-0531-1 CHAMPION SPRAYON ACRYLIC MATTE FINISH

| | | | |
|-----------------------------------|---------|--|---|
| 108-88-3 | | | RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ |
| Ethylbenzene 100-41-4 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |
| Butyl benzyl phthalate 85-68-7 | 100 lb | | RQ 100 lb final RQ RQ 45.4 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals. This product contains <0.1% naphthalene, a chemical known to the state of California to cause cancer.

| Chemical name | California Proposition 65 |
|----------------------------------|---------------------------|
| Toluene - 108-88-3 | Developmental |
| Ethylbenzene - 100-41-4 | carcinogen |
| Butyl benzyl phthalate - 85-68-7 | Developmental |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| Acetone 67-64-1 | X | X | X |
| Propane 74-98-6 | X | X | X |
| N-Butane 106-97-8 | X | X | X |
| n-Butyl acetate 123-86-4 | X | X | X |
| Xylenes (o-, m-, p- isomers) 1330-20-7 | X | X | X |
| Toluene 108-88-3 | X | X | X |
| Magnesium Silicate 14807-96-6 | X | X | X |
| Ethylbenzene 100-41-4 | X | X | X |
| Butyl benzyl phthalate 85-68-7 | X | X | X |

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information

| | | | | |
|-------------|-------------------|----------------|--------------------|---|
| <u>NFPA</u> | Health Hazards 2 | Flammability 4 | Instability 1 | Physical and chemical properties Not applicable |
| <u>HMIS</u> | Health Hazards 2* | Flammability 4 | Physical hazards 1 | Personal Protection B - Eyes and hands protection |

Prepared by Regulatory Department
Issue date 09-Nov-2016

Revision note

This SDS supersedes a previous MSDS dated February 24, 2012.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet