# MATERIAL SAFETY DATA SHEET



Page 1 of 5

# **DECO MAGIC PROF SPRAY GLUE 4 OZ**

Manufacturer

Chase Products Co.

19th and Gardner Road

Broadview, IL 60155 USA

## 1. Product And Company Identification

<u>Supplier</u>

Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA

Company Contact: Laura E. Radevski Telephone Number: 708-865-1000

**FAX Number:** 708-865-0923 **E-Mail:** sales@chaseproducts.com **Web Site:** www.chaseproducts.com

**Supplier Emergency Contacts & Phone Number** 

Chem-Tel: 1-800-255-3924

Company Contact: Laura E. Radevski

**Telephone Number:** 708-865-1000 **FAX Number:** 708-865-0923

E-Mail: sales@chaseproducts.com
Web Site: www.chaseproducts.com

Manufacturer Emergency Contacts & Phone Number

Chem-Tel: 1-800-255-3924

Issue Date: 12/03/2010

Product Name: DECO MAGIC PROF SPRAY GLUE 4 OZ

Chemical Name: 7-7840-1 MSDS Number: 4807 Product Code: 499-0540-4

<u>Product/Material Uses</u> - Glue for glitter

## 2. Composition/Information On Ingredients

·			
Ingredient Name	CAS Number		Percent Of Total Weight
ACETONE	67-64-1		
BUTANE	106-97-8		
ETHYL BENZENE	100-41-4	<	1
HEPTANE	142-82-5		
PROPANE	74-98-6		
XYLENE (MIXED ISOMERS)	1330-20-7		1 - 5

The ingredients listed on this section are only the hazardous components of the product.

#### 3. Hazards Identification

<u>Primary Routes(s) Of Entry</u> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. **Eye Hazards** - Causes eye irritation.

**Skin Hazards** - Causes skin irritation after prolonged contact with skin.

<u>Ingestion Hazards</u> - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately.

<u>Inhalation Hazards</u> - Deliberate inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea.

<u>Chronic/Carcinogenicity Effects</u> - Prolonged exposure to petroleum solvents has been associated with nervous system damage. Xylene has been associated with kidney and liver disorders. Contains ethyl benzene, IARC has evaluated and classified ethyl benzene as a possibly human carcinogen (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans."Warning: This product contains a chemical known to the State of California to cause cancer".

**Epidemiology** - Not known

Teratogenicity (Birth Defects) - Not known

Reproductive Effects - Not known

#### 3. Hazards Identification - Continued

**Neurotoxicity** - Not known

Mutagenicity (Genetic Effect) - Not known

<u>Signs And Symptoms</u> - Acute: Deliberate inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Causes eye irritation. Causes skin irritation after prolonged contact with skin.

<u>Conditions Aggravated By Exposure</u> - May aggravate pre-existing skin, kidney, liver and respiratory disorders.

Conditions Aggravated By Overexposure - May aggravate pre-existing skin, kidney, liver and respiratory disorders.

## First Aid (Pictograms)





#### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**Skin** - Wash skin with soap and water. If irritation develops, consult a physician.

<u>Ingestion</u> - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

<u>Inhalation</u> - If overcome by vapor move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

## 5. Fire Fighting Measures

Flash Point: Not available °F Not available °C

Flash Point Method: Not available Lower Explosive Limit: Not available Upper Explosive Limit: Not available

Fire And Explosion Hazards - This product is an aerosol product for which Flame Projection is over 18 in. with 2

in. flashback. Temperatures above 120 F may cause cans to burst.

**Extinguishing Media** - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

## 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

## **Handling & Storage (Pictograms)**



### 7. Handling And Storage

<u>Handling And Storage Precautions</u> - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

<u>Handling Precautions</u> - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

<u>Storage Precautions</u> - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B)** 

Work/Hygienic Practices - Wash hands thoroughly after using this product.

## **Protective Clothing (Pictograms)**





# 8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

Skin Protection - Household or rubber gloves.

<u>Respiratory Protection</u> - Use in well-ventilated area ONLY. **When using indoors, keep windows and doors open until fumes dissipate.** None required if used in a well-ventilated area.

## Ingredient(s) - Exposure Limits

**ACETONE** 

ACGIH TLV-STEL 750 ppm; ACGIH TLV-TWA 500 ppm; OSHA PEL-TWA 1,000 ppm

**BUTANE** 

ACGIH TLV-TWA 1000 ppm

ETHYL BENZENE

ACGIH TLV-STEL 125 ppm (Notice of intended change); ACGIH TLV-TWA 100 ppm (Notice of Intended Change);

OSHA PEL-TWA 100 ppm

**HEPTANE** 

ACGIH TLV-STEL 500 ppm; ACGIH TLV-TWA 400 ppm; OSHA PEL-TWA 500 ppm

**PROPANE** 

ACGIH TLV-TWA 2500 ppm; OSHA PEL-TWA 1,000 ppm

XYLENE (MIXED ISOMERS)

ACGIH TLV-STEL 150 ppm; ACGIH TLV-TWA 100 ppm; OSHA PEL-TWA 100 ppm

#### 9. Physical And Chemical Properties

<u>Appearance</u> - Clear liquid. <u>Odor</u> - Petroleum solvent odor.

Chemical Type: Mixture Physical State: Liquid

**Melting Point:** Not applicable °F Not applicable °C **Boiling Point:** Heptane 200-211 °F Heptane 96.6 °C

Specific Gravity: 0.733 concentrate

Percent VOCs: 64.79 Solubility: Insoluble

Evaporation Rate: Faster than butyl acetate

#### 10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

**Incompatible Materials** - Avoid heat, open flame and contact with strong oxidizers or reducing agents...

<u>Hazardous Decomposition Products</u> - Thermal decomposition may yield gases like carbon monoxide and carbon

dioxide.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

## 11. Toxicological Information

## Ingredient(s) - Carcinogenicity

ETHYL BENZENE

Listed In The IARC Monographs

## 12. Ecological Information

<u>Ecotoxicological Information</u> - No specific ecological data is available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

## 13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** place in garbage or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

## 14. Transport Information

**Proper Shipping Name** - ORM-D Consumer Commodity

## **Hazard Class**

2.1

## **DOT Identification Number**

UN1950

## **DOT Shipping Label**

Aerosol Consumer Commodity

## 15. Regulatory Information

<u>U.S. Regulatory Information</u> - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

## **SARA Hazard Classes**

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

<u>SARA Section 313 Notification</u> - This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material. This product contains xylene and ethyl benzene. See Section 2 for % amounts in the product.

## Ingredient(s) - U.S. Regulatory Information

ETHYL BENZENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

XYLENE (MIXED ISOMERS)

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

## Ingredient(s) - State Regulations

#### ACETONE

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### **BUTANE**

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

## ETHYL BENZENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania -

# 15. Regulatory Information - Continued

## Ingredient(s) - State Regulations - Continued

Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### **HEPTANE**


New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### XYLENE (MIXED ISOMERS)

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance



#### 16. Other Information

# Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supersedes A Previous MSDS Dated: 05/29/2002

#### **Disclaimer**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

#### Chase Products Co.

Printed Using MSDS Generator™ 2000