

MATERIAL SAFETY DATA SHEET

Date of Last Revision: 1/12

GlobalTech®

Solder Paste & Flux Remover

Product Code:

PFR

FOR CHEMICAL EMERGENCY call INFOTRAC at 1-800-535-5053

24 Hrs. per day, 7 days per week

Section 1 ... Composition/Information on Ingredients

Ingredients

	Weight %	TWA/TLV
Glycols	<5	100ppm OSHA 29CFR.1910
Aliphatic Glycol Ethers	>90	NE
N-Amino Ethanol	<5	8 TWA

Section 2 ... First Aid Measures

Eye Contact:	Flush with large amount of water for 15 minutes. Contact physician.
Skin Contact:	Flush with large amount of water for 15 minutes. Contact physician. Remove contaminated clothing, wash before reuse.
Inhalation:	Move subject to fresh air. Give artificial respiration if not breathing, call physician.
Ingestion:	If conscious, drink 1 pint of luke warm water. Do NOT induce vomiting. Obtain medical attention promptly.

Section 3 ... Health Hazards, Routes of Entry and Effects of Overexposure

Work Place Exposure Limits:

300 ppm

Eye Contact:

Irritation may cause eye reddening.

Skin Contact:

Prolonged contact results in skin drying.

Inhalation:

May cause irritation to nose and throat.

Ingestion:

Irritation to throat, mouth, esophagus. May cause nausea, vomiting, dizziness, diarrhea.

Section 4 ... Special Protection Information

Ventilation:

Use local exhaust ventilation to maintain vapor below TWA's.

Respiratory Protection:

Self-contained breathing apparatus in high vapor concentrations.

Gloves & Glasses:

Chemically resistant gloves. Safety Glasses.

Other Protective Equipment:

Eye bath, safety shower.

Section 5 ... Reactivity Data

Stability:

Stable

Conditions to Avoid:

Temperatures above 250° C. Avoid heat, sparks and flame.

Hazardous Polymerization:

Will not occur

Conditions to Avoid:

NA

Incompatibility (material to avoid):

Strong: Oxidizers, bases, acids. Ketones, aldehydes, anhydrides.

Hazardous Decomposition:

Oxides of Carbon and Nitrogen.

Section 6 ... Spill or Leak Procedures and Waste Disposal

Precautions in Case of Release:

Wear suitable protective equipment. Collect small spills with absorbents, large spills flush with water, avoid discharge into sewers and waterways.

Waste Disposal Method:

Incinerate where permitted under Federal, State and Local regulations.

Section 7 ... Handling and Storage Precautions

Avoid eye and skin contact. Keep away from children. Keep away from heat and flame. Use with adequate ventilation. Avoid inhalation of vapor or mist. Avoid contact with copper/copper alloys (such as brass). Use only Polyethylene valves and containers.

Storage Temperature: Ambient

Indoor: Ambient

Heated: NA

Outdoor: Ambient

Refrigerated: NA

Section 8 ... Hazard Data

Hazard Class (Hazard Rating Scale: 0=minimal, 1=slight, 2=moderate, 3=high, 4=extreme):

Health: 2

Flammability: 2

Reactivity: 0

Personal Protection:

Hazard Class: Combustible liquid

Explosive Limits (volume %):

Lower: NA

Upper: NA

Flash Point: 117° F(47° C) TCC

Auto Ignition Temp: Will not occur

Extinguishing Media: Foam, CO₂, dry chemical

Fire and Explosion Hazards: During fire, oxides of Nitrogen may evolve.

Fire Fighting Procedures: Self-contained breathing apparatus and full protective gear.

Section 9 ... Physical Data

Boiling Point:	302°F (150°C)	Vapor Density (air=1):	3.8
Evaporation Rate (butyl acetate=1):	0.2	% Volatile (by weight):	100
Vapor Pressure (in mmHg):	1.5 @ 20°C	% Water Soluble:	100
Specific Gravity (water=1):	0.89	Melting/Freezing Point:	-50°C F.P.
Appearance:	Clear colorless liquid	Viscosity:	NA
Odor:	Mild odor		

Section 10 ... Toxicity Information

This product does not require reporting under the Comprehensive Environmental and Liability Act (CERCLA) of 1980. It is TSCA listed. It is not listed on Hazardous Air Pollutant (HAPS) list of the 1990 Clean Air Act Amendments and is not subject to Sara Title III regulations.

Section 11 ... Miscellaneous Information

Ventilation Protection: Refer to current edition of "Industrial Ventilation; A Manual of Recommended Practice", ACGIH, for the design, installation, use and maintenance of ventilation system.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

The information contained herein is based on data believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the material. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk for his use thereof. JNJ accepts no responsibility for any personal injury, property damage, or other type of loss due to negligence or otherwise resulting from the use or handling of this material.