

**11. Identification of the Substance and Company**
**Thermolabel Temperature-Sensitive Tape**
**Product No. EQ1009**
**SDS No. S127US**
**Prepared by: M. Ebers**
[asksteris\\_msds@steris.com](mailto:asksteris_msds@steris.com)
**Date Created: September 16, 2002    Date Reviewed: April 30, 2014**
**Date Revised: NA**
**NFPA 704 HAZARD RATING:**
**HEALTH: 0**
**FIRE: 0**
**REACTIVITY: 0**

STERIS Corporation, P. O. Box 147, St. Louis, MO 63166, US  
 Emergency Telephone No. 1-314-535-1395 (STERIS); 1-800-424-9300 (CHEMTREC)  
 Telephone Number for Information: 1-800-548-4873 (Customer Service-Healthcare Products)

STERIS Limited, Chancery House, 190 Waterside Road, Hamilton Industrial Park, Leicester,  
 LE5 1QZ, UK

Emergency Phone No: +44 (0) 1895 622 639

Product/Technical Information Phone No: +44 (0) 116 276 8636

<b>PRODUCT NAME:</b>	<b>PRODUCT NUMBER:</b>
Thermolabel Temperature-Sensitive Tape	EQ1009
<b>SHIPPING INFORMATION:</b>	<b>NOT RESTRICTED</b>

Thermolabel Temperature-Sensitive Tape is a NOT hazardous product according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

The Thermolabel is a process indicator designed for use in common washing processes with a 180°F (82°C) rinse. The Thermolabel consists of a waterproof, adhesive backed label which changes from light gray to black when the 180°F (82°C) temperature printed on the label is reached. Thermolabels should be stored in a cool dry place.