



MATERIAL SAFETY DATA SHEET

KEM CANADA MFG.
 4 BLAIR DRIVE
 BRAMPTON, ONTARIO
 L6T 2H5
 TEL# (905) 456-9444

EMERGENCY # CANUTEC (613) 996-6666
"USE IN CASE OF CHEMICAL EMERGENCY ONLY"

W.H.M.I.S. CLASSIFICATION: B3, D1B, E

MATERIAL REFERENCE NO: 574300

SECTION I - MATERIAL IDENTIFICATION AND USE

MATERIAL NAME/I.D.: RT-743	
CHEMICAL NAME: NOT APPLICABLE	CHEMICAL FAMILY: ALKALINE BLEND
CHEMICAL FORMULA: MIXTURE	MOLECULAR WEIGHT: NOT APPLICABLE
SYNONYMS: NONE	
MATERIAL USE: RETURN LINE TREATMENT	

SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL

HAZARDOUS INGREDIENTS	APPROX. % CONCENT.	TLV PPM	C.A.S. NUMBERS	LD 50 ORAL, RAT
MORPHOLINE	7.0-13.0	20	110-91-8	1450 MG/KG

SECTION III - PHYSICAL DATA FOR MATERIAL

PHYSICAL STATE: LIQUID		
ODOUR AND APPEARANCE: CLEAR, COLOURLESS LIQUID; AMINE ODOUR.		
ODOUR THRESHOLD (PPM)	SPECIFIC GRAVITY	VAPOUR PRESSURE (MM)
0.1	1.001	NOT AVAILABLE
VAPOUR DENSITY (AIR=1)	EVAPORATION RATE	SOLUBILITY IN WATER
NOT ESTABLISHED	(WATER = 1) 1.0	(20°C) COMPLETE
BOILING POINT (C)	FREEZING POINT (C)	% VOLATILE (BY WEIGHT)
>100 (EST.)	<0	100
pH (10% SOLUTION)	DENSITY (G/ML)	COEF.OF WATER/OIL DISTR
10.5-11.5	NOT APPLICABLE	NOT AVAILABLE



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 574300

SECTION IV - FIRE AND EXPLOSION HAZARD OF MATERIAL

FLAMMABILITY: FLAMMABLE		
IF YES, UNDER WHICH CONDITIONS: VAPOURS MAY BE FLAMMABLE.		
MEANS OF EXTINCTION: ALCOHOL FOAM, CO2, WATER SPRAY, DRY CHEMICAL.		
SPECIAL PROCEDURES: WEAR FULL PROTECTIVE GEAR INCLUDING SELF-		
CONTAINED BREATHING APPARATUS. VAPOURS ARE HEAVIER THAN AIR AND MAY		
TRAVEL TO IGNITION SOURCE AND FLASH BACK.		
FLASH POINT (C) AND METHOD: MINIMUM 35 TCC		
HAZARDOUS COMBUSTION PRODUCTS: MAY EVOLVE NITROGEN OXIDES, CARBON		
DIOXIDE, CARBON MONOXIDE, AMMONIA, ALDEHYDES, KETONES, IRRITATING		
VAPOURS.		
UPPER EXPLOSION LIMIT	LOWER EXPLOSION LIMIT	AUTOIGNITION TEMP (C)
1.8 (MORPHOLINE)	10.8 (MORPHOLINE)	NOT AVAILABLE
EXPLOSION DATA SENSITIVITY	RATE OF BURNING	EXPLOSIVE POWER
TO CHEMICAL IMPACT		
NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
SENSITIVITY TO STATIC DISCHARGE: NOT AVAILABLE		

SECTION V - REACTIVITY DATA

CHEMICAL STABILITY: STABLE		
IF NO, UNDER WHICH CONDITIONS:		
INCOMPATIBILITY TO OTHER SUBSTANCES: YES		
IF SO, WHICH ONES: STRONG ACIDS, OXIDIZING AGENTS, NITRITES AND		
OTHER NITROSATING AGENTS.		
REACTIVITY AND UNDER WHAT CONDITIONS: NITROSAMINE MAY BE FORMED WHEN		
MIXED WITH NITRITES OR OTHER NITROSATING AMINES. NITROSAMINES MAY		
CAUSE CANCER.		
HAZARDOUS POLYMERIZATION WILL NOT OCCUR.		
HAZARDOUS DECOMPOSITION PRODUCTS: NITROUS OXIDES, CARBON MONOXIDE,		
CARBON DIOXIDE, AMMONIA, ALDEHYDES, KETONES, IRRITATING VAPOURS.		

SECTION VI - HEALTH HAZARD DATA

ROUTE OF ENTRY:		
SKIN CONTACT: YES	SKIN ABSORPTION: YES	EYE CONTACT: YES
INHALATION: YES	INGESTION: YES	



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 574300

|EFFECTS OF ACUTE EXPOSURE TO MATERIAL: |
 |EYES-MAY CAUSE SEVERE IRRITATION, INTENSE WATERING, REDNESS. MAY |
 |CAUSE CHEMICAL BURNS, EYE DAMAGE. |
 |SKIN-MAY CAUSE IRRITATION, INFLAMMATION, REDNESS, POSSIBLE BURNS. |
 |PROLONGED OR REPEATED CONTACT MAY RESULT IN ABSORPTION OF POTENTIALLY |
 |HARMFUL AMOUNTS. |
 |INHALATION-MAY CAUSE IRRITATION OF NOSE, EYES AND THROAT, COUGHING, |
 |DIFFICULTY IN BREATHING. EXCESSIVE INHALATION MAY CAUSE BRONCHITIS, |
 |PULMONARY EDEMA AND CHEMICAL PNEUMONITIS. |
 |INGESTION-MAY CAUSE IRRITATION AND BURNING SENSATION OF LIPS, MOUTH |
 |AND THROAT, PAIN IN SWALLOWING, GASTRO-INTESTINAL IRRITATION, |
 |ABDOMINAL PAIN, NAUSEA AND VOMITING. |
 |

|EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: PROLONGED EXPOSURE MAY |
 |CAUSE KIDNEY AND/OR LIVER DAMAGE. |

LD 50 OF MATL.	LC 50 OF MATL.	EXPOSURE LIMIT(S)	IRRITANCY OF MATL
NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE	TOXIC

SENSITIZATION OF MATERIAL	SYNERGISTIC MATERIALS
NOT AVAILABLE	NOT AVAILABLE

|CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY |
 |NONE KNOWN. |
 |MORPHOLINE MAY REACT WITH NITRITES TO FORM N-NITROSAMINES (KNOWN |
 | CARCINOGENS) |
 |

SECTION VII - PREVENTIVE MEASURES

|PERSONAL PROTECTIVE EQUIPMENT: |

| GLOVES: BUTYL RUBBER, NITILE |
 |RESPIRATORY: NIOSH APPROVED FOR ORGANIC VAPOURS. |
 | EYE: FACE SHIELD OR SAFETY GOGGLES |
 | CLOTHING: LONG SLEEVED SHIRTS, TROUSERS, BUTYL RUBBER BOOTS AND |
 | APRON. |
 | OTHER: EYE WASH AND SAFETY SHOWER |
 |ENGINEERING CONTROLS (EG VENTILATION, ENCLOSED PROCESS): MECHANICAL |
 | RECOMMENDED TO MAINTAIN CONCENTRATION BELOW TLV. |

|LEAK AND SPILL PROCEDURE: WEAR RECOMMENDED PERSONAL PROTECTIVE |
 |EQUIPMENT. REMOVE IGNITION SOURCES. STOP LEAKS AND CONTAIN SPILL. |
 |RECLAIM IF POSSIBLE. ABSORB ONTO NON-COMBUSTIBLE ABSORBENT AND PLACE |
 |IN APPROVED CONTAINER FOR DISPOSAL. DO NOT ALLOW LIQUID TO FLOW INTO |
 |WATERWAYS. PRODUCT IS EXPECTED TO BE TOXIC TO AQUATIC LIFE. |

|WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH LOCAL, PROVINCIAL AND |
 |FEDERAL REGULATIONS. |
 |



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 574300

SECTION VIII - FIRST AID MEASURES

| PROCEDURES: EYES-IMMEDIATELY FLUSH EYES WITH RUNNING WATER FOR AT |
| LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET IMMEDIATE MEDICAL |
| ATTENTION. |
| SKIN-REMOVE CONTAMINATED CLOTHING AND FLUSH AFFECTED AREA WITH |
| WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. LAUNDRER |
| CLOTHING BEFORE REUSE. |
| INHALATION-MOVE VICTIM TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE |
| OXYGEN. GET MEDICAL ATTENTION. |
| INGESTION-DO NOT INDUCE VOMITING. SLOWLY GIVE 1-2 GLASSES OF WATER |
| OR MILK. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR |
CONVULSING PERSON. GET IMMEDIATE MEDICAL

SOURCES USED: RAW MATERIAL SUPPLIER'S MATERIAL SAFETY DATA SHEETS

ADDITIONAL INFORMATION: NONE

SECTION IX - TDG SHIPPING INFORMATION

SHIPPING NAME	CLASS	UN NO.	PG
CORROSIVE LIQUID, FLAMMABLE, N.O.S.	8(3)	2920	II
(MORPHOLINE)			

| HANDLING PROCEDURES AND EQUIPMENT: AVOID CONTACT WITH EYES, SKIN AND |
| CLOTHING. USE IN ADEQUATELY VENTILATED AREAS. WASH THOROUGHLY AFTER |
HANDLING.

| STORAGE REQUIREMENTS: STORE IN A COOL, DRY WELL VENTILATED AREA IN |
| ORIGINAL CONTAINER. STORE AWAY FROM INCOMPATIBLE MATERIALS. KEEP |
CONTAINER CLOSED WHEN NOT IN USE.

SPECIAL SHIPPING INFORMATION: NONE

SECTION X - HMIS HAZARD RATING INFORMATION

| FLAMMABILITY | REACTIVITY | HEALTH |
| 3 | 0 | 2 |

SECTION XI - PREPARATION DATE OF MSDS

| PREPARED BY: TECHNICAL DEPARTMENT TELEPHONE # (905) 456-9444 |
REVIEWED: OCTOBER 10, 2009

DISCLAIMER:

THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILITY FOR THE ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING FROM THE USE OF THE INFORMATION.