



Material Safety Data Sheet

| WHMIS (Pictograms) | WHMIS (Classification) | Protective Clothing | TDG (pictograms) |
|--------------------|------------------------|---------------------|------------------|
| | Not controlled | | |

Section 1. Chemical Product and Company Identification

| | | | |
|----------------------|---|-----------------------------|--|
| Product Name | MAXIMUM 5W30, 10W30, 10W40 | Code | 410-336, MAX53 410-335, MAX13 410-337, MAX14 |
| Synonym | Not available | Validated on | 4/01/2008. |
| Manufacturer | PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3 | In case of Emergency | Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s). |
| Material Uses | Designed for lubrication of all gasoline engines where the manufacturer recommends the use of API SL, SJ, or SH quality oils. SAE 5W-30, 10W-30 grades also meet the requirements of ILSAC GF-3, GF-2 and GF-1. | | |

Section 2. Composition and Information on Ingredients

| | | | Exposure Limits (ACGIH) | | |
|---|---|---------|--------------------------------|---------------------------------|-----------------|
| Name | CAS # | % (W/W) | TLV-TWA(8 h) | STEL | CEILING |
| 1) Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and other proprietary, non-hazardous additives. | Mixture | 100 | 5 mg/m ³ (oil mist) | 10 mg/m ³ (oil mist) | Not established |
| Manufacturer Recommendation | Not applicable | | | | |
| Other Exposure Limits | Consult local, state, provincial or territory authorities for acceptable exposure limits. | | | | |

Section 3. Hazards Identification.

| | |
|---------------------------------|---|
| Potential Health Effects | Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected to be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS. |
|---------------------------------|---|

Section 4. First Aid Measures

| | |
|--------------------------|---|
| Eye Contact | IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention. |
| Skin Contact | Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention. |
| Inhalation | Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention. |
| Ingestion | DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention. |
| Note to Physician | Not available |

Section 5. Fire-fighting Measures

| | | | |
|---|---|--|--|
| Flammability | May be combustible at high temperature. | Flammable Limits | Not available. |
| Flash Points | OPEN CUP: $\geq 221^{\circ}\text{C}$ (430°F) (Cleveland) | Auto-Ignition Temperature | Not available. |
| Fire Hazards in Presence of Various Substances | Low fire hazard. This material must be heated before ignition will occur. | Explosion Hazards in Presence of Various Substances | Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire. |
| Products of Combustion | Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), smoke and irritating vapours as products of incomplete combustion. | | |

| | |
|---|---|
| Fire Fighting Media and Instructions | NAERG96, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. DO NOT extinguish a leaking gas flame unless leak can be stopped. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, or CO ₂ . LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel. |
|---|---|

Section 6. Accidental Release Measures

| | |
|----------------------------------|--|
| Material Release or Spill | Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately. |
|----------------------------------|--|

Section 7. Handling and Storage

| | |
|-----------------|---|
| Handling | Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid eye contact. Avoid skin contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated. |
| Storage | Store away from incompatible and reactive materials (See section 5 and 10). Keep container tightly closed. Store in dry, cool, well-ventilated area. |

Section 8. Exposure Controls/Personal Protection

| | |
|--|--|
| Engineering Controls | For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station. |
| Personal Protection - <i>The selection of personal protective equipment varies, depending upon conditions of use.</i> | |
| Eyes | Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered. |
| Body | Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn. |
| Respiratory | Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation. |
| Hands | Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated. |
| Feet | Wear appropriate footwear to prevent product from coming in contact with feet and skin. |

Section 9. Physical and Chemical Properties

| | | | |
|--------------------------------------|---|--------------------------------------|---|
| Physical State and Appearance | Viscous liquid. | Viscosity | 5W30: 63.9 cSt @ 40°C (104°F), 10.8 cSt @ 100°C (212°F), VI=160 10W30: 69.1 cSt @ 40°C (104°F), 10.6 cSt @ 100°C (212°F), VI=141 10W40: 98.5 cSt @ 40°C (104°F), 14.5 cSt @ 100°C (212°F), VI=152 |
| Colour | Light yellow. | Pour Point | 5W-30: -42°C (-43.6°F) 10W-30: -36°C (-32.8°F) 10W-40: -33°C (-27.4°F) |
| Odour | Mild petroleum oil like. | Softening Point | Not applicable. |
| Odour Threshold | Not available. | Dropping Point | Not applicable. |
| Boiling Point | Not available. | Penetration | Not applicable. |
| Density | 0.8565 to 0.8672 kg/L @ 15°C (59°F). | Oil / Water Dist. Coefficient | Not available |
| Vapour Density | Not available. | Ionicity (in water) | Not available |
| Vapour Pressure | Negligible at ambient temperature and pressure. | Dispersion Properties | Not available |
| Volatility | Non-volatile | Solubility | Insoluble in water. |

Section 10. Stability and Reactivity

| | | | |
|--|--|---------------------------------|---|
| Corrosivity | 5W30, 10W30: Copper corrosion, 3h, 100°C (ASTM D0130): 1a. 10W40: Copper corrosion, 3h, 100°C (ASTM D0130): 1b. | | |
| Stability | The product is stable under normal handling and storage conditions. | Hazardous Polymerization | Will not occur under normal working conditions. |
| Incompatible Substances / Conditions to Avoid | Reactive with oxidizing agents and acids. | Decomposition Products | May release COx, H2S, amines, methacrylate monomers, smoke and irritating vapours when heated to decomposition. |

Section 11. Toxicological Information

| | | | |
|---------------------------------------|--|--|--|
| Routes of Entry | Skin contact, eye contact, inhalation, and ingestion. | | |
| Acute Lethality | Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below: Acute oral toxicity (LD50): >5000 mg/kg (rat); Acute dermal toxicity (LD50): >2000 mg/kg (rabbit); Acute inhalation toxicity (LC50): >2500 mg/m ³ /4h (rat) | | |
| Chronic or Other Toxic Effects | | | |
| Dermal Route: | Prolonged or repeated contact may defat and dry skin, and cause dermatitis. Short-term exposure is expected to cause only slight irritation, if any. | | |
| Inhalation Route: | With its relatively low vapour pressure, this product is not expected to be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. | | |
| Oral Route: | Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs). May produce a laxative effect. | | |
| Eye Irritation/Inflammation: | Short-term exposure is expected to cause only slight irritation, if any. | | |
| Immunotoxicity: | Not available. | | |
| Skin Sensitization: | Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components. | | |
| Respiratory Tract Sensitization: | Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components. | | |
| Mutagenic: | This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen. | | |
| Reproductive Toxicity: | This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin. | | |
| Teratogenicity/Embryotoxicity: | This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin. | | |
| Carcinogenicity (ACGIH): | This product is not known to contain any chemicals at reportable quantities that are listed as Group A1 or A2 carcinogens by ACGIH. | | |
| Carcinogenicity (IARC): | This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC. | | |
| Carcinogenicity (NTP): | This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP. | | |
| Carcinogenicity (IRIS): | This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS. | | |
| Carcinogenicity (OSHA): | This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA. | | |
| Other Considerations | No additional remark. | | |

Section 12. Ecological Information

| | | | |
|---------------------------|-----------------------|--|----------------|
| Environmental Fate | Not available | Persistence/Bioaccumulation Potential | Not available |
| BOD5 and COD | Not available. | Products of Biodegradation | Not available. |
| Additional Remarks | No additional remark. | | |



Section 13. Disposal Considerations

| | |
|-----------------------|--|
| Waste Disposal | Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations. |
|-----------------------|--|

Section 14. Transport Information

| | | | |
|---------------------------|---|---|-----------------|
| TDG Classification | Not a hazardous material for transport according to the TDG Regulations. (Canada) | Special Provisions for Transport | Not applicable. |
|---------------------------|---|---|-----------------|

Section 15. Regulatory Information

| | | | | | | | | | | | | | | | | | |
|----------------------------------|---|--|--|---------------------------------|---|---|---|------------|---|---------------------|---|----------------------|--|---|--|---------------|--|
| Other Regulations | | This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL. | | | | | | | | | | | | | | | |
| | | All components of this formulation are listed on the US EPA-TSCA Inventory. | | | | | | | | | | | | | | | |
| | | This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. | | | | | | | | | | | | | | | |
| | | Please contact Product Safety for more information. | | | | | | | | | | | | | | | |
| DSD/DPD (Europe) | | Not classified under the Dangerous Substances or Dangerous Preparations Directives. | | HCS (U.S.A.) | | Does not meet the definitions of a health or physical hazard according to the OSHA - Hazard Communication Standard. (United States) | | | | | | | | | | | |
| ADR (Europe) (Pictograms) | |  | | DOT (U.S.A) (Pictograms) | |  | | | | | | | | | | | |
| HMIS (U.S.A.) | | <table><tr><td>Health Hazard</td><td>1</td></tr><tr><td>Fire Hazard</td><td>1</td></tr><tr><td>Reactivity</td><td>0</td></tr><tr><td>Personal Protection</td><td>B</td></tr></table> | | Health Hazard | 1 | Fire Hazard | 1 | Reactivity | 0 | Personal Protection | B | NFPA (U.S.A.) | | <div><div><div>1</div><div>1</div><div>0</div><div>0</div></div><div>HealthFire HazardReactivitySpecific hazard</div></div> | | Rating | 0 Insignificant 1 Slight 2 Moderate 3 High 4 Extreme |
| Health Hazard | 1 | | | | | | | | | | | | | | | | |
| Fire Hazard | 1 | | | | | | | | | | | | | | | | |
| Reactivity | 0 | | | | | | | | | | | | | | | | |
| Personal Protection | B | | | | | | | | | | | | | | | | |

Section 16. Other Information

| | | | |
|-------------------------|---|--|--|
| References | Available upon request. * Marque de commerce de Petro-Canada - Trademark | | |
| Glossary | <div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days CAN/CGA B149.2 Propane Installation Code CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemicals Hazard Information and Packaging Approved Supply List COD5 - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations DOT - Department of Transport DSCL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe) DSL - Domestic Substance List EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning and Community Right to Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer </div> <div style="width: 48%;"> IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NAERG'96 - North American Emergency Response Guide Book (1996) NFPA - National Fire Prevention Association NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act SD - Single Dose STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration TLm - Median Tolerance Limit TLV-TWA - Threshold Limit Value-Time Weighted Average TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System </div> </div> | | |
| For Copy of MSDS | <p>The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:</p> <p>Internet: www.petro-canada.ca/msds</p> | | |
| | <p>Prepared by Product Safety - JDW on 5/31/2004.</p> <p>Data entry by Product Safety - RS.</p> | | |

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:
1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.