

## Safety Data Sheet



## Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

### 1.1 Product identifier

<b>Product Name</b>	• <b>Acetaldehyde in Nitrogen</b>
<b>Synonyms</b>	• Acetaldehyde (100-500 ppm), Nitrogen (Balance)
<b>Product Code</b>	• M-20222/E-1

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

<b>Relevant identified use(s)</b>	• Please provide product use
-----------------------------------	------------------------------

### 1.3 Details of the supplier of the safety data sheet

<b>Manufacturer</b>	• Air Liquide 2700 Post Oak Blvd. Houston, TX 77056 United States www.us.airliquide.com sds@airliquide.com
<b>Telephone (Technical)</b>	• 713-896-2896
<b>Telephone (Technical)</b>	• 800-819-1704

### 1.4 Emergency telephone number

<b>Manufacturer</b>	• 800-424-9300 - CHEMTREC
<b>Manufacturer</b>	• +1 703-527-3887 - Outside United States

## Section 2: Hazards Identification

### EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]  
According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

### 2.1 Classification of the substance or mixture

<b>CLP</b>	• Compressed Gas - H280
<b>DSD/DPD</b>	• Not classified

### 2.2 Label Elements

CLP

#### WARNING



### Precautionary statements

**Storage/Disposal** • P403 - Store in a well-ventilated place.

**DSD/DPD**

**Risk phrases** ● No label element(s) required

**2.3 Other Hazards**

**CLP** ● This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.  
According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

**DSD/DPD** ● This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.  
According to European Directive 1999/45/EC this preparation is not considered dangerous.

**United States (US)**

According to OSHA 29 CFR 1910.1200 HCS

**2.1 Classification of the substance or mixture**

**OSHA HCS 2012** ● Compressed Gas - H280  
Simple Asphyxiant

**2.2 Label elements**

**OSHA HCS 2012**

**WARNING**

**Hazard statements** ● Contains gas under pressure; may explode if heated - H280  
May displace oxygen and cause rapid suffocation.

**Precautionary statements**

**Storage/Disposal** ● Store in a well-ventilated place. - P403

**2.3 Other hazards**

**OSHA HCS 2012** ● Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

**Canada**

According to WHMIS

**2.1 Classification of the substance or mixture**

**WHMIS** ● Compressed Gas - A

**2.2 Label elements**

**WHMIS**




● Compressed Gas - A

**2.3 Other hazards**

**WHMIS** ● This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.  
In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

## 2.4 Other information



## Section 3 - Composition/Information on Ingredients

### 3.1 Substances

- Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

### 3.2 Mixtures

Composition				
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive
Acetaldehyde	CAS:75-07-0 EC Number:200-836-8 EU Index:605-003-00-6	100ppm TO 500ppm	Ingestion/Oral-Rat LD50 • 661 mg/kg Skin-Rabbit LD50 • 3540 mg/kg Inhalation-Rat LC50 • 13300 ppm 4 Hour(s)	EU DSD/DPD: Annex I - F+; R12 Xi; R36/37 Carc.Cat.3; R40 EU CLP: Annex VI - Flam. Liq. 1, H224; Eye Irrit. 2, H319; Carc. 2, H351; STOT SE 3, H335 OSHA HCS 2012: Flam. Liq. 1; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3: Resp. Irrit. & Narc.; Acute Tox. 4 (orl); Carc. 2
Nitrogen	CAS:7727-37-9 EINECS:231-783-9	Balance	NDA	EU DSD/DPD: Not Classified EU CLP: Self Classified - Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.

See Section 16 for full text of H-statements and R-phrases.

## Section 4 - First Aid Measures

### 4.1 Description of first aid measures

#### Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

#### Skin

- Although exposure is unlikely, in case of contact immediately flush skin with running water. If skin irritation develops get medical advice/attention.

#### Eye

- First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If irritation develops and persists, get medical attention.

#### Ingestion

- Ingestion is not considered a potential route of exposure.

### 4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. A potential health hazard associated with this gas is anoxia.

## 4.4 Other information

- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. **RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT.** At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after over-exposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

## Section 5 - Firefighting Measures

### 5.1 Extinguishing media

**Suitable Extinguishing Media** • Use extinguishing agent suitable for type of surrounding fire.

**Unsuitable Extinguishing Media** • No data available

### 5.2 Special hazards arising from the substance or mixture

**Unusual Fire and Explosion Hazards** • Containers may explode when heated. Ruptured cylinders may rocket.

**Hazardous Combustion Products** • No data available

### 5.3 Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.  
Always wear thermal protective clothing when handling refrigerated/cryogenic liquids. Wear positive pressure self-contained breathing apparatus (SCBA).  
Move containers from fire area if you can do it without risk.  
**FIRE:** If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.  
**FIRE INVOLVING TANKS:** Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.  
**FIRE INVOLVING TANKS:** Cool containers with flooding quantities of water until well after fire is out.  
**FIRE INVOLVING TANKS:** Do not direct water at source of leak or safety devices; icing may occur.  
**FIRE INVOLVING TANKS:** Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.  
**FIRE INVOLVING TANKS:** ALWAYS stay away from tanks engulfed in fire.

## Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**Personal Precautions** • Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

**Emergency Procedures** • Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. Do not direct water at spill or source of leak. **LARGE SPILL:** Consider initial downwind evacuation for at least 500 meters (1/3 mile)

### 6.2 Environmental precautions

- Prevent spreading of vapors through sewers, ventilation systems and confined areas.

### 6.3 Methods and material for containment and cleaning up

**Containment/Clean-up Measures** • Stop leak if you can do it without risk. Do not direct water at spill or source of leak.

Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.

If possible, turn leaking containers so that gas escapes rather than liquid.

Isolate area until gas has dispersed.

Ventilate the area.

## 6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

## Section 7 - Handling and Storage

### 7.1 Precautions for safe handling

#### Handling

- Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Wear appropriate personal protective equipment, avoid direct contact. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

- Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over.

### 7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

## Section 8 - Exposure Controls/Personal Protection

### 8.1 Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	China	France
Acetaldehyde (75-07-0)	Ceilings	25 ppm Ceiling	25 ppm Ceiling	25 ppm Ceiling; 45 mg/m <sup>3</sup> Ceiling	45 mg/m <sup>3</sup> Ceiling [MAC]	Not established
	TWAs	Not established	Not established	Not established	Not established	100 ppm TWA [VME]; 180 mg/m <sup>3</sup> TWA [VME]
Exposure Limits/Guidelines (Con't.)						
	Result	Germany DFG	Germany TRGS	Ireland	Israel	OSHA
Acetaldehyde (75-07-0)	STELs	Not established	Not established	25 ppm STEL; 45 mg/m <sup>3</sup> STEL	Not established	Not established
	TWAs	Not established	50 ppm TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, ceiling factor 2, exposure factor 1); 91 mg/m <sup>3</sup> TWA AGW (The risk of damage to the embryo or fetus can	25 ppm TWA; 45 mg/m <sup>3</sup> TWA	Not established	200 ppm TWA; 360 mg/m <sup>3</sup> TWA

			be excluded when AGW and BGW values are observed, ceiling factor 2, exposure factor 1)			
	Ceilings	50 ppm Peak; 91 mg/m3 Peak	Not established	Not established	25 ppm Ceiling	Not established
	MAKs	50 ppm TWA MAK; 91 mg/m3 TWA MAK	Not established	Not established	Not established	Not established

**Exposure Limits/Guidelines (Con't.)**

	Result	OSHA Vacated	Portugal	Spain	Sweden
Acetaldehyde (75-07-0)	Ceilings	Not established	25 ppm Ceiling [VLE-CM]	Not established	Not established
	STELs	150 ppm STEL; 270 mg/m3 STEL	Not established	25 ppm STEL [VLA-EC]; 46 mg/m3 STEL [VLA-EC]	50 ppm STV; 90 mg/m3 STV
	TWAs	100 ppm TWA; 180 mg/m3 TWA	Not established	Not established	25 ppm LLV; 45 mg/m3 LLV

**Exposure Control Notations**

**Portugal**

- Acetaldehyde (75-07-0): **Carcinogens:** (A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans)
- Nitrogen (7727-37-9): **Simple Asphyxiants:** (Simple Asphyxiant)

**Italy**

- Acetaldehyde (75-07-0): **Carcinogens:** (Category 3 Carcinogen)

**France**

- Acetaldehyde (75-07-0): **Carcinogens:** (Carcinogen category 3)

**Ireland**

- Nitrogen (7727-37-9): **Simple Asphyxiants:** (Asphyxiant)

**Spain**

- Nitrogen (7727-37-9): **Simple Asphyxiants:** (simple asphyxiant)

**Sweden**

- Acetaldehyde (75-07-0): **Carcinogens:** (Carcinogen)

**Germany DFG**

- Acetaldehyde (75-07-0): **Carcinogens:** (Category 5 (low carcinogenic potency)) | **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to)

**8.2 Exposure controls**

**Engineering Measures/Controls**

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Personal Protective Equipment**

**Respiratory**

- Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

**Eye/Face**

- Wear safety glasses.

**Skin/Body**

- Wear leather gloves when handling cylinders.

**Environmental Exposure Controls**

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

**Key to abbreviations**

ACGIH = American Conference of Governmental Industrial Hygiene

OSHA = Occupational Safety and Health Administration

LLV = Limit Level Value is the exposure limit for 8-hour work day  
 MAK = Maximale Arbeitsplatz Konzentration is the maximum permissible concentration

STEL = Short Term Exposure Limits are based on 15-minute exposures  
 TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

## Section 9 - Physical and Chemical Properties

### 9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Gas	Appearance/Description	Colorless gas with a fruity, pungent odor.
Color	Colorless	Odor	Fruity, pungent.
Odor Threshold	2.3 ppm		
General Properties			
Boiling Point	Data lacking	Melting Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	Data lacking	Water Solubility	1.485 cm <sup>3</sup> /100 cm <sup>3</sup>
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	0.967 Air=1
Evaporation Rate	Data lacking		
Flammability			
Flash Point	Data lacking	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Nonflammable Gas.		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

### 9.2 Other Information

- No additional physical and chemical parameters noted.

## Section 10: Stability and Reactivity

### 10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

- Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

### 10.4 Conditions to avoid

- Excess heat.

### 10.5 Incompatible materials

- Nitrogen reacts with Li, Nd, and Ti at high temperatures. Oxidizing agents, acids and bases. Also reacts violently with oxidizers and organic materials such as alcohol's, amines, acetones and ammonia.

## 10.6 Hazardous decomposition products

- None known.

## Section 11 - Toxicological Information

### 11.1 Information on toxicological effects

Components	
Acetaldehyde (100ppm TO 500ppm)	75-07-00 <b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 661 mg/kg; <i>Peripheral Nerve and Sensation:</i> <b>Spastic paralysis with or without sensory change</b> ; <i>Behavioral:</i> <b>Altered sleep time (including change in righting reflex)</b> ; <i>Lungs, Thorax, or Respiration:</i> <b>Dyspnea</b> ; Inhalation-Rat LC50 • 13300 ppm 4 Hour(s); <i>Behavioral:</i> <b>Excitement</b> ; <i>Lungs, Thorax, or Respiration:</i> <b>Dyspnea</b> ; Skin-Rabbit LD50 • 3540 mg/kg; <b>Irritation:</b> Eye-Rabbit • 40 mg • Severe irritation; Skin-Rabbit • 500 mg-Open • Mild irritation

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-SE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met

### Potential Health Effects

#### Inhalation

##### Acute (Immediate)

- This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements,

- respiratory collapse and death.
- Chronic (Delayed)**
  - No data available
- Skin**
- Acute (Immediate)**
  - Under normal conditions of use, no health effects are expected.
- Chronic (Delayed)**
  - Under normal conditions of use, no health effects are expected.
- Eye**
- Acute (Immediate)**
  - Under normal conditions of use, no health effects are expected.
- Chronic (Delayed)**
  - Under normal conditions of use, no health effects are expected.
- Ingestion**
- Acute (Immediate)**
  - Ingestion is not anticipated to be a likely route of exposure to this product.
- Chronic (Delayed)**
  - Ingestion is not anticipated to be a likely route of exposure to this product.
- Carcinogenic Effects**
  - This material does contain a component that may cause cancer, however based on regulatory criteria this material is not classified as a carcinogen.

Carcinogenic Effects			
	CAS	IARC	NTP
Acetaldehyde	75-07-0	Group 1-Carcinogenic	Reasonably Anticipated to be Human Carcinogen

**Key to abbreviations**

LC = Lethal Concentration

LD = Lethal Dose

## Section 12 - Ecological Information

### 12.1 Toxicity

- Material data lacking.

### 12.2 Persistence and degradability

- Material data lacking.

### 12.3 Bioaccumulative potential

- Material data lacking.

### 12.4 Mobility in Soil

- Material data lacking.

### 12.5 Results of PBT and vPvB assessment

- PBT and vPvB assessment has not been conducted for this material.

### 12.6 Other adverse effects

- No studies have been found.

## Section 13 - Disposal Considerations

### 13.1 Waste treatment methods

**Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Packaging waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1956	Compressed gas, n.o.s (Nitrogen, Acetaldehyde)	2.2	NDA	NDA
TDG	UN1956	COMPRESSED GAS, N.O.S. (Nitrogen, Acetaldehyde)	2.2	NDA	Potential Marine Pollutant
IMO/IMDG	UN1956	COMPRESSED GASES, N.O.S. (Nitrogen, Acetaldehyde)	2.2	NDA	NDA
IATA/ICAO	UN1956	Compressed gases, n.o.s. (Nitrogen, Acetaldehyde)	2.2	NDA	NDA

### 14.6 Special precautions for user

- Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Not relevant.

## Section 15 - Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Pressure(Sudden Release of), Acute

State Right To Know				
Component	CAS	MA	NJ	PA
Acetaldehyde	75-07-0	Yes	Yes	Yes
Nitrogen	7727-37-9	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS
Acetaldehyde	75-07-0	Yes	No	Yes	Yes	No
Nitrogen	7727-37-9	Yes	No	Yes	Yes	No

Inventory (Con't.)		
Component	CAS	TSCA
Acetaldehyde	75-07-0	Yes
Nitrogen	7727-37-9	Yes

## Canada

### Labor

#### Canada - WHMIS - Classifications of Substances

- |                |           |         |
|----------------|-----------|---------|
| • Acetaldehyde | 75-07-0   | B2, D2A |
| • Nitrogen     | 7727-37-9 | A       |

**Canada - WHMIS - Ingredient Disclosure List**

• Acetaldehyde	75-07-0	1 %
• Nitrogen	7727-37-9	Not Listed

**Environment****Canada - CEPA - Priority Substances List**

• Acetaldehyde	75-07-0	Priority Substance List 2 (substance considered toxic)
• Nitrogen	7727-37-9	Not Listed

**China****Environment****China - Ozone Depleting Substances - First Schedule**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**China - Ozone Depleting Substances - Second Schedule**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**China - Ozone Depleting Substances - Third Schedule**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**Other****China - Annex I & II - Controlled Chemicals Lists**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**China - Dangerous Goods List**

• Acetaldehyde	75-07-0	
• Nitrogen	7727-37-9	(compressed or refrigerated liquid)

**China - Export Control List - Part I Chemicals**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**Europe****Other****EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification**

• Acetaldehyde	75-07-0	F+; R12 Xi; R36/37 Carc.Cat.3; R40
• Nitrogen	7727-37-9	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling**

• Acetaldehyde	75-07-0	F+ Xn R:12-36/37-40 S:(2)-16- 33-36/37
• Nitrogen	7727-37-9	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases**

• Acetaldehyde	75-07-0	S:(2)-16-33-36/37
• Nitrogen	7727-37-9	Not Listed

**Germany****Environment****Germany - TA Luft - Types and Classes**

• Acetaldehyde	75-07-0	organic Substance: 5.2.5, Class I
• Nitrogen	7727-37-9	Not Listed

**Germany - Water Classification (VwVwS) - Annex 1**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	ID Number 1351, not considered hazardous to water

**Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes**

• Acetaldehyde	75-07-0	ID Number 1, hazard class 1 - low hazard to waters
• Nitrogen	7727-37-9	Not Listed

**Germany - Water Classification (VwVwS) - Annex 3**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**Other****Germany - Specifically Regulated Chemicals in TRGS**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**Portugal****Other****Portugal - Prohibited Substances**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**United Kingdom****Environment****United Kingdom - Pollution Inventory - Schedule 1 - Thresholds for Releases to Air**

• Acetaldehyde	75-07-0	100 kg
• Nitrogen	7727-37-9	Not Listed

**Other****United Kingdom - Workplace Exposure Limits (WELs) - Substances in Review**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**United Kingdom - List of Dangerous Substances in Water**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**United States**

**Labor**

**U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• Acetaldehyde	75-07-0	2500 lb TQ
• Nitrogen	7727-37-9	Not Listed

**U.S. - OSHA - Specifically Regulated Chemicals**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**Environment**

**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Acetaldehyde	75-07-0	
• Nitrogen	7727-37-9	Not Listed

**U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities**

• Acetaldehyde	75-07-0	1000 lb final RQ; 454 kg final RQ
• Nitrogen	7727-37-9	Not Listed

**U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

• Acetaldehyde	75-07-0	0.1 % de minimis concentration
• Nitrogen	7727-37-9	Not Listed

**U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing**

• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

**U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics**

• Acetaldehyde	75-07-0	waste number U001 (Ignitable waste)
• Nitrogen	7727-37-9	Not Listed

**United States - California**

**Environment**

**U.S. - California - Proposition 65 - Carcinogens List**

• Acetaldehyde	75-07-0	carcinogen, initial date 4/1/88
• Nitrogen	7727-37-9	Not Listed
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>		
• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed
<b>U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)</b>		
• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed
<b>U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)</b>		
• Acetaldehyde	75-07-0	90 µg/day NSRL (inhalation)
• Nitrogen	7727-37-9	Not Listed
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>		
• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Male</b>		
• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

## United States - Pennsylvania

### Labor

<b>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List</b>		
• Acetaldehyde	75-07-0	
• Nitrogen	7727-37-9	Not Listed
<b>U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances</b>		
• Acetaldehyde	75-07-0	Not Listed
• Nitrogen	7727-37-9	Not Listed

## 15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

## 15.3 Other Information

- WARNING: This product contains a chemical known to the State of California to cause cancer.

## Section 16 - Other Information

### Relevant Phrases (code & full text)

- H224 - Extremely flammable liquid and vapour
- H319 - Causes serious eye irritation
- H335 - May cause respiratory irritation
- H351 - Suspected of causing cancer.
- R12 - Extremely flammable.
- R36/37 - Irritating to eyes and respiratory system.
- R40 - Limited evidence of a carcinogenic effect.

### Last Revision Date

- 08/September/2014

### Preparation Date

- 08/September/2014

### Disclaimer/Statement of

- To the best of Air Liquide's knowledge, the information contained herein is reliable and

**Liability**

accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

**Key to abbreviations**

NDA = No Data Available

---