



# CITGO COMPRESSORGARD® PAG 200

## Material Safety Data Sheet

CITGO Petroleum Corporation  
P.O. Box 3758  
Tulsa, OK 74102-3758

MSDS No. 632539001  
Revision Date 10/11/2000

Hazard Rankings		
	HMIS	NFPA
Health Hazard	* 1	1
Fire Hazard	1	1
Reactivity	0	0

\* = Chronic Health Hazard

**IMPORTANT:** Read this MSDS before handling or disposing of this product and pass this information on to employees, customers and users of this product.

Emergency Overview			
Physical State	Liquid.		
Color	Clear to light amber.	Odor	Characteristic.
<b>WARNING:</b> Can cause eye, skin and respiratory tract irritation. Vapor or mists of the product and thermal degradation products can be harmful, if inhaled.			

Protective Equipment
Minimum Requirements See Section 8 for Details
 


### SECTION 1: IDENTIFICATION

Trade Name	CITGO COMPRESSORGARD® PAG 200	Technical Contact	(918) 495-5933
Product Number	632539001	Medical Emergency	(918) 495-4700
CAS Number	Mixture.	CHEMTREC Emergency	(800) 424-9300
Product Family	Compressor Lubricant		
Synonyms	Synthetic Lubricant; High-Pressure Reciprocating Compressor Lubricant; Former ILS Code: 32539; CITGO SAP Product Code No.: 632539001;		

### SECTION 2: COMPOSITION

Component Name(s)	CAS Registry No.	Concentration (%)
1) Polyoxyalkylene glycol	9038-95-3	95 - 100
2) Proprietary Ingredients	Proprietary Mixture	0 - 5

### SECTION 3: HAZARDS IDENTIFICATION

Also see Emergency Overview and Hazard Ratings on the top of Page 1 of this MSDS.

Major Route(s) of Entry Skin contact.

#### Signs and Symptoms of Acute Exposure

**Inhalation** No significant adverse health effects are expected to occur upon short-term exposure at ambient temperatures. Overexposure to vapor, aerosol or mist generated at elevated temperatures or in enclosed spaces can cause respiratory tract irritation, dizziness and nausea. Overexposure can result in inhalation of harmful amounts of the material.

## CITGO COMPRESSORGARD® PAG 200

<b>Eye Contact</b>	Mild to moderate eye irritation can result from short-term contact with liquid, mist, or vapor.
<b>Skin Contact</b>	No skin irritation is expected from short-term exposure. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and rash (dermatitis).
<b>Ingestion</b>	If swallowed, no significant adverse health effects are anticipated. Ingestion can cause mild irritation to the digestive tract or cause a laxative effect.
<b>Chronic Health Effects Summary</b>	Repeated or prolonged exposure can result in skin, eye or respiratory tract irritation, nausea or vomiting.
<b>Conditions Aggravated by Exposure</b>	Personnel with pre-existing skin disorders should avoid repeated or prolonged contact with this product.
<b>Target Organs</b>	Skin.
<b>Carcinogenic Potential</b>	This product does not contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC, or NTP.

OSHA Hazard Classification is indicated by an "X" in the box adjacent to the hazard title. If no "X" is present, the product does not exhibit the hazard as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).							
OSHA Health Hazard Classification				OSHA Physical Hazard Classification			
Irritant	<input checked="" type="checkbox"/>	Toxic	<input type="checkbox"/>	Combustible	<input type="checkbox"/>	Explosive	<input type="checkbox"/>
Sensitizer	<input type="checkbox"/>	Highly Toxic	<input type="checkbox"/>	Flammable	<input type="checkbox"/>	Oxidizer	<input type="checkbox"/>
Corrosive	<input type="checkbox"/>	Carcinogenic	<input type="checkbox"/>	Compressed Gas	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>
						Pyrophoric	<input type="checkbox"/>
						Water-reactive	<input type="checkbox"/>
						Unstable	<input type="checkbox"/>

### SECTION 4: FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

<b>Inhalation</b>	Move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, 100 percent humidified oxygen should be administered by a qualified individual. Seek medical attention immediately. Keep the affected individual warm and at rest.
<b>Eye Contact</b>	Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water for at least 15 minutes while occasionally lifting and lowering eyelids. Do not use eye ointment unless directed to by a physician. Seek medical attention if excessive tearing, irritation, or pain persists.
<b>Skin Contact</b>	Remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with soap and water. Seek medical attention if tissue appears damaged or if irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods. If material is injected under the skin, into muscle, or into the bloodstream, seek medical attention immediately.
<b>Ingestion</b>	Do not induce vomiting unless directed to by a physician. Do not give anything to drink unless directed to by a physician. Never give anything by mouth to a person who is not fully conscious. If large amounts are swallowed or irritation or discomfort occurs, seek medical attention immediately.
<b>Notes to Physician</b>	Treat symptomatically.

### SECTION 5: FIRE FIGHTING MEASURES

<b>NFPA Flammability Classification</b>	NFPA Class-IIIB combustible material. Slightly combustible!		
<b>Flash Point Method</b>	OPEN CUP: 268°C (514°F) (Cleveland.).		
<b>Lower Flammable Limit</b>	No data.	<b>Upper Flammable Limit</b>	No data.
<b>Autoignition Temperature</b>	Not available.		
<b>Hazardous Combustion Products</b>	Combustion gases may contain carbon monoxide, carbon dioxide, and irritating or acrid combustion products.		

## CITGO COMPRESSORGARD® PAG 200

<b>Special Properties</b>	Do not direct a solid stream of water or foam into hot, burning pools as this may cause frothing and increase the intensity of the fire.
<b>Extinguishing Media</b>	Use dry chemical, "alcohol" foam or Carbon Dioxide. Water may be ineffective as an extinguishing medium, but may be used to cool fire-exposed containers.
<b>Fire Fighting Protective Clothing</b>	Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Withdraw immediately from the area if there is a rising sound from a venting safety device or discoloration of vessels, tanks, or pipelines.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this MSDS.

Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard; do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spill as soon as possible. In natural environments, seek cleanup advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.

### SECTION 7: HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapor, aerosol and mist. Do not store in open or unlabeled containers. Use with adequate ventilation. Wash thoroughly after handling. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues. FOR INDUSTRIAL USE ONLY.
<b>Storage</b>	Keep container closed. Do not store with strong oxidizing agents. Do not store at temperatures above 120° F or in direct sunlight for extended periods of time. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

### SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

<b>Engineering Controls</b>	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits (see below). An eye wash station and safety shower should be located near the work-station.
<b>Personal Protective Equipment</b>	Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. The following pictograms represent the minimum requirements for personal protective equipment. For certain operations, additional PPE may be required.



<b>Eye Protection</b>	Safety glasses with side shields are recommended as a minimum protection. During transfer operations or when there is a likelihood of misting, splashing, or spraying, chemical goggles should be worn. Suitable eye wash water should be readily available.
<b>Hand Protection</b>	Use gloves constructed of glycol-resistant materials such as butyl rubber if frequent or prolonged contact is expected. Use heat-protective gloves when handling product at elevated temperatures.
<b>Body Protection</b>	Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing may include long-sleeve outer garment, apron, or lab coat. If significant contact occurs, remove oil-contaminated clothing as soon as possible and promptly shower. Launder contaminated before reuse or discard. Wear heat protective boots and protective clothing when handling material at elevated temperatures.

## CITGO COMPRESSORGARD® PAG 200

**Respiratory Protection** Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).

**General Comments** Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners. Since specific exposure standards/control limits have not been established for this product, the "Oil Mist, Mineral" exposure limits shown below are suggested as minimum control guidelines.

### Occupational Exposure Guidelines

Substance	Applicable Workplace Exposure Levels
1) Oil Mist, Mineral	TWA: 5 STEL: 10 (mg/M <sup>3</sup> ) from ACGIH (TLV) TWA: 5 (mg/M <sup>3</sup> ) from OSHA (PEL) TWA: 5 STEL: 10 (mg/M <sup>3</sup> ) from NIOSH

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State</b>	Liquid.	<b>Color</b>	Clear to light amber.	<b>Odor</b>	Characteristic.
<b>Specific Gravity</b>	Not available.	<b>pH</b>	Not Applicable.	<b>Vapor Density</b>	Not available.
<b>Boiling Point/Range</b>	Not available.	<b>Melting/Freezing Point</b>			Not available.
<b>Vapor Pressure</b>	<1 mm of Hg (@ 20°C)	<b>Viscosity (cSt @ 40°C)</b>			197
<b>Solubility in Water</b>	Soluble in cold water.	<b>Volatile Characteristics</b>			Slightly volatile.
<b>Additional Properties</b>	API Gravity (ASTM D287) = AP 3.2 @ 60° F Density = 8.76 Lbs/gal. Viscosity (ASTM D2161) =996 SUS @ 100° F				

## SECTION 10: STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable.	<b>Hazardous Polymerization</b>	Not expected to occur.
<b>Conditions to Avoid</b>	Keep away from extreme heat, sparks, open flame, and strongly oxidizing conditions.		
<b>Materials Incompatibility</b>	Strong acids, alkalis, and oxidizers such as liquid chlorine and oxygen. This material is incompatible with materials that are reactive with hydroxyl compounds.		
<b>Hazardous Decomposition Products</b>	No additional hazardous decomposition products were identified other than the combustion products identified in Section 5 of this MSDS.		

## SECTION 11: TOXICOLOGICAL INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this MSDS.

### Toxicity Data

#### Polyoxyalkylene Glycol:

Oral: Lethargy and gastrointestinal discomfort.  
Oral LD50 (rat): 12.3 mL/kg.  
Dermal LD50 (rabbit): 20 mL/Kg.  
Skin and Eye: Mild irritant.

#### Synthetic Compressor Lubricants:

This product can cause mild eye and skin irritation. Inhalation of vapors or mists can cause mild respiratory tract irritation. Repeated or prolonged exposure can cause irritation, nausea and vomiting.

**SECTION 12: ECOLOGICAL INFORMATION**


<b>Ecotoxicity</b>	Ecotoxicity data are not available for this product.
<b>Environmental Fate</b>	This product is soluble in water and is expected to readily disperse in marine environments.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.**

Conditions of use may cause this material to become a "hazardous waste", as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact the RCRA/Superfund Hotline at (800) 424-9346 or your regional US EPA office for guidance concerning case specific disposal issues. Empty drums and pails retain residue. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose this product's empty container to heat, flame, or other ignition sources. DO NOT attempt to clean it. Empty drums and pails should be drained completely, properly bunged or sealed, and promptly sent to a reconditioner.

**SECTION 14: TRANSPORT INFORMATION**

<b>DOT Status</b>	Not a U.S. Department of Transportation regulated material.		
<b>Proper Shipping Name</b>	Hydraulic Fluids other than Petroleum		
<b>Hazard Class</b>	Not a DOT controlled material (United States).	<b>Packing Group(s)</b>	Not applicable.
		<b>UN/NA ID</b>	Not applicable.
<b>Reportable Quantity</b>	A Reportable Quantity (RQ) has not been established for any components of this material.		
<b>Placards</b>		<b>Emergency Response Guide No.</b>	Not applicable.
		<b>HAZMAT STCC No.</b>	Not available.
		<b>MARPOL III Status</b>	Not a DOT "Marine Pollutant" per 49 CFR 171.8.

**SECTION 15: REGULATORY INFORMATION**

<b>TSCA Inventory</b>	This product and/or its components are listed on the Toxic Substance Control Act (TSCA) inventory.
<b>SARA 302/304</b>	The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.
<b>SARA 311/312</b>	The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Acute (Immediate) Health Hazard, Chronic (Delayed) Health Hazard
<b>SARA 313</b>	This product contains the following components in concentrations above de minimis levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA: No components were identified.

## CITGO COMPRESSORGARD® PAG 200

<b>CERCLA</b>	The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. This product or refinery stream is not known to contain chemical substances subject to this statute. However, it is recommended that you contact state and local authorities to determine if there are any other reporting requirements in the event of a spill.
<b>CWA</b>	This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.
<b>California Proposition 65</b>	This product is not known to contain the any components for which the State of California has found to cause cancer, birth defects or other reproductive harm.
<b>New Jersey Right-to-Know Label</b>	For New Jersey R-T-K labeling requirements, refer to components listed in Section 2.
<b>Additional Regulatory Remarks</b>	No additional regulatory remarks.

## SECTION 16: OTHER INFORMATION

Refer to the top of Page 1 for the HMIS and NFPA Hazard Ratings for this product.

### REVISION INFORMATION

<b>Version Number</b>	1.0
<b>Revision Date</b>	10/11/2000
<b>Print Date</b>	Printed on 10/11/2000.

### ABBREVIATIONS

AP = Approximately Established	EQ = Equal	> = Greater Than	< = Less Than	NA = Not Applicable	ND = No Data	NE = Not
ACGIH = American Conference of Governmental Industrial Hygienists				AIHA = American Industrial Hygiene Association		
IARC = International Agency for Research on Cancer				NTP = National Toxicology Program		
NIOSH = National Institute of Occupational Safety and Health				OSHA = Occupational Safety and Health Administration		
NPCA = National Paint and Coating Manufacturers Association				HMIS = Hazardous Materials Information System		
NFPA = National Fire Protection Association				EPA = Environmental Protection Agency		

### DISCLAIMER OF LIABILITY

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

\*\*\*\*\* END OF MSDS \*\*\*\*\*