

# SAFETY DATA SHEET

## 1. Identification

**Material name:** TREMPRO 651 ALUMINUM STONE 30CTG  
**Material:** 651851 323

**Recommended use and restriction on use**

**Recommended use:** Sealant  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

Tremco U.S Sealants  
3735 Green Road  
Beachwood OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:** 216-292-5000  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Serious Eye Damage/Eye Irritation	Category 2A
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

#### Unknown toxicity - Health

Acute toxicity, oral	80.86 %
Acute toxicity, dermal	81.44 %
Acute toxicity, inhalation, vapor	99.95 %
Acute toxicity, inhalation, dust or mist	99.97 %

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	96.29 %
Chronic hazards to the aquatic environment	100 %

### Label Elements

**Hazard Symbol:**



**Signal Word:**

Danger

**Hazard Statement:** Causes serious eye irritation.  
May cause genetic defects.  
May cause cancer.

**Precautionary Statement:**

**Prevention:** Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

**Response:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	40 - 70%
Stoddard solvent (Mineral Spirits)	8052-41-3	10 - 30%
Talc	14807-96-6	5 - 10%
Xylene	1330-20-7	1 - 5%
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.5 - 1.5%
Aluminum oxide	1344-28-1	0.1 - 1%
1,3,5-Trimethylbenzene	108-67-8	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

**Ingestion:** Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

**Most important symptoms/effects, acute and delayed**

**Symptoms:** May cause skin and eye irritation.

**Indication of immediate medical attention and special treatment needed**

**Treatment:** Symptoms may be delayed.

**5. Fire-fighting measures**

**General Fire Hazards:** No unusual fire or explosion hazards noted.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** No data available.

**Methods and material for containment and cleaning up:** Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

## 7. Handling and storage

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

**Conditions for safe storage, including any incompatibilities:** Store locked up.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Talc - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
Talc	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Total dust.	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values

			(2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,3,5-Trimethylbenzene	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)

Chemical name	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for

			Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable particles.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc	TWAEV	2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWAEV	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

**Biological Limit Values**

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

**Appropriate Engineering Controls**

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

**Individual protection measures, such as personal protective equipment**

**General information:**

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Eye/face protection:**

Wear safety glasses with side shields (or goggles).

**Skin Protection**

**Hand Protection:**

Use suitable protective gloves if risk of skin contact.

<b>Other:</b>	Wear suitable protective clothing.
<b>Respiratory Protection:</b>	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
<b>Hygiene measures:</b>	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes.

## 9. Physical and chemical properties

### Appearance

<b>Physical state:</b>	solid
<b>Form:</b>	Paste
<b>Color:</b>	Gray
<b>Odor:</b>	Slight odor
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	No data available.
<b>Evaporation rate:</b>	Slower than Ether
<b>Flammability (solid, gas):</b>	No
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.52
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of Hazardous Reactions:</b>	No data available.
<b>Conditions to Avoid:</b>	Avoid heat or contamination.

<b>Incompatible Materials:</b>	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**11. Toxicological information****Information on likely routes of exposure**

<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.
<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin. Causes mild skin irritation.
<b>Eye contact:</b>	Causes serious eye irritation.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

<b>Oral</b>	
<b>Product:</b>	ATEmix: 37,379.52 mg/kg
<b>Dermal</b>	
<b>Product:</b>	ATEmix: 2,682.24 mg/kg
<b>Inhalation</b>	
<b>Product:</b>	No data available.

<b>Repeated dose toxicity</b>	
<b>Product:</b>	No data available.

<b>Skin Corrosion/Irritation</b>	
<b>Product:</b>	No data available.

<b>Serious Eye Damage/Eye Irritation</b>	
<b>Product:</b>	No data available.

**Specified substance(s):**

Stoddard solvent (Mineral Spirits)	Irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
1,2,4-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating
Ethylbenzene	Irritating
Aluminum oxide	in vivo (Rabbit, 24 hrs): Not irritating
1,3,5-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Talc	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Crystalline Silica Known To Be Human Carcinogen.  
(Quartz)/ Silica  
Sand

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**  
**Product:** No data available.

**In vivo**  
**Product:** No data available.

**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

<b>12. Ecological information</b>
-----------------------------------

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

1,2,4-Trimethylbenzene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality

Ethylbenzene LC 50 (Bluegill (Lepomis macrochirus), 24 h): 70 - 149 mg/l Mortality  
LC 50 (Bluegill (Lepomis macrochirus), 24 h): 112 - 170 mg/l Mortality  
LC 50 (Bluegill (Lepomis macrochirus), 24 h): 113 - 162 mg/l Mortality  
LC 50 (Bluegill (Lepomis macrochirus), 24 h): 66 - 276 mg/l Mortality  
LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 24 h): 11 - 18 mg/l Mortality

1,3,5-Trimethylbenzene LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

1,2,4-Trimethylbenzene LC 50 (Scud (Elasmopus pectinicus), 24 h): 4.89 - 5.62 mg/l Mortality

Ethylbenzene EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication  
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication  
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication  
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication  
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

1,3,5-Trimethylbenzene EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result  
Aluminum oxide NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

**Persistence and Degradability****Biodegradation**

**Product:** No data available.

**BOD/COD Ratio**

**Product:** No data available.

**Bioaccumulative Potential****Bioconcentration Factor (BCF)**

**Product:** No data available.

**Partition Coefficient n-octanol / water (log Kow)**

**Product:** No data available.

**Specified substance(s):**

Stoddard solvent (Mineral Spirits) Log Kow: 3.16 - 7.15

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

**Mobility in Soil:** No data available.

**Other Adverse Effects:** No data available.

**13. Disposal considerations**

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

**14. Transport information**

**TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

**15. Regulatory information****US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Cumene	5000 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Hazard categories**

Immediate (Acute) Health Hazards

Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Copper phthalocyanine	
Cumene	5000 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Calcium Carbonate (Limestone)	500 lbs
Stoddard solvent (Mineral Spirits)	500 lbs
Talc	500 lbs
Xylene	500 lbs
1,2,4-Trimethylbenzene	500 lbs
Ethylbenzene	500 lbs
Crystalline Silica (Quartz)/ Silica Sand	500 lbs
Aluminum oxide	500 lbs
1,3,5-Trimethylbenzene	500 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>
Xylene
Ethylbenzene

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

**US State Regulations****US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

**US. New Jersey Worker and Community Right-to-Know Act**

<u>Chemical Identity</u>
Calcium Carbonate (Limestone)
Stoddard solvent (Mineral Spirits)
Talc
Xylene

**US. Massachusetts RTK - Substance List**

<u>Chemical Identity</u>
Calcium Carbonate (Limestone)
Stoddard solvent (Mineral Spirits)
Talc
Xylene
Crystalline Silica (Quartz)/ Silica Sand

**US. Pennsylvania RTK - Hazardous Substances**

<u>Chemical Identity</u>
Calcium Carbonate (Limestone)
Stoddard solvent (Mineral Spirits)
Talc
Xylene

**US. Rhode Island RTK**

**Chemical Identity**

Xylene

**Other Regulations:**

<b>Regulatory VOC (less water and exempt solvent):</b>	231 g/l
<b>VOC Method 310:</b>	15.22 %

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

<b>16. Other information, including date of preparation or last revision</b>
--

**Revision Date:** 07/30/2015

**Version #:** 1.0

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.