

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 10/01/2019

SECTION 1: Identificat	tion of the substa	ance/mixture and of the company/undertaking
1.1. Product identifier		
Product form	:	Mixture
Product name	:	NAPA Windshield Wash -20 °F
1.2. Relevant identified	d uses of the substan	ce or mixture and uses advised against
Use of the substance/mixture		Windshield washer fluid
	olier of the safety data	a sheet
Old World Industries, LLC 3100 Sanders Road Northbrook, IL 60062 - USA T (847) 559-2000 www.oldworldind.com		
1.4. Emergency teleph	one number	
Emergency number		800 424 9300 (United States); 00 1 703 527 3887 (International) Chemtrec
<b>SECTION 2: Hazards i</b>	dentification	
2.1. Classification of the	ne substance or mixtu	ure
<b>GHS-US</b> classification		
Flammable liquids, Category 3	H226	Flammable liquid and vapor
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (dermal), Category 3	H311	Toxic in contact with skin.
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled.
Specific target organ toxicity — single exposure, Category 1	H370	Causes damage to organs (May cause blindness if swallowed)
Full text of H statements : see	e section 16	
2.2. Label elements		
GHS-US labelling		
Hazard pictograms (GHS-US)	) :	GHS02 GHS06 GHS08
Signal word (GHS-US)	:	Danger
Hazard statements (GHS-US)		H226 - Flammable liquid and vapor H302+H332 - Harmful if swallowed or if inhaled H311 - Toxic in contact with skin. H370 - Causes damage to organs (May cause blindness if swallowed)
		<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/Bond container and receiving equipment</li> <li>P241 - Use explosion-proof electrical, lighting, ventilating equipment.</li> <li>P242 - Use only non-sparking tools.</li> <li>P243 - Take precautionary measures against static discharge.</li> <li>P260 - Do not breathe mist, spray, vapors</li> <li>P264 - Wash affected areas thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> </ul>

EN (English)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS-US) continued	<ul> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P280 - Wear personal protective equipment as required.</li> <li>P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower</li> <li>P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing</li> <li>P307+P311 - If exposed: Call a poison center/doctor</li> <li>P301+P310 - If swallowed: Immediately call doctor/physician or poison center. Rinse Mouth</li> <li>P312 - Call doctor/physician or poison center if you feel unwell</li> <li>P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.</li> <li>P370+P378 - In case of fire: Use Carbon dioxide, Dry powder, foam, sand to extinguish.</li> <li>P403+P235 - Store in a well-ventilated place. Keep cool.</li> <li>P405 - Store locked up.</li> <li>P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations</li> </ul>
---	--

#### 2.3. **Other hazards**

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

## **SECTION 3: Composition/information on ingredients**

#### 3.1. **Substances**

Not applicable

#### 3.2. **Mixtures**

Name	Product identifier	% by wt	GHS-US classification
water	(CAS-No.) 7732-18-5	>= 67	Not classified
methanol	(CAS-No.) 67-56-1	<= 33	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).		
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical advice. Allow the victim to rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.		
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse immediately with plenty of water (for at least 15 minutes). If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Take victim to an ophthalmologist if irritation persists.		
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Rinse mouth. Obtain emergency medical attention.		
4.2. Most important symptoms and effect	s, both acute and delayed		
Symptoms/effects after inhalation	: High concentrations may cause central nervous system characterized by severe headaches, dizziness, nausea and confusion. May cause irritation of the nose and throat.		
Symptoms/effects after skin contact	: Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness.		
Symptoms/effects after eye contact	May cause severe irritation.		
Symptoms/effects after ingestion	: May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death.		
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.		

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Indication of any immediate medical attention and special treatment needed

Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. This product contains/consists of methanol which can cause intoxication and depression of the central nervous system.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: ABC powder. Foam. Dry powder. Carbon dioxide. Sand.	
Unsuitable extinguishing media	: Do not use a heavy water stream. May spread fire.	
5.2. Special hazards arising from the su	bstance or mixture	
Fire hazard	: Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or may be moved by ventilation.	
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.	
5.3. Special protective equipment and p	recautions for fire-fighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.	
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.	

**SECTION 6: Accidental release measures** 6.1. Personal precautions, protective equipment and emergency procedures General measures : Do not breathe mist, spray, vapors. In case of inadequate ventilation wear respiratory protection. Remove ignition sources. Use special care to avoid static electric charges. 6.1.1. For non-emergency personnel Emergency procedures : Evacuate unnecessary personnel. Keep upwind. Mark the danger area. 6.1.2. For emergency responders Protective equipment : Equip cleanup crew with proper protection. : Ventilate area. Emergency procedures 6.2. **Environmental precautions** Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3.	Methods and material for containment and cleaning up		
For conta	inment	: Contain released product, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Dilute combustible/toxic gases/vapors with water spray.	
Methods	for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.	

### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	In use, may form flammable vapor-air mixture.	
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formatio of vapor.	n
Hygiene measures	: Wash contaminated clothing before reuse.	
7.2. Conditions for safe storage, includin	ig any incompatibilities	
Technical measures	: Use explosion-proof ventilating, lighting, electrical equipment. Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed	ed.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources, h surfaces, open flames, sparks. Keep container closed when not in use. Do not store near foor foodstuffs, drugs or potable water supplies. Do not cut, drill, weld, use a blowtorch on, etc. containers even when empty.	
Incompatible products	: Keep away from strong acids, strong bases and oxidizing agents.	
Incompatible materials	: Sources of ignition.	
10/01/2019	EN (English) 3.	8/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

8.1. Control parameters			
methanol (67-56-1)			
ACGIH	Local name	Methanol	
ACGIH	ACGIH TWA (ppm)	200 ppm (Skin)	
ACGIH	ACGIH STEL (ppm)	250 ppm (Skin)	
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea	
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m³ (Skin)	
OSHA OSHA PEL (TWA) (ppm) 200 ppm (Skin)			
water (7732-18-5)			
Not applicable			

## 8.2. Appropriate engineering controls

## No additional information available

8.3. Individual protection measures/Personal protective equipment

## Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Safety glasses.

### Hand protection:

Wear protective gloves.

## Eye protection:

Chemical goggles or safety glasses

## Skin and body protection:

Wear suitable protective clothing

## **Respiratory protection:**

In case of inadequate ventilation wear respiratory protection. Wear appropriate mask



## Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Color	: Blue	
Odor	: alcohol	
Odor threshold	: No data available	
Relative evaporation rate (butylacetate=1)	: Greater than n-butyl acetate	
Freezing point	: -28.9 °C (-20 °F)	
Boiling point	: 81.7 °C (179 °F)	
Flash point	: 33.3 °C (92 °F)	
Auto-ignition temperature	: No data available	
10/01/2019	EN (English)	4/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, M	larch 26, 2012 / Rules and Regulations		
Decomposition temperature	No data available		
Flammability (solid, gas)	No data available		
	43 mm Hg @ 20 °C		
	Heavier than air		
	: 0.96 @ 20 °C		
	Water: Complete		
Log Pow	No data available		
Log Kow	No data available		
Viscosity, kinematic	No data available		
Viscosity, dynamic	No data available		
	6 - 36 vol %		
	No data available		
	No data available		
9.2. Other information			
	: < 33 %		
SECTION 10: Stability and reactivity			
10.1. Reactivity			
No additional information available			
10.2. Chemical stability			
Stable.			
10.3. Possibility of hazardous reactions			
Hazardous polymerization will not occur.			
<b>10.4.</b> Conditions to avoid Keep away from heat, hot surfaces, sparks, open f	lames and other ignition sources. No smoking		
	เลกษอ ลกษ อนายา เราแบบท อบนายออ. พบ อิทายกิทษู.		
10.5. Incompatible materials			
Keep away from strong acids, strong bases and ox	kidizing agents.		
10.6. Hazardous decomposition products			
Fume. Carbon monoxide. Carbon dioxide.			
<b>SECTION 11: Toxicological informatio</b>	n		
11.1. Information on toxicological effects			
	Not classified		
methanol (67-56-1)	1187 - 2769 mg/kg bodyweight (BASF test, Rat, Male / female, Weight of evidence, Aqueous		
LD50 oral rat	solution, Oral, 7 day(s))		
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)		
LC50 inhalation rat (mg/l)	128.2 mg/l/4h (BASF test, 4 h, Rat, Male/female, Weight of evidence)		
ATE US (oral)	100 mg/kg bodyweight		
ATE US (dermal) 300 mg/kg bodyweight			
ATE US (gases) 700 ppmv/4h			
ATE US (vapors)	3 mg/l/4h		
ATE US (dust,mist)	0.5 mg/l/4h		
Skin corrosion/irritation	Not classified		
Serious eye damage/irritation	Not classified		
Respiratory or skin sensitisation	Not classified		
Germ cell mutagenicity	Not classified		
Carcinogenicity	Not classified		
Denne desettes test if			
Reproductive toxicity	Not classified		

STOT-single exposure	: (	Causes damage to organs (May cause blindness if swallowed) .
STOT-repeated exposure	: N	Not classified

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	Not classified		
Symptoms/effects after inhalation	: High concentrations may cause central nervous system characterized by severe headaches, dizziness, nausea and confusion. May cause irritation of the nose and throat.		
Symptoms/effects after skin contact	Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness.		
Symptoms/effects after eye contact	: May cause severe irritation.		
Symptoms/effects after ingestion	: May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death.		
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.		

## **SECTION 12: Ecological information**

12.1. Toxicity

methanol (67-56-1)	
LC50 fish 1	15,400.00 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	18,260.00 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	22,000.00 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

#### 12.2. Persistence and degradability

methanol (67-56-1)						
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.					
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance					
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance					
ThOD	1.50 g O <sub>2</sub> /g substance					

#### 12.3. **Bioaccumulative potential**

methanol (67-56-1)					
BCF fish 1 1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)					
Log Pow -0.77 (Experimental value)					
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).				

#### 12.4. Mobility in soil

methanol (67-56-1)			
Surface tension 0.02 N/m (20 °C)			
Log Koc 0.09 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Highly mobile in soil.		

12.5. Other adverse effects			
Effect on the ozone layer	: No known effect on the ozone layer		
Other information	: Avoid release to the environment.		
SECTION 13: Disposal considerations			

13.1.	Waste treatment methods		
Product/P	ackaging disposal recommendations	:	Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.
Ecology -	waste materials	:	Avoid release to the environment.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT

Transport document description	UN1993 Flammable liquids, n.o.s., 3, III				
UN-No.(DOT)	:	: UN1993			
Proper Shipping Name (DOT)	:	Flammable liquids, n.o.s.			
Class (DOT)	:	3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120			
Packing group (DOT)	:	III - Minor Danger			
Hazard labels (DOT)	:	3 - Flammable liquid			
		CAMMARE LEGID			
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203			
DOT Packaging Bulk (49 CFR 173.xxx)	:	242			
DOT Symbols	:	G - Identifies PSN requiring a technical name			
DOT Packaging Exceptions (49 CFR 173.xxx)	:	150			
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	60 L			
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	220 L			
DOT Vessel Stowage Location	•	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.			
Emergency Response Guide (ERG) Number	:	128			
Other information	: In inner packaging no more than 5.0 L: Proper Shipping Name: Limited Quantity of Class III 49 CFR Part 173.10 (PG III, inner packaging no more than 5.0L).				

## **Transportation of Dangerous Goods**

## Refer to current TDG Canada for further Canadian regulations

### Transport by sea .

In accordance with IMDG / IMO				
Transport document description (IMDG) UN-No. (IMDG)	: UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol) , 3, III : 1992			
Proper Shipping Name (IMDG)	: Flammable Liquid, Toxic, n.o.s. (methanol)			
Class (IMDG)	: 3 - Flammable liquids			
Packing group (IMDG)	: III - substances presenting low danger			
Limited quantities (IMDG)	In Non-Bulk quantities with inner packaging no more than 5.0L: Proper Shipping Name: Dangerous Goods in Limited Class 3 (Windshield Wash Containing Methanol) Packages or pallets must be marked "Dangerous Goods in Limited Quantities of Class 3" Outer Package cannot weigh more than 30 kg.			
Limited quantities (IMDG)	: 5L			
Air transport In accordance with IATA / ICAO				
	: UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol), 3 (6.1), III			
In accordance with IATA / ICAO	: UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol), 3 (6.1), III : 1992			
In accordance with IATA / ICAO Transport document description (IATA)				
In accordance with IATA / ICAO Transport document description (IATA) UN-No. (IATA)	: 1992			
In accordance with IATA / ICAO Transport document description (IATA) UN-No. (IATA) Proper Shipping Name (IATA)	: 1992 : Flammable Liquid, Toxic, n.o.s. (methanol)			
In accordance with IATA / ICAO Transport document description (IATA) UN-No. (IATA) Proper Shipping Name (IATA) Class (IATA)	: 1992 : Flammable Liquid, Toxic, n.o.s. (methanol) : 3 - Flammable Liquids			

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 15: Regulatory information

## 15.1. US Federal regulations

NAPA Windshield Wash -20 °F				
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed			
SARA Section 302 Threshold Planning Quantity (TPQ)	None			
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard			
SARA Section 313 - Emission Reporting	33 % (Methanol CAS # 67-56-1)			

methanol (67-56-1)				
CERCLA RQ	5000 lb(s) (2270 kg)			
water (7732-18-5)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				

### 15.2. International regulations

### CANADA

NAPA Windshield Wash -20 °F				
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.			

## 15.3. US State regulations

This product can expose you to methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose leve (MADL)
No	Yes	No	No		47000 μg/day (inhalation); 23,000 μg/day (oral)

## methanol (67-56-1)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

### Revision date

: 10/01/2019

Full text of H-statements:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H370	Causes damage to organs

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.	2
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.	
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.	

SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.