

MATERIAL SAFETY DATA SHEET

According to 29 CFR 1910.1200(g)



Date Issued: 07/07/2000

MSDS No: 10070

Date-Revised: 01/29/2010

Revision No: 8

Seal-It®

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Seal-It®
PRODUCT DESCRIPTION: Automotive Polish
PRODUCT CODE: 70
PRODUCT FORMULATION NAME: Seal-It®
GENERIC NAME: Automotive Polish

MANUFACTURER

Auto Wax - An ITW Company

Auto Magic®

1275 Round Table Drive

Dallas, TX 75247

Product Stewardship: 1-800-826-0828

Transportation: 1-800-826-0828

Service Number: 1-214-631-4000

Auto Wax - An ITW Company

Auto Magic®

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-826-0828

COMMENTS: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR 1910.1200.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Flammable liquid and vapor. CAUTION! May cause eye irritation.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: May cause slight irritation.

INGESTION: This material may be harmful or fatal if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: overexposure to vapors may cause headaches, dizziness, confusion and nausea,

CHRONIC EFFECTS: not available

CARCINOGENICITY: not available

MEDICAL CONDITIONS AGGRAVATED: dermatitis may be aggravated by excessive exposure to skin.

ROUTES OF ENTRY: include skin contact, skin absorption, eye contact , inhalation and ingestion

TARGET ORGAN STATEMENT: not available

CANCER STATEMENT: not available

SENSITIZATION: not available

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | Wt. % | CAS | EINECS | Classification |
|-----------------|---------|------------|-----------|---------------------|
| Mineral Spirits | 40 - 50 | 64475-85-0 | | |
| Naphtha | 25 - 30 | 8032-32-4 | 232-453-7 | F, Xn; R11-65-66-67 |

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Seek medical attention if irritation persists.

SKIN: Remove contaminated clothing. Wash with soap and water.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: ~ 33°C (91°F) TCC

FLAMMABLE LIMITS: Not Available

Notes: not available

AUTOIGNITION TEMPERATURE: Not Available

FLAMMABLE CLASS: Extremely Flammable. Material will readily ignite at room temperatures.

FLAME PROPAGATION OR BURNING RATE OF SOLIDS: not available

GENERAL HAZARD: Flammable liquid. Keep away from heat and open flames.

EXTINGUISHING MEDIA: use foam, dry chemical or carbon dioxide extinguisher

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide and Carbon Dioxide

EXPLOSION HAZARDS: not available

SENSITIVITY TO IMPACT: not available

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Remove all ignition sources. Contain and collect with absorbent

LARGE SPILL: Remove all ignition sources. Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent. Proper disposal of absorbent is required after use.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of Children.

STORAGE: Keep away from open flames and excessive heat.

STORAGE TEMPERATURE: (32°F) Minimum to (95°F) Maximum

SHELF LIFE: one year

ELECTROSTATIC ACCUMULATION HAZARD: Ground and bond containers when transferring material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) | | | | | | | |
|---|------|-----------------|-------------------|-----------|-------------------|--------------|-------------------|
| | | EXPOSURE LIMITS | | | | | |
| | | OSHA PEL | | ACGIH TLV | | Supplier OEL | |
| Chemical Name | | ppm | mg/m ³ | ppm | mg/m ³ | ppm | mg/m ³ |
| Mineral Spirits | TWA | 100 ppm | | 100 ppm | | 200 ppm | |
| Naphtha | TWA | 300 ppm | | 300 ppm | | | |
| | STEL | | | 400 ppm | | | |

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles.

SKIN: Use Nitrile/ Vinyl gloves

RESPIRATORY: NIOSH respirator -(organic vapor) in absence of proper environmental control.

PROTECTIVE CLOTHING: Clean, body-covering clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: hydrocarbon odor
APPEARANCE: White Liquid
pH: Not applicable
PERCENT VOLATILE: 85-95
VAPOR PRESSURE: Not Available
VAPOR DENSITY: Not Available
BOILING POINT: ~ 149°C
FLASHPOINT AND METHOD: ~ 33°C (91°F) TCC
SOLUBILITY IN WATER: Not Available
SPECIFIC GRAVITY: ~ 0.850 gm/ml

10. STABILITY AND REACTIVITY

STABLE: Yes
HAZARDOUS POLYMERIZATION: No
CONDITIONS TO AVOID: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION

ACUTE

| Chemical Name | INHALATION LC ₅₀ (rat) |
|---------------|--------------------------------------|
| Naphtha | ~ 3400 ppm/ 4H- rat |

CHRONIC: not available

CARCINOGENICITY

IARC: Listed by IARC- NO

NTP: Listed by NTP- NO

OSHA: Listed by OSHA- NO

NEUROTOXICITY: not available

REPRODUCTIVE EFFECTS: not available

TARGET ORGANS: not available

TERATOGENIC EFFECTS: not available

MUTAGENICITY: not available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: not available

ECOTOXICOLOGICAL INFORMATION: not available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal laws.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

OTHER SHIPPING INFORMATION: Refer to bill of lading or container label for DOT or other transportation hazard classification, if any.

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All Ingredients are on the TSCA Inventory or are not required to be listed on the TSCA Inventory

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION


Flammable Liquid



Toxic

16. OTHER INFORMATION**PREPARED BY:** Tony Casmus**REVISION SUMMARY:** Revision #: 8. This MSDS replaces the July 18, 2008 MSDS. Any changes in information are as follows: In Section 1: MSDS Classification**HMIS RATING**

| | | |
|-----------------------------|---|---|
| HEALTH: | - | 2 |
| FLAMMABILITY: | | 3 |
| PHYSICAL HAZARD: | | 0 |
| PERSONAL PROTECTION: | | |

NFPA CODES

MANUFACTURER DISCLAIMER: The information in this MSDS was obtained from current and reputable sources. However, the data is provided without any warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.