

Product: Quicksilver Touch-Up Paint - Clear Coat (Aerosol)**Product #:** 92-802878Q53, 92-827933 53**SECTION I - MANUFACTURER INFORMATION****Name:** Mercury Marine**Emergency:** 800-424-9300 (ChemTrec)**Address:** W6250 W. Pioneer Rd.**Information:** 920-929-5418

PO Box 1939

Date Prepared: 04-09-97

Fond du Lac WI 54936-1939

Revised: 12-04-98**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components*	OSHA PEL	ACGIH TLV	Other	% (Opt.)
Ethyl Benzene (100-41-4)**	N/D	100ppm		3
N-Butane (106-97-8)	800ppm	800ppm		8
Propane (74-98-6)	N/D	1000ppm		16
Xylene (1330-20-7)**	100ppm	100ppm		13
Acetone (67-64-1)	750ppm	750ppm		35
Propylene Glycol Methyl Ether Acetate (108-65-6)	N/E	N/E		7

* Specific Chemical Identity, Common Name (CAS)

**This component is listed as a SARA Section 313 Toxic Chemical.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**Boiling Point:** 1° to 302°F**Specific Gravity (H₂O=1):** 0.7620**Vapor Pressure (mmhg):** 5585.2 @ 20°C**Melting Point:** N/D**Vapor Density (Air=1):** N/A**Evaporation Rate:** 7.7**Solubility in Water:** N/D**(Butyl Acetate=1)****Appearance and Odor:** Opaque liquid, solvent odor**SECTION IV - FIRE AND EXPLOSION HAZARD DATA****Flash Point (Method Used):** < -25° F (No Method Listed)**Flammable Limits:** LEL - 1.0 UEL - 13.1**Extinguishing Media:** Carbon Dioxide, dry chemical, chemical foam**Special Fire Fighting Procedures:** Full protective equipment including SCBA to avoid inhalation of vapors should be used. Water spray should not be used except to keep down vapors or cool closed containers to prevent buildup of pressure. If water is used, fog nozzles are preferred.**Unusual Fire and Explosion Hazards:** Contents under pressure. Aerosol containers may explode when exposed to extreme heat. Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.**SECTION V - REACTIVITY DATA****Stability:** Unstable () Stable (X)**Conditions to Avoid:** Contact with heat, sparks, and open flame.**Incompatibility (Materials to Avoid):** Strong oxidizing agents.**Hazardous Decomposition or Byproducts (Thermal):** May produce Carbon Dioxide, Carbon Monoxide, and unidentifiable organic materials.**Hazardous Polymerization:** May Occur () Will Not Occur (X)**ADDITIONAL INFORMATION**

Mercury Marine Emergency Information Number: 920-929-5000

Manufacturer, Raabe Corp., Emergency Number: 414-255-9500

SECTION VI - HEALTH HAZARD DATA**Route(s) of Entry:** Inhalation (Y) Skin (Y) Eye (Y) Ingestion (Y)**Health Hazards (Acute and Chronic):** Liquid or vapor may be irritating to skin, eyes, throat, and lungs. Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal. Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals: anemia and damage to kidney, eye, and liver. Chronic overexposure has also been suggested as a cause of cardiac abnormalities in humans. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.**Carcinogenicity:** NTP (N) IARC Monographs (N) OSHA Regulated (N)**Signs and Symptoms of Exposure:** Eye - May cause severe irritation. Skin - May cause irritation. Inhalation - Exposure to high concentrations may cause dizziness, breathing difficulty, headaches, or respiratory irritation. Extremely high concentrations may also cause drowsiness, staggering, confusion, unconsciousness, coma, or death. Ingestion - Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis. Aspiration into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.**Medical Conditions Generally Aggravated by Exposure:** N/D**Emergency and First Aid Procedures:** Eye - Immediately flush with large quantities of water for 15 minutes. If irritation persists, seek medical attention. Skin - Remove contaminated clothing and wash affected area thoroughly with soap and water. Seek medical attention. Launder contaminated clothing before reuse. Inhalation - Move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention. Ingestion - SEEK MEDICAL ATTENTION IMMEDIATELY! The decision to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE****Steps to be Taken in Case Material is Released or Spilled:** Remove all sources of ignition. Ventilate area of spill and adjacent low-lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials with non-sparking tools.**Waste Disposal Method:** Place in closed containers. Dispose of product in accordance with federal, state, county, and local regulations.**Precautions to be taken in Handling and Storing:** Store in a cool, dry area (<120°F) with ventilation suitable for storing materials shown in Section II. Keep away from heat, sparks, and flame. Store away from direct sunlight or sources of ignition. Wash hands thoroughly after handling.**Other Precautions:** KEEP AWAY FROM CHILDREN!**SECTION VIII - CONTROL MEASURES****Respiratory Protection (Specify Type):** A NIOSH/OSHA-approved respirator suitable for components listed is in Section II recommended if workplace exposure limits are to be exceeded.**Ventilation: Local Exhaust & Mechanical** - Provide sufficient ventilation, in volume and pattern, to keep air contamination below current applicable PELs and TLVs.**Protective Gloves:** Chemical-resistant plastic or rubber**Eye Protection:** Chemical goggles with side shields or face shield**Other Protective Clothing or Equipment:** Impervious clothing for prolonged or repeated contact.**Work/Hygiene Practices:** Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED

Y = YES

N/A = NOT APPLICABLE

N/AV = NOT AVAILABLE

N = NO