

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **Touchdown Kwik Seam Latex**
ITEM NUMBER: 710-4
ITEM DESCRIPTION: 710 Touchdown Kwik Seam Latex Adh 4-gal
PRODUCT DESCRIPTION: LATEX BASED ADHESIVE
CHEMICAL FAMILY: NATURAL LATEX ADHESIVE
REVISION DATE: 01/21/14 REVIEW DATE: / / PRINT DATE: 01/24/14 PRINT TIME: 07:58

HMIS HAZARD RATING

LEAST:	0	HEALTH:	1
SLIGHT:	1	FLAMMABLE:	0
MODERATE:	2	REACTIVITY:	0
HIGH:	3		
EXTREME:	4		

PREPARED BY: ROBERT DDAMULIRA
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

Methanol

Contains low level of ammonia below regulatory threshold.

SECTION III PHYSICAL DATA

Hazard	CAS #	WT/Wt % Less Than
METHANOL	67-56-1	3 - 4 SARA Rep.
ACGIH TLV: 200 PPM (TWA)		
OSHA PEL: 200 PPM (TWA)		

BOILING POINT: 212 DEGREES F
LBS / GAL: 7.6 - 8.0
EVAPORATION RATE: SAME AS WATER
VAPOR DENSITY: SAME AS WATER.
PERCENT VOLATILE: 43 - 47 (BY WEIGHT)
COLOR: WHITE
ODOR: AMMONIA-LIKE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

PRODUCT NAME: **Touchdown Kwik Seam Latex**
ITEM NUMBER: 710-4
ITEM DESCRIPTION: 710 Touchdown Kwik Seam Latex Adh 4-gal
REVISION DATE: 01/21/14 REVIEW DATE: / / PRINT DATE: 01/24/14 PRINT TIME: 07:58

FLASH POINT, TAG C.C.: N.A.
AUTO IGNITION TEMPERATURE, F: N.A.
FLAAMABLE LIMITS IN AIR, VOLUME %: LOWER: N.A. UPPER: N.A.
FIRE EXTINGUISHING MEDIA: WATER SPRAY, CARBON DIOXIDE, FOAM, DRY CHEMICAL
SPECIAL FIREFIGHTING PROCEDURES: WEAR SELF CONTAINED BREATHING APPARATUS
UNUSUAL FIRE AND EXPLOSION HAZARD: NONE KNOWN

SECTION V HEALTH HAZARD IDENTIFICATION

THE PRODUCT HAS NOT BEEN EVALUATED AS A WHOLE FOR HEALTH EFFECTS. INFORMATION PROVIDED ON THE HEALTH EFFECTS OF THE PRODUCTS IS BASED ON INDIVIDUAL COMPONENTS. PRODUCT CONTAINS LOW LEVELS OF METHANOL AND AMMONIA.

SYMPTOMS OF OVER EXPOSURE:

INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.

EYES: VAPOR MAY CAUSE IRRITATION.

SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.

INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: MAY CAUSE MILD SKIN AND RESPIRATORY TRACT IRRITATION

CHRONIC: NOT KNOWN

FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR, ADMINISTER OXYGEN. IF NECESSARY, SEEK MEDICAL ATTENTION.

INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VI REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: NONE KNOWN TO W.F.TAYLOR

INCOMPATIBILITY-MATERIALS TO AVOID: OXIDIZING MATERIALS

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): THERMAL DECOMPOSITION MAY YIELD OXIDES OF CARBON AND NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VII SPILL OR LEAK PROCEDURES

PRODUCT NAME: **Touchdown Kwik Seam Latex**
ITEM NUMBER: 710-4
ITEM DESCRIPTION: 710 Touchdown Kwik Seam Latex Adh 4-gal
REVISION DATE: 01/21/14 REVIEW DATE: / / PRINT DATE: 01/24/14 PRINT TIME: 07:58

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

IF TLV IS EXCEEDED, USE SELF CONTAINED BREATHING APPARATUS.

SOAK UP MATERIAL WITH SAWDUST OR VERMICULITE AND PLACE INTO CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: SUFFICIENT TO KEEP WORKPLACE CONCENTRATION BELOW TLV. USE MECHANICAL EXHAUST IF TLV IS EXCEEDED.

RESPIRATORY PROTECTION: NONE REQUIRED, UNLESS EXPOSURE IS OVER TLV. USE NIOSH RESPIRATOR IF ABOVE TLV. USE PRODUCT IN WELL VENTILATED AREA.

PROTECTIVE GLOVES: POLYETHYLENE OR NEOPRENE

EYE PROTECTION: SPLASH PROOF GOGGLES

OTHER CLOTHING AND EQUIPMENT: WEAR NEPRENE APRON IF SPLASHING IS A PROBLEM.

WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.

OTHER HANDLING AND STORAGE REQUIREMENTS: PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL PLACE.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES.

WEAR SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED.

SECTION IX SPECIAL PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.

PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL DRY PLACE (50 - 90 DEGREES F). KEEP AWAY FROM HEAT AND SPARKS. KEEP FROM FREEZING.

NOTICE

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.
