

**1. Identification of the Substance and Company**

**TST Bowie Dick Test Pack**

Product No. 2352AB, 2352

SDS No. B114US

Prepared by: Richard Bancroft

[asksteris\\_msds@steris.com](mailto:asksteris_msds@steris.com)

**NFPA 704 HAZARD RATING:**

**HEALTH:** 0

**FIRE:** 0

**REACTIVITY:** 0

**Date Created: November 14, 2005 Date Revised: July 21, 2014**

**Date Reviewed: NA**

STERIS Corporation, P.O. Box 147, St. Louis, Mo 63166, US  
Emergency Telephone No. 1-314-535-1395 (STERIS); 1-800-424-9300 (CHEMTREC)  
Telephone Number for information: 1-800-444-9009 (Customer Service-Scientific Products)

Albert Browne Limited, Chancery House, 190 Waterside Road, Hamilton Industrial Park,  
Leicester, LE5 1QZ, UK

Emergency Phone No: +44 (0) 1895 622 639

Product/Technical Information Phone No: +44 (0) 116 276 8636

Product Number	Cycle Type	Cycle Parameters
2352AB	Prevacuum	134°C -137°C/273°F - 279°F for up to 3.5 minutes
2352	Prevacuum	134°C -137°C/273°F - 279°F for up to 3.5 minutes

TST Bowie Dick Test Packs are not hazardous products according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200 and the Controlled Products Regulations; and are free of lead and other heavy metals.

TST Bowie Dick Test Packs do not contain any components derived from animal origin, do not come into contact with materials of animal origin and therefore comply with the "Note for guidance of minimizing the risk of transmitting animal spongiform encephalopathy agents via human Veterinary medicinal products (EMA/410/01 Rev. 2-October 2003)."

The TST Bowie Dick Test Pack verifies that the prevacuum sterilizer effectively removes air and provides efficient steam penetration. The advanced thermochromic ink formulation can detect problems with steam quality.

Store at 0-30°C in dry (30 – 60% RH) conditions away from direct sunlight.