

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.****W. F. Taylor Co., Inc.**

11545 Pacific Avenue  
Fontana, CA 92337-8228  
951/360-6677  
CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **TOUCHDOWN PRESSURE SENSITIVE AEROSOL**  
ITEM NUMBER: 725-20  
ITEM DESCRIPTION: 725 Touchdown Pressure Sensitive Aerosol Spr \*\*  
PRODUCT DESCRIPTION: RUBBER BASED ADHESIVE  
CHEMICAL FAMILY: SYNTHETIC RUBBER, RESIN BLEND  
REVISION DATE: 06/05/08  
MANUFACTURED BY: Camie - Campbell  
ADDRESS: 9225 Watson Industrial Park  
St. Louis, MO 63126  
EMERGENCY PHONE NO: (800) 424-9300  
CHEMICAL NAMES, COMMON NAMES: SYNTHETIC RUBBER, RESIN BLEND  
MANUFACTURER'S CODE IDENTIFICATION: FPATAYLOR 125  
TRADE NAME: W. F. Taylor Touchdown 725 Adhesive

## HMIS HAZARD RATING

LEAST: 0	HEALTH: 2
SLIGHT: 1	FLAMMABLE: 4
MODERATE: 2	REACTIVITY: 1
HIGH: 3	
EXTREME: 4	

## PREEMPTS PREVIOUS MSDS SHEETS

SECTION II		HAZARDOUS INGREDIENTS		
COMPONENT/CAS #	ACGIH TLV	OSHA PEL	% WT	NOTES
ACETONE				
67-64-1	500 PPM	1000 PPM	25	SARA Rep.
HEXANE				
110-54-3	50 PPM	500 PPM	25	SARA Rep.
PROPANE				
74-98-6	2500 PPM	1000 PPM	25	SARA Rep.
DIMETHYL ETHER				
115-10-6	N.E.	N.E.	15	SARA Rep.

**SECTION III PHYSICAL DATA**

BOILING POINT: 144 - 500 degrees F  
ODOR: Mint when wet  
APPEARANCE: Light Yellow Liquid  
SOLUBILITY IN WATER: Negligible  
VAPOR DENSITY: Heavier than air  
EVAPORATION RATE: Faster than Butyl Acetate  
DENSITY: 5.82 lbs per gallon  
VAPOR PRESSURE: N. D.  
% VOLATILE: 77.2 (By Weight)  
MAX VOC'S: 54.1% 378 grams/liter Total Product  
475 grams/ liter less water and Exempt

PRODUCT NAME: **TOUCHDOWN PRESSURE SENSITIVE AEROSOL**  
ITEM NUMBER: 725-20  
ITEM DESCRIPTION: 725 Touchdown Pressure Sensitive Aerosol Spr \*\*  
REVISION DATE: 06/05/08

---

#### **SECTION IV FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT, TAG C.C.: -156 degrees F  
AUTO IGNITION TEMPERATURE, DEGREES F: ND  
FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: 1.0% UEL: 18.0 %  
EXTINGUISHING MEDIA:

(X) Water Spray      (X) Carbon Dioxide      ( ) Other  
(X) Foam              (X) Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignited by ignition sources at locations distant from material handling point. For aerosol prodcuts - exposure to temperatures over 130 F may cause containers to burst releasing highly flammable gas.

---

#### **SECTION V HEALTH HAZARD IDENTIFICATION**

SYMPTOMS OF OVER EXPOSURE:

INHALATION: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation. Overexposure may cause damage to nervous system.

EYES: Can cause severe irritation, redness, tearing and blurred vision.

SKIN: Prolonged or repeated eye contact can cause moderate irritation, defatting, dermatitis.

INGESTION: No information.

HEALTH EFFECTS OR RISKS FROM CHRONIC OVEREXPOSURE:

Overexposure to this material (or its components) has been apparently been found to cause the following effects in laboratory animals: kidney damage, eye damage, liver damage, lung damage, nasal damage, nasal system damage, testis damage. Overexposure to this material (or its components)has apparently been found to cause the following effects on humans: visual impairment, central nervous system effects.

Primary route of entry: Skin contact, skin absorption, inhalation, eye contact.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with large amount of water, lifting upper and lower lids occasionally. Get medical attention.

SKIN:Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. Get medical attention if irritation persists. Mineral oil, baby oil, make-up remover mineral spirits or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.

INHALATION: Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.

INGESTION: Do not induce vomiting. Give two glasses of water if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention.

---

PRODUCT NAME: **TOUCHDOWN PRESSURE SENSITIVE AEROSOL**  
ITEM NUMBER: 725-20  
ITEM DESCRIPTION: 725 Touchdown Pressure Sensitive Aerosol Spr \*\*  
REVISION DATE: 06/05/08

---

#### **SECTION VI REACTIVITY DATA**

CONDITIONS TO AVOID: Heat, sparks, welding arcs, open flame, pilot lights, static electricity, or other source of ignition.  
INCOMPATIBILITY: Oxidizing agents, acids, reducing agents, strong oxidizers.  
HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): carbon monoxide and carbon dioxide, various hydrocarbons, acetic acids, nitrogen oxide, nitrogen peroxide, aldehydes, carboxylic acids.  
HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.  
STABILITY: Stable under normal storage conditions.

---

#### **SECTION VII SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate sources of ignition and ventilate area. Persons not properly equipped should be excluded from area. Stop spill at source to prevent spreading. Avoid inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into proper containers for disposal. Use non-sparking scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.

---

#### **SECTION VIII SPECIAL HANDLING INFORMATION**

VENTILATION AND ENGINEERING CONTROLS: Provide sufficient mechanical ventilation (general and/or local exhaust) to maintain below TLV(s).  
RESPIRATORY PROTECTION: If work place exposure limits of product or any component is exceeded, use a NIOSH approved respirator. Consult safety equipment supplier for recommendation.  
EYE PROTECTION: Wear safety glasses at minimum. Extensive protection may be necessary depending on how the product is to be used.  
SKIN PROTECTION: Wear impervious gloves if method of use involves skin contact with product. Consult safety supply vendor for glove recommendation.  
OTHER CLOTHING AND EQUIPMENT: Wear impervious clothing if bodily exposure is anticipated. Consult safety supply vendor for recommendation.  
WORK PRACTICES, HYGIENIC PRACTICES: Wash hands before eating and smoking. Smoke in designated areas only. Remove and launder clothing if contaminated. Avoid breathing of vapors. Keep away from children.  
OTHER HANDLING AND STORAGE REQUIREMENTS: Containers of this material may be hazardous when emptied, since containers retain product residues (vapor, liquid and/or solid). All hazard precautions given should be observed. Do not flame cut, braze or use welding torch on containers. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. STORAGE: Do not store above 120 degrees F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks, and other sources of ignition.

---

#### **SECTION IX TOXICOLOGICAL PROPERTIES**

No product or component toxicological information is available.

---

#### **SECTION X ECOLOGICAL INFORMATION**

No information available

---

#### **SECTION XII SHIPPING DATA**

49 CFR 172.101 - 102  
D.O.T. PROPER SHIPPING NAME : Aerosols  
D.O.T. HAZARD CLASSIFICATION : 2.1  
HAZARD SUBCLASS: None  
D.O.T IDENTIFICATION NUMBER : UN 1950  
D.O.T. PACKAGING GROUP: None

PRODUCT NAME: **TOUCHDOWN PRESSURE SENSITIVE AEROSOL**  
ITEM NUMBER: 725-20  
ITEM DESCRIPTION: 725 Touchdown Pressure Sensitive Aerosol Spr \*\*  
REVISION DATE: 06/05/08

---

D.O.T. LABELS REQUIRED : 3

Additional information: For domestic ground and air shipment, this product may be shipped as Consumer Commodity ORM-D. Outer cartons must have the ORM-D or ORM-D Air designation. (Original cartons are preprinted with the ORM-D designation for ground shipment.)

---

### SECTION XI REGULATORY INFORMATION

U.S. Federal Regulations as follows:

OSHA: hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA Hazard Category:

This product has been reviewed according to the EPA hazard categories promulgated under Section 311 and 312 of the Superfund Amendment and reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard

Chronic Health Hazard

Fire Hazard

Pressurized Gas Hazard

#### SARA SECTION 313

This product contains the following substances subject to reporting requirements of Sections 313 of Title III of the Superfund amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Hexane (110-54-3) less than 25% (by weight)

#### TOXIC SUBSTANCES CONTROL ACT (TSCA)

This product contains the following chemicals subject to the reporting requirements of TSCA 12 (B) if exported from the United States.

No information available

#### U.S.STATE REGULATIONS

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

Chemical (CAS no.)

Benzene (71-43-2) 18 ppm

Acetaldehyde (75-07-0) 5 ppm

Formaldehyde (50-00-0) 5 ppm

#### INTERNATIONAL REGULATIONS

Canadian WHMIS: This MSDS has been prepared in compliance with Controlled product regulations except for the use of 16 headings.

Canadian WHMIS Class: No information available.

TSCA Inventory: All components of this product are in the US TSCA inventory.

---

---

PRODUCT NAME:	<b>TOUCHDOWN PRESSURE SENSITIVE AEROSOL</b>
ITEM NUMBER:	725-20
ITEM DESCRIPTION:	725 Touchdown Pressure Sensitive Aerosol Spr **
REVISION DATE:	06/05/08

---

#### **NOTICE**

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE  
HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL  
LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION,  
INVESTIGATION AND VERIFICATION.

---