

MATERIAL SAFETY DATA SHEET

Finished Product

Date-Issued: 01/07/2003
MSDS Ref. No: 2106-G/5G
Date-Revised: 06/04/2004
Revision No: 1

Fine-L-Kote HT

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Fine-L-Kote HT
PRODUCT DESCRIPTION: Silicone Conformal Coating
PRODUCT CODE: 2106-G, 2106-5G

MANUFACTURER

Techspray, L.P.
 1001 N.W. 1st Street
 P.O. Box 949
 Amarillo, TX 79107
Contact: Chemtrec
Product Stewardship: 1-800-858-4043

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (U.S.): (800) 424-9300
CANUTEC: (613) 996-6666
Emergency Phone: 1-800-858-4043

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS#</u>	<u>EINECS#</u>
Benzene- methyl, (Toluene)	50 - 70	108-88-3	203-625-9
Xylenes (o-,m-,p- isomers)	10 - 20	1330-20-7	
Polysiloxane mixture	13 - 24		

EEC LABEL SYMBOL AND CLASSIFICATION



R11 - Highly flammable.

EEC Highly flammable - "F"



R20/21 - Harmful by inhalation and in contact with skin.

EEC Harmful - "Xn"

R36 - Irritating to eyes.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Flammable liquid and vapor. Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

POTENTIAL HEALTH EFFECTS

EYES: Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

SKIN: Prolonged or repeated contact may cause skin irritation.

INGESTION: This product is toxic by ingestion. Ingestion may cause irritation of the digestive tract. Nausea and vomiting will most likely occur.

INHALATION: Prolonged or repeated inhalation may cause lung damage and/or central nervous system disturbances.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Symptoms of overexposure include: stinging, tearing, redness and pain.

SKIN: Prolonged exposure causes redness, pain, drying and cracking of the skin.

INGESTION: Swallowing of this material may result in nausea, vomiting and weakness followed by central nervous system depression.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result.

CHRONIC: CNS depression, dermatitis, reproductive hazard.

ROUTES OF ENTRY: Inhalation is major route of entry.

TARGET ORGAN STATEMENT: Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.

SENSITIZATION: Possible cardiac sensitization.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. Get prompt medical attention.

INGESTION: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but do not induce. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Call a physician immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (40°F)TAG CC

FLAMMABLE LIMITS: Not Established to Not Established

GENERAL HAZARD: Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point.

EXTINGUISHING MEDIA: Water, foam, dry chemical, carbon dioxide.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

EXPLOSION HAZARDS: Vapors may form explosive mixture with air.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: NEVER FLUSH TO SEWER.

GENERAL PROCEDURES: Absorb the liquid and scrub the area with detergent and water.

7. HANDLING AND STORAGE

HANDLING: Empty containers will retain product residue and vapor and should be handled as if they were full.

STORAGE: Store in a cool place in original container and protect from sunlight.

STORAGE PRESSURE: Store at local atmospheric pressure.

STORAGE TEMPERATURE: Store in a cool place below (120) F (49) C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

	<u>EXPOSURE LIMITS</u>						
	<u>OSHA PEL</u>		<u>ACGIH TLV</u>		<u>Supplier OEL</u>		
	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>	
Benzene- methyl, (Toluene)	TWA	200 ^[1]	375	S 50 ^[2]	188	NL	NL
	STEL	C300 ^[3]	560	NL	NL	NL	NL
Xylenes (o-,m-,p- isomers)	TWA	435		434			
	STEL	150		651			
Polysiloxane mixture							

OSHA TABLE COMMENTS:

1. NL = Not Listed
2. S = Skin
3. C = Ceiling

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN: The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection.

Viton, Solvex, Butyl, Buna, Neoprene.

Butyl Rubber
Solvex

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

WORK HYGIENIC PRACTICES: Wash hands before eating and wash before reuse.

OTHER USE PRECAUTIONS: Emergency shower and eyewash facility should be in close proximity.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Aromatic odor.

APPEARANCE: Clear water-white viscous liquid with aromatic odor.

COLOR: Colorless

PERCENT VOLATILE: 80

VAPOR DENSITY: >1 (Air=1)

BOILING POINT: 110°C (230°F)

FREEZING POINT: Not Determined

SOLUBILITY IN WATER: Insoluble

EVAPORATION RATE: Not Established

DENSITY: 0.92

(VOC): 724 g/L (non-exempt VOC)

10. STABILITY AND REACTIVITY

STABLE: YES

HAZARDOUS POLYMERIZATION: NO

CONDITIONS TO AVOID: Heat, flames, ignition sources, and incompatibles.

STABILITY: Stable.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide and carbon Monoxide may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION

ACUTE

EYES: Moderately to severely irritating

DERMAL LD₅₀: 12124 mg/kg (rabbit)

ORAL LD₅₀: 636 mg/kg (rat)

INHALATION LC₅₀: 5000 ppm, 4-hour

EYE EFFECTS: High vapor concentrations may cause moderate to severe eye irritation.

SKIN EFFECTS: Causes irritation to skin.

CARCINOGENICITY:

IARC: NOT listed

NTP: NOT listed

OSHA: NOT listed

REPRODUCTIVE EFFECTS: Xylene and toluene are listed as reproductive hazards.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.

GENERAL COMMENTS: Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Flammable Liquid, N.O.S. (Toluene, Xylene)

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN1993

PACKING GROUP: II

AIR (ICAO/IATA)

PROPER SHIPPING NAME: Flammable Liquid, N.O.S. (Toluene, Xylene)

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN1993

PACKING GROUP: II

IATA NOTE: Domestic shipments only. When shipping International contact TechSpray shipping department.
CARGO AIRCRAFT ONLY. OVERPACK MUST BE USED.

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Flammable Liquid, N.O.S. (Toluene, Xylene)

PRIMARY HAZARD CLASS/DIVISION: 3.2

UN/NA NUMBER: UN1993

PACKING GROUP: II

IMDG NOTE: Page 3285. Note 2106-P can ship as DANGEROUS GOODS IN LIMITED QUANTITIES OF CLASS 3.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: IMMEDIATE / DELAYED

FIRE: YES ACUTE: YES CHRONIC: YES

313 REPORTABLE INGREDIENTS: Xylene Toluene

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: Listed in Table 302.4 of 40 CFR Part 302 as a hazardous substance with a reportable quantity of 1000 lbs.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Contains toluene (#108-88-3). Contains xylene (#1330-20-7).

CERCLA RQ: 1000 Lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are either listed or exempt from listing in the TSCA inventory.

RCRA STATUS: U220 U239

OSHA HAZARD COMM. RULE: Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS

CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CANADA

WHMIS (WORKER HAZARDOUS MATERIALS INFORMATION SYSTEM): This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION



R11 - Highly flammable.

EEC Highly flammable - "F"



R20/21 - Harmful by inhalation and in contact with skin.

EEC Harmful - "Xn"

R36 - Irritating to eyes.

CALIFORNIA PROPOSITION 65: This product contains a component known to the state of California to cause reproductive toxicity: Toluene (CAS#108883)

16. OTHER INFORMATION

APPROVED BY: Pierce A. Pillon **TITLE:** Chemist


REVISION SUMMARY Revision #: 1

This MSDS replaces the January 07, 2003 MSDS. Any changes in information are as follows:

In Section 15

EEC Risk Phrase Codes

NFPA CODES



DATA SOURCES: Code of Federal Regulations (CFR)
The Sigma-Aldrich Library of Regulatory and Safety Data
OSHA Hazard Communication Standard (29CFR1910.1200)
Various Federal, State and Local Regulations

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.