

**DOW CORNING(R) 756 SMS BUILDING SEALANT GRAY**

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

---

**SECTION 1. IDENTIFICATION**

Product name : DOW CORNING(R) 756 SMS BUILDING SEALANT GRAY  
Product code : 000000000004104508

**Manufacturer or supplier's details**

Company name of supplier : Dow Corning Corporation  
Address : South Saginaw Road  
Midland Michigan 48686  
Telephone : (989) 496-6000  
Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Construction materials and additives


---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with 29 CFR 1910.1200**

Skin sensitization : Category 1

**GHS label elements**

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.

**Disposal:**

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Silicone  
Sealant

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Calcium carbonate treated with stearic acid	Not Assigned	>= 47 - <= 51
Titanium dioxide	13463-67-7	<= 2.4
Antimony nickel titanium oxide yellow	8007-18-9	<= 1.6
Vinyltri (methylethylketoxime) silane	2224-33-1	>= 0.7 - <= 0.76
Carbon black	1333-86-4	<= 0.64
Cobalt titanite green spinel	68186-85-6	<= 0.32
Aminoethylaminoisobutylmethyldimethoxysilane	23410-40-4	>= 0.31 - <= 0.34

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.

## DOW CORNING(R) 756 SMS BUILDING SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Metal oxides  
Formaldehyde  
Silicon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

## SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Keep away from water.  
Protect from moisture.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate treated with stearic acid	Not Assigned	TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
Antimony nickel titanium oxide yellow	8007-18-9	TWA	0.5 mg/m <sup>3</sup> (antimony)	OSHA Z-1
		TWA	1 mg/m <sup>3</sup> (Nickel)	OSHA Z-1

## SAFETY DATA SHEET

DOW CORNING

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

		TWA	0.5 mg/m <sup>3</sup> (antimony)	ACGIH
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (Inhalable fraction)	0.2 mg/m <sup>3</sup> (Nickel)	ACGIH
		TWA	0.5 mg/m <sup>3</sup> (antimony)	NIOSH REL
		TWA	0.015 mg/m <sup>3</sup> (Nickel)	NIOSH REL
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	3 mg/m <sup>3</sup>	ACGIH
Cobalt titanite green spinel	68186-85-6	TWA	0.02 mg/m <sup>3</sup> (Cobalt)	ACGIH
		TWA	0.015 mg/m <sup>3</sup> (Nickel)	NIOSH REL
		TWA	1 mg/m <sup>3</sup> (Nickel)	OSHA Z-1
		TWA (Inhalable fraction)	0.2 mg/m <sup>3</sup> (Nickel)	ACGIH

**Hazardous components without workplace control parameters**

Ingredients	CAS-No.
Vinyltri (methylethylketoxime) silane	2224-33-1
Aminoethylaminoisobutylmethylmethoxysilane	23410-40-4

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Calcium carbonate treated with stearic acid

Titanium dioxide

Carbon black

Antimony nickel titanium oxide yellow

Cobalt titanite green spinel

**Occupational exposure limits of decomposition products**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 756 SMS BUILDING SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
 Date of first issue: 12/22/2014

		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1
--	--	-----	----------------------------------	----------

### Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Cobalt titanite green spinel	68186-85-6	Cobalt (Cobalt)	Urine	End of shift at end of work-week	15 µg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.  
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**  
**Material** : Chemical-resistant gloves

**Remarks** : For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 756 SMS BUILDING SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

---

breaks and at the end of workday.

- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : No data available
- Odor : slight
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Not classified as a flammability hazard
- Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapor pressure : Not applicable
- Relative vapor density : No data available
-

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

---

Relative density : 1.43

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-  
octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- : Use at elevated temperatures may form highly hazardous  
tions : compounds.  
Can react with strong oxidizing agents.  
Methyl Ethyl Ketoxime (MEKO) is formed upon contact with  
water or humid air.  
Hazardous decomposition products will be formed upon con-  
tact with water or humid air.  
Hazardous decomposition products will be formed at elevated  
temperatures.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents  
Water

**Hazardous decomposition products**

Contact with water or humid : Methanol  
air

Thermal decomposition : Formaldehyde

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

## SECTION 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Antimony nickel titanium oxide yellow:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

**Vinyltri (methylethylketoxime) silane:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: On basis of test data.  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

**Carbon black:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 0.0046 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

**Cobalt titanite green spinel:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

---

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Acute oral toxicity : LD50 (Rat): 653 mg/kg  
Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

**Skin corrosion/irritation**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Species: Rabbit  
Result: No skin irritation

**Antimony nickel titanium oxide yellow:**

Species: Rabbit  
Result: No skin irritation

**Carbon black:**

Species: Rabbit  
Result: No skin irritation

**Cobalt titanite green spinel:**

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Species: Rabbit  
Result: No skin irritation  
Remarks: On basis of test data.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Species: Rabbit  
Result: No eye irritation

**Vinyltri (methylethylketoxime) silane:**

Species: Rabbit

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

---

Result: Irreversible effects on the eye  
Remarks: On basis of test data.

**Carbon black:**

Species: Rabbit  
Result: No eye irritation

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Species: Rabbit  
Result: Irreversible effects on the eye  
Remarks: On basis of test data.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Result: negative

**Vinyltri (methylethylketoxime) silane:**

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test  
Species: Guinea pig  
Remarks: Based on data from similar materials

**Carbon black:**

Test Type: Buehler Test  
Routes of exposure: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative

**Cobalt titanite green spinel:**

Assessment: Probability or evidence of low to moderate skin sensitization rate in humans  
Remarks: Based on data from similar materials

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Assessment: Probability or evidence of skin sensitization in humans

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

---

Test Type: Maximization Test  
Species: Guinea pig  
Remarks: Causes sensitization.  
On basis of test data.

Test Type: Local lymph node assay (LLNA)  
Species: Mouse  
Remarks: Causes sensitization.  
On basis of test data.

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**Antimony nickel titanium oxide yellow:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Vinyltri (methylethylketoxime) silane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative  
Remarks: On basis of test data.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

**Carbon black:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Cobalt titanite green spinel:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

: Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.

**Carcinogenicity**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 24 Months  
Method: OECD Test Guideline 453  
Result: positive  
Remarks: The mechanism or mode of action may not be relevant in humans.  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**Cobalt titanite green spinel:**

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 2 Years  
Result: positive  
Remarks: Based on data from similar materials  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**IARC**

Group 1: Carcinogenic to humans

Antimony nickel titanium oxide yellow 8007-18-9

Cobalt titanite green spinel 68186-85-6

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Carbon black 1333-86-4

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

**OSHA** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP** Known to be human carcinogen

Antimony nickel titanium oxide yellow 8007-18-9

Cobalt titanite green spinel 68186-85-6

**Reproductive toxicity**

Not classified based on available information.

**Ingredients:****Antimony nickel titanium oxide yellow:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

**Cobalt titanite green spinel:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY**

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

---

**Ingredients:****Vinyltri (methylethylketoxime) silane:**

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

**Carbon black:**

Routes of exposure: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**Cobalt titanite green spinel:**

Routes of exposure: inhalation (dust/mist/fume)

Target Organs: Lungs

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Repeated dose toxicity****Ingredients:****Titanium dioxide:**

Species: Rat

NOAEL: 24,000 mg/kg

Application Route: Ingestion

Exposure time: 28 Days

Species: Rat

NOAEL: 10 mg/m<sup>3</sup>

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 y

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Antimony nickel titanium oxide yellow:**

Species: Rat

NOAEL: >= 450 mg/kg

Application Route: Ingestion

Exposure time: 90 Days

**Vinyltri (methylethylketoxime) silane:**

Species: Rat

Application Route: Ingestion

Target Organs: Blood

Remarks: Based on data from similar materials

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

**Carbon black:**

Species: Rat

NOAEL: 1 mg/m<sup>3</sup>LOAEL: 7 mg/m<sup>3</sup>

Application Route: Inhalation

Test atmosphere: dust/mist

Exposure time: 90 Days

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Cobalt titanite green spinel:**

Species: Mouse

LOAEL: 0.00125 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 y

Remarks: Based on data from similar materials

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks: During use of the material, small amounts of methylethylketoxime (MEKO) will be released. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed significant increases in liver tumor rates.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Titanium dioxide:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 hToxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 hToxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209**Antimony nickel titanium oxide yellow:**

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

**Vinyltri (methylethylketoxime) silane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

**Carbon black:**

Toxicity to fish : LC0 (Danio rerio (zebra fish)): 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 5,600 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**Cobalt titanite green spinel:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l  
Exposure time: 96 h  
Method: DIN 38412  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

---

EC10 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: 33 mg/l  
Exposure time: 30 min  
Method: ISO 8192  
Remarks: Based on data from similar materials

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 200 mg/l  
Exposure time: 96 h  
Method: EPA-660/3-75-009  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 81 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.  
Remarks: Based on data from similar materials

Toxicity to algae : NOEC: 3.1 mg/l  
  
ErC50 (Selenastrum capricornutum (green algae)): 8.8 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Pseudomonas putida): 67 mg/l  
Exposure time: 16 h  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

**Persistence and degradability****Ingredients:****Vinyltri (methylethylketoxime) silane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A

Stability in water : Degradation half life: < 1 min (2 °C)  
Method: OECD Test Guideline 111

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

---

**Aminoethylaminoisobutylmethyldimethoxysilane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 11.1 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
Remarks: Based on data from similar materials

Stability in water : Degradation half life: 15 min (20 °C) pH: 7  
Remarks: Based on data from similar materials

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

---

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version 4.1      Revision Date: 11/07/2016      SDS Number: 998896-00011      Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

## SECTION 15. REGULATORY INFORMATION

## EPCRA - Emergency Planning and Community Right-to-Know

## CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	*
Toluene	108-88-3	1000	*
n-Hexane	110-54-3	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylenediamine	107-15-3	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Antimony nickel titanium oxide yellow      8007-18-9      1 - 5 %

Cobalt titanite green spinel      68186-85-6      0.1 - 1 %

## US State Regulations

## Pennsylvania Right To Know

Calcium carbonate treated with stearic acid	Not Assigned
Dimethyl siloxane, trimethoxysilyl-terminated	Not Assigned
Dimethyl siloxane, hydroxy-terminated	70131-67-8
Titanium dioxide	13463-67-7
Aluminium	7429-90-5
Methanol	67-56-1

## California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

Antimony nickel titanium oxide yellow      8007-18-9

Cobalt titanite green spinel      68186-85-6

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Methanol      67-56-1

Toluene      108-88-3

## California List of Hazardous Substances

Antimony nickel titanium oxide yellow      8007-18-9

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

**California Permissible Exposure Limits for Chemical Contaminants**

Calcium carbonate treated with stearic acid	Not Assigned
Titanium dioxide	13463-67-7
Antimony nickel titanium oxide yellow	8007-18-9

**The ingredients of this product are reported in the following inventories:**

- NZIoC : All ingredients listed or exempt.
- ENCS/ISHL : Some components are not listed or not identified on ENCS/ISHL.
- REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- AICS : One or more ingredients are not listed or exempt.
- IECSC : One or more components of this product may not be listed on the IECSC inventory, but this component(s) is (are) notified under Dow Corning entity in China for scientific experimentation, research, analysis, or product/process development purposes only. Consult your local Dow Corning office.
- PICCS : Consult your local Dow Corning office.
- DSL : This product contains one or more substances which are not on the Canadian Domestic Substances List (DSL). Import of this product into Canada has volume limitations. For volume limits please consult Dow Corning Regulatory Compliance.
- TCSI : All ingredients listed or exempt.

**Additional regulatory information**

Dime- 37843-26-8  
thylbis(methylethylketoxime)silane

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.10261


For further information contact Dow Corning Regulatory Compliance.

DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAYVersion  
4.1Revision Date:  
11/07/2016SDS Number:  
998896-00011Date of last issue: 09/19/2016  
Date of first issue: 12/22/2014

## SECTION 16. OTHER INFORMATION

## Further information

## NFPA:



## HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Conven-

**DOW CORNING(R) 756 SMS BUILDING  
SEALANT GRAY**

Version	Revision Date:	SDS Number:	Date of last issue: 09/19/2016
4.1	11/07/2016	998896-00011	Date of first issue: 12/22/2014

---

tion for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/07/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8