

MATERIAL SAFETY DATA SHEET
29 CFR 1910.1200 OSHA Hazard
Communication Rule Format
Chem-Tel 24 Hour Emergency # 1-800-255-3924

MINE SAFETY APPLIANCES COMPANY
P.O. Box 426
Pittsburgh, PA 15230
PHONE (412) 967-3000

This product contains nitrogen, a substance subject to the Pennsylvania Worker and Community Right-To-Know Act.

PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 812784 Calibration Check Gas, 30 ppm R - 123 in Nitrogen

CHEMICAL NAME - 2,2 - Dichloro - 1,1,1 - Trifluoroethane in Nitrogen

ADDITIONAL IDENTITIES - MSA P/N 812784 Calibration Gas 30 ppm R - 123 in Nitrogen

FORMULA - CHCl_2CF_3 in N_2

APPLICABLE CHEMICAL CONTENTS

		<u>%</u>	<u>TWA</u>
CHCl_2CF_3 (CAS 306-83-2)		0.003	None established*
Nitrogen (CAS 7727-37-9)	Balance	None	

*AEL (Dupont) 50ppm TWA , WEEL (AIHA) 50 ppm TWA

NOTE: Gas under pressure, 1000 PSIG at 70°F, Approx. 100 Liters gas at atmospheric pressure

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless, odorless gas mixture

BOILING POINT - N/A

VAPOR PRESSURE - N/A

VAPOR DENSITY (AIR = 1) - > 1

SOLUBILITY IN WATER - CHCl_2CF_3 - approx. 0.39% WT @25C (77F)

Nitrogen - $2.3 \text{ cm}^3/100 \text{ ml}$ (0°C)

SPECIFIC GRAVITY ($\text{H}_2\text{O} = 1$) - N/A

PERCENT VOLATILE BY VOLUME - N/A

N/A - Not Applicable

PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed gas, 1000 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - Avoid bases. Avoid powdered active metals such as aluminum, alkali metals or alkaline earth metals.

FLASH POINT - N/A

EXTINGUISHING MEDIA - This calibration gas mixture is not flammable.

SPECIAL FIRE FIGHTING PROCEDURES - CHCl_2CF_3 decomposes at 250°C yielding toxic halogen compounds. Use self-contained pressure demand type breathing apparatus with full-face piece.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas under pressure, 1000 PSIG at 70°F. Do not exceed 120°F.

HEALTH HAZARDS

HEALTH HAZARDS - No TWA has been set for R-123. Dupont suggests 50 ppm TWA-8 hr. AIHA suggests 50ppm TWA. Inhalation 4-hour LC₅₀ (Rat) is 32,000 ppm. Skin absorption LD₅₀ (Rabbit) is >2000 mg/kg. Nitrogen is an asphyxiant. In isolated instances some workers overexposed to R-123 were found to have elevated liver enzymes. These elevated enzymes returned to normal when the overexposure ceased.

SIGNS AND SYMPTOMS OF EXPOSURE: None known for 100 ppm R - 123. Significant dilution of ambient air by asphyxiants causes air hunger, increased breathing frequency, drowsiness, weakness, and ringing in ears.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - Lungs

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No Information

EXPOSURE LIMITS - Not established for R-123 - Dupont suggests 50 ppm TWA-8 hr ; AIHA suggests 50ppm TWA.

CARCINOGENICITY DATA - Neither Nitrogen nor R - 123 is listed by NIOSH RTECS, IARC, NTP or OSHA.

EMERGENCY AND FIRST AID PROCEDURES - Remove victim from exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid breathing gas.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate area.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state and federal regulations.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 6, April 2005

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users

assume all risks in handling, using or storing this product.