

# **Material Safety Data Sheet**

Prepared according to OSHA Hazard Communication Standard (29 CFR 1910.1200) and ANSI MSDS Standard (Z400.1). Complies with Canadian Workplace Hazardous Materials Information System (WHMIS) standards.

Revision Date 10-Jun-2013

**Revision Number** 1

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SWEPCO 816 Food Grade Silicone Spray (Aerosol)

Product Code W30901A

Chemical Family Petroleum hydrocarbon

Recommended Use Lubricant

Supplier Address Southwestern Petroleum Corporation, 534 North Main St, Fort Worth, TX 76106 USA

1-800-877-9372 www.swepcousa.com

**Emergency Telephone Number** 

**UN-No** 


Chemtrec 1-800-424-9300 in US; Canutec 1-613-996-6666 in Canada.

None

# 2. HAZARDS IDENTIFICATION

DANGER! Emergency Overview

Flammable aerosol. May be harmful if swallowed, inhaled, or absorbed through skin.





**NFPA** 

Health 2 Flammability 4 Instability 0

WHMIS B5 - Flammable Aerosol, D2B - Other Toxic

AppearanceClear, CloudyPhysical StateAerosolOdorOdorless

Principle Routes of Exposure Skin contact. Inhalation. Eye contact.

**Acute Health Effects** 

Skin Avoid prolonged and/or repeated contact with skin. Prolonged and/or repeated contact with

this material may produce skin irritation or inflammation. Personnel with pre-existing skin

disorders should avoid contact with this product.

**Eyes** Contact with eyes may cause irritation.

**Inhalation** Avoid breathing of vapors or spray mist. May cause respiratory irritation or other pulmonary

effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limits (ACGIH TLV TWA: 5 mg/m³; ACGIH TLV

STEL: 10 mg/m<sup>3</sup>; OSHA PEL TWA: 5 mg/m<sup>3</sup>).

**Ingestion** Ingestion is not considered a likely route of exposure. Harmful if swallowed.

Carcinogenic Effects Carcinogenic effect of the complete mixture has not been evaluated. Information on

individual ingredients which may have carcinogenic effects, if any, will be found in Section 3

& 11.

#### **Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to petroleum based products with liver, kidney, brain and nervous system damage. There is, however, no reported human evidence that these effects occur when exposure is maintained below OSHA and ACGIH limits

**Aggravated Medical Conditions** No information available.

See Section 11 for additional toxicological information.

See Section 12 for ecological information.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

If any of the components of this product are defined as hazardous by OSHA Hazard Communication Standard 1910.1200 and are present at 1% or more (0.1% or more for carcinogens) or are considered hazardous components according to Canadian WHIMIS standards, they will be listed in this section. If no components appear in this section, no components of the product meet or exceed the reporting requirements.

Component	CAS-No	EINECS	Weight %	IARC	OSHA	NTP Carc	WHMIS
Butane	106-97-8	203-448-7	1 - 9.99	-	-	-	A, B1
106-97-8 (1 - 9.99)							
Propane	74-98-6	200-827-9	10 - 19.99	-	-	-	A, B1
74-98-6 ( 10 - 19.99							
)							
Heptane (n-)	142-82-5	205-563-8	20 - 39.99	-	-	-	B2, D2B
142-82-5 ( 20 -							
39.99)							
Acetone	67-64-1	200-662-2	40 - 59.99	-	-	-	B2, D2B
67-64-1 ( 40 - 59.99							
)							

## 4. FIRST AID MEASURES

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial

respiration. If symptoms persist, call a physician.

**Ingestion** Do not induce vomiting without medical advice. Consult a physician. If vomiting occurs,

keep head below hips to prevent aspiration.

Notes to Physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Flammable Properties Flammable aerosol. Containers may explode when heated.

Suitable Extinguishing Media Water spray or fog, Dry chemical, Carbon dioxide (CO2), Foam,

Cool containers with flooding quantities of water until well after

fire is out

Hazardous Combustion Products

No information available.

Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources

of ignition.

**Protective Equipment and Precautions for Firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent) and

full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing.

Methods for Containment Prevent further leakage or spillage if safe to do so. Use inert absorbent materials to confine

spills and absorb spill.

Methods for Clean-up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

**Other Information** Report spills as required to the appropriate authorities.

## 7. HANDLING AND STORAGE

**Handling** Contents under pressure. Do not puncture, crush or incinerate cans. Do not stick pin or any

other sharp object into opening on top of can. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapors or spray mist. Avoid contact with skin, eyes

and clothing. Do not eat, drink or smoke when using this product.

Storage Store containers below 120° F (49° C). Keep out of the reach of children. Store in

cool/well-ventilated place.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Guidelines**

The table below lists known exposure levels for any components of this product which are considered hazardous. Keep in mind, however, that these exposure levels are for pure concentrations of these ingredients. If no table appears below, occupational exposure limits have not been established or are not known for any of the ingredients in this product:

Chemical Name	ACGIH TLV	OSHA PEL	Quebec OEL	Ontario TWAEV	EU OEL
Butane	TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup> TWA: 800 ppm	TWA: 1900 mg/m <sup>3</sup> TWA: 800 ppm	TWA: 1900 mg/m <sup>3</sup> TWA: 800 ppm	
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm	
Heptane (n-)	TWA: 400 ppm STEL: 500 ppm	TWA: 1600 mg/m <sup>3</sup> TWA: 400 ppm STEL: 2000 mg/m <sup>3</sup> STEL: 500 ppm	STEL: 2050 mg/m <sup>3</sup> STEL: 500 ppm TWA: 1640 mg/m <sup>3</sup> TWA: 400 ppm	STEL: 2045 mg/m <sup>3</sup> STEL: 500 ppm TWA: 1635 mg/m <sup>3</sup> TWA: 400 ppm	TWA: 2085 mg/m <sup>3</sup> TWA: 500 ppm
Acetone	TWA: 500 ppm STEL: 750 ppm	TWA: 1800 mg/m <sup>3</sup> TWA: 750 ppm STEL: 1000 ppm STEL: 2400 mg/m <sup>3</sup>	STEL: 1000 ppm STEL: 2380 mg/m <sup>3</sup> TWA: 1780 mg/m <sup>3</sup> TWA: 750 ppm	STEL: 750 ppm TWA: 500 ppm	TWA: 500 ppm TWA: 1210 mg/m³

**Engineering Controls**Use in well-ventilated area. If user operations generate an oil mist, use process enclosures,

local exhaust ventilation or other engineering controls to control airborne levels below the recommended mineral oil mist exposure limits (ACGIH TLV TWA: 5 mg/m³; ACGIH TLV

STEL: 10 mg/m<sup>3</sup>; OSHA PEL TWA: 5 mg/m<sup>3</sup>).

**Eye/face Protection** Safety glasses with side-shields.

**Skin Protection** Use protective gloves and clothing if contact with product is likely.

**Respiratory Protection** If personal exposure levels cannot be maintained below accepted exposure limits or if

irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear, Cloudy Odor Odorless

Physical State Aerosol pH No data available

Flash Point

°F Autoignition Temperature No data available
Boiling Point/Range > Melting Point/Range No data available

Flammability Limits in Air, % No information available

Specific Gravity (Water=1) 0.86 Solubility In Water Insoluble

Vapor Density (Air=1) No data available Volatiles, % Vol No data available

## 10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended storage conditions.

**Conditions to Avoid** Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents.

Hazardous Decomposition Products Hydrogen sulfide (H2S) may be produced above 250° F (121° C).

**Hazardous Polymerization** Hazardous polymerization does not occur.

#### 11. TOXICOLOGICAL INFORMATION

Toxicity of this complete mixture has not been evaluated. If information is available on any of the individual components of the mixture, it is presented in this section. If no information appears in this section, there is no toxicological information available for any of the components of the mixture.

#### **Acute Toxicity**

The table below indicates toxicological information for specific ingredients at concentrations indicated. If no table appears, no toxicological information was found.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Butane			658 g/m³ (Rat)4 h
Propane		658 mg/kg (Rat)	
Heptane (n-)			103 g/m <sup>3</sup> (Rat)4 h
Acetone	1800 mg/kg (Rat)	20000 mg/kg (Rabbit)	76 mg/L (Rat) 4 h

**Chronic Toxicity** 

Reports have associated repeated and prolonged occupational overexposure to petroleum based products with liver, kidney, brain and nervous system damage. There is, however, no reported human evidence that these effects occur when exposure is maintained below OSHA and ACGIH limits.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. If no table appears, no toxicological information was found.

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Ecotoxicity and biodegradability of this complete mixture have not been evaluated. Consequently, this material should be kept out of sewage and drainage systems and all bodies of water and should not be considered readily biodegradable. If information is available on any of the individual components of the mixture, it is presented in this section. If no information appears in this section, there is no ecotoxicity or biodegradability information available for any of the components of the mixture.

Chemical Name	Freshwater Algae	Microtox	Water Flea	<b>DOT Marine Pollutant</b>
Heptane (n-)			EC50 > 10 mg/L 24 h	
Acetone		EC50 = 14500 mg/L 15 min	EC50 = 0.0039 mg/L 48 h EC50 = 12600 mg/L 48 h EC50 = 12700 mg/L 48 h	

# 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method** 

Do not puncture, crush or incinerate can. Do not cut on empty containers as they may contain vapors that are flammable. Dispose of in accordance with local regulations.

Chemical Name	RCRA	RCRA - Basis for Listing		RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream:			waste number U002
		F039			(Ignitable waste)
Chemical Name				California Hazardous Wa	aste Status
Heptane (n-)		Toxic; Ignitable			
Acetone				Ignitable	

## 14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Consumer commodity

Hazard Class ORM-D

**Description** Consumer commodity ,ORM-D

<u>TDG</u>

Proper Shipping Name Aerosols
Hazard Class 2.1
UN-No UN1950

<u>MEX</u>

Hazard Class 2.2 UN-No UN1950

**Description** UN1950 Aerosols,2.2,

**ICAO** 

UN-No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

**Description** Aerosols,UN1950

<u>IATA</u>

**UN-No** UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1 ERG Code 10L

**Description** UN1950,Aerosols, flammable,2.1

IMDG/IMO

Proper Shipping Name Heptanes

 Hazard Class
 2

 UN-No
 UN1950

 EmS No.
 F-D, S-U

**Description** UN1950, Aerosols,2

RID

Hazard Class 2

UN-No UN1950 Classification Code 5A

**Description** UN1950 Aerosols,2,,RID

ADR/RID-Labels

ADR

Proper Shipping Name Aerosols
Hazard Class 2
UN-No UN1950
Classification Code 5A

**Description** UN1950 Aerosols,2,,ADR

ADR/RID-Labels 2

ADN

Proper Shipping Name Aérosols
Hazard Class 2
UN-No UN1950

\_\_\_\_\_

# 15. REGULATORY INFORMATION

<u>U.S. Regulations & Inventories</u> The table below lists any regulatory or inventory listing information found for ingredients of this product which are considered hazardous. All other components are either listed on the inventories referenced or are exempt from listing. See Section 16 for explanation of column headings:

Chemical Name	CAS-No	TSCA	TSCA 12(b)	CERCLA/SARA 313 (de minimis concentration)	SARA Hazardous Substance Required Qty
Butane	106-97-8	Present	-	-	•
Propane	74-98-6	Present	-	-	-
Heptane (n-)	142-82-5	Т	Section 4	-	-
Acetone	67-64-1	Present	-	-	RQ= 2270 kg final RQ RQ= 5000 lb final RQ

<u>U.S. State Right-to-Know Regulations</u> The table below lists any regulatory or inventory listing information found for ingredients of this product which are considered hazardous. All other components are either listed on the inventories referenced or are exempt from listing. See Section 16 for explanation of column headings:

Chemical Name	Calif. Prop. 65	Massachusetts	New Jersey	Pennsylvania	Rhode Island
Butane		X	Χ	X	X
Propane		X	Х	Х	Х
Heptane (n-)		X	Х	Х	Х
Acetone		X	Х	Х	Х

<u>Canada Regulations & Inventories</u> The table below lists any regulatory or inventory listing information found for ingredients of this product which are considered hazardous. All other components are either listed on the inventories referenced or are exempt from listing. See Section 16 for explanation of column headings:

Chemical Name	CAS-No	DSL	NDSL	WHMIS
Butane	106-97-8	X	-	A, B1
Propane	74-98-6	X	-	A, B1
Heptane (n-)	142-82-5	X	-	B2, D2B
Acetone	67-64-1	X	-	B2, D2B

This product has been classified in accordance with the hazard criteria of the Candian CPR (Controlled Products Regulations) and the MSDS contains all the information required by the CPR.

<u>International Regulations & Inventories</u> The table below lists any regulatory or inventory listing information found for ingredients of this product which are considered hazardous. All other components are either listed on the inventories referenced or are exempt from listing. See Section 16 for explanation of column headings:

Chemical Name	EINECS	AICS	CHINA	ENCS	PICCS
Butane	203-448-7	Х	Х	X	X
Propane	200-827-9	Х	Х	Х	Х
Heptane (n-)	205-563-8	Х	X	X	X
Acetone	200-662-2	Х	X	Χ	X

# 16. OTHER INFORMATION

#### **Regulatory Lists Searched & Other Sources of Information**

ACGIH - American Converence of Governmental Industrial Hygienists

ADN - European Agreement for International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement for International Carriage of Dangerous Goods by Road

AICS - Australian Inventory of Chemical Substances

ANSI - American National Standards Institute

CAP65 - California Proposition 65 Hazard List

CAS - Chemical Abstract Services

CERCLA - Comprehensive Environmental Response, Compensation & Liability Act

CHINA - China Inventory

**CPR - Canadian Controlled Products Regulations** 

DOT - United States Department of Transportation

DSL - Canada Domestic Substances List

EINECS - European Union (EU) European Inventory of Existing Commercial Chemical Substances

**ENCS - Japan Existing and New Chemical Substances** 

IARC - International Agency for Research on Cancer

IATA - International Air Transport Association

ICAO - International Civil Aviation Organization

IMDG - International Maritime Dangerous Goods Code

MARTK - Massachusetts Right To Know List

NDSL - Canada Non-Domestic Substances List

NFPA - United States National Fire Protection Association

NIOSH - United States National Institute for Occupational Safety & Health

NJRTK - New Jersey Right To Know List

NTP - United States National Toxicology Program

OSHA - United States Occupational Safety & Health Administration

PARTK - Pennsylvania Right To Know List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

RCRA - United States Resources Conservation & Recovery Act

RID - European Agreement for International Carriage of Dangerous Goods by Rail

RIHSL - Rhode Island Hazardous Substance List

SARA - United States Superfund Amendments & Reauthorization Act

TDG - Canada Transportation of Dangerous Goods Act

TSCA - US Toxic Substances Control Act

WHMIS - Canada Workplace Hazardous Materials Information System

#### **Definitions**

EC50 - Effective Concentration (Concentration of a compound where 50% of the expected effect is observed.)

LC50 - Lethal Concentration (The concentration in water that will kill 50% of the test animals within a specific period of time, usually 96 hours.)

LD50 - Lethal Dose (The single dose that will kill 50% of the test animals by any route other than inhalation such as by ingestion or skin contact.)

OEL - Occupational Exposure Limit

PEL - Permissible Exposure Limits

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TWA - Time Weighted Average

TWAEV - Time Weighted Average Exposure Value

**Revision Date** 

10-Jun-2013

**End of MSDS** 

\_\_\_\_\_