



## Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

### \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Product Code:** Prefix 50

**Chemical Name:** ECOPOWER WAY OIL ISO 68 (OEM)

**Product Use:** For lubricating machine tool ways.

If this product is used in combination with other products, refer to the Material Safety Data Sheets for those products.

**Synonyms:** Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant.

Safety-Kleen Systems, Inc.

Phone: 1-800-669-5740

5360 Legacy Drive

Building 2, Suite 100

Plano, TX 75024

Emergency # 1-800-468-1760

**Issue Date:**

January 4, 2012

**Supersedes Issue Date**

New Issue MSDS

**Original Issue Date**

New Issue MSDS

PREPARED BY: Product MSDS Coordinator

APPROVED BY: MSDS Task Force

### \*\*\* Section 2 - Hazardous Identification \*\*\*

#### EMERGENCY OVERVIEW

##### Appearance

Amber liquid, petroleum odor.

##### Signal Word

CAUTION!

##### Health Hazards

May be harmful if swallowed.

May irritate eyes and skin.

#### POTENTIAL HEALTH EFFECTS

##### Inhalation (Breathing)

This product is not likely to present an inhalation hazard at normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

##### Eyes

May cause irritation.

##### Skin

May cause irritation. A single prolonged exposure is not likely to be absorbed through the skin in harmful amounts.

##### Ingestion (Swallowing)

May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

##### Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

##### Chronic

Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

# Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

## Cancer Information

No known carcinogenicity. For more information, see **SECTION 11: MUTAGENICITY AND CARCINOGENICITY**.  
Also see **SECTION 15: CALIFORNIA**.

## Environmental Hazards

Not available. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

## \* \* \* Section 3 - Composition / Information on Ingredients \* \* \*

CAS	Component	Percent
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	81
72623-83-7	Lubricating oils (petroleum), C>25, hydrotreated bright stock	0.1-17*
64742-62-7	Residual oils (petroleum), solvent dewaxed	0.1-17*
64742-01-4	Residual oils (petroleum), solvent refined	0.1-17*
64742-54-7	Petroleum distillates, hydrotreated heavy paraffinic	0.6-1.2

\*Only one of the above listed Bright Stocks will be present at any one time at the indicated WT%.

## \* \* \* Section 4 - First Aid Measures \* \* \*

### Inhalation (Breathing)

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

### Eyes

If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

### Skin

Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician should immediately evaluate the individual as a medical emergency.

### Ingestion (Swallowing)

Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything by mouth to an unconscious person.

### Notes to Physicians

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

## \* \* \* Section 5 - Fire Fighting Measures \* \* \*

### Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.

### Conditions of Flammability

Sparks or flame. Product may burn, but does not ignite readily.

### Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

### Protective Equipment For Firefighting

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

### Fire Fighting Equipment/Instructions

Keep storage containers cool with water spray.

### NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

# Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

## Fire and Explosion Hazards

Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

## \* \* \* Section 6 - Accidental Release Measures \* \* \*

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk.

Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE**

**CONTROLS/PERSONAL PROTECTION.** Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or absorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal.

Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

## \* \* \* Section 7 - Handling and Storage \* \* \*

### Handling Procedures

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools and explosion-proof equipment. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

### Shipping and Storing

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

## \* \* \* Section 8 - Exposure Controls / Personal Protection \* \* \*

### Exposure Guidelines

#### Component Exposure Limits

##### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

ACGIH: 5 mg/m<sup>3</sup> TWA (excluding metal working fluids, highly & severely refined, inhalable fraction, related to Oil mist, mineral)

OSHA Final: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)

OSHA Vacated: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)

NIOSH: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)  
10 mg/m<sup>3</sup> STEL (related to Oil mist, mineral)

##### Residual oils (petroleum), solvent dewaxed (64742-62-7)

ACGIH: 5 mg/m<sup>3</sup> TWA (excluding metal working fluids, highly & severely refined, inhalable fraction, related to Oil mist, mineral)

OSHA Final: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)

OSHA Vacated: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)

NIOSH: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)  
10 mg/m<sup>3</sup> STEL (related to Oil mist, mineral)

##### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

ACGIH: 5 mg/m<sup>3</sup> TWA (excluding metal working fluids, highly & severely refined, inhalable fraction, related to Oil mist, mineral)

OSHA Final: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)

OSHA Vacated: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)

NIOSH: 5 mg/m<sup>3</sup> TWA (related to Oil mist, mineral)  
10 mg/m<sup>3</sup> STEL (related to Oil mist, mineral)

### Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

# Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

## Personal Protective Equipment: Respiratory

Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

## Personal Protective Equipment: Eyes/Face

Where eye contact is likely, wear safety glasses; contact lens use is not recommended.

## Personal Protective Equipment: Skin

Where skin contact is likely, wear neoprene, nitrile, or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended.

When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing.

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

## Personal Protective Equipment: Personal Hygiene

Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard leather articles, such as shoes, saturated with this product.

## Other Personal Protective Equipment

Where spills and splashes are likely, facilities storing or using this product should be equipped with an emergency eyewash and shower, both equipped with clean water, in the immediate work area.

## \* \* \* Section 9 - Physical & Chemical Properties \* \* \*

Appearance/Odor :	Amber liquid, petroleum odor.	pH:	Not applicable
Boiling Point:	475°F (246°C) (minimum)	Melting Point:	Not available [pour point 16°F (-9°C) (maximum)]
Solubility (H <sub>2</sub> O):	Insoluble	Specific Gravity:	0.88 (water = 1) (approximately)
Density:	7.3 LB/US gal (880 g/L) (approximately)	Octanol/H <sub>2</sub> O Coeff.:	Not available
Evaporation Rate:	Not available	Molecular Weight:	Not applicable
Odor Threshold:	Not available	Auto Ignition:	Not Available
LFL:	Not available	Flash Point:	410°F (210°C) (minimum) (Cleveland Open Cup)
UFL:	Not available	Viscosity:	Greater than 100 SUS
Vapor Pressure:	Less than 0.1 mm Hg @ 68°F (20°C)		

## \* \* \* Section 10 - Chemical Stability & Reactivity Information \* \* \*

### Stability

Stable under normal temperatures and pressures.

### Incompatibility

Avoid oxidizing agents.

### Reactivity

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

### Hazardous Decomposition Products

None under normal temperatures and pressures. See also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.**

### Conditions To Avoid

Sparks, flame and incompatible materials.

# Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

## \* \* \* Section 11 - Toxicological Information \* \* \*

### Component Analysis - LD50/LC50

#### Residual oils (petroleum), solvent dewaxed (64742-62-7)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

#### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Oral LD50 Rat >5000 mg/kg

#### Residual oils (petroleum), solvent refined (64742-01-4)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

#### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

### Acute Effects

May irritate eyes and skin. May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

### Carcinogenicity

#### Component Carcinogenicity

##### Residual oils (petroleum), solvent dewaxed (64742-62-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

##### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

##### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Target Organ Effects

Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation.

### Sensitization

Based on best current information, there is no known human sensitization associated with these products.

### Mutagenicity

Experimental evidence suggests that these products do not cause mutagenesis.

### Reproductive Toxicity

Based on best current information, there is no known reproductive toxicity associated with these products.

Also see SECTION 15: CALIFORNIA.

### Teratogenicity

Based on best current information, there is no known teratogenicity associated with these products.

## \* \* \* Section 12 - Ecological Information \* \* \*

### Ecotoxicity

No information available for these products.

### Component Analysis - Ecotoxicity - Aquatic Toxicity

#### Residual oils (petroleum), solvent refined (64742-01-4)

Duration/Test/Species	Concentration/Conditions/Notes
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L

#### Residual oils (petroleum), solvent dewaxed (64742-62-7)

Duration/Test/Species	Concentration/Conditions/Notes
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L

#### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Duration/Test/Species	Concentration/Conditions/Notes
96 Hr LC50 Lepomis macrochirus	>10000 mg/L

#### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Duration/Test/Species	Concentration/Conditions/Notes
96 Hr LC50 Brachydanio rerio	79.6 mg/L [semi-static]
96 Hr LC50 Pimephales promelas	3.2 mg/L [semi-static]

# Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

## Persistence/Degradability

May cause long-term adverse effects in the aquatic environment.

## Bioaccumulation/Accumulation

No data available for the product.

## Mobility in Environmental Media

Product is expected to float on water and have low mobility through soil.

## Other Adverse Effects

No information available for the product.

## \* \* \* Section 13 - Disposal Considerations \* \* \*

### Disposal Instructions

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

### US EPA Waste Number & Descriptions

These products, if discarded, are not expected to be a characteristic or listed hazardous waste. If recycled in the USA, they must be managed in accordance with 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of these products.

## \* \* \* Section 14 - Transportation Information \* \* \*

### Emergency Response Guide Number

Not applicable. Reference *North American Emergency Response Guidebook*

DOT **Shipping Name:** Not regulated.

TDG **Shipping Name:** Not regulated.

## \* \* \* Section 15 - Regulatory Information \* \* \*

### Volatile Organic Compounds (As Regulated)

Negligible; As per 40 CFR Part 51.100(s)

### SARA Sections 311/312

This product poses the following health hazard(s) as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard

Delayed (Chronic) Health Hazard

### SARA 302/304

### Component Analysis

This product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

### SARA Section 313

This product does not contain "toxic" chemical(s) subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

### Component Analysis

This product does not contain any "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

### CERCLA

### Component Analysis

This product does not contain any "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

### TSCA

All the components of this product are listed on, or are automatically included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA Inventory.

# Material Safety Data Sheet

Material Name: ECOPOWER WAY OIL ISO 68 (OEM)

ID: 820116

## Component Analysis

Component	CAS #	TSCA
Residual oils (petroleum), solvent refined	64742-01-4	Yes
Residual oils (petroleum), solvent dewaxed	64742-62-7	Yes
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	Yes
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	Yes

## California

This product does not contain any chemical known to the State of California to cause cancer.

This product does not contain any chemical known to the State of California to cause birth defects or other reproductive harm.

## Canadian Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

## Component Analysis

Component	CAS #	CAN
Residual oils (petroleum), solvent refined	64742-01-4	DSL
Residual oils (petroleum), solvent dewaxed	64742-62-7	DSL
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	DSL
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	DSL

## Canadian WHMIS Information

Not regulated.

## Canadian Environmental Protection Act (CEPA)

All the components of these products are listed on, or are automatically included as "substance occurring in nature" on, or are exempted from the requirements to be listed on, the Canadian Domestic Substances List (DSL).

## \* \* \* Section 16 - Other Information \* \* \*

### Label/Other Information

Not available.

### Revision Information

New issue MSDS.

### Disclaimer

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplier to the user.

End of Sheet 820116