



## Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

### \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Product Code:** Prefix 26

**Chemical Name:** America's Choice GL-5 Gear Oil

**Product Use:** For lubricating differentials and final drives of automotive equipment. If this product is used in combination with other products, refer to the Material Safety Data Sheet for those products.

**Synonyms:** Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant; Automotive gear oil.

Safety-Kleen Systems, Inc.  
2600 North Central Expressway  
Suite 400  
Richardson, TX 75080

Phone: 1-800-669-5740

Emergency # 1-800-468-1760  
[www.safety-kleen.com](http://www.safety-kleen.com)

**Issue Date**

November 12, 2012

**Supersedes Issue Date**

December 3, 2009

**Original Issue Date**

May 12, 1994

PREPARED BY: Product MSDS Coordinator

APPROVED BY: MSDS Task Force

### \*\*\* Section 2 - Hazardous Identification \*\*\*

#### EMERGENCY OVERVIEW

**Appearance**

Amber liquid, petroleum odor.

**Signal Word**

CAUTION!

**Health Hazards**

May be harmful if swallowed.

May irritate eyes and skin.

#### POTENTIAL HEALTH EFFECTS

**Inhalation (Breathing)**

This product is not likely to present an inhalation hazard at normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

**Eyes**

May cause irritation.

**Skin**

May cause irritation. Not likely to be absorbed through the skin in harmful amounts.

**Ingestion (Swallowing)**

May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

**Medical Conditions Aggravated by Exposure**

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## Chronic

Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

## Cancer Information

No known carcinogenicity. For more information, see **SECTION 11: MUTAGENICITY** and **CARCINOGENICITY**. Also see **SECTION 15: CALIFORNIA**.

## Environmental Hazards

Not available. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

### \*\*\* Section 3 - Composition / Information on Ingredients \*\*\*

CAS	Component	Percent
72623-83-7	Lubricating oils (petroleum), C>25, hydrotreated bright stock	27-93
64742-62-7	Residual oils (petroleum), solvent dewaxed	27-93
64742-57-0	Residual oils (petroleum), hydrotreated	27-93
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	0-45
Trade Secret	Polyolefin*	0-18
Trade Secret	Mineral Oil*	3-5
Trade Secret	Phosphoric acid esters, amine salts*	1-2
Trade Secret	Olefin sulfide*	1-2
64742-54-7	Petroleum distillates, hydrotreated heavy paraffinic	0-2
72623-86-0	Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	0.3-1.0
64741-88-4	Petroleum distillates, solvent-refined heavy paraffinic	0.3-1.0

## Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Oil mist, mineral (8012-95-1).

### \*\*\* Section 4 - First Aid Measures \*\*\*

#### Inhalation (Breathing)

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

#### Eyes

If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

#### Skin

Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician should immediately evaluate the individual as a medical emergency. Wash contaminated clothing before reuse.

#### Ingestion (Swallowing)

Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything by mouth to an unconscious person.

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## Notes to Physicians

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

## \*\*\* Section 5 - Fire Fighting Measures \*\*\*

### Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce hydrogen sulfide, sulfides, alkyl mercaptans, methacrylate monomers, aldehydes, nitrogen oxides, sulfur oxides, phosphorus oxides, carbon monoxide, and unidentified organic compounds.

### Conditions of Flammability

Sparks or flame. Product may burn, but does not ignite readily.

### Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

### Fire Fighting Equipment/Instructions

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

## NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Fire and Explosion Hazards

Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Handling Procedures

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools and explosion-proof equipment. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

### Shipping and Storing

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

### Exposure Guidelines

#### Component Exposure Limits

None available.

#### Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

#### Personal Protective Equipment: Respiratory

No respiratory protection is normally required. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respiratory selection guidance.

#### Personal Protective Equipment: Eyes/Face

Where eye contact is likely, wear safety glasses; contact lens use is not recommended.

#### Personal Protective Equipment: Skin

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended.

When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

#### Personal Protective Equipment: Personal Hygiene

Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse.

Discard leather articles, such as shoes, saturated with this product.

#### Other Personal Protective Equipment

Where spills and splashes are likely, facilities storing or using this product should be equipped with an emergency eyewash and shower, both equipped with clean water, in the immediate work area.

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Appearance/Odor :</b>	Amber liquid	<b>pH:</b>	Not applicable
<b>Boiling Point:</b>	425 °F (218°C) (minimum)	<b>Melting Point:</b>	Not available
<b>Solubility (H2O):</b>	Insoluble	<b>Specific Gravity:</b>	0.89 (water=1)
<b>Density:</b>	7.4 LB/US gal (890 g/l)	<b>Octanol/H2O Coeff.:</b>	Not available
<b>Evaporation Rate:</b>	Not available	<b>Molecular Weight:</b>	Not applicable
<b>Odor Threshold:</b>	Not available	<b>Auto Ignition:</b>	Not Available
<b>LFL:</b>	Not Available	<b>Flash Point:</b>	374°F (190°C)
<b>UFL:</b>	Not Available		
<b>Vapor Pressure:</b>	<0.1 mm Hg at 68°F (20°C)		

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

### Stability

Stable under normal temperatures and pressures.

### Incompatibility

Avoid oxidizing agents.

### Reactivity

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

### Hazardous Decomposition Products

None under normal temperatures and pressures. See also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS**.

### Conditions To Avoid

Avoid heat, sparks, or flame when not in use.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Toxicity Data

#### Component Analysis - LD50/LC50

##### Residual oils (petroleum), hydrotreated (64742-57-0)

Oral LD50 Mouse 22 g/kg (related to Oil mist, mineral)

##### Residual oils (petroleum), solvent dewaxed (64742-62-7)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

##### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Oral LD50 Rat >5000 mg/kg

##### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

##### Mineral Oil\* (Trade Secret)

Oral LD50 Mouse 22 g/kg (related to Oil mist, mineral)

##### Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

Oral LD50 Mouse 22 g/kg (related to Oil mist, mineral)

##### Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

##### Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

### Acute Effects

May be harmful if swallowed. May irritate eyes and skin. May cause throat irritation, nausea, vomiting, and or diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## Component Carcinogenicity

### Residual oils (petroleum), hydrotreated (64742-57-0)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Residual oils (petroleum), solvent dewaxed (64742-62-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Mineral Oil\* (Trade Secret)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

### Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

ACGIH: A4 - Not Classifiable as a Human Carcinogen (highly & severely refined); A2 - Suspected Human Carcinogen (poorly & mildly refined, related to Oil mist, mineral)

## Sensitization

Methacrylate, which may be produced upon combustion, is a severe eye and skin irritant and a skin sensitizer in animals.

## Mutagenicity

Experimental evidence suggests that this product does not cause mutagenesis.

## Reproductive Toxicity

Based on best current information, there is no known reproductive toxicity associated with this product.

## Teratogenicity

Based on best current information, there is no known teratogenicity associated with this product.

## \*\*\* Section 12 - Ecological Information \*\*\*

## Ecotoxicity

Not available.

## Component Analysis - Ecotoxicity - Aquatic Toxicity

### Residual oils (petroleum), solvent dewaxed (64742-62-7)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L	

### Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Lepomis macrochirus	>10000 mg/L	

### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Brachydanio rerio	79.6 mg/L [semi-static]	
96 Hr LC50 Pimephales promelas	3.2 mg/L [semi-static]	

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L	

## Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L	

## Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L	

### Persistence/Degradability

May cause long-term adverse effects in the aquatic environment.

### Mobility in Environmental Media

No information available.

### Other Adverse Effects

No additional information available.

## \*\*\* Section 13 - Disposal Considerations \*\*\*

### Disposal Instructions

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

### US EPA Waste Number & Descriptions

This product, if discarded, is not expected to be a characteristic or listed hazardous waste. If recycled as used oil in the USA this product can be managed in accordance with the used oil exemption under 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product.

## \*\*\* Section 14 - Transportation Information \*\*\*

### Emergency Response Guide Number

Not applicable.

Reference .North American Emergency Response Guidebook.

**DOT Shipping Name:** Not regulated as a hazardous material.

**TDG Shipping Name:** Not regulated as a dangerous good.

### IATA Information

No Classification Assigned.

### IMDG Information

No Classification Assigned.

## \*\*\* Section 15 - Regulatory Information \*\*\*

### Volatile Organic Compounds (As regulated)

Negligible, As per 40 CFR 51.100(s)

### SARA Sections 311/312

These products pose the following health hazard(s) as defined in 40 CFR Part 370 and are subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard

Delayed (Chronic) Health Hazard

# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

## SARA 302/304

### Component Analysis

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

## SARA Section 313

### Component Analysis

This product does not contain any "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

## CERCLA

### Component Analysis

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

## TSCA

All the components of this product are listed on, or are exempted from the requirement to be listed on, the TSCA Inventory.

### Component Analysis

Component	CAS #	TSCA
Residual oils (petroleum), hydrotreated	64742-57-0	Yes
Residual oils (petroleum), solvent dewaxed	64742-62-7	Yes
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	Yes
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	Yes
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Yes
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	Yes
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0	Yes

## State Regulations

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	MA	MN	NJ	PA	CA
Residual oils (petroleum), hydrotreated (¹related to: Oil mist, mineral)	64742-57-0	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹
Residual oils (petroleum), solvent dewaxed (¹related to: Oil mist, mineral)	64742-62-7	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹
Lubricating oils (petroleum), C>25, hydrotreated bright stock (¹related to: Oil mist, mineral)	72623-83-7	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹
Lubricating oils, petroleum, hydrotreated spent (¹related to: Oil mist, mineral)	64742-58-1	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹
Mineral Oil* (¹related to: Oil mist, mineral)	Trade Secret	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹
Petroleum distillates, hydrotreated heavy paraffinic (¹related to: Oil mist, mineral)	64742-54-7	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹



# Material Safety Data Sheet

Material Name: AMERICA'S CHOICE GL-5 GEAR OIL

ID: 82620

Petroleum distillates, solvent-refined heavy paraffinic (¹related to: Oil mist, mineral)	64741-88-4	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (¹related to: Oil mist, mineral)	72623-86-0	Yes¹	Yes¹	Yes¹	Yes¹	Yes¹

## California

This product does not contain any chemicals known to the State of the California to cause cancer.

This product does not contain any chemicals known to the State of California to cause birth defects or other reproductive harm.

## Canadian Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

## Component Analysis

Component	CAS #	CAN
Residual oils (petroleum), hydrotreated	64742-57-0	DSL
Residual oils (petroleum), solvent dewaxed	64742-62-7	DSL
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	DSL
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	DSL
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	DSL
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	DSL
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0	DSL

## Canadian WHMIS Information

Not regulated.

## Canadian Environmental Protection Act (CEPA)

All the components of this product are listed on, or are automatically included as "substance occurring in nature" on, or are exempted from the requirements to be listed on, the Canadian Domestic Substances List (DSL).

## \*\*\* Section 16 - Other Information \*\*\*

## Label/Other Information

Not available.

## Revision Information

Update to MSDS format, corrected to SK oil template.

## Disclaimer

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.