**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** Seche Base Coat DBP Free**DATE:** 2/7/2006**FORMULA:** 83002**REV.** NEW**Section 1. Material Identification and Information****Hazardous Ingredients:**

Component	CAS #	%	TOXICOLOGICAL DATA
Butyl Acetate	123-86-4	30-40%	ACGIH-TWA: 150ppm OSHA-PEL: 150ppm
Toluene*	108-88-3	10-20%	ACGIH-TWA: 150ppm OSHA-PEL: 150ppm
Ethyl Acetate	141-78-6	10-20%	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
Nitrocellulose	9004-70-0	10-20%	ACGIH-TWA: 400ppm
Isopropyl Alcohol	67-63-0	5-10%	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
Camphor	76-22-2	1-5%	ACGIH-TWA: 2ppm OSHA-PEL: 2ppm

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

WARNING: This product contains toluene, a chemical known to the State of California to cause birth defects and other reproductive harm.

Section 2. Physical / Chemical Characteristics

Boiling Range: 171°F-228°F
Vapor Pressure: Not Determined
(mm Hg and Temperature)

Vapor Density: Not Determined
(Air = 1)

Solubility in Water: Partial

Appearance: Colored Viscous Liquid

Odor: Sweet Ester Odor

Specific Gravity: 7.578lb/gl
(H₂O = 1)

Melting Point: Not Determined

Evaporation Rate: Information not available
(m-butyl acetate = 1)

Water Reactive: N/A

Density: Not Determined

Coating V.O.C.: 1.87 lb/gl

Material V.O.C.: Not Determined

Section 3. Fire and Explosion Hazard Data


Flash Point and Method Used: 24°F TCC

Auto-Ignition Temperature: N/A

Flammability Limits in Air % by Volume:
LEL: 1.2%
UEL: 12.7%

Extinguisher Media: Water is the most effective fire-extinguishing medium for Nitrocellulose. It is recommended to be used in large volume. Dry chemical, CO₂, or universal type foam could be used to extinguish small fires.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** Seche Base Coat DBP Free**DATE:** 2/7/2006**FORMULA:** 83002**REV.** NEW

Unusual Fire and Explosion Hazards: prevent contact with skin and eyes. Use water spray to keep fire exposed containers cool.
Material is flammable. Vapors may travel considerable distance to a source of ignition and flash back. Keep away from heat, sparks, and flame. Keep container closed. Use with adequate ventilation.

Section 4. Reactivity Hazard Data**Stability:** ☒ Stable ☐ Unstable**Conditions to Avoid:** Flame, Electric spark, static and heat.**Incompatibility (Materials to Avoid):**

This product is incompatible with strong acids or bases and oxidizers.

Hazardous Decomposition:

Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide and nitrogen oxide. Under some conditions, methane, irritating aldehydes and carboxylic acids and hydrogen cyanide may be formed.

Hazardous Polymerization:☐ May Occur ☒ Will Not Occur**Section 5. Health Hazard Data****Primary Routes of Entry:**☒ Inhalation ☒ Skin Absorption ☐ Eyes ☐ Ingestion

Health Hazards: No ingredient present in this product is identified as a carcinogen or probably carcinogen by NTP, IARC, or OSHA. Reports have associated repeated and prolonged occupational overexposure to solvent present in this product with permanent brain and nervous system damage (sometimes referred to as solvent or painter's syndrome). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Signs and Symptoms of Exposure:

Headache, dizziness, nausea, staggering gate, confusion and unconsciousness.

Eyes: This product may cause eye irritation. Direct contact with this material or exposure to its vapors or mists (greater than approximately 1000 ppm) may cause burning, tearing, redness and swelling.

Inhalation: May cause nose and throat irritation.


Skin: This product may cause skin irritation. Prolonged or repeated exposure to this material may cause redness and burning, drying, and cracking of the skin and dermatitis.

Ingestion: Gastrointestinal distress, call a physician.

Medical Conditions Generally Aggravated by Exposure:

Respiratory symptoms associated with pre-existing lung disorders (e.g. asthma-like conditions) may be aggravated by exposure to the vapors of this material. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

Emergency First Aid Procedures:

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Seche Base Coat DBP Free	DATE:	2/7/2006
FORMULA:	83002	REV.	NEW

Inhalation:	In case of irritation by vapor, remove from exposure, treat symptomatically and get medical attention if symptoms persist.
Eye Contact:	Any material that contacts the eye should be washed out immediately and medical attention obtained if symptoms persists.
Skin Contact:	Wash with soap and plenty of water.
Ingestion:	Call a physician or poison control center immediately. Induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person.

Proposition 65 Statement:

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Section 6. Control and Protective Measures**Respiratory Protections (Specific Type):**

When vapor concentration exceed the established exposure limits respiratory protection is necessary. Depending on the airborne concentration, use a respirator or gas mask with appropriate cartridges and canisters (NIOSH approved organic vapor) or supplied air equipment.

Protective Gloves: The use of gloves impermeable to the specific material handled is advised to prevent skin contact and possible irritation.

Eye Protection: Safety glasses with side shields (or goggles) are recommended for any type of industrial chemical handling.

Ventilation to be Used:

The ventilation system should be designed to be able to maintain airborne concentrations below the established exposure limits. If the current ventilation is not adequate to maintain this level, additional ventilation or exhaust systems may be required. Use explosion proof equipment.


Other Protective Clothing and Equipment:

The use of gloves impermeable to the specific material handled is advised to prevent skin contact and possible irritation. Use splash goggles (NIOSH approved) to safeguard against potential eye contact, irritation or injury.

Hygienic Work Practices:

Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Maintain a source of clean water to be available in work area for flushing eyes and skin. Remove contaminated clothing; launder or dry-clean before use. Remove contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact before breaks and meals, and at the end of work period. Product is rapidly removed from skin by waterless hand cleaners or solvent (acetone or esters) followed by washing with soap and water. Impervious clothing should be worn as needed.

Section 7. Precautions for Safe Handling and Use / Leak Procedures

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** Seche Base Coat DBP Free**DATE:** 2/7/2006**FORMULA:** 83002**REV.** NEW**Steps to be Taken if Material is Spilled or Released:**

Highway or railway spills call Chemtrec (800) 424-9300 continental US or collect (920) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (800) 424-8802 in case if the spill is in excess of EPA reportable quantity.

Waste Disposal Methods:

Dispose of in accordance with your local, state, and federal regulations.

Precautions to be taken in Handling and Storing:

Use non-sparking utensils when handling this material. Keep containers, tightly closed, cool, dry and away from sources of ignition.

Other Precautions and/or Special Hazards:

Smoking in an area where this material is used should be strictly prohibited. Use with adequate ventilation. If normal ventilation use with NIOSH approved respirator or exhaust fan.

Section 8. Shipping Information**Proper Shipping Name:**

Paint

DOT Hazard Class:

3 (Flammable Liquid)

Packaging Group:

PG II

UN ID Number:

1263