

# SAFETY DATA SHEET

203A EP Industrial Machine Lube with Moly ISO 68, 100, 150, 220 203B EP Industrial Machine Lube with Soluble Moly with Tack ISO 32, 46, 68, 100, 150, 220

203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

### **Section 1. Identification**

**GHS** product identifier

: 203A EP Industrial Machine Lube with Moly ISO 68, 100, 150, 220

203B EP Industrial Machine Lube with Soluble Moly with Tack ISO 32, 46, 68, 100, 150, 220 203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

Other means of identification

: Not available.

Product type : Liquid.

### **Identified uses**

Light to medium viscosity general purpose extreme pressure gear lubricant.

Supplier's details

: Schaeffer Mfg. Company

102 Barton Street

Saint Louis, Missouri 63104

Tel: 314-865-4100 Fax: 314-865-4107 Toll Free: 1-800-325-9962 E-Mail: safety@schaefferoil.com Web: http://www.schaefferoil.com

Emergency telephone number (with hours of operation) : +1 314 865-4105 (24-hour response number)

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN SENSITIZATION - Category 1
AQUATIC HAZARD (ACUTE) - Category 3
AQUATIC HAZARD (LONG-TERM) - Category 3

**GHS label elements** 

Hazard pictograms



Signal word

: Warning

**Hazard statements** 

: May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention** 

: Wear protective gloves. Avoid release to the environment. Avoid breathing vapor. Contaminated work clothing should not be allowed out of the workplace.

### Section 2. Hazards identification

Response

: IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.

**Storage** 

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Base Oil(s)(*)	60 - 100	See below.
Long-chain alkyl amine	0.1 - 1	-
Long-chain alkenyl amine	0.1 - 1	-
2,6-di-tert-Butylphenol	0.1 - 1	128-39-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Base oil(s) contained in this material may be described by one or more of the following CAS Nos.: 64742-01-4, 64742-52-5, 64742-54-7, 64742-57-0, 64742-62-7, 64742-65-0, 72623-85-9, 72623-87-1.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.

**Inhalation** 

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed Potential acute health effects

203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

### Section 4. First aid measures

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Adverse symptoms may include the following:

irritation redness

Ingestion : No known significant effects or critical hazards.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

: Use an extinguishing agent suitable for the surrounding fire.

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: No specific data.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

: No special measures are required.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

# Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. U.S.A. regulations may require reporting spills of this material that could reach any surface waters. Report spills to all applicable Federal, State, Provincial and local authorities and/or the United States National Response Center at (800) 424-8802 as appropriate or required.

### Methods and materials for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### **Precautions for safe handling**

#### Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

**Control parameters** 

Occupational exposure limits

### Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Base Oil(s)(*)	NIOSH REL (United States, 10/2013).  TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist  ACGIH TLV (United States).  TWA: 5 mg/m³ Form: Oil mist. STEL: 10 mg/m³ Form: Oil mist.  OSHA PEL (United States).  TWA: 5 mg/m³ Form: Oil mist.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

**Eye/face protection**: Wear eye protection such as safety glasses, chemical goggles, or face shields if engineering controls or work practices are not adequate to prevent eye contact.

**Skin protection** 

**Hand protection** : Use nitrile or oil resistant gloves.

Body protection : Personal protective clothing such as gloves, aprons, boots and complete facial protection should be selected based on the task being performed and the risks involved.

Users should determine acceptable performance characteristics of protective clothing. Consider physical requirements and other substances present when selecting protective

clothing.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved.

Respiratory protection : If a risk assessment indicates that respiratory protection is required, use a properly fitted,

air-purifying or supplied air respirator that complies with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### Section 9. Physical and chemical properties

Strong.

**Appearance** 

Physical state : Liquid.

Color : Blue-Green.

Odor threshold : Not available.

pH : Not applicable.

Melting point/ Dropping

**Point** 

Odor

: Not available.

**Boiling point** : >300°C (>572°F)

Flash point : Open cup: 215.56 to 232.22°C (420 to 450°F)

**Evaporation rate** : Not available.

### Section 9. Physical and chemical properties

Flammability (solid, gas)

Lower and upper explosive

Not available. : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available. Relative density : 0.8735 to 0.8871 Solubility : Insoluble in water.

Partition coefficient: n-

octanol/water

: Not available.

**Auto-ignition temperature** 

: Not available. : Not available.

**Decomposition temperature Viscosity** 

: Kinematic (100°C): 5.6 to 21.89 cSt Kinematic (40°C): 28.8 to 242 cSt

**Volatility** : Not available.

# Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and

handling condtitions of temperature and pressure.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : High heat, high energy ignition sources.

**Incompatible materials** : Reactive or incompatible with the following materials: Strong oxidizing and reducing

agents.

**Hazardous decomposition** 

: Oxides of carbon, sulfur and by-products of incomplete combustion.

products

# Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2,6-di-tert-Butylphenol	LD50 Dermal LD50 Oral		>10 g/kg 1320 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,6-di-tert-Butylphenol	Skin - Moderate irritant	Rat	-	0.5 mL	-

#### **Sensitization**

There is no data available.

### Carcinogenicity

There is no data available.

# 203B EP Industrial Machine Lube with Soluble Moly With Tack ISO 32, 46, 68, 100, 150, 220 203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

### Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

**Section 11. Toxicological information** 

There is no data available.

**Aspiration hazard** 

There is no data available.

Information on the likely

routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Adverse symptoms may include the following:

irritation redness

**Ingestion**: No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

effects

: No known significant effects or critical hazards.

**Potential delayed effects**: No known significant effects or critical hazards.

Long term exposure

**Potential immediate** 

: No known significant effects or critical hazards.

effects

**Potential delayed effects**: No known significant effects or critical hazards.

Potential chronic health effects

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

There is no data available.

### **Section 12. Ecological information**

#### **Toxicity**

There is no data available.

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2,6-di-tert-Butylphenol	4.5	-	high

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

**AERG**: Not applicable

203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

### **Section 14. Transport information**

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available.

to Annex II of MARPOL 73/78 and the IBC Code

### Section 15. Regulatory information

**U.S. Federal regulations** : TSCA 8(a) PAIR: Diphenylamine; Naphthalene

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): At least one component is not listed.

Clean Water Act (CWA) 307: Naphthalene

Clean Water Act (CWA) 311: Naphthalene; Ammonia

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

### **SARA 302/304**

#### Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : Immediate (acute) health hazard

### **Composition/information on ingredients**

Name	%	hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Long-chain alkyl amine	0.1 - 1	No.	-	No.	Yes.	No.
Long-chain alkenyl amine	0.1 - 1	No.		No.	Yes.	No.
2,6-di-tert-Butylphenol	0.1 - 1	No.		No.	Yes.	No.

#### **SARA 313**

No products were found.

#### **State regulations**

**Massachusetts** : None of the components are listed. **New York** : None of the components are listed. 203B EP Industrial Machine Lube with Soluble Moly with Tack ISO 32, 46, 68, 100, 150, 220 203C EP Industrial Machine Lube with Soluble Moly No Tack ISO 32, 46, 68, 100, 150, 220

### Section 15. Regulatory information

**New Jersey** 

: The following components are listed: Residual oils (petroleum), hydrotreated; Distillates (petroleum), hydrotreated heavy naphthenic; Residual oils (petroleum), solvent-refined; Residual oils (petroleum), solvent-dewaxed; Distillates (petroleum), solvent-dewaxed heavy paraffinic

**Pennsylvania** 

: None of the components are listed.

California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	•		Maximum acceptable dosage level
Naphthalene Ethyl acrylate			Yes. No.	No. No.

### Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**

Health: 1 Flammability: 1 Physical hazards: 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller.

The customer is responsible for determining the PPE code for this material.

#### National Fire Protection Association (U.S.A.)

Health: 1 Flammability: 1 Instability: 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

US Tariff Heading Number : 2710.19.3080 Schedule B Code : 2710.19.3080

**History** 

Date of issue mm/dd/yyyy : 06/15/2015

Version : 1

Prepared by : KMK Regulatory Services Inc.

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.