**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Seche Erase	DATE:	10/24/2005
FORMULA:	87-3017	REV.	NEW

Section 1. Material Identification and Information

Hazardous Ingredients:

Component	CAS #	TOXICOLOGICAL DATA
Acetone	67-64-1	OSHA TWA: 750ppm, STEL: 1000ppm ACGIH TWA: 750ppm, STEL: 1000ppm


Section 2. Physical / Chemical Characteristics

Boiling Point:	133°F	Specific Gravity:	N/D
Vapor Pressure:	N/A	(@ 25°C)	
(mm Hg and Temperature)		Melting Point:	N/A
Vapor Density:	Heavier than air	Evaporation Rate:	>1.0
(Air = 1)		Water Reactive:	N/A
Solubility in Water:	Soluble	pH:	Not Determined
Appearance:	Clear Liquid	Material VOC:	4.63lb/gl
Odor:	Ketone Odor	Coating V.O.C:	4.63 lb/gl

Section 3. Fire and Explosion Hazard Data

Flash Point and Method Used:	-4°F
Flammability Limits in Air % by Volume:	LEL: 2.6% UEL: 12.8%
Extinguisher Media:	Small fires: Use carbon dioxide or dry chemical. Large fires: Use "alcohol" type foam; water spray will reduce intensity of flames.
Special Fire Fighting Procedures:	High heat on drums of this material will cause the evaporation of solvent contents, resulting in an increase in pressure causing the release of the drum lid or even the drum explosion. Do not approach fires involving this material before cooling the drums in the fire to decrease the chance of drum lid release or drum explosion. Fight fires from a safe distance. Self-contained breathing apparatus should be used, to eliminate or minimize breathing vapor, fumes or gases released from the decomposed product. Use water to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures. Avoid spreading burning material with water.
Unusual Fire and Explosion Hazards:	Vapors are heavier than air and can travel considerable distance to a source of ignition and flashback. This material creates a special hazard because it floats on water. This material is flammable and may be ignited by heat, flame or static electricity.

Section 4. Reactivity Hazard Data

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET**PRODUCT NAME:** Seche Erase**DATE:** 10/24/2005**FORMULA:** 87-3017**REV.** NEW**Stability:** ☒ Stable ☐ Unstable**Conditions to Avoid:** Flame, electric spark, static and heat.**Incompatibility (Materials to Avoid):**

This product is incompatible with strong acids or bases and oxidizers.

Hazardous Decomposition:

Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide and nitrogen oxide. Under some conditions, methane, irritating aldehydes and carboxylic acids and hydrogen cyanide may be formed.

Hazardous Polymerization:☐ May Occur ☒ Will Not Occur**Section 5. Health Hazard Data****Primary Routes of Entry:**☒ Inhalation ☒ Skin Absorption ☒ Ingestion ☒ Eye Contact**Carcinogen Listed In:**☐ NTP ☐ IARC Monograph ☐ OSHA ☒ Not Listed**Health Hazards:** Reports have associated repeated and prolonged occupational overexposure to solvent present in this product with permanent brain and nervous system damage (sometimes referred to as solvent or painter's syndrome). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.**Signs and Symptoms of Exposure:**

Inhalation: Breathing high concentrations of vapors or mists may cause irritation of the nose and throat. Signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination and fatigue.)

Eye: This product may cause eye irritation. Direct contact with this material or exposure to its vapors or mists (greater than approximately 1000ppm) may cause burning, tearing, redness and swelling.

Skin: This product may cause skin irritation. Prolonged or repeated exposure to this material may cause redness and burning, drying and cracking of the skin and dermatitis.


Ingestion: Ingestion of excessive quantities may cause irritation of the digestive tract. Signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Medical Conditions Generally Aggravated by Exposure:

Respiratory symptoms associated with pre-existing lung disorders (e.g. asthma-like conditions) may be aggravated by exposure to the vapors of this material. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

Emergency First Aid Procedures:

Eye Contact: Move victim away from exposure to vapors and into fresh air. If irritation or redness develops, seek medical attention. For direct contact flush the effected eye(s) with clean water for at least 15 minutes. Seek medical attention.

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Seche Erase	DATE:	10/24/2005
FORMULA:	87-3017	REV.	NEW

Skin Contact: Remove all contaminated clothing. Cleanse affected areas thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

Inhalation: If symptoms of exposure develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, artificial respiration should be administered by qualified personnel. If breathing difficulties develop, oxygen should be administered by qualified personnel. See immediate medical attention.

Ingestion: Seek medical attention, if victim is drowsy or unconscious, place on left side with head down. Do not give anything by mouth. If victim is conscious and alert, vomiting should be induced for ingestion of large amounts (more than 5 ounces in an adult) preferably with syrup of IPECAC under direction from a physician or poison center. If syrup of IPECAC is not available, vomiting can be induced by giving three tablespoons of liquid dishwashing soap in a glass of water, or by gently placing two fingers in the back of the throat. If possible, do not leave victim unattended. Seek medical attention.

Section 6. Control and Protective Measures**Preventive Measures:**

Keep containers and storage containers closed when not in use. Do not store near heat, sparks, flame or strong oxidants. While transferring this material the containers used in this process has to be effectively grounded (ultimately to an earth ground) to prevent fire or explosion risk from static accumulation in accordance with the National Fire Protection Association standard for petroleum products.

Respiratory Protections (Specific Type):

When vapor concentration exceed the established exposure limits respiratory protection is necessary. Depending on the airborne concentration, use a respirator or gas mask with appropriate cartridges and canisters (NIOSH approved organice vapor) or supplied air equipment.

Protective Gloves: The use of gloved impermeable to the specific material handled is advised to prevent skin contact and possible irritation.

Eye Protection: Safety glasses with side shields (or goggles) are recommended for any type of industrial chemical handling.


Ventilation to be Used:

☒ Local Exhaust

☒ Mechanical

Hygienic Work Practices:

Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Maintain a source of clean water to be available in work area for flushing eyes and skin. Remove contaminated clothing; launder or dry-clean before reuse. Cleanse skin thoroughly after contact, before breaks and meals and at end of work period. Product is readily removed from skin by waterless hand cleaners or solvents (acetone or esters) followed by washing with soap.

**AMERICAN INTERNATIONAL INDUSTRIES**

2220 GASPAR AVENUE
LOS ANGELES, CA 90040
CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Seche Erase	DATE:	10/24/2005
FORMULA:	87-3017	REV.	NEW

and water. Impervious clothing should be worn as needed.

Section 7. Precautions for Safe Handling and Use / Leak Procedures

Steps to be Taken if Material is Spilled or Released:

Highway or railway spills call Chemtrec (800) 424-9300 continental US or collect 9202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers or waterways. use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (800) 424-8802 in case if the spill is in excess of EPA reportable quantity.

Waste Disposal Methods:

Dispose of in accordance with your local, state, and federal regulations.

Precautions to be taken in Handling and Storing:

Use non-sparking utensils when handling this material. Keep containers, tightly closed, cool, dry and away from sources of ignition.

Other Precautions and/or Special Hazards:

Smoking in an area where this material is used should be strictly prohibited. Use with adequate ventilation. If normal ventilation use with NIOSH approved respirator or exhaust fan.

Section 8. Shipping Information

Proper Shipping Name:	Paint related material
DOT Hazard Class:	3 (Flammable Liquid)
Packaging Group:	PG II
UN ID Number:	1263