

Material Safety Data Sheet



Section 1: PRODUCT AND COMPANY IDENTIFICATION

Vi-Jon Incorporated
8515 Page Avenue
Saint Louis, MO 63114

Phone: 314-427-1000
In Case of Spill Emergency Contact:
Chemtrec: 1-800-424-9300

Product Name: Whitening Pre-Brush Rinse

Product Code: 8M2

Product Use: Mouthwash

Issue Date: 04/14/2008

Supersedes Date: None

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Keep out of reach of children.

Appearance/Odor: Clear, colorless liquid with a cool mint odor and taste.

WARNING:

Flammable (ethyl alcohol)

Strong Oxidizer and Corrosive (hydrogen peroxide)

Target (ethyl alcohol) respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

Target (hydrogen peroxide) eye, skin and upper respiratory tract irritation.

Harmful to fish (hydrogen peroxide).

Potential Health Effects: See Section 11 for more information.

Symptoms of Exposure:

Inhalation: May cause irritation of the respiratory tract.

Ingestion: May cause nausea, vomiting and diarrhea.

Eyes: May cause irritation to the eyes.

Skin: May cause irritation to the skin.

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

This product contains components that is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200):

Potential Environmental Effects: See Section 12 for more information.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS#	% by Wt.
Ethyl Alcohol	64-17-5	8.0%
Hydrogen Peroxide	7722-84-1	2.0%

Section 4: FIRST AID MEASURES

Emergency first aid procedures by route of exposure:

Inhalation: If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Do not induce vomiting. If the material is swallowed, get medical attention or advice.

Skin: For skin contact, flush with water. If irritation persists, get medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, get medical attention.

Section 5: FIRE FIGHTING MEASURES

Flash Point: 133°F

Method Used: Not Available

Auto Ignition: (Ethyl Alcohol) 363°C

Combustibility Classification: Combustible Liquid Class II

Suitable Extinguishing Media: Use methods appropriate for the surrounding fire. Consider water spray or fog, carbon dioxide, dry chemical powder, or alcohol resistant foam.

Unsuitable Extinguishing Media: Chemical extinguishing agents may accelerate decomposition.

Products of Combustion: Upon decomposition this product may emit carbon dioxide, carbon monoxide and/or low molecular weight hydrocarbons.

Fire Fighting Equipment/Instructions: Wear protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and self contained breathing apparatus.

NFPA Rating: Health:1 Fire: 2 Reactivity:0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: For large spills wear gloves, safety glasses and when levels exceed OSHA PEL use appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

Environmental Precautions: Prevent discharge to open waters.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

Methods for Clean-Up: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container. Wash spill area with water.

Section 7: HANDLING AND STORAGE

Handling: Keep away from heat, sparks and flame. Prevent contact with eyes. Avoid inhalation.

Storage: Keep the container tightly closed and in a cool, well ventilated place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Ethyl Alcohol (64-17-5)

ACGIH: 1,000 ppm TWA

OSHA: 1,000 ppm TWA; 1,900 mg/m³ TWA

Hydrogen Peroxide (7722-84-1)

ACGIH: 1 ppm TWA

OSHA: 1 ppm TWA; 1.4 mg/m³ TWA

Engineering Controls: Normal room ventilation is usually adequate under normal use.

Personal Protective Equipment (PPE)

Eye/Face Protection: None needed under normal use.

Skin Protection: None needed under normal use.

Respiratory Protection: None needed under normal use.

General Hygiene Considerations: Wash hands after use.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Color: Clear Colorless

Odor: Mint

Physical State: Liquid

pH: 5.2 – 6.2

Vapor Density: (Ethyl Alcohol) 1.6

Boiling Point: (Ethyl Alcohol) 78.5°C

Vapor Pressure: (Ethyl Alcohol) 57.3 hPa at 20°C

Melting Point: (Ethyl Alcohol) -114.1°C

Freezing Point: Not Available

Flash Point (see section 5)

Flammability Properties (see section 5)

Solubility (in water): Soluble

Specific Gravity @ 25°C: 0.999 – 1.003

Evaporation Rate: Not Available

Octanol/Water partition coefficient (K_{ow}): (Ethyl Alcohol): - 0.32

Auto-ignition temperature: (Ethyl Alcohol) 363°C

Decomposition temperature: Not Available

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal ambient temperatures 70°C (21°C)

Condition to Avoid: Avoid excessive heat or sources of ignition. Avoid contact with readily oxidizable materials.

Incompatible Materials: This product reacts with strong acid, strong bases, oxidizing agents and Combustibles.

Hazardous Decomposition: Upon decomposition, this product evolves carbon monoxide, carbon dioxide, and/or low weight hydrocarbons.

Hazardous Reactions: Hazardous polymerization will not occur.

Section 11: TOXICOLOGY INFORMATION

ACUTE EFFECTS:

A: General Product information

Product contains ethyl alcohol and hydrogen peroxide. Not expected to cause irritation when used in accordance to label.

B: Component Analysis LD50

Ethyl Alcohol (64-17-5)

Oral LD50 Rat: 7060 mg/kg

Hydrogen Peroxide (7722-84-1)

Inhalation LC50 Rat: 2 mg/l/4H

Oral LD50 Rat: 801 mg/kg

Dermal LD50 Rat: 4060mg/kg

Dermal LD50 Rabbit: 2000 mg/kg

CHRONIC EFFECTS:

Component

Ethyl Alcohol (64-17-5)

Carcinogenicity: ACGIH A4 – Not Classifiable as a Human Carcinogen

Neurotoxicity: This product contains ethyl alcohol, a central nervous system target.

Mutagenicity: No information available for product.

Reproductive: No information available for product.

Developmental: Ethyl alcohol is a developmental toxin when consumed during pregnancy.

Target Organs: When consumed, ethyl alcohol can target the respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

Hydrogen Peroxide (7722-84-1)

Carcinogenicity: ACGIH A3 – Confirmed animal carcinogen with unknown relevance to humans.

Neurotoxicity: No information available for product.

Mutagenicity: No information available for product.

Reproductive: No information available for product.

Developmental: No information available for product.

Target Organs: Eye, skin and upper respiratory tract irritation.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Ethyl Alcohol (64-17-5)

96 hour LC50 Oncorhynchus mykiss: 12,900 mg/L (flow-through) (30days old)
96 hour LC50 Pimephales promelas 14.2 mg/L
5 min EC50 Photobacterium phosphoreum: 35,470 mg/L
30 min EC50 Photobacterium phosphoreum: 34,634 mg/L
48 hour EC50 Daphnia magna: 9,268 mg/L
24 hour EC50 Daphnia magna: 10,800 mg/L

Ecotoxicity: Hydrogen Peroxide (7722-84-1)

Category 3 – Harmful to fish

72 Hr EC50 Chlorella Vulgaris: 2.5 mg/L
48 Hr LC50 Cyprinus Carpio: 42 mg/L
96 Hr LC50 Pimephales promelas: 16.4 mg/L
24 Hr LC50 Cyprinus carpio: 42 mg/L
96 Hr LC50 Pimephales promelas: 16.4 mg/L
24 Hr EC50 Daphnia magna: 7.7 mg/L

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state, and local regulations.

Section 14: TRANSPORTATION INFORMATION

This material is not regulated as a hazardous material for transportation.

Section 15: REGULATORY INFORMATION

Ethyl alcohol, a component of this product, is on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This material contains ethyl alcohol, listed on Proposition 65 as developmental toxicity when in alcoholic beverages.

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS#	CA	MA	MN	NJ	PA
Hydrogen Peroxide	7722-84-1	YES	YES	YES	YES	YES
Ethyl Alcohol	64-17-5	YES	YES	YES	YES	YES

Section 16: Other Information

Prepared by: Vi-Jon Inc.

Disclaimer:

The information and recommendations contained in the Material Safety Data Sheet (MSDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Vi-Jon, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will Vi-Jon be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY VI-JON HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.