

Safety Data Sheet

Printing date 05/08/2019

Revised On 05/08/2019

1 Identification of the substance and manufacturer

Trade name: GLOSS SAFETY RED
Product code: BD1214
Recommended use: Paint and coatings application.
 Industrial use only.
 Industrial use only.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Class C Solutions Group, a business of MSC Industrial Supply Co.
 75 Maxess Road
 Melville NY 11747-3151
 1-866-438-6767
 2595 Skymark Ave. Suite 202
 Mississauga, ON L4W 4L5
Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 STOT SE 3 H335 May cause respiratory irritation.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Danger

Hazard statements

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May cause respiratory irritation.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	18.39%
74-98-6	propane	15.74%
106-97-8	n-butane	9.24%
7727-43-7	barium sulfate	8.79%
110-19-0	Isobutyl Acetate	6.7%
2807-30-9	Glycol Ether EP	6.59%
108-65-6	PM acetate	3.82%
123-86-4	butyl acetate	3.34%
107-87-9	Methyl Propyl Ketone	1.34%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

Safety Data Sheet

Printing date 05/08/2019

Revised On 05/08/2019

Trade name: GLOSS SAFETY RED

Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm
REL (USA) Long-term value: 590 mg/m³, 250 ppm
TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA) refer to Appendix F in TLVs&BEIs book; D, EX

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm
TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm
(EX)

7727-43-7 barium sulfate

PEL (USA) Long-term value: 15* 5** mg/m³
*total dust **respirable fraction
REL (USA) Long-term value: 10* 5** mg/m³
*total dust **respirable fraction
TLV (USA) Long-term value: 5* mg/m³
*inhalable fraction; E

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm
REL (USA) Long-term value: 700 mg/m³, 150 ppm
TLV (USA) Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

123-86-4 butyl acetate

PEL (USA) Long-term value: 710 mg/m³, 150 ppm
REL (USA) Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm
TLV (USA) Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

107-87-9 Methyl Propyl Ketone

PEL (USA) Long-term value: 700 mg/m³, 200 ppm
REL (USA) Long-term value: 530 mg/m³, 150 ppm
TLV (USA) Short-term value: 529 mg/m³, 150 ppm

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA) 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.
Wash hands after use.

(Contd. on page 3)

Safety Data Sheet

Printing date 05/08/2019

Revised On 05/08/2019

Trade name: GLOSS SAFETY RED

(Contd. of page 2)

Breathing equipment:	Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content (less exempt solvents):	48.8 %
Water:	0.0 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

123-86-4 butyl acetate

Oral LD50 14,000 mg/kg (rat)

Inhalative LC50/4 h >21 mg/l (rat)

Information on toxicological effects:	No data available.
Skin effects:	No irritant effect.
Eye effects:	Irritating effect.
Sensitization:	No sensitizing effects known.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.

(Contd. on page 4)

Safety Data Sheet

Printing date 05/08/2019

Revised On 05/08/2019

Trade name: GLOSS SAFETY RED

Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

(Contd. of page 3)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT N/A
DOT Consumer Commodity ORM-D
 Aerosols, flammable
 1950 Aerosols
ADR
Transport hazard class(es):
Class 2.1
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act (TSCA):

All hazardous ingredients for this product are found on the inventory list of substances.

Consumer Product Safety**Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone
 13463-67-7 titanium dioxide
 100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1	Acetone	I
7727-43-7	barium sulfate	D, CBD(inh), NL(oral)
110-19-0	Isobutyl Acetate	D

16 Other information

Contact: Regulatory Affairs