XEROX Material Safety Data Sheet MSDS No: A-0014

Date: 4/15/85 **Revision:** 9/7/07

Manufacturer: Telephone #(s): Safety Information: (800) 828-6571

Xerox Corporation Health Emergency: (585) 422-2177

Rochester, NY 14644 Transportation Emergency: (585)422-1230

Section I - Product Identification

Trade Names/Synonyms: 6500 Magenta Toner **Part No.:** 6R198; RX:6R90143

Chemical Name: None

WHMIS Status: This is not a WHMIS controlled product.

Ingredients (% by wt.)CAS No.Styrene/acrylate polymer (>90%)25213-39-2Magenta pigment (<10%)</td>980-26-7

Section II - Emergency and First Aid

Primary Route of Entry: Symptoms of Overexposure:

Inhalation Minimal respiratory tract irritation may occur as with **Eyes:** exposure to large amounts of any non-toxic dust.

Flush with water.

Skin: Medical Conditions Generally Aggravated by Exposure:

Wash with soap and water.

None when used as described by product literature.

Inhalation:

Remove from exposure.

Ingestion:Dilute stomach contents with several glasses of water.

Additional Information:
See Sections V and VII.

Section III - Toxicology and Health Information

This material has been evaluated by Xerox Corporation.

Oral LD50:>23 g/kg (rats) practically non-toxic.TLV:10mg/m³ (total dust)Dermal LD50:>3 g/kg (rabbits) practically non-toxic.PEL:15 mg/m³ (total dust)Inhalation LC50:>5 mg/l (rats, 4 hr exposure)practically non-toxic.¹5 mg/m³ (respirable dust)

>20 mg/l (calculated 1 hr exposure) non-poisonous, DOT. STEL: N.E.

Eye Irritation: Not an irritant Ceiling: N.E.

Skin Sensitization:Not a sensitizerXEL2:2.5 mg/m3 (total dust)Skin Irritation:Not an irritant.0.4 mg/m3 (respirable dust)

Human Patch: Non-irritating, non-sensitizing.

Mutagenicity: Non-mutagenicity detected in Ames, Micronucleus, WP₂, and UDS Assays.

Carcinogens: None present

Aquatic LC₅₀: >1000 mg/l (fathead minnows) non-toxic.

Additional Information: The results obtained from a Xerox sponsored, Chronic Toner Inhalation Study, demonstrated no lung change in rats for the lowest (1mg/m³) exposure level (i.e. the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of the animals at the middle (4mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with EPA testing protocol. The test toner was ten times more respirable than commercially available Xerox toner, and would not be functionally suitable for Xerox equipment.

XEROX Trade Name: 6500 Magenta Toner MSDS No.: A-0014

Section IV - Physical Data

Appearance/Odor: Dark red powder / faint odor **Softening Range:** 85°C to 100°C

Boiling Point:N.A.Melting Point:N.A.Solubility in Water:NegligibleSpecific Gravity (H2O=1):~1Evaporation Rate:N.A.Vapor Pressure (mm Hg):N.A.Vapor Density (Air=1):N.A.pH:N.A.

Volatile: N.A.% (Wgt) N.A. % (Vol.)

Section V - Fire and Explosion Data

Flash Point (Method Used): N.A. Flammable LEL: N.A. Limits UEL: N.A.

Extinguishing Media: Water, dry chemical, carbon dioxide or foam.

Special Fire Fighting Procedures: Avoid inhalation of smoke. Wear protective clothing and self-contained breathing apparatus.

Fire and Explosion Hazards: Toner is a combustible powder. Like most organic materials in powder form, when

dispersed in air, it can form explosive mixtures.

Section VI -Reactivity Data

Stability: Stable

Hazardous Polymerization: Will Not Occur

Hazardous Decomposition Products: Products of combustion may be toxic. Avoid breathing smoke.

Incompatibility (Materials to Avoid): None known

Section VII - Special Protection Information

Respiratory Protection:None required when used as intended in Xerox equipment.
None required when used as intended in Xerox equipment.
Protective Gloves:
None required when used as intended in Xerox equipment.

Other: For use other than normal customer - operating procedures (such as in bulk toner

processing facilities), goggles and respirators may be required. For more information,

contact Xerox.

Section VIII - Special Precautions

Handling and Storage: None

Conditions to Avoid: Avoid prolonged inhalation of excessive dust.

Section IX- Spill, Leak, and Disposal Procedures

For Spills or Leakage: Sweep up or vacuum spilled toner and carefully transfer into sealable waste container. Sweep slowly

to minimize generation of dust during clean-up. If a vacuum is used, the motor must be rated as dust tight. A conductive hose bonded to the machine should be used to reduce static buildup (See Section V). Residue can be removed with soap and cold water. Garments may be washed or dry cleaned,

after removal of loose toner.

Waste Disposal Method: When disposed, this material is not a hazardous waste according to Federal Regulation 40 CFR 261.

However, State and Local requirements may be more restrictive. Therefore, consultation with the appropriate State and Local waste disposal authorities is advised. Incinerate only in a closed

container.

Section X - Transportation Information

DOT Proper Shipping Name: N.A. (Not Regulated) **ID Number:** N.A. **Hazard Classification:** N.A. **Packing Group:** N.A.

600E56030