

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MAVIDON ACETONE

GENERAL USE: Solvent

PRODUCT DESCRIPTION: Colorless liquid, extremely flammable



MANUFACTURER'S NAME

Mavidon Medical Products

DATE PREPARED: July 2, 2001

SUPERSEDES: New

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

2105 7th Avenue North

TELEPHONE NUMBER FOR INFORMATION

(561) 585-2227

(CITY, STATE AND ZIP CODE)

Lake Worth, FL 33461-

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

Infotrac (800) 535-5053 Outside USA (352) 323-3500

DISTRIBUTOR'S NAME

Same

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION

(CITY, STATE AND ZIP CODE)

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS

CAS #

%

(by weight)

OSHA PEL

ACGIH TWA

SARA

TITLE III

RQ

PPM

MG/M³

PPM

MG/M³

LBS

Acetone (a,b)

67-64-1

100

1000

2400

500

5000

(a) See Section 15

(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Colorless flammable liquid, potentially hazardous vapors. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas. Hazard symbols for this product - F, XI, XN

POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.

EYES: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.

INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MATERIAL SAFETY DATA SHEET			
PRODUCT NAME: MAVIDON ACETONE July 2, 2001			Page 2 of 4
SECTION 4 - FIRST AID MEASURES			
INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.			
SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.			
EYES: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.			
INGESTION: Give two glasses of water for dilution; Induce vomiting by sticking fingers down throat; never give anything by mouth to an unconscious person; seek medical attention.			
SECTION 5 - FIRE FIGHTING MEASURES			
FLASH POINT (METHOD USED) -18° F (-27.8 ° C) TCC	FLAMMABLE LIMITS AUTOIGNITION TEMPERATURE:	LEL: 2.6% Not determined	UEL: 12.8% NFPA CLASS: IA
GENERAL HAZARDS: Product is flammable. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.			
EXTINGUISHING MEDIA Carbon dioxide, water fog, dry chemical, chemical foam			
FIRE FIGHTING PROCEDURES Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will scatter and spread fire. Fine water spray can be used to keep fire - exposed containers cool.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers can explode due to buildup of pressure when exposed to extreme heat. Do not use direct stream of water on pool fires as product may reignite on water surface. Caution - Material is flammable!			
HAZARDOUS COMBUSTION PRODUCTS Smoke, fumes, oxides of carbon			
SECTION 6 - ENVIRONMENTAL RELEASE MEASURES			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - FLAMMABLE - Evacuate and ventilate area; confine and absorb into absorbent; place material into approved containers for disposal; for spills in excess of allowable limits notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements.			
SECTION 7 - HANDLING AND STORAGE			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use non-sparking tools when opening and closing containers. Maintain well ventilated work areas to minimize exposure when handling this material.			
SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION			
ENGINEERING CONTROLS			
The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment. See Section 2 for Component Exposure Guidelines.			
PERSONAL PROTECTION:			
RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.			
PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs.			
EYE PROTECTION: Safety goggles with side shields			
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby			
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.			

MATERIAL SAFETY DATA SHEET				
PRODUCT NAME: MAVIDON ACETONE July 2, 2001				Page 3 of 4
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES				
VAPOR PRESSURE (MM Hg) 181 mm Hg @ 20 ° C		VAPOR DENSITY (AIR = 1) 2.0		
SPECIFIC GRAVITY (WATER = 1) 0.785		EVAPORATION RATE (n-BUTYL ACETATE = 1) 7.7		
SOLUBILITY IN WATER Complete		FREEZING POINT Not determined		
pH 7.0		APPEARANCE AND ODOR Clear water-white liquid, sweet pungent odor		
BOILING POINT 133°F (56.1° C)		PHYSICAL STATE Liquid		
VISCOSITY Not listed		VOLATILE ORGANIC COMPOUNDS (Total VOC's) 6.5 pounds / gallon		
SECTION 10 - STABILITY AND REACTIVITY				
STABILITY UNSTABLE: STABLE: XXX		CONDITIONS TO AVOID: Extreme temperatures, open flames, sparks		
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids				
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.				
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX		CONDITIONS TO AVOID: None		
SECTION 11 - TOXICOLOGICAL INFORMATION				
Hazardous Ingredients	%	CAS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Acetone (a,b)	100	67-64-1	9750 mg / kg Oral - rat	16,000 ppm / 4 hr Inhalation - rat
SECTION 12 - ECOLOGICAL INFORMATION				
No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.				
SECTION 13 - DISPOSAL CONSIDERATIONS				
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce concentrated hazardous vapors or fumes in a disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for ignitable materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.				
SECTION 14 - TRANSPORT INFORMATION				
PROPER SHIPPING NAME: Acetone				
HAZARD CLASS / Pack Group: 3 / II REFERENCE: 49 CFR 173.150, .202, .242 IDENTIFICATION NUMBER: UN 1090 LABEL: FLAMMABLE LIQUID		IATA HAZARD CLASS / Pack Group: 3 / II IMDG HAZARD CLASS: 3 / II RID/ADR Dangerous Goods Code: 3 Canadian TDG Class / Division: 3.2 HAZARD SYMBOLS: F		
Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, Canadian TDG, and United Nations TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.				

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: MAVIDON ACETONE
July 2, 2001

Page 4 of 4

SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic substance Control Act)

Components of this product are listed on the TSCA Inventory.

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories

Acute health, flammable

313 Reportable Ingredients:

None

CERCLA (Comprehensive Response Compensation and Liability Act)

(b) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 5000 lbs) or greater amounts, according to 40 CFR 302.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations

IDL (Canadian Ingredient Disclosure List)

Components of this product listed on the Canadian Ingredient Disclosure List are shown in Section 2.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product are on the European Inventory of Existing Commercial Chemical Substances

EC Risk Phrases

R11 Highly flammable
R20 Harmful by inhalation
R36 Irritating to eyes
R38 Irritating to skin.

EC Safety Phrases

S16 Keep away from sources of ignition
S23 Do not breathe vapor
S25 Avoid contact with eyes
S28 After contact with skin, wash immediately with plenty of soap and water
S29 Do not empty into drains

SECTION 16 - OTHER INFORMATION

No specific notes.

HMIS HAZARD RATINGS

HEALTH	1	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	3	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

PERSONAL PROTECTIVE EQUIPMENT B Safety Glasses, Gloves

REVISION SUMMARY:

This MSDS has been revised in the following sections:
No revisions available

MSDS Prepared by: Comprehensive Data Base, Inc.
P.O. Box 5604
Lakeland, FL 33807 USA
(863) 644 - 3298 www.compdatabase.com

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.