# SAFETY DATA SHEET

M47027 - ANSI - EN





# **AKTIVOX**®

**SDS No.**: M47027 **SDS Revision Date**: 06-May-2015

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Identification: Occidental Chemical Corporation

5005 LBJ Freeway P.O. Box 809050 Dallas, TX 75380-9050 1-800-752-5151

24 Hour Emergency Telephone

Number:

1-800-733-3665 or 1-972-404-3228 (USA); CHEMTREC (within USA and

Canada): 1-800-424-9300; CHEMTREC (outside USA and Canada): +1

703-527-3887; CHEMTREC Contract No: CCN16186

To Request an SDS: MSDS@oxy.com or 1-972-404-3245

**Customer Service:** 1-800-752-5151 or 1-972-404-3700

Product Identifier: AKTIVOX®

Trade Name: AKTIVOX®, EZ FLOW, DICHLOR L, DIKLOR L

**Synonyms:** 25% Active Sodium Chlorite Solution

Product Use: oxidizing agent, bleaching agent, odor control, air scrubbing, chemical

manufacturing, and etching

Uses Advised Against: None identified.

# 2. HAZARDS IDENTIFICATION

**Print date:** 06-May-2015 **1 of 16** 

**SDS No.**: M47027 **SDS Revision Date**: 06-May-2015

OSHA REGULATORY STATUS: This material is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

### **EMERGENCY OVERVIEW:**

**Color:** Pale, yellow **Physical State:** Liquid

Appearance:Slightly cloudyOdor:Slight chlorine odor

Signal Word: DANGER

MAJOR HEALTH HAZARDS: CORROSIVE. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. TOXIC IF INHALED. HARMFUL IF SWALLOWED. INGESTION MAY CAUSE DAMAGE TO: BLOOD SYSTEM, AND KIDNEY SYSTEM. INHALATION MAY CAUSE DAMAGE TO THE RESPIRATORY SYSTEM. MAY CAUSE DAMAGE TO THE BLOOD AND KIDNEYS THROUGH PROLONGED OR REPEATED EXPOSURES.

PHYSICAL HAZARDS: Dried material can ignite upon contact with combustibles.

**AQUATIC TOXICITY: HARMFUL TO AQUATIC LIFE.** 

**PRECAUTIONARY STATEMENTS:** Wash thoroughly after handling. Wear protective gloves, protective clothing, eye, and face protection. Do not eat, drink or smoke when using this product. Do not breathe mist, vapors, or spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Keep container tightly closed. Store in a secure manner. Always package, store, transport and dispose of all waste and contaminated equipment in accordance with all applicable federal, state, and local health and environmental regulations. Do not contaminate with acids, reducing agents, combustible materials, oxidizing materials, hypochlorite, organic solvents and compounds, garbage, dirt, organic matter, household products, chemicals, soap products, paint products, vinegar, beverages, oils, pine oil, dirty rags, sulfur-containing rubber, or any other foreign matter.

**ADDITIONAL HAZARD INFORMATION:** This material is corrosive and an oxidizer when dry. This material's pH and oxidative action contribute to its health and physical hazards.

### **GHS CLASSIFICATION:**

GHS: CONTACT HAZARD - SKIN:	Category 1B - Causes severe skin burns and eye damage.
GHS: CONTACT HAZARD - EYE:	Category 1 - Causes serious eye damage
GHS: ACUTE TOXICITY -	Category 3 - Toxic if inhaled
INHALATION:	
GHS: ACUTE TOXICITY - ORAL:	Category 4 - Harmful if swallowed.
GHS: ACUTE TOXICITY -	Not classified as acutely toxic for dermal exposure.
DERMAL:	
GHS: TARGET ORGAN	Category 2 - May cause damage to Respiratory System, Blood, Kidneys
TOXICITY (SINGLE EXPOSURE):	

**Print date:** 06-May-2015 **2 of 16** 

**SDS No.**: M47027 **SDS Revision Date**: 06-May-2015

	Category 2 - May cause damage to Blood, Kidney through prolonged or repeated exposure
	Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC, or OSHA.
GHS: HAZARDOUS TO AQUATIC ENVIRONMENT - ACUTE HAZARD:	Category 3 - Harmful to aquatic life

**UNKNOWN ACUTE TOXICITY:** Not applicable. This product was tested as a whole. This information only pertains to untested mixtures. 100% of this product consists of ingredient(s) of known acute toxicity.

GHS SYMBOL: Skull and Crossbones, Corrosion, Health hazard







GHS SIGNAL WORD: DANGER

#### **GHS HAZARD STATEMENTS:**

### GHS - Health Hazard Statement(s)

Toxic if inhaled Causes severe skin burns and eye damage Causes serious eye damage

Harmful if swallowed

May cause damage to organs: (Respiratory, Kidney, and Blood Systems)

May cause damage to Renal system (Kidneys), and Blood system through prolonged or repeated exposure

### GHS - Precautionary Statement(s) - Prevention

Do not breathe dust, fume, gas, mist, vapors, or spray In case of inadequate ventilation, wear respiratory protection Wear protective gloves, protective clothing, eye, and face protection Wash thoroughly after handling Use only outdoors or in a well-ventilated area Do not eat, drink or smoke when using this product

**Print date:** 06-May-2015 **3 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

#### GHS - Precautionary Statement(s) - Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor/physician

Specific treatment (see First Aid information on product label and/or Section 4 of the SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower Wash contaminated clothing before reuse

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Call a POISON CENTER or doctor/physician if you feel unwell

Specific treatment is urgent (see Section 4 of SDS or first aid information on this label)

### GHS - Precautionary Statement(s) - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### GHS - Precautionary Statement(s) - Disposal

Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations.

#### **Hazards Not Otherwise Classified (HNOC)**

None identified

See Section 11: TOXICOLOGICAL INFORMATION

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Synonyms:** 25% Active Sodium Chlorite Solution

Component	Percent [%]	CAS Number
Water	71 - 76	7732-18-5
Sodium chlorite	24 - 26	7758-19-2
Sodium Chloride	1 - 3	7647-14-5
Sodium Bicarbonate	< 0.4	144-55-8

### 4. FIRST AID MEASURES

**INHALATION:** If inhalation occurs and adverse effects result, remove to uncontaminated area. Evaluate ABC's (is Airway constricted, is Breathing occurring, and is blood Circulating) and treat symptomatically. GET MEDICAL ATTENTION IMMEDIATELY. Specific Treatment: There is no specific antidote. Treat symptomatically. Pulse oximetry may not be reliable, see notes to physician.

**Print date:** 06-May-2015 **4 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

**SKIN CONTACT:** Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry and shoes. Wash contaminated areas with large amounts of water. GET MEDICAL ATTENTION IMMEDIATELY. SPECIFIC TREATMENT: Irrigation with water. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods.

**EYE CONTACT:** Immediately flush contaminated eyes with a directed stream of water for as long as possible. Remove contact lenses, if present, then continue rinsing. GET MEDICAL ATTENTION IMMEDIATELY.

**INGESTION:** If swallowed, do not induce vomiting. Give large amounts of water. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. Never give anything by mouth to an unconscious or convulsive person. GET MEDICAL ATTENTION IMMEDIATELY. For specific treatment, see Notes to Physician.

### Most Important Symptoms/Effects (Acute and Delayed) :.

Acute Symptoms/Effects: Listed below.

**Inhalation (Breathing):** Respiratory System Effects: Inhalation exposure may cause irritation, redness of upper and lower airways, coughing, laryngeospasm and edema, shortness of breath, bronchoconstriction, and possible pulmonary edema. The pulmonary edema may develop several hours after a severe acute exposure.

**Skin:** Skin Corrosion. Skin exposure may cause redness, irritation, burning sensation, swelling, blister formation, first, second, or third degree burns.

**Eye:** Serious Eye Damage. Exposure to eyes may cause irritation and burns to the eye lids, conjunctivitis, corneal edema, and corneal burn. Significant and prolonged contact may cause damage to the internal contents of the eye.

**Ingestion (Swallowing):** Ingesting this material may cause irritation, nausea, and vomiting. Oxidation may cause significant metabolic issues such as: methemogobinemia, hemolysis, and intravascular coagulation and renal failure.

#### **Delayed Symptoms/Effects:**

- Repeated and prolonged skin contact may cause a dermatitis

**Interaction with Other Chemicals Which Enhance Toxicity:** Mixing with ammonia, acids, detergents, or organic matter will release chlorinated compounds, which are irritating to eyes, lungs, and mucus membranes. Chlorine dioxide vapors are emitted when this product contacts acids, chlorine, or bleach.

**Medical Conditions Aggravated by Exposure:** May aggravate preexisting conditions such as:. Eye disorders that decrease tear production or have reduced integrity. Skin disorders that compromise the integrity of the skin such as: psoriasis, rashes, eczema, skin infections. Respiratory conditions including asthma and other breathing disorders. Ingestion may induce G6PD deficiency, hemolysis and renal failure. G6PD deficiency, hemoglobinopathies, renal compromise, and conditions causing hypoxia may be aggravated by ingestion of this material.

**Protection of First-Aiders:** Protect yourself by avoiding contact with this material. Avoid contact with skin and eyes. Do not ingest. Use personal protective equipment. Refer to Section 8 for specific personal protective equipment recommendations. At minimum, treating personnel should utilize PPE sufficient for prevention of bloodborne pathogen transmission.

**Print date:** 06-May-2015 **5 of 16** 

**SDS No.**: M47027 **SDS Revision Date**: 06-May-2015

Notes to Physician: Treat as a corrosive due to the pH of this material. This is also a strong oxidizer which will react with tissue in the presence of water. For prolonged exposures and significant exposures, consider delayed injury to exposed tissues. There is no specific antidote. Treatment is supportive care. Follow normal parameters for airway, breathing, and circulation. Ingestion of even small amounts of solution should be closely monitored for methemoglobinemia, hemolysis, and glutathione depletion, followed by renal failure. This chemical acts similarly to its related compound chlorate, and produces a drug induced G6PD deficiency. Methylene blue has not been reported as effective. Consult the PubMed Case Report PMID 22996135 for the case description and treatment utilized. Chlorine dioxide vapors are emitted when this product contacts acids or chlorine. If these vapors are inhaled, monitor patient closely for delayed development of pulmonary edema which may occur up to 48-72 hours post-inhalation. Following ingestion, neutralization and use of activated charcoal is not indicated. Probable mucosal damage may contraindicate the use of gastric lavage.

# 5. FIRE-FIGHTING MEASURES

**Fire Hazard:** Negligible fire hazard. Avoid evaporation to dryness. Dried material can ignite upon contact with combustibles. This product may represent an explosion hazard if it contacts acids, chlorine, or organic materials (Refer to Section 10).

**Extinguishing Media:** Use extinguishing agents appropriate for surrounding fire.

**Fire Fighting:** Wear NIOSH approved positive-pressure self-contained breathing apparatus. Consider evacuation of personnel located downwind. Keep unnecessary people away, isolate hazard area and deny entry. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Flood with fine water spray. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

**Hazardous Combustion** 

**Products:** 

Chlorine, Oxides of sodium

**Sensitivity to Mechanical** 

Impact:

Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Lower Flammability Level (air): Not flammable

Upper Flammability Level (air): Not flammable

Flash point: Not applicable

Auto-ignition Temperature: Not applicable

# 6. ACCIDENTAL RELEASE MEASURES

**Print date:** 06-May-2015 **6 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

#### **Personal Precautions:**

Isolate hazard area and deny entry. Keep unnecessary and unprotected personnel from entering the area. Avoid contact with skin and eyes. Do not breathe vapors, fumes or mist. Wear appropriate personal protective equipment recommended in Section 8, Exposure Controls / Personal Protection, of the SDS.

#### Methods and Materials for Containment and Cleaning Up:

Contain spill. Spilled materials may be absorbed using non-combustible and non-organic commercial absorbents. Dampen and scoop spilled material into clean, dedicated equipment. Every attempt should be made to avoid mixing spilled material with other chemicals or debris when cleaning up. Keep collected material damp and put into drums. Dried material can ignite upon contact with combustibles. Dispose of promptly. Dispose of in accordance with all applicable regulations.

#### **Environmental Precautions:**

This material is harmful to aquatic life. This material is alkaline and may raise the pH of surface waters with low buffering capacity. Keep out of water supplies and sewers. Releases should be reported, if required, to appropriate agencies. See Section 12 for additional ecological information.

# 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling:**

Do not taste or swallow. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors or mist when opening container. Avoid creation of vapor or mist. Wear personal protective equipment as described in Exposure Controls/Personal Protection (Section 8) of the SDS. Wash thoroughly after handling. Use clean utensils. Do not add the product to any dispensing device containing residuals of other products. Contamination may start a chemical reaction with generation of heat, liberation of hazardous gases (chlorine dioxide a poisonous, explosive gas), and possible fire and explosion. Do not contaminate with acids, reducing agents, combustible materials, oxidizing materials, hypochlorite, organic solvents and compounds, garbage, dirt, organic matter, household products, chemicals, soap products, paint products, vinegar, beverages, oils, pine oil, dirty rags, sulfur-containing rubber, or any other foreign matter. Dried material can ignite upon contact with combustibles.

### Safe Storage Conditions:

Store and handle in accordance with all current regulations and standards. Store in tightly closed, labeled containers away from combustible materials. Store in a cool, dry area. Store in a well-ventilated area. Do not allow water to get in container. Store below 212 °F (100 °C). Avoid exposure to sunlight or ultraviolet light. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

### Incompatibilities/ Materials to Avoid:

acids, reducing agents, combustible material, oxidizing agents, hypochlorite, organic solvents and compounds, garbage, dirt, organic materials, household products, chemicals, soap products, paint products, vinegar, beverages, oils, pine oil, dirty rags, sulfur-containing rubber, or any other foreign matter

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Regulatory Exposure Limit(s):** None. This product does not contain any components that have regulatory occupational exposure limits (OEL's) established.

**Print date**: 06-May-2015 **7 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit

**NON-REGULATORY EXPOSURE LIMIT(S):** Listed below for the product components that have advisory (non-regulatory) occupational exposure limits (OEL's) established.

- The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).
- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

OXY REL 8 hr TWA	1 mg/m³ recommended Time Weighted Average - 8 hour (internal Occupational Exposure Limit) This value is based on potential systemic effects from inhalation		
3 TWA	of sodium chlorite dust		

**ENGINEERING CONTROLS:** Use only in well-ventilated areas. Provide local exhaust ventilation where vapors, mist or aerosols may be generated.

#### PERSONAL PROTECTIVE EQUIPMENT:

**Eye Protection:** Wear chemical safety goggles. Where splashing or spraying is possible, use a face-shield in addition to chemical protective goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**Skin and Body Protection:** Wear protective clothing to minimize skin contact. Contaminated clothing should be removed and laundered before reuse. Discard contaminated leather goods.

**Hand Protection:** Wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove.

Protective Material Types: Neoprene

**Respiratory Protection:** A NIOSH approved full-face respirator equipped with N95 (dust, fume, mist) cartridges may be permissible when symptoms have been observed that are indicative of overexposure. If chlorine or chlorine dioxide is present, an acid gas cartridge is also required. An approved self-contained breathing apparatus operated in the pressure demand mode or an airline respirator with escape pack is required when an air purifying respirator is not adequate or for spills / emergencies of unknown concentrations. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

**Print date:** 06-May-2015 **8 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

Appearance: Slightly cloudy
Color: Pale, yellow
Odor: Slight chlorine odor
Odor Threshold [ppm]: No data available.

Molecular Weight: 90.45 Molecular Formula: NaClO2

Decomposition Temperature:

Boiling Point/Range:

Freezing Point/Range:

Melting Point/Range:

Vapor Pressure:

Vapor Density (air=1):

No data available

(water=1):

**Density:** 10.1 - 10.6 lbs/gal @ 25 °C

Water Solubility: Soluble

pH: 11.5 - 11.7 @ 25 °C Volatility: 68 - 76% by volume Evaporation Rate (ether=1): No data available Not applicable

(n-octanol/water):

Flash point:

Flammability (solid, gas):

Lower Flammability Level (air):

Upper Flammability Level (air):

Auto-ignition Temperature:

Viscosity:

Not applicable

Not flammable

Not applicable

Not applicable

Not applicable

# 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal temperatures and pressures.

**Chemical Stability:** Stable at normal temperatures and pressures.

#### **Possibility of Hazardous Reactions:**

Avoid heat, flames, sparks and other sources of ignition. Avoid evaporation to dryness. Dried material can ignite upon contact with combustibles. Avoid contamination with foreign materials. Avoid exposure to sunlight or ultraviolet light.

#### **Conditions to Avoid:**

(e.g., static discharge, shock, or vibration) -. Avoid mechanical shock or impact, if contaminated.

#### Incompatibilities/ Materials to Avoid:

acids. reducing agents. combustible material. oxidizing agents. hypochlorite. organic solvents and compounds. garbage. dirt. organic materials. household products. chemicals. soap products. paint products. vinegar, beverages, oils, pine oil, dirty rags, sulfur-containing rubber, or any other foreign matter.

**Hazardous Decomposition Products:** Chlorine dioxide is formed on contact with acids, Thermal decomposition products include chlorine and oxides of sodium

Hazardous Polymerization: Will not occur.

**Print date:** 06-May-2015 **9 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

# 11. TOXICOLOGICAL INFORMATION

#### **TOXICITY DATA:**

**PRODUCT TOXICITY DATA:** Aktivox

LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
390 mg/kg (Rat)	> 2 gm/kg skin-rabbit	0.58 mg/L (4 hr Rat)

### **COMPONENT TOXICITY DATA:**

Note: The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given.

Component	LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
Sodium chlorite 7758-19-2	165 mg/kg (Rat)	107.2 mg/kg (Rabbit)	230 mg/m³ (4 hr-Rat)
Sodium Chloride 7647-14-5	3 g/kg (Rat)	10 g/kg (Rabbit)	42 g/m³ (1 hr-Rat)
Sodium Bicarbonate 144-55-8	4220 mg/kg (Rat)		

### **POTENTIAL HEALTH EFFECTS:**

**Eye contact:** Causes serious eye damage. Eye exposures may cause burns to the eye lids,

conjunctivitis, corneal edema, and corneal burn. May cause permanent eye damage including blindness. Significant and prolonged contact may cause

damage to the internal contents of eye.

**Skin contact:** Causes severe skin burns. May cause redness, irritation, burning sensation,

swelling, blister formation, first, second, or third degree burns.

**Inhalation:** Toxic if inhaled. Inhalation may cause coughing, irritation (possibly severe),

redness of upper and lower airways, shortness of breath, chemical burns and possibly pulmonary edema. Pulmonary edema may develop several hours after a

severe acute exposure.

**Ingestion:** Harmful if swallowed. Ingestion may cause irritation, nausea, and vomiting.

Causes significant metabolic issues through oxidation. May induce

methemoglobinemia, hemolysis, and intravascular coagulation and renal failure.

#### SIGNS AND SYMPTOMS OF EXPOSURE:

Depending on the degree and duration of exposure, possible signs and symptoms from contact of this material with the skin and eyes, breathing this material, and swallowing this material may include:.

**Print date:** 06-May-2015 **10 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

**Inhalation (Breathing):** Respiratory System Effects: Inhalation exposure may cause irritation, redness of upper and lower airways, coughing, laryngeospasm and edema, shortness of breath, bronchoconstriction, and possible pulmonary edema. The pulmonary edema may develop several hours after a severe acute exposure.

**Skin:** Skin Corrosion. Skin exposure may cause redness, irritation, burning sensation, swelling, blister formation, first, second, or third degree burns.

**Eye:** Serious Eye Damage. Exposure to eyes may cause irritation and burns to the eye lids, conjunctivitis, corneal edema, and corneal burn. Significant and prolonged contact may cause damage to the internal contents of the eye.

**Ingestion (Swallowing):** Ingesting this material may cause irritation, nausea, and vomiting. Oxidation may cause significant metabolic issues such as: methemogobinemia, hemolysis, and intravascular coagulation and renal failure.

#### **CHRONIC TOXICITY:**

Sodium chlorite has produced hemolytic anemia in several animal species at concentrations of 100 mg/L or higher. In a subchronic study using rats, hematological alterations included decreased erthrocyte counts, hemoglobin levels, and hemacrit. Methemoglobin levels decreased in females, but increased in males. There is no evidence of kidney effects in humans; however, in animal studies with sodium chlorite, there is limited evidence of kidney effects.

**Interaction with Other Chemicals Which Enhance Toxicity:** Mixing with ammonia, acids, detergents, or organic matter will release chlorinated compounds, which are irritating to eyes, lungs, and mucus membranes. Chlorine dioxide vapors are emitted when this product contacts acids, chlorine, or bleach.

#### **GHS HEALTH HAZARDS:**

GHS: ACUTE TOXICITY - ORAL: Category 4 - Harmful if swallowed.

**GHS: ACUTE TOXICITY -** Not classified as acutely toxic for dermal exposure.

**DERMAL:** 

**GHS: ACUTE TOXICITY -** Category 3 - Toxic if inhaled.

INHALATION:

GHS: CONTACT HAZARD - Category 1B - Causes severe skin burns and eye damage

SKIN:

GHS: CONTACT HAZARD - EYE: Category 1 - Causes serious eye damage

**GHS: CARCINOGENICITY:** 

Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC, or OSHA.

#### **SPECIFIC TARGET ORGAN TOXICITY (Single Exposure):**

Category 2 - Respiratory System, Blood, Renal System (Kidneys)

### SPECIFIC TARGET ORGAN TOXICITY (Repeated or Prolonged Exposure):

Category 2 - Blood, Renal System (Kidneys)

#### **MUTAGENIC DATA:**

Not classified as a mutagen per GHS criteria. Sodium chlorite has tested positive in some studies. The significance of these test results for human health is unclear because the oxidizing effects of the chlorite or salting effects of sodium may significantly affect the ability of the tests to accurately detect mutagens.

**Print date:** 06-May-2015 **11 of 16** 

**SDS No.**: M47027 **SDS Revision Date**: 06-May-2015

### **REPRODUCTIVE TOXICITY:**

Not classified as a reproductive toxin per GHS criteria. There is limited evidence of male reproductive effects in animal studies.

#### **DEVELOPMENTAL TOXICITY:**

Not classified as a developmental or reproductive toxin per GHS criteria. Observations in animal studies include decreased serum levels of thyroid hormones in offspring.

## 12. ECOLOGICAL INFORMATION

#### **ECOTOXICITY DATA:**

### **Aquatic Toxicity:**

LC50 rainbow trout = 290 mg/l as 80% NaClO2 (96 hour); LC50 bluegill = 265-310 mg/l as 80% NaClO2 (96 hour); LC50 Sheepshead minnow = 62-90 ppm (96 hour)

#### **Invertebrate Toxicity:**

LC50 Daphnia Magna = 0.29 mg/L as 80% NaClO2 (48 hour)

#### **Other Toxicity:**

LD50 Mallard duck = 0.49-1.00g/kg as 80% NaClO2 (gavage); LD50 Bob White quail = 0.66 g/kg as 80% NaClO2 (gavage); Sodium chlorite in the diet of birds was not acutely toxic. Eight-day dietary LC50's in the Mallard duck and Bob White quail were > 10,000 ppm

#### **FATE AND TRANSPORT:**

BIODEGRADATION: Chlorite ions are reduced by some bacteria under anaerobic conditions

PERSISTENCE: This material will eventually degrade to sodium chloride

**BIOCONCENTRATION:** This material will not bioaccumulate.

# 13. DISPOSAL CONSIDERATIONS

#### Waste from material:

Reuse or recycle if possible. Dispose in accordance with all applicable regulations. Do not put product, spilled product, or filled or partially filled containers into the trash or waste compactor. Contact with incompatible materials could cause a reaction and fire. Contact Technical Service to obtain neutralization instructions. Keep out of water supplies and sewers. May be subject to disposal regulations.

**Print date**: 06-May-2015 **12 of 16** 

SDS No.: M47027 SDS Revision Date: 06-May-2015

### **Container Management:**

Container management: Containers are non-refillable. Do not reuse or refill containers. Offer for recycling if available. Offer for reconditioning if appropriate. Triple rinse or pressure rinse container promptly after emptying. Triple rinse containers 5-gallons or smaller as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Triple rinse containers larger than 5 gallons as follows: Empty remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Pressure rinse as follows: Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip. Hold container upside down over application equipment or mix tank or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the side of the container, and rinse about 40 PSI for at least 30 seconds. Drain for 10 seconds, after the flow begins to drip. Container rinsate must be disposed of in compliance with applicable regulations.

## 14. TRANSPORT INFORMATION

### **LAND TRANSPORT**

U.S. DOT 49 CFR 172.101:

UN NUMBER: UN1908

PROPER SHIPPING NAME: Chlorite solution

HAZARD CLASS/ DIVISION: 8
PACKING GROUP: ||
LABELING REQUIREMENTS: 8

#### **CANADIAN TRANSPORTATION OF DANGEROUS GOODS:**

UN NUMBER: UN1908

SHIPPING NAME: Chlorite solution

CLASS OR DIVISION: 8
PACKING/RISK GROUP: ||
LABELING REQUIREMENTS: 8

### MARITIME TRANSPORT (IMO / IMDG) :

UN NUMBER: UN1908

PROPER SHIPPING NAME: Chlorite Solution

HAZARD CLASS / DIVISION: 8
Packing Group: ||
LABELING REQUIREMENTS: 8

**Print date:** 06-May-2015 **13 of 16** 

**SDS No.**: M47027 **SDS Revision Date**: 06-May-2015

# 15. REGULATORY INFORMATION

#### **U.S. REGULATIONS**

#### **OSHA REGULATORY STATUS:**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

### CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

Not regulated.

#### SARA EHS Chemical (40 CFR 355.30)

Not regulated

#### EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):

Acute Health Hazard

### **EPCRA SECTION 313 (40 CFR 372.65):**

Not regulated.

#### OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):

Not regulated

### **NATIONAL INVENTORY STATUS**

U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA): All components are listed or exempt.

TSCA 12(b): This product is not subject to export notification.

Canadian Chemical Inventory: All components of this product are listed on either the DSL or the NDSL.

### **STATE REGULATIONS**

### California Proposition 65:

This product and its ingredients are not listed, but it may contain impurities/trace elements known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act. For additional information, contact OxyChem Technical Services at 1-800-733-1165.

Component	Proposition 65 Cancer WARNING:	Proposition 65 CRT List - Male reproductive	Proposition 65 CRT List - Female	Right to Know Hazardous	Hazardous	New Jersey Special Health Hazards Substance List
Sodium chlorite 7758-19-2	Not Listed	Not Listed	Not Listed	Listed	1689	corrosive; reactive - second degree

**Print date:** 06-May-2015 **14 of 16** 

**SDS No.:** M47027 **SDS Revision Date:** 06-May-2015

Component	Environmental		to Know Special Hazardous	to Know	Rhode Island Right to Know Hazardous Substance List
Sodium chlorite 7758-19-2	Not Listed	Listed	Not Listed	Not Listed	Not Listed

#### **CANADIAN REGULATIONS**

• This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations

### WHMIS - Classifications of Substances:

- D1A Poisonous and Infectious Material; Materials causing immediate and serious toxic effects Very toxic material
- D1B Poisonous and Infectious Material; Materials causing immediate and serious toxic effects Toxic material
- E Corrosive material

# **16. OTHER INFORMATION**

Prepared by: OxyChem Corporate HESS - Product Stewardship

Rev. Date: 06-May-2015

Print date: 06-May-2015

HMIS: (SCALE 0-4) (Rated using National Paint & Coatings Association HMIS: Rating Instructions, 2nd Edition)

Health Rating: 3 Flammability Rating: 0 Reactivity Rating: 1

NFPA 704 - Hazard Identification Ratings (SCALE 0-4)

Health Rating: 3 Flammability: 0 Reactivity Rating: 1

15 of 16

SDS No.: M47027 SDS Revision Date: 06-May-2015

#### Reason for Revision:

- Updated the (M)SDS header
- Changed the SDS format to meet the GHS requirements of the revised 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)
- Updated 24 Hour Emergency Telephone Number: SEE SECTION 1
- Product Identifier has been added or updated: SEE SECTION 1
- Updated Uses Advised Against information: SEE SECTION 1
- Revised Hazard(s) Identification information: SEE SECTION 2
- Added OSHA Status: SEE SECTION 2
- Emergency Overview was revised: SEE SECTION 2
- Added GHS Information: SEE SECTION 2
- Updated First Aid Measures: SEE SECTION 4
- Modified Fire Fighting Measure Recommendations: SEE SECTION 5
- Revised Accidental Release Measures: SEE SECTION 6
- Revised Handling and Storage Recommendations: SEE SECTION 7
- PPE recommendations have been modified: SEE SECTION 8
- Updated Physical and Chemical Properties. SEE SECTION 9
- Stability and Reactivity recommendations: SEE SECTION 10
- Toxicological Information has been revised: SEE SECTION 11
- Updated Disposal Considerations. SEE SECTION 13
- Revised Preparer Information: SEE SECTION 16
- Added SDS Revision Date: SEE SECTION 16
- Added/Updated Revision Log: SEE SECTION 16
- Added "End of Safety Data Sheet" phrase

#### IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees

\_\_\_\_\_

**End of Safety Data Sheet** 

**Print date:** 06-May-2015 **16 of 16**