

## Safety Data Sheet



### Section 1: Identification

**Product Name:** Slop Oil

**Recommended Use:** Processing

**Manufacturer:** Anadarko Petroleum Corporation  
1201 Lake Robins Dr.  
The Woodlands, TX 77380  
United States  
www.anadarko.com  
(832) 636-1000 (General)

**Emergency Telephone Number:** ChemTel: (831) 248-0585 (International)  
(800) 255-3924 (North America)

### Section 2: Hazard Identification

**Classification:** • Not classified.

**Label Elements:**

**DANGER**



**Hazard Statements:**

- Highly flammable liquid and vapor.
- May be fatal if swallowed and enters airways.
- Causes skin irritation.
- Causes eye irritation.
- May cause drowsiness or dizziness.
- May cause genetic defects.
- May cause cancer.
- Suspected of damaging fertility or the unborn child.

**Precautionary Statements:**

**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep container tightly closed.
- Avoid breathing dust/fume/gas/mist/vapor/spray.
- Wash thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.

**Response**

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.
- IF exposed or concerned: Get medical advice/attention.

**Storage/Disposal**

- Store in a well-ventilated place. Keep container tightly closed.
- Protect from sunlight.
- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Other information:**



**NFPA 704 Hazard Class**

Health: 1  
Flammability: 2  
Instability: 0

(0-Minimum, 1-Slight, 2-Moderate, 3-Serious, 4-Severe)

**HMIS Hazard Rating**

Health	1
Flammability	2
Physical Hazard	0

(0-Minimum, 1-Slight, 2-Moderate, 3-Serious, 4-Severe)

### Section 3: Composition/Information on Ingredients

Component	CAS Number	Concentration
Crude Oil	8002-05-9	100%

All concentrations are percent by weight unless ingredient is gas. Gas concentrations are in percent by volume.

Crude oil, natural gas and natural gas condensate can contain minor amounts of sulfur, nitrogen and oxygen containing organic compounds as well as trace amounts of heavy metals like mercury, arsenic, nickel, and vanadium. Composition can vary depending on the source of crude.

**Synonyms:** None

### Section 4: First-Aid Measures

<b>Inhalation:</b>	Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.
<b>Skin:</b>	Wash skin with soap and water. Take off contaminated clothing and wash before reuse. If irritation develops and persists, get medical attention.
<b>Eye:</b>	In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
<b>Ingestion:</b>	Do NOT induce vomiting. Do not use mouth-to-mouth method if victim ingested the substance. Give plenty of water to drink. Obtain medical attention immediately if ingested.
<b>Most Important Symptoms and Effects, both Acute and Delayed:</b>	Refer to Section 11 - Toxicological Information.
<b>Notes to Physician:</b>	All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

### Section 5: Fire-Fighting Measures

<b>Suitable Extinguishing Media:</b>	Water spray, foam, dry powder or carbon dioxide
<b>Unsuitable Extinguishing Media:</b>	No data available.
<b>Unusual Fire and Explosion Hazards:</b>	Containers may explode when heated. Vapor explosion hazard indoors, outdoors or in sewers. HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Many liquids are lighter than water. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff to sewer may create fire or explosion hazard. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

**Hazardous Combustion Products:**

Carbon Monoxide, Carbon Dioxide, Hydrocarbon Vapors, Smoke.

**Advice for Firefighters:**

Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

**Section 6: Accidental Release Measures**

**Personal Precautions:**

Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Emergency Procedures:**

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

**Environmental Precautions:**

Prevent entry into waterways, sewers, basements or confined areas.

**Methods for Containment and Clean-up:**

Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors. All equipment used when handling the product must be grounded. LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces. LARGE SPILLS: Dike far ahead of spill for later disposal.

**Section 7: Handling and Storage**

**Precautions for Safe Handling:**

Use only with adequate ventilation. Keep away from heat, sparks, and flame. All equipment used when handling the product must be grounded. Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist, vapors and/or spray. Avoid contact with skin, eyes, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

**Conditions for Safe Storage:** Store in a cool/low-temperature, well-ventilated dry place away from heat and ignition sources. Keep away from incompatible materials.

## Section 8: Exposure Controls/Personal Protection

Component	ACGIH	NIOSH	OSHA	Other
Crude Oil	TWA: 5 mg/m <sup>3</sup> for Oil Mists	Ceiling (15 min): 1800 mg/m <sup>3</sup> TWA: 350 mg/m <sup>3</sup>		

<b>Engineering Measures/Controls:</b>	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.
<b>Respiratory Protection:</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Eye/Face Protection:</b>	Wear chemical splash safety goggles.
<b>Skin/Body Protection:</b>	Gloves constructed of nitrile, neoprene, or PVC are recommended. Chemical protective clothing such as of E.I. DuPont Tyvek QC®, Saranex®, TyChem® or equivalent recommended based on degree of exposure.
<b>Environmental Exposure Controls:</b>	Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

## Section 9: Physical and Chemical Properties

<b>Physical Form:</b>	Liquid
<b>Appearance:</b>	Clear to black viscous liquid
<b>Color:</b>	Clear to black
<b>Odor:</b>	Petroleum Odor
<b>Odor Threshold:</b>	No data available
<b>Boiling Point:</b>	90 to 1000°F (32 to 538°C)
<b>Melting Point:</b>	No data available
<b>Decomposition Temperature:</b>	No data available
<b>pH:</b>	No data available
<b>Specific Gravity (water=1):</b>	<1
<b>Water Solubility:</b>	Insoluble
<b>Viscosity:</b>	No data available
<b>Explosive Properties:</b>	No data available
<b>Oxidizing Properties:</b>	No data available
<b>Vapor Pressure:</b>	2 - 8 psi @ 100°F (37.78°C)
<b>Vapor Density (air=1):</b>	>1
<b>Evaporation Rate (water=1):</b>	<1
<b>VOC (Vol.):</b>	>90%
<b>Flash Point (TCC):</b>	50 to 200°F (10 to 93.3°C)
<b>UEL:</b>	7%
<b>LEL:</b>	0.9%
<b>Autoignition:</b>	>460°F (>238°C)
<b>Flammability (solid, gas):</b>	No data available
<b>Octanol/Water Partition Coefficient:</b>	No data available

## Section 10: Stability and Reactivity

<b>Reactivity:</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Possibility of Hazardous Reactions:</b>	Hazardous polymerization will not occur.
<b>Conditions to Avoid:</b>	High temperatures, open flames, other ignition sources.
<b>Incompatible Materials:</b>	Strong oxidizers, strong acids.
<b>Hazardous Decomposition Products:</b>	Fire Conditions only - Carbon Monoxide, Carbon Dioxide, Hydrocarbon Vapors, Smoke.

## Section 11: Toxicological Information

Components	CAS Number	Acute Toxicity
Crude Oil (100%)	8002-05-9	Ingestion/Oral-Rat LD50: >2000 mg/kg Inhalation-Rate LC50: 0.5 - 2 mg/L

### Potential Health Effects

<b>Inhalation:</b>	May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
<b>Skin:</b>	Causes skin irritation.
<b>Eye:</b>	Causes eye irritation.
<b>Ingestion:</b>	Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
<b>Chronic (Delayed):</b>	No data available.
<b>Mutagenic Effects:</b>	May cause genetic defects.
<b>Carcinogenic Effects:</b>	No data available.
<b>Reproductive Effects:</b>	Repeated and prolonged exposure may affect the reproductive system.

## Section 12: Ecological Information

<b>Toxicity:</b>	Material data lacking.
<b>Persistence and Degradability:</b>	Material data lacking.

<b>Bioaccumulative Potential:</b>	Material data lacking.
<b>Mobility in Soil:</b>	Material data lacking.
<b>Other Adverse Effects:</b>	No studies have been found.

### Section 13: Disposal Considerations

<b>Product Waste:</b>	Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
<b>Packaging Waste:</b>	Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### Section 14: Transport Information

	UN Number	UN Proper Shipping Name	Transport Hazard Class(es)	Packing Group
DOT	UN1267	Petroleum crude oil	3	II
TDG	UN1267	Petroleum crude oil	3	II
IMO/MDG	UN1267	Petroleum crude oil	3	II
IATA/ICAO	UN1267	Petroleum crude oil	3	II

**Special Precautions for User:** None specified.

**Transport in bulk according to Annex II Of MARPOL 73/78 and the IBC Code:** No data available.

### Section 15: Regulatory Information

#### CERCLA/SARA – Section 311/312 (Title III Hazard Categories)

Acute Health: Yes  
 Chronic Health: No  
 Fire Hazard: Yes  
 Pressure Hazard: No  
 Reactive Hazard: No

#### International Hazard Classification

##### **Canada:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by Regulations.

##### **WHMIS Hazard Class:**

B2

#### National Chemical Inventories

Component	CAS Number	TSCA
Crude Oil	8002-05-9	Yes

## Section 16: Other Information

**Last Revision Date:** 22/September/2010

**Preparation Date:** 29/May/2015

**Other Information:** Version 1

**Disclaimer/Statement of Liability:** The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

### Key to abbreviations

NDA = No data available

LD = Lethal Dose

TC = Toxic Concentration

D = Toxic Dose

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures