RESENE ACRYLIC UNDERCOAT WHITE

Resene Paints Ltd

Version No: **1.2**Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 0

Issue Date: 25/11/2015 Print Date: 25/11/2015 Initial Date: 03/09/2014 L.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier		
Product name	RESENE ACRYLIC UNDERCOAT WHITE	
Synonyms	9263	
Other means of identification	Not Available	
Relevant identified uses o	of the substance or mixture and uses advised against	
Relevant identified uses	Use according to manufacturer's directions.	
Details of the supplier of t	he safety data sheet	
Registered company name	Resene Paints Ltd	
Address	32-50 Vogel Street Naenae 5011 Wellington New Zealand	
Telephone	+64 4 577 0500	
Fax	+64 4 577 3327	
Website	www.resene.co.nz	
Email	advice@resene.co.nz	
Emergency telephone nun	nber	
Association / Organisation	NZ POISONS (24hr 7 days)	
Emergency telephone numbers	0800 764 766	
Other emergency telephone numbers	Not Available	
CHEMWATCH EMERGENCY	V DESDONSE	
CHEWWAICH EWERGENCY	KESPUNSE	

Primary Number	Alternative Number 1	Alternative Number 2
+800 2436 2255	+612 9186 1132	Not Available

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

GHS Classification [1]	Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	9.1C, 9.1D

Label elements

GHS label elements	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Precautionary statement(s) Prevention

P273	Avoid release to the environment.

Version No: 1.2 Page 2 of 6 Issue Date: 25/11/2015

RESENE ACRYLIC UNDERCOAT WHITE

Print Date: 25/11/2015

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

The specific chemical identity and/ or exact percentage of composition has been withheld as a trade secret

Mixtures

CAS No %[weight] Name

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

Advice for firefighters

Fire Fighting	► Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	Non combustible. May emit poisonous fumes.May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	► Clean up all spills immediately.
Major Spills	Chemical Class: bases For release onto land: recommended sorbents listed in order of priority. Moderate hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling	
Safe handling	
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	► As supplied by manufacturer

 Version No: 1.2
 Page 3 of 6
 Issue Date: 25/11/2015

RESENE ACRYLIC UNDERCOAT WHITE

Print Date: 25/11/2015

Storage incompatibility

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
RESENE ACRYLIC UNDERCOAT WHITE	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
RESENE ACRYLIC UNDERCOAT WHITE	Not Available		Not Available	

MATERIAL DATA

For calcium carbonate:

The TLV-TWA is thought to be protective against the significant risk of physical irritation associated with exposure.

for propylene glycol:

Saturated vapour concentration @ 20 deg C = 65.8 ppm, 204.6 mg/m3; i.e higher concentrations can only occur as aerosols or at higher temperatures.

for exposure to ammonia gas/ vapours:

Odour Threshold Value: Variously reported as 0.019 ppm and 55 ppm; AlHA Value 16.7 ppm (detection)

NOTE: Detector tubes for ammonia, measuring in excess of 1 ppm, are commercially available.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. CARE: Explosive vapour air mixtures may be present on opening vessels which have contained liquid ammonia.
Personal protection	
Eye and face protection	► Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. NOTE: The material may produce skin sensitisation in predisposed individuals. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	See Other protection below
Other protection	▶ Overalls.
Thermal hazards	Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Thick white liquid		
Physical state	Liquid	Relative density (Water = 1)	1.45
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8-9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	1100
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	50

Version No: **1.2** Page **4** of **6** Issue Date: **25/11/2015**

RESENE ACRYLIC UNDERCOAT WHITE

13300	Date.	23/11/2013
Print	Date:	25/11/2015

			4
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	33

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

rmation on toxicologi	cal effects		
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tr	act (as classified by EC Directives using animal models).	
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.		
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models).		
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).		
RESENE ACRYLIC	TOXICITY IRRITATIO	V	
UNDERCOAT WHITE	Not Available Not Available		
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		
RESENE ACRYLIC UNDERCOAT WHITE	No significant acute toxicological data identified in literature search. The acute oral toxicity of propylene glycol is very low, and large quantities are required to cau	se perceptible health damage in humans.	
Acute Toxicity	○ Carcinogenic	ity 🛇	
Skin Irritation/Corrosion	Reproductiv	ity 🛇	
Serious Eye Damage/Irritation	STOT - Single Exposu	re 🛇	
Respiratory or Skin sensitisation	STOT - Repeated Exposu	re 🛇	
Mutagenicity	○ Aspiration Haza	rd 🛇	

Legend:

X − Data available but does not fill the criteria for classification
 ✓ − Data required to make classification available

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters.

In air ammonia is persistent whilst, in water, it biodegrades rapidly to nitrate, producing a high oxygen demand.

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

 Version No: 1.2
 Page 5 of 6
 Issue Date: 25/11/2015

 Print Date: 25/11/2015
 Print Date: 25/11/2015

RESENE ACRYLIC UNDERCOAT WHITE

Ingredient	Bioaccumulation
	No Data available for all ingredients
M = 1, 114 - 1 11	

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

- ► DO NOT allow wash water from cleaning or process equipment to enter drains.
- ► Recycle wherever possible.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006	

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities	
Not Applicable	Not Applicable	
Refer Group Standards for further information		
National Inventory	Status	
reactional involutory	Status	
Australia - AICS	Y	

Canada - DSL	Υ
Canada - NDSL	Υ
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Y

 Version No: 1.2
 Page 6 of 6
 Issue Date: 25/11/2015

RESENE ACRYLIC UNDERCOAT WHITE

Print Date: 25/11/2015

Legend:

Y = All ingredients are on the inventory

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC — TWA: Permissible Concentration-Time Weighted Average PC — STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.