

**SIMONIZ BASEBOARD STRIPPER S3343012**

Quick Identifier (In Plant Common Name)

Material Safety Data Sheet

Simoniz USA, Inc.
201 Boston Tpke
Bolton, CT 06043

HMIS Symbol:

Health	3
Flammability	1
Reactivity	2

HMIS	NFPA
Minimal 0	Insignificant
Slight 1	Slight
Moderate 2	Moderate
Serious 3	High
Severe 4	Extreme

NFPA Symbol:

Emergency Telephone No. (770) 433-0210 (8am-5pm;M-F)
(800) 255-3924 24 Hours

Date Prepared: February 16, 2012

Prepared By: *V. Burnell*

Supersedes: NEW

SECTION 1 – IDENTITY

Common Name: (used on label) **SIMONIZ BASEBOARD STRIPPER S3343012**
(Trade name & Synonyms)

Chemical Name Mixture packaged in pressurized aerosol spray can.

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s)	CAS No.	OSHA PEL	ACGIH TLV	Other Limits
Potassium Hydroxide	1310-58-3	2mg/m ³	2mg/m ³	
*Ethylene Glycol Monobutyl Ether	111-76-2	25 ppm	25 ppm	
Propane	74-98-6	Unknown	1000 ppm	
Butane	106-97-8	Unknown	800 ppm	

*Section 313 Supplier Notification - Indicates hazardous ingredients which are toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	>100°F	Specific Gravity (H₂O=1)(Conc)	1.007 – 1.027g/mL	Vapor Pressure (Propellant)	No Data
% - VOC	12.7%	Evaporation Rate (BuAc=1)	<1.00	pH	13.0 – 14.0
Solubility In Water	Soluble	Appearance and Odor	Beige slightly viscous liquid with a mint odor		

SECTION 4 - FIRE & EXPLOSION DATA

Flammability (per flame projection)	NON-FLAMMABLE	Flammable Limits in Air (Propellants)	Lower N/A	Upper N/A	Extinguisher Media	Water, Dry Chemical, CO ₂ , Foam
Special Fire Fighting Procedures	Keep containers cool using water spray. Use proper equipment to protect personnel from bursting containers.					
Unusual Fire and Explosion Hazards	Contents under pressure. Do not expose to temperatures exceeding 120° F as containers may vent, rupture or burst.					

SECTION 5 - PHYSICAL HAZARDS

Stability	Unstable ☐ Stable ☒	Conditions to Avoid	Open Flames; Temp. > 120°F.	Hazardous Polymerization	May Occur ☐ Will not Occur ☒
------------------	---	----------------------------	--------------------------------	---------------------------------	--

Incompatibility (Materials to Avoid) Strong oxidizers, acids and metals

Hazardous Decomposition Products Hydrocarbons, CO, CO₂

SECTION 6 - HEALTH HAZARDS

Routes of Entry **Inhalation:** Yes **Eyes / Skin:** Yes **Ingestion:** Unlikely

Signs and Symptoms of Exposure (Acute & Chronic) **Inhalation:** May cause respiratory irritation. Symptoms may include coughing, sneezing, damage to the nasal or respiratory tract. **Ingestion:** Swallowing may cause severe burns of mouth, throat and stomach. Other symptoms may include vomiting, diarrhea; **Skin Contact:** Corrosive! Contact with skin can cause irritation or severe burns and scarring **Eye Contact:** Corrosive! Causes irritation of eyes with tearing, redness, swelling;

Medical Conditions

Generally Aggravated by Exposure Pre-existing skin disorders, eye problems or impaired respiratory functions

Chemical Listed as Carcinogen or Potential Carcinogen	National Toxicology Program	Yes ☐ No ☒	I.A.R.C. Monographs	Yes ☐ No ☒	OSHA	Yes ☐ No ☒
--	------------------------------------	--	----------------------------	--	-------------	--

Emergency and First Aid Procedures

- 1. Inhalation** Remove victim to fresh air. Apply artificial respiration if needed. Get medical attention.
- 2. Eyes** Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.
- 3. Skin** Remove contaminated clothing and wash skin with water. Get medical attention if irritation persists.
- 4. Ingestion** DO NOT INDUCE VOMITING unless directed by a physician or poison control center. Get medical attention immediately.

SECTION 7 – SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type) None required for normal use. Use with adequate ventilation. Use a respirator when TLVs exceeded.

Ventilation	Local Exhaust	Maintain adequate ventilation.	Mechanical (General)	N/A	Special	N/A	Other	N/A
--------------------	----------------------	--------------------------------	-----------------------------	-----	----------------	-----	--------------	-----

Protective Gloves Chemical Resistant **Eye Protection** Safety Glasses

Other Protective Clothing or Equipment Wash hands after use.

SECTION 8 – SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken Handling and Storage **DANGER! CORROSIVE. CAUSES SEVERE BURNS TO SKIN, EYES, RESPIRATORY TRACT. MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED.** Avoid contact with skin, eyes or clothing. Wear chemical resistant gloves during use to avoid skin contact. Use only with adequate ventilation. Wash thoroughly after handling. Do not breathe vapors. Do not store at temperatures above 120°F. Do not puncture or incinerate containers. Keep out of reach of children. Store in a cool, dry well ventilated area away from incompatible materials. Store in accordance with **NFPA 30B** for **Level 1 Aerosols**.

Other Precautions Read label cautions carefully. Follow label directions to avoid injury.

Steps to be Taken in Case Material is Released or Spilled Absorb spill with inert material then place in a chemical waste container. Dispose of spill material in accordance with regulations.

Waste Disposal Methods Dispose of in accordance with local, state, and federal regulations.

Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986
This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to the proposition.

Transportation Info **DOT CLASSIFICATION:** HAZARDOUS **PACKING GROUP:** N/A
DESCRIPTION: CONSUMER COMMODITY, ORM-D
UN NUMBER: UN 1950 **HAZARD CLASS:** 2.1

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.

12712357 / 9012357 121602