



Ascent Battery Supply, LLC
925 Walnut Ridge Drive
Hartland, Wisconsin 53029

Safety Data Sheet (SDS)

Lithium-Ion (Li-Ion) Batteries

The information and recommendations below are believed to be accurate at the date of document preparation. Ascent Battery Supply makes no warranty or merchantability or any other warranty, express or implied, with respect to this information and assumes no liability resulting from its use. This SDS provides guidelines for safe use and handling of product. It does not, and cannot, advise all possible situations. All specific uses of this product must be evaluated by the end user to determine if additional safety precautions should be taken.

SECTION 1 - IDENTIFICATION

Product Name	Lithium-Ion Battery	Emergency Number	INFOTRAC (800) 535-5053
Common Name(s)	Li-Ion Battery	Overseas Emergency Number	INFOTRAC (352) 323-3500 (Collect)
Synonyms	Lithiated Cobalt Oxide; Li-Ion Secondary Battery; Li-Ion Rechargeable Battery		
DOT Description	Dry Battery		
Chemical Name	Lithium-Ion		
Distributed By	Ascent Battery Supply, LLC 925 Walnut Ridge Drive Hartland, Wisconsin 53029		

SECTION 2 – HAZARD(S)

Unusual Fire and Explosion Hazards	Cells or batteries may flame or leak potentially hazardous organic vapors if exposed to excessive heat, fire or short circuit condition. Damaged or opened cells or batteries can result in rapid heating and the release of flammable vapors. Vapors may be heavier than air and may travel along the ground or be moved by ventilation to an ignition source and flash back.
---	--

SECTION 3 – COMPOSITION

Chemical Name	CAS No.	Percentage %
Lithium Cobalt Oxide	12190-79-3	25-40
Iron	7439-89-6	15-25
Aluminum	7429-90-5	2-6
Graphite: Natural	7782-42-5	10-20
Graphite: Artificial	7740-44-0	
Copper	7440-50-8	5-15
Organic Electrolyte		10-20

SECTION 4 – FIRST AID MEASURES

For Li-Ion Chemicals:

Inhalation	Get fresh air. If symptoms persist seek medical attention
Eyes and Skin	Skin: Flush with copious quantities of flowing lukewarm water for a minimum of 15 minutes; wash with soap and water. Eyes: Flush with copious quantities of flowing lukewarm water for a minimum of 15 minutes; get immediate medical attention.
Ingestion	Ingestion of battery chemicals can be harmful. Call The National Battery Ingestion Hotline (202-625-3333) 24 hours a day, for procedures treating ingestion of chemicals. Dilute with plenty of water, do not induce vomiting, and seek immediate medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguisher Media	Use water, foam or dry powder
Special Fire Fighting Procedures	Use a positive pressure self-contained breathing apparatus if batteries are involved in a fire. Full protective clothing is necessary. During water application, caution is advised as burning pieces of flammable particles may be ejected from the fire.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Damaged batteries that are *NOT* hot or burning should be placed in a sealed plastic bag or plastic-lined metal container. Chemical resistance gloves must be used to handle all battery components. If cells rupture and a thermal event follows: using shovel or broom, cover battery or spilled substances with dry sand or vermiculite, place in approved container (after cooling if necessary) and dispose in accordance with local regulations.

SECTION 7 – HANDLING AND STORAGE

1. Use only approved chargers and charging procedures.
2. Do not disassemble a battery or bypass any safety device.
Batteries should be separated from other materials and stored in a non-combustible, well-ventilated, sprinkler-protected structure with sufficient clearance between walls and battery stacks.
3. Do not place batteries near heating equipment; do not expose to direct sunlight for extended periods.
4. Do not store batteries above 60 °C or below -32°C. Store batteries in a cool (below 21°C (70°F)), dry area that is subject to little temperature change. Elevated temperatures can result in reduced battery service life. Battery exposure to temperatures in excess of 130°C will result in the battery venting flammable liquid and gases.
5. Do not store batteries in a manner that allows terminals to short circuit.

SECTION 8 – EXPOSURE/PERSONAL PROTECTION

Respiratory Protection None required under normal handling conditions; see also *Section 5 – Fire Fighting Measures*.
Gloves Wear chemical resistant gloves if cell is ruptured, corroded, or leaking materials.
Safety Glasses Always wear safety glasses with working with battery cells.

SECTION 9 – PHYSICAL/CHEMICAL PROPERTIES

Boiling Point	N/A	Melting Point	N/A
Vapor Pressure	N/A	Vapor Density	N/A
Specific Gravity	N/A	Evaporation Rate	N/A
Solubility in Water	N/A	Appearance and Odor	Geometric, solid object

SECTION 10 – STABILITY & REACTIVITY

Reactivity in Water	N/A	Auto-Ignition Temperature	N/A
Flash Point	N/A	Flammable Limits in Air, by vol.	N/A
Percent Volatile By Volume	N/A		
Stable	Avoid electrically shorting the cell and prolonged exposure to humid conditions. See also <i>Section 7 – Handling and Storage</i> .		
Incompatibility (materials to avoid)	N/A		

SECTION 11 – TOXICOLOGICAL INFORMATION

Threshold Limit Value	Exposure limit of $\text{LiCoO}_2 = 0.1\text{mg/m}^3$ (OSHA)
Signs and Symptoms of Exposure	None. (In fire or rupture situations, refer to sections 4, 5, & 8.)
Medical Conditions Generally Caused by Exposure	Chemicals may cause burns to skin, eyes, gastrointestinal tract and mucous membranes.
Routes of Entry	Skin, Eyes, Ingestion (swallowing), Inhalation (fumes)

SECTION 12 – ECOLOGICAL INFORMATION

Hazardous Decomposition Products	None under normal conditions. During Fire: combustible vapors (including CO), formation of Hydrogen fluoride (HF) and phosphorous oxides. Reaction with Water: may produce irritant Hydrogen fluoride (HF)
Hazardous Polymerization	Will not occur
When properly used and disposed, these batteries are not hazardous to the environment. Do not carelessly discard. Never discard Li-Ion batteries into a fire. Dispose of properly or recycle.	

SECTION 13 - DISPOSAL

1. When completely discharged, Li-Ion batteries have no hazardous waste characteristics and can be landfilled.
2. This product does not contain any materials listed by the EPA as requiring specific waste disposal procedures.
3. When disposing of large quantities of Li-Ion batteries or cells, consult local/state/federal guidelines.
4. Fully discharge the battery and tape/cap terminals prior to disposal.

SECTION 14 – TRANSPORT

Product is shipped as:

Ground (DOT)

Non-Hazardous by ground UN3480

Air (IATA/ICAO)

Lithium ion Batteries – Not restricted UN3480

Sea (IMDG)

Lithium ion Batteries – Not restricted

Special Shipping Information: These batteries have been tested to Section 38.3 of the “UN Manual of Test and Criteria”

SECTION 15 – REGULATORY INFORMATION

IATA-DRG Air transportation – Packing instruction 965 Section II, IATA Dangerous Goods 51st Edition

IMO-IMDG Sea transportation

DOT 49 Code of Federal Regulations (USA)

SECTION 16 - OTHER

Document Control No:	SDS20004 – Ascent SDS for Lithium-Ion Batteries	Revision:	1	Effective Date:	07/23/13
-----------------------------	---	------------------	---	------------------------	----------