



MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: BH-TwistTube 2410

Manufacturer:

Federal Mogul Corporation
26555 Northwestern Highway
Southfield, MI 48033

MSDS# TN-110

24hr Emerg # (Infotrac): 1-800-535-5053

International: 001-352-323-3500

Non-Emerg #: 248-354-9844

SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

BH-TwistTube 2410 is a lightweight, flexible, self-wrapping oversleeve designed to provide mechanical protection for wiring. Its design allows flexibility for quick and easy bundling of wire and cable assemblies and superior abrasion protection. The polyester construction eliminates problems associated with trapped heat and humidity.

This information provides minimum criteria for safe usage and handling of this product. Companies using this product should develop their own occupational health program to protect employees from injury or adverse health effects.

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV
Thermoplastic Polyester	None Established	99.5	None Established	None Established
Inorganic Pigments	None Established	0.5	None Established	None Established

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Shipped material is not considered hazardous, but operations (e.g., overheating, burning, machining, grinding, abrading, or riveting) that can create airborne dust should be avoided.

POTENTIAL HEALTH EFFECTS

Inhalation: Dust from abnormal abrasion or vapors generated from heating to greater than 300°C can cause irritation.

Skin: Molten material can cause thermal burns

Eye: Dust particles may cause irritation or corneal injury.

Ingestion: Not a probable route of entry.

POTENTIAL HEALTH EFFECTS (continued)

Carcinogenicity:

	COMPONENT
	NTP
	IARC
	OSHA
Thermoplastic Polyester	No No No
Inorganic Pigments	No No No

Symptoms and Effects of Exposure to Selected Individual Components

Exposure Hazards: None known

SECTION 4: FIRST AID MEASURES

Inhalation:	Move to fresh air. Seek medical attention.
Eye Contact:	Rinse thoroughly with ample amounts of water for 15 minutes. Seek medical attention.
Skin Contact:	Wash thoroughly with soap and water. If molten material falls on skin, do not attempt to remove material; cool immediately with water. Seek medical attention.
Ingestion:	If significant quantities have been consumed, give two glasses of water to induce vomiting. Seek medical attention.

SECTION 5: FIRE FIGHTING MEASURES

This product is inherently flame resistant, but may ignite at temperature exceeding 600°C in an oxygen-enriched atmosphere.

Flashpoint: N/A **LEL:** N/A **UEL:** N/A **Autoignition Temperature:** N/A

Extinguishing Media: Use media suitable for surrounding fire.

Unusual Fire and Explosion Hazards: None

Special Fire-Fighting Procedure: Wear self-contained breathing apparatus when extinguishing. Hazardous decomposition products are generated in fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Scrap monofilament may present a slipping hazard. Sweep up and dispose of according to all federal and state disposal procedures. If dust is generated during machining, grinding, abrading or riveting, remove dust by vacuuming or wet-mopping. Vacuums should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

SECTION 7: HANDLING AND STORAGE

Store in a cool, dry place. Shipping and storage may accumulate dust in shipping containers, remove dust by vacuuming or wet-mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Protection: Any operation which may produce dust, including machining, grinding, riveting, or abrading this product, should be adequately exhausted to prevent inhalation of dust.

Respiratory Protection: Use a NIOSH-approved respirator if there is a potential for exposure to dust, vapor, or fume exceeding PELs or TLVs. (See 29 CFR 1910.134, OSHA Respiratory Protection Standard.)

Skin Protection: If skin irritation occurs, gloves and other protective garments may be worn.

Eyes: Wear safety glasses or goggles, as necessary, if dust exposure is possible.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	N/A	Vapor Pressure:	N/A
Melting Point:	250°C	Vapor Density (air = 1):	N/A
pH:	N/A	% Volatile:	N/A
Specific Gravity:	1.38 g/cc	Evaporation Rate:	N/A
Water Solubility:	Insoluble	Form, Color and Odor:	Solid, black and odorless

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and storage conditions.

Incompatibility (Materials/Conditions to Avoid): Strong bases

Hazardous Polymerization: Will not polymerize

Decomposition Products: Avoid exposing to temperatures greater than 300°C for prolonged periods of time. At this temperature, chemical decomposition starts to occur producing such by-products as carbon monoxide and trace amounts of esters, alcohols, acids and acetaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation: Refer to Section 3

Skin: Refer to Section 3

Eye: Refer to Section 3

Ingestion: Refer to Section 3

Acute: None known

Chronic: None known

SECTION 12: ECOLOGICAL INFORMATION

N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Federal and state law regulates disposal of scrap material or dust as solid waste; disposal must be in accordance with federal and state laws. Contact local regulatory agencies for guidance.

SECTION 14: TRANSPORTATION INFORMATION

Proper Shipping Name: Not regulated by these modes of transportation

Hazard Class: None

Identification Number: None

Packing Group: N/A

Shipping Label: None

Additional Marking Requirement: None

SECTION 15: REGULATORY INFORMATION

U.S. TSCA: All chemicals used in the manufacture of this product are listed on the U.S. Toxic Substances Control Act (TSCA) Inventory

California Proposition 65: This product does not contain ingredients known to the State of California to cause cancer, birth defects or other reproductive effects.

SARA Title III – Section 313 Supplier Notification: This product does not contain chemicals subject to SARA Title III/CERCLA “reportable quantities” (RQs) and/or “threshold planning quantities” (TPQs) and/or are classified as “Toxic Chemicals” under the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 40 CFR 372.

RCRA Hazardous Waste Code: Not Available

CERCLA Hazardous Substances: Not Available

OSHA: Not Available

WHMIS Classification: Not Available

SECTION 16: OTHER INFORMATION

Abbreviations:

CAS No.: Chemical Abstract Services Number
OSHA PEL: U.S. Occupational Safety and Health Administration Permissible Exposure Limit
ACGIH TLV: American Conference of Governmental Industrial Hygienists Threshold Limit Value (2004)
N/A: Not Applicable
IARC: International Agency for Research on Cancer
NTP: National Toxicology Program

The information and recommendations stated above are taken from sources believed to be accurate as of the date of this revision. Federal-Mogul makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability, including direct, incidental or consequential damages for any reliance thereof.

This MSDS should not be used as a complete or accurate summary of the content of this product. For specific information on brand names, manufacturers, or quantities, please refer to product specification documents, wherever available.