Product: BH-126



# MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: BH – Therm-L-Shield® Manufacturer:

Federal-Mogul Corporation 26555 Northwestern Highway

Southfield, MI 48033

MSDS# BH-126 24hr Emerg # (Infotrac): 1-800-535-5053

International: 001-352-323-3500 Non-Emerg #: 248-354-9844

### SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

BH – Therm-L-Shield<sup>®</sup> is a woven fiberglass fabric that has aluminum foil laminated to its outer surface and an pressure-sensitive acrylic adhesive on its inner surface. It can be slitted to widths and lengths or custom die-cut to complex geometric shapes. It provides superior protection from radiant heat for plastic fuel tanks, plastic engine components, and areas where a self-adhesive thermal protection may be required. It can be attached to heat shields for added protection.

Although several of the ingredients used to formulate this product may be hazardous in the raw state, the manufacturing process results in a solid, infusible form, binding and otherwise, rendering the product inert. The constituents identified below may be present in quantities greater than 1% (0.1% for carcinogens) that may be released from the product by such operations as overheating, burning, machining, abrading, or riveting.

The information in this document provides the minimum criteria for safe usage and handling of this product. Companies using this product should develop their own occupational health program to protect employees from injury or adverse health effects.

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV (2005)
Continuous filament glass fibers	65997-17-3	<90	1 f/cc*	1 f/cc or 5 mg/m <sup>3</sup>
Aluminum foil	7429-90-5	10	15 mg/m <sup>3</sup> (total dust)	10 mg/m <sup>3</sup> (total dust)
Acrylic-based adhesive	Proprietary	<1	None established	None established

<sup>\*</sup> proposed

### **SECTION 3: HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

The product is not considered hazardous, but operations (e.g., overheating, burning, machining, abrading, or riveting) that can create airborne dust should be avoided.

#### POTENTIAL HEALTH EFFECTS

**Inhalation:** Dust or vapor may cause respiratory irritation.

**Skin**: Prolonged contact may cause skin irritation.

Eye: Dust particles may cause irritation or corneal injury due to mechanical action.

**Ingestion:** Not a probable route of entry.

Revised: 10/4/2005 Page 1 of 5

**POTENTIAL HEALTH EFFECTS (continued)** 

Carcinogenicity:

COMPONENT

NTP IARC OSHA

Aluminum foil

No No No

Continuous filament glass fibers

No 3 No

### Symptoms and Effects of Exposure to Selected Individual Components

#### **ALUMINUM FLAKE**

**Acute** - May cause eye irritation, rashes or dermatitis, dizziness, headaches, nausea, vomiting, narcosis, and other nervous system effects.

**Chronic** – May cause damage to the liver, kidney, or other internal organs.

### **CONTINUOUS FILAMENT GLASS FIBERS**

**Acute** - May cause irritation to skin, eyes, nose, and throat. May cause skin rash, conjunctivitis, coughing and sneezing.

**Chronic** – Although some studies of fibrous and mineral wool workers have shown a link to lung cancer in humans, those studies have clearly provided no evidence of a link between lung cancer and continuous filament fiberglass exposure.

**SECTION 4: FIRST AID MEASURES** 

**Inhalation:** Move to fresh air. If irritation persists, seek medical attention.

**Eye Contact:** Rinse thoroughly with ample amounts of water. If irritation persists, seek medical

attention.

Skin Contact: Wash exposed area with soap and cool water. Avoid scratching irritated areas. If

irritation persists, seek medical attention.

**Ingestion:** Not a probable route of entry.

# **SECTION 5: FIRE FIGHTING MEASURES**

This product is self-extinguishing.

Flashpoint: N/A LEL: N/A UEL: N/A Autoignition Temperature: N/A

**Extinguishing Media:** Use appropriate media type for surrounding materials.

**Unusual Fire and Explosion Hazards:** None known.

**Special Fire-Fighting Procedure:** Wear self-contained breathing apparatus when extinguishing a

fire.

Revised: 10/4/2005 Page 2 of 5

Product: BH-126

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

If dust is generated, remove the dust by vacuuming or wet-mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

#### **SECTION 7: HANDLING AND STORAGE**

Store in a cool, dry place. If dust is generated during shipping, remove the dust from the container by vacuuming or wet-mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from surfaces.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ventilation Protection:** Any operation which may produce dust, including machining, grinding, riveting, or

abrading this product, should be adequately exhausted to prevent inhalation of dust.

**Respiratory Protection:** Use a NIOSH-approved respirator if there is a potential for exposure to exceed

applicable PELs or TLVs. (See 29 CFR 1910.134, OSHA Respiratory Protection

Standard.)

**Skin Protection:** If skin irritation occurs, gloves and other protective garments may be worn. For

cutting operations, gloves and loose-fitting clothing are recommended to be worn.

**Eyes:** Wear safety glasses or goggles when cutting the material.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Boiling Point:** N/A Vapor Pressure: N/A **Melting Point:** Vapor Density (air = 1): N/A >200°C pH: % Volatile: N/A N/A **Evaporation Rate:** Specific Gravity: 2.2 N/A

Water Solubility: Insoluble Form, Color, and Odor: Solid, aluminum color, odorless

#### **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable at normal temperatures and storage conditions

**Incompatibility** Strong oxidizing agents

(Materials/Conditions to Avoid):

Hazardous Polymerization: Will not polymerize

**Decomposition Products:** Thermal decomposition will occur at temperatures above 250°C and may

produce carbon monoxide, carbon dioxide, and nitrogen oxide.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

**Inhalation:** Refer to Section 3

Revised: 10/4/2005 Page 3 of 5

Product: BH-126

Skin: Refer to Section 3

Eye: Refer to Section 3

Ingestion: Refer to Section 3

Acute: None known

Chronic: None known

#### **SECTION 12: ECOLOGICAL INFORMATION**

Not available.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Federal and state law regulates disposal of scrap material or dust as solid waste. Contact local regulatory agencies for guidance.

### **SECTION 14: TRANSPORTATION INFORMATION**

**Proper Shipping Name:** Not regulated

**Hazard Class:** N/A N/A **Identification Number: Packing Group:** N/A Shipping Label: None Additional Marking Requirement: None

#### **SECTION 15: REGULATORY INFORMATION**

U.S. TSCA: The chemicals used to manufacture this product are listed on the U.S.

Toxic Substances Control Act (TSCA) Inventory.

California Proposition 65: This product does not contain ingredients known to the State of California

to cause cancer, birth defects or other reproductive effects.

SARA Title III -

This product contains aluminum, a chemical subject to SARA Title III/CERCLA "reportable quantities" (RQs) and/or "threshold planning Section 313 Supplier Notification:

quantities" (TPQs) and/or is classified as a "Toxic Chemical" under the Emergency Planning and Community Right-To-Know Act (EPCRA) of

1986 and 40 CFR 372.

RCRA Hazardous Waste Code: Not available.

**CERCLA Hazardous Substances:** Not available.

OSHA: OSHA has established a PEL for aluminum but not for the product.

WHMIS Classification: Not available.

Revised: 10/4/2005 Page 4 of 5

### **SECTION 16: OTHER INFORMATION**

## Abbreviations:

CAS No.: Chemical Abstract Services Number

OSHA PEL: U.S. Occupational Safety and Health Administration, Permissible Exposure Limit

ACGIH TLV: American Conference of Governmental Industrial Hygienists, Threshold Limit Value (2005)

f/cc: Fibers per cubic centimeter of sampled air

mg/m<sup>3</sup>: Milligrams of contaminant per cubic meter of sampled air, on a weight-to-volume basis

N/A: Not Applicable

IARC: International Agency for Research on Cancer

NTP: National Toxicology Program HEPA: High-efficiency particulate air

NIOSH: National Institute of Occupational Safety and Health

The information and recommendations stated above are taken from sources believed to be accurate as of the date of this revision. Federal-Mogul makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability, including direct, incidental or consequential damages for any reliance thereof.

This MSDS should not be used as a complete or accurate summary of the content of this product. For specific information on brand names, manufacturers, or quantities, please refer to product specification documents, wherever available.

Revised: 10/4/2005 Page 5 of 5