

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
 Substance name : BRAKE PARTS CLEANER (HEXANE)
 Product code : 2633
 Formula : C6H14
 Synonyms : dipropyl / gettysolve-B / hex (=normal-hexane) / hexane, anhydrous / hexane,pure grade / Hexanes / hexyl hydride / n-caproylhydride / n-hexane / n-hexyl hydride / normal-caproyl hydride / normal-hexane / normal-hexyl hydride / skellysolve B / solvent hexane

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Solvent
 Cleansing product
 Laboratory chemical
 Fuel: additive

1.3. Details of the supplier of the safety data sheet

Brody Chemical
 6125 W. Double Eagle Cr.
 Salt Lake City, UT 84118 - USA
 T (801) 963-2436

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225
 Skin Irrit. 2 H315
 STOT SE 3 H336
 STOT RE 2 H373
 Asp. Tox. 1 H304
 Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H336 - May cause drowsiness or dizziness
 H373 - May cause damage to organs through prolonged or repeated exposure
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof ventilation equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P260 - Do not breathe fumes/vapors
 P261 - Avoid breathing fumes/vapors
 P264 - Wash hands and all exposed skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment
P280 - Wear protective gloves/eye protection/face protection
P301+P310 - If swallowed: Immediately call poison control center
P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P312 - Call poison control center if you feel unwell
P314 - Get medical advice/attention if you feel unwell
P331 - Do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use foam/dry chemical to extinguish
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to in accordance to all regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%	Classification (GHS-US)
BRAKE PARTS CLEANER (HEXANE) (Main constituent)		100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink. Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
- First-aid measures after skin contact : Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Take victim to an ophthalmologist if irritation persists. Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Rinse mouth with water. Do not induce vomiting. Give activated charcoal. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital. Doctor: gastric lavage. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause drowsiness or dizziness.
- Symptoms/injuries after inhalation : EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Dizziness. Narcosis. Drunkenness. Headache. Nausea. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Disturbances of consciousness.
- Symptoms/injuries after skin contact : Tingling/irritation of the skin. Irritation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue.

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Symptoms/injuries after ingestion : Vomiting. Risk of aspiration pneumonia. Nausea. Symptoms similar to those listed under inhalation. Risk of lung edema.
- Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Loss of weight. Dry skin. Tingling/irritation of the skin. Skin rash/inflammation. Disturbed tactile sensibility. Movement disturbances. Myasthenia. Cramps/uncontrolled muscular contractions. Paralysis. Gastrointestinal complaints. Loss of appetite. Visual disturbances.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Preferably: alcohol resistant foam. Water spray. Polyvalent foam. AFFF foam. BC powder. Carbon dioxide. Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : DIRECT FIRE HAZARD. Highly flammable. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD. May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard". Highly flammable liquid and vapor.
- Explosion hazard : DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
- Reactivity : Upon combustion: CO and CO₂ are formed. Reacts with (strong) oxidizers: (increased) risk of fire/explosion. Highly flammable liquid and vapor.

5.3. Advice for firefighters

- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.
- Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective goggles. Head/neck protection. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. Large spills/in enclosed spaces: gas-tight suit. See "Material-Handling" to select protective clothing.
- Emergency procedures : Ventilate spillage area. Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes. No open flames, no sparks, and no smoking. Do not breathe fumes/vapor. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills. Collect spillage.

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Take up liquid spill into absorbent material. Liquid spill: dam up with sand/earth. Take up liquid spill into a non combustible material e.g.: sand/earth or kieselguhr. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe strict hygiene. Keep container tightly closed. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe fumes/vapor. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Storage temperature : 20 °C
Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.
Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.
Storage area : Store in a cool area. Ventilation at floor level. Fireproof storeroom. Provide for a tub to collect spills. Provide the tank with earthing. Meet the legal requirements.
Special rules on packaging : SPECIAL REQUIREMENTS: closing. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
Packaging materials : SUITABLE MATERIAL: steel. stainless steel. aluminium. iron. copper. bronze. polyethylene. polypropylene. glass. MATERIAL TO AVOID: No data available.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BRAKE PARTS CLEANER (HEXANE)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm
ACGIH	Remark (ACGIH)	CNS impair; peripheral neuropathy; eye irr; skin; BEI
OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Materials for protective clothing : GIVE EXCELLENT RESISTANCE: nitrile rubber. PVA. tetrafluoroethylene. viton. GIVE GOOD RESISTANCE: No data available. GIVE LESS RESISTANCE: No data available. GIVE POOR RESISTANCE: butyl rubber. natural rubber. neoprene. polyethylene. PVC. styrene-butadiene rubber.
Hand protection : Gloves.
Eye protection : Safety glasses.

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection	: Head/neck protection. Protective clothing.
Respiratory protection	: Wear gas mask with filter type A if conc. in air > exposure limit.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless
Odor	: Petroleum-like odour Mild odour
Odor threshold	: 64 - 244 ppm 225 - 859 mg/m ³
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 69 °C
Critical temperature	: 234 °C
Critical pressure	: 30120 hPa
Flash point	: -22 °C
Relative evaporation rate (butyl acetate=1)	: > 10
Relative evaporation rate (ether=1)	: 1.3
Flammability (solid, gas)	: No data available
Explosion limits	: 1.1 - 7.5 vol % 42 - 265 g/m ³
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 160 hPa
Vapor pressure at 50 °C	: 540 hPa
Relative density	: 0.7
Relative vapor density at 20 °C	: 2.97
Relative density of saturated gas/air mixture	: 1.3
Specific gravity / density	: 660 kg/m ³
Molecular mass	: 86.18 g/mol
Solubility	: Insoluble in water. Substance floats in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in chloroform. Soluble in oils/fats. Water: < 0.01 g/100ml Ethanol: soluble Ether: soluble Acetone: soluble
Log Pow	: 3.5 - 3.94 (Calculated)
Log Kow	: No data available
Auto-ignition temperature	: 225 °C
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: 0.455 mm ² /s (20 °C)
Viscosity, dynamic	: 0.0003 Pa.s (25 °C)

9.2. Other information

Minimum ignition energy	: 0.24 mJ
Specific conductivity	: 100 pS/m
Saturation concentration	: 564 g/m ³
VOC content	: 100 %
Other properties	: Gas/vapour heavier than air at 20°C. Clear. Volatile. Substance has neutral reaction. May generate electrostatic charges.

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed. Reacts with (strong) oxidizers: (increased) risk of fire/explosion. Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

BRAKE PARTS CLEANER (HEXANE)	
LD50 oral rat	25000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	3000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (ppm)	48000 ppm/4h (Rat; Literature study)
ATE US (oral)	25000.000 mg/kg body weight
ATE US (dermal)	3000.000 mg/kg body weight
ATE US (gases)	48000.000 ppmV/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Dizziness. Narcosis. Drunkenness. Headache. Nausea. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Disturbances of consciousness.
Symptoms/injuries after skin contact	: Tingling/irritation of the skin. Irritation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue.
Symptoms/injuries after ingestion	: Vomiting. Risk of aspiration pneumonia. Nausea. Symptoms similar to those listed under inhalation. Risk of lung edema.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Loss of weight. Dry skin. Tingling/irritation of the skin. Skin rash/inflammation. Disturbed tactile sensibility. Movement disturbances. Myasthenia. Cramps/uncontrolled muscular contractions. Paralysis. Gastrointestinal complaints. Loss of appetite. Visual disturbances.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Dangerous for the environment. Toxic to aquatic life with long lasting effects.
Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). TA-Luft Klasse 5.2.5/l.
Ecology - water	: Fouling to shoreline. Toxic to fishes. Toxic to invertebrates (Daphnia). Harmful to algae.

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BRAKE PARTS CLEANER (HEXANE)	
LC50 fish 1	2.5 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	2.1 mg/l (48 h; Daphnia magna)
LC50 fish 2	4 mg/l (24 h; Carassius auratus)
EC50 Daphnia 2	0.4 mg/l (96 h; Chaetogammarus marinus)
Threshold limit other aquatic organisms 1	9.049 mg/l (Protozoa)
Threshold limit algae 1	10 mg/l (Laminariales; Photosynthesis)
Threshold limit algae 2	26 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

BRAKE PARTS CLEANER (HEXANE)	
Persistence and degradability	Readily biodegradable in water. Photooxidation in water. Biodegradable in the soil.
ThOD	3.52 g O ₂ /g substance
BOD (% of ThOD)	0.63 % ThOD

12.3. Bioaccumulative potential

BRAKE PARTS CLEANER (HEXANE)	
BCF fish 1	501.187 (Pimephales promelas)
Log Pow	3.5 - 3.94 (Calculated)
Bioaccumulative potential	Bioaccumable.

12.4. Mobility in soil

BRAKE PARTS CLEANER (HEXANE)	
Surface tension	0.018 N/m

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Incinerate under surveillance with energy recovery. Do not discharge into surface water. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.
Additional information	: LWCA (the Netherlands): KGA category 03. Hazardous waste according to Directive 2008/98/EC. Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT	
Transport document description	: UN1208 Hexanes, 3, II
UN-No.(DOT)	: UN1208
Proper Shipping Name (DOT)	: Hexanes
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



Packing group (DOT)	: II - Medium Danger
Dangerous for the environment	: Yes

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 1208, 3, II, (D/E)

Packing group (ADR) : II

Class (ADR) : 3 - Flammable liquid


Hazard identification number (Kemler No.) : 33

Classification code (ADR) : F1

Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code (ADR) : D/E

Transport by sea

UN-No. (IMDG) : 1208

Proper Shipping Name (IMDG) : HEXANES

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

EmS-No. (1) : F-E

EmS-No. (2) : S-D

Air transport

UN-No. (IATA) : 1208

Proper Shipping Name (IATA) : Hexanes

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

BRAKE PARTS CLEANER (HEXANE)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
--------------------------------------------------------------	---------

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Repr. 2 H361f
Asp. Tox. 1 H304
STOT RE 2 H373
Skin Irrit. 2 H315
STOT SE 3 H336
Aquatic Chronic 2 H411
Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11
Repr.Cat.3; R62
Xn; R65
Xn; R48/20
Xi; R38
R67
N; R51/53

Full text of R-phrases: see section 16

National regulations

No additional information available

15.3. US State regulations

BRAKE PARTS CLEANER (HEXANE)(I)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
----------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 16: Other information

Full text of H-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

BRAKE PARTS CLEANER (HEXANE)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product