

SAFETY DATA SHEET

Product Trade Name: BaraBlend™-665

Revision Date: 23-Apr-2015

Revision Number: 9

1. Identification

1.1. Product Identifier

Product Trade Name: BaraBlend™-665
Synonyms: None
Chemical Family: Mineral
Internal ID Code: HM007835

1.2 Recommended use and restrictions on use

Application: Loss Circulation Material
Uses Advised Against: No information available

1.3 Manufacturer's Name and Contact Details

Manufacturer/Supplier

Baroid Fluid Services
Product Service Line of Halliburton
P.O. Box 1675
Houston, TX 77251
Telephone: (281) 871-4000
Emergency Telephone: 1-866-519-4752 (US, Canada, Mexico) or 1-760-476-3962

Halliburton Energy Services
645 - 7th Ave SW Suite 2200
Calgary, AB
T2P 4G8
Canada

Prepared By: Chemical Stewardship
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

1.4. Emergency telephone number

Emergency Telephone Number: (281) 575-5000

2. Hazard(s) Identification

2.1 Classification in accordance with paragraph (d) of §1910.1200

Skin Corrosion / Irritation	Category 2 - H315
Serious Eye Damage / Eye Irritation	Category 1 - H318
Carcinogenicity	Category 1A - H350
Specific Target Organ Toxicity - (Single Exposure)	Category 3 - H335

2.2. Label Elements

Hazard Pictograms



Signal Word

Danger

Hazard Statements

H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H335 - May cause respiratory irritation
 H350 - May cause cancer by inhalation

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
 P264 - Wash face, hands and any exposed skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective gloves/eye protection/face protection

Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
 P332 + P313 - If skin irritation occurs: Get medical advice/attention
 P362 - Take off contaminated clothing and wash before reuse
 P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing
 P312 - Call a POISON CENTER/doctor/physician if you feel unwell
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a POISON CENTER or doctor/physician
 P308 + P313 - IF exposed or concerned: Get medical advice/attention

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
 P405 - Store locked up

Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

Contains

Substances

Calcium oxide
 Calcium carbonate
 Crystalline silica, quartz

CAS Number

1305-78-8
 471-34-1
 14808-60-7

2.3 Hazards not otherwise classified

None known

3. Composition/information on Ingredients

Substances	CAS Number	PERCENT (w/w)	GHS Classification - US
Calcium oxide	1305-78-8	30 - 60%	Skin Irrit. 2 (H315) Eye Corr. 1 (H318) STOT SE 3 (H335)
Calcium carbonate	471-34-1	10 - 30%	Not classified

Crystalline silica, quartz	14808-60-7	0.1 - 1%	Carc. 1A (H350) STOT RE 1 (H372)
----------------------------	------------	----------	-------------------------------------

The exact percentage (concentration) of the composition has been withheld as proprietary.

4. First-Aid Measures

4.1. Description of first aid measures

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Skin Wash with soap and water. Get medical attention if irritation persists.

Ingestion Under normal conditions, first aid procedures are not required.

4.2 Most important symptoms/effects, acute and delayed

Causes severe eye irritation which may damage tissue. Causes skin irritation. May cause respiratory irritation. Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

All standard fire fighting media

Extinguishing media which must not be used for safety reasons

None known.

5.2 Specific hazards arising from the substance or mixture

Special Exposure Hazards

Not applicable.

5.3 Special protective equipment and precautions for fire-fighters

Special Protective Equipment for Fire-Fighters

Not applicable.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use appropriate protective equipment. Avoid creating and breathing dust.
See Section 8 for additional information

6.2. Environmental precautions

None known.

6.3. Methods and material for containment and cleaning up

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. Handling and storage

7.1. Precautions for Safe Handling

Handling Precautions

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Information

Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Do not reuse empty container. Product has a shelf life of 36 months.

8. Exposure Controls/Personal Protection

8.1 Occupational Exposure Limits

Substances	CAS Number	OSHA PEL-TWA	ACGIH TLV-TWA
Calcium oxide	1305-78-8	5 mg/m ³	TWA: 2 mg/m ³
Calcium carbonate	471-34-1	15 mg/m ³	10 mg/m ³
Crystalline silica, quartz	14808-60-7	TWA: 10 mg/m ³ %SiO ₂ + 2	TWA: 0.025 mg/m ³

8.2 Appropriate engineering controls

Engineering Controls

Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Personal Protective Equipment

If engineering controls and work practices cannot prevent excessive exposures, the selection and proper use of personal protective equipment should be determined by an industrial hygienist or other qualified professional based on the specific application of this product.

Respiratory Protection

If engineering controls and work practices cannot keep exposure below occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, AS/NZS 1715:2009, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or other qualified professional.

Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), AS/NZS 1715, or equivalent respirator when using this product.

Hand Protection

Chemical-resistant protective gloves (EN 374) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Nitrile gloves. (>= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced. Manufacturer's directions for use should be observed because of great diversity of types.

Skin Protection

Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.

Eye Protection

Wear safety glasses or goggles to protect against exposure.

Other Precautions

None known.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State: Granules	Color: White to gray to Red
Odor: Odorless	Odor No information available
	Threshold:

<u>Property</u>	<u>Values</u>
<u>Remarks/ - Method</u>	
pH:	No data available
Freezing Point/Range	No data available
Melting Point/Range	No data available
Boiling Point/Range	No data available
Flash Point	No data available
Flammability (solid, gas)	No data available
upper flammability limit	No data available
lower flammability limit	No data available
Evaporation rate	No data available
Vapor Pressure	No data available
Vapor Density	No data available
Specific Gravity	2.7
Water Solubility	Soluble in water
Solubility in other solvents	No data available
Partition coefficient: n-octanol/water	No data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity	No data available
Explosive Properties	No information available
Oxidizing Properties	No information available

9.2. Other information

VOC Content (%) No data available

10. Stability and Reactivity

10.1. Reactivity

Not expected to be reactive.

10.2. Chemical Stability

Stable

10.3. Possibility of Hazardous Reactions

Will Not Occur

10.4. Conditions to Avoid

None anticipated

10.5. Incompatible Materials

Strong acids. Prolonged contact with aluminum. Ammonium salts.

10.6. Hazardous Decomposition Products

Carbon monoxide and carbon dioxide. Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).

11. Toxicological Information

11.1 Information on likely routes of exposure

Principle Route of Exposure Eye or skin contact, inhalation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Acute Toxicity

Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact

Causes severe eye irritation. May cause eye burns.

Skin Contact

Causes skin irritation. May cause alkali burns with confined contact.

Ingestion

Irritation of the mouth, throat, and stomach.

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2). There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

11.3 Toxicity data

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Calcium oxide	1305-78-8	> 2000 mg/kg (Rat)	> 2500 mg/kg	No data available
Calcium carbonate	471-34-1	6450 mg/kg (Rat) > 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4h
Crystalline silica, quartz	14808-60-7	>15,000 mg/kg (Human)	No data available	No data available

Substances	CAS Number	Skin corrosion/irritation
Calcium oxide	1305-78-8	Extremely corrosive and destructive to tissue
Calcium carbonate	471-34-1	Non-irritating to the skin (Rabbit)
Crystalline silica, quartz	14808-60-7	Non-irritating to the skin

Substances	CAS Number	Eye damage/irritation
Calcium oxide	1305-78-8	Causes eye burns. (Rabbit)

Calcium carbonate	471-34-1	Non-irritating to the eye (Rabbit)
Crystalline silica, quartz	14808-60-7	Mechanical irritation of the eyes is possible.

Substances	CAS Number	Skin Sensitization
Calcium oxide	1305-78-8	Patch test on human volunteers did not demonstrate sensitization properties
Calcium carbonate	471-34-1	Did not cause sensitization on laboratory animals (mouse)
Crystalline silica, quartz	14808-60-7	No information available.

Substances	CAS Number	Respiratory Sensitization
Calcium oxide	1305-78-8	No information available
Calcium carbonate	471-34-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

Substances	CAS Number	Mutagenic Effects
Calcium oxide	1305-78-8	In vitro tests did not show mutagenic effects
Calcium carbonate	471-34-1	In vitro tests did not show mutagenic effects
Crystalline silica, quartz	14808-60-7	Not regarded as mutagenic.

Substances	CAS Number	Carcinogenic Effects
Calcium oxide	1305-78-8	Did not show carcinogenic effects in animal experiments (similar substances)
Calcium carbonate	471-34-1	No information available.
Crystalline silica, quartz	14808-60-7	Contains crystalline silica which may cause silicosis, a delayed and progressive lung disease. The IARC and NTP have determined there is sufficient evidence in humans of the carcinogenicity of crystalline silica with repeated respiratory exposure. Based on available scientific evidence, this substance is a threshold carcinogen with a mode of action involving indirect genotoxicity secondary to lung injury.

Substances	CAS Number	Reproductive toxicity
Calcium oxide	1305-78-8	Animal testing did not show any effects on fertility. Did not show teratogenic effects in animal experiments.
Calcium carbonate	471-34-1	Animal testing did not show any effects on fertility. Did not show teratogenic effects in animal experiments.
Crystalline silica, quartz	14808-60-7	No information available

Substances	CAS Number	STOT - single exposure
Calcium oxide	1305-78-8	May cause respiratory irritation.
Calcium carbonate	471-34-1	No significant toxicity observed in animal studies at concentration requiring classification.
Crystalline silica, quartz	14808-60-7	No significant toxicity observed in animal studies at concentration requiring classification.

Substances	CAS Number	STOT - repeated exposure
Calcium oxide	1305-78-8	None under normal use conditions
Calcium carbonate	471-34-1	No significant toxicity observed in animal studies at concentration requiring classification.
Crystalline silica, quartz	14808-60-7	Causes damage to organs through prolonged or repeated exposure if inhaled: (Lungs)

Substances	CAS Number	Aspiration hazard
Calcium oxide	1305-78-8	Not applicable
Calcium carbonate	471-34-1	Not applicable
Crystalline silica, quartz	14808-60-7	Not applicable

12. Ecological Information

12.1. Toxicity

Ecotoxicity Effects

Product Ecotoxicity Data

No data available

Substance Ecotoxicity Data

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Calcium oxide	1305-78-8	EC50 (72h) 184.57 mg/L (Pseudokirchnerella)	LC50 33.884 mg/L (Clarias gariepinus)	EC50 (3h) 300.4 mg/L (activated sludge) (similar)	EC50 (48h) 49.1 mg/L (Daphnia magna) (similar)

		subcapitata) (similar substance)	LC50 (96h) 1070 mg/L (Cyprinus carpio) NOEC (46d) 100 mg/L (Tilapia nilotica)	substances)	substance) LC50 (96h) 158 mg/L (Crangon septemspinosa) (similar substance) NOEC (14d) 32 mg/L (Crangon septemspinosa) (similar substance) LC50 (14d) 53.1 mg/L (Crangon septemspinosa) (similar substance)
Calcium carbonate	471-34-1	EC50(72h): > 14 mg/L (growth rate) (Desmodemus subspicatus)	LC50(96h): > 100 mg/L (saturated solution) (Oncorhynchus mykiss)	EC50(3h): > 1000 mg/L (Activated sludge)	EC50(48h): > 100 mg/L (saturated solution) (Daphnia magna)
Crystalline silica, quartz	14808-60-7	No information available	LL0 (96h) 10,000 mg/L (Danio rerio) (similar substance)	No information available	LL50 (24h) > 10,000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

Substances	CAS Number	Persistence and Degradability
Calcium oxide	1305-78-8	The methods for determining biodegradability are not applicable to inorganic substances.
Calcium carbonate	471-34-1	The methods for determining biodegradability are not applicable to inorganic substances.
Crystalline silica, quartz	14808-60-7	The methods for determining biodegradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

Does not bioaccumulate

Substances	CAS Number	Log Pow
Calcium oxide	1305-78-8	Log Kow = -0.571 BCF = 0.5
Calcium carbonate	471-34-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

Substances	CAS Number	Mobility
Calcium oxide	1305-78-8	No information available
Calcium carbonate	471-34-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1. Waste treatment methods

Disposal Method Bury in a licensed landfill according to federal, state, and local regulations.
Contaminated Packaging Follow all applicable national or local regulations.

14. Transport Information

US DOT

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable
Environmental Hazards: Not applicable

US DOT Bulk

DOT (Bulk) Not applicable

Canadian TDG

UN Number: Not restricted
 UN Proper Shipping Name: Not restricted
 Transport Hazard Class(es): Not applicable
 Packing Group: Not applicable
 Environmental Hazards: Not applicable

IMDG/IMO

UN Number: Not restricted
 UN Proper Shipping Name: Not restricted
 Transport Hazard Class(es): Not applicable
 Packing Group: Not applicable
 Environmental Hazards: Not applicable

IATA/ICAO

UN Number: UN1910
 UN Proper Shipping Name: Calcium oxide
 Transport Hazard Class(es): 8
 Packing Group: III
 Environmental Hazards: Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. Regulatory Information

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Substances	CAS Number	EPA SARA Title III Extremely Hazardous Substances
Calcium oxide	1305-78-8	Not applicable
Calcium carbonate	471-34-1	Not applicable
Crystalline silica, quartz	14808-60-7	Not applicable

EPA SARA (311,312) Hazard Class

Acute Health Hazard
 Chronic Health Hazard

EPA SARA (313) Chemicals

Substances	CAS Number	Toxic Release Inventory (TRI) - Group I	Toxic Release Inventory (TRI) - Group II
Calcium oxide	1305-78-8	Not applicable	Not applicable
Calcium carbonate	471-34-1	Not applicable	Not applicable
Crystalline silica, quartz	14808-60-7	Not applicable	Not applicable

EPA CERCLA/Superfund Reportable Spill Quantity

Substances	CAS Number	CERCLA RQ
Calcium oxide	1305-78-8	Not applicable
Calcium carbonate	471-34-1	Not applicable
Crystalline silica, quartz	14808-60-7	Not applicable

EPA RCRA Hazardous Waste Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.

California Proposition 65	The California Proposition 65 regulations apply to this product.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
NFPA Ratings:	Health 1, Flammability 0, Reactivity 0
HMIS Ratings:	Health 1*, Flammability 0, Reactivity 0 , PPE: E

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

16. Other information

Preparation Information

Prepared By Chemical Stewardship
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

Revision Date: 23-Apr-2015

Reason for Revision SDS sections updated:
SECTION:
2

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Stewardship at 1-580-251-4335.

Key or legend to abbreviations and acronyms

bw – body weight
CAS – Chemical Abstracts Service
EC50 – Effective Concentration 50%
ErC50 – Effective Concentration growth rate 50%
LC50 – Lethal Concentration 50%
LD50 – Lethal Dose 50%
LL50 – Lethal Loading 50%
mg/kg – milligram/kilogram
mg/L – milligram/liter
NIOSH – National Institute for Occupational Safety and Health
NTP – National Toxicology Program
OEL – Occupational Exposure Limit
PEL – Permissible Exposure Limit
ppm – parts per million
STEL – Short Term Exposure Limit
TWA – Time-Weighted Average
UN – United Nations
h - hour
mg/m³ - milligram/cubic meter
mm - millimeter

mmHg - millimeter mercury
w/w - weight/weight
d - day

Key literature references and sources for data

www.ChemADVISOR.com/

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Safety Data Sheet