

HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: BaraECD System - SARALINE 185V

Revision Date: 26-Sep-2014

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: BaraECD System - SARALINE 185V
Synonyms: None
Chemical Family: Blend
Application: Mud System

Manufacturer/Supplier: Baroid Fluid Services
Product Service Line of Halliburton
P.O. Box 1675
Houston, TX 77251
Telephone: (281) 871-4000
Emergency Telephone: (281) 575-5000

Prepared By: Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Distillates (Fischer-Tropsch), C8-26-branched and linear	848301-67-7	30 - 60%	Not applicable	Not applicable
Barium sulfate	7727-43-7	30 - 60%	TWA: 10 mg/m ³	15 mg/M3
Calcium chloride	10043-52-4	1 - 5%	Not applicable	Not applicable
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	1 - 5%	Not applicable	Not applicable
Crystalline silica, quartz	14808-60-7	0.1 - 1%	TWA: 0.025 mg/m ³	10 mg/m ³ %SiO ₂ + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

3. HAZARDS IDENTIFICATION

Hazard Overview

May cause allergic skin reaction. Aspiration into the lungs may cause chemical pneumonitis including coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal. Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, AS/NZS 1715, or equivalent respirator when using this product. Review the Safety Data Sheet (SDS) for this product, which has been provided to your employer.

4. FIRST AID MEASURES

Inhalation	If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.
Skin	Wash with soap and water. Get medical attention if irritation persists.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.
Ingestion	Get medical attention! If vomiting occurs, keep head lower than hips to prevent aspiration.
Notes to Physician	Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	> 354
Flash Point/Range (C):	> 85
Flash Point Method:	PMCC
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	210
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

Fire Extinguishing Media	Water fog, carbon dioxide, foam, dry chemical.
Special Exposure Hazards	Use water spray to cool fire exposed surfaces. Decomposition in fire may produce toxic gases.
Special Protective Equipment for Fire-Fighters	Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.
NFPA Ratings:	Health 1, Flammability 0, Reactivity 0
HMS Ratings:	Health 1*, Flammability 0, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures	Use appropriate protective equipment.
Environmental Precautionary Measures	None known.

Procedure for Cleaning / Absorption

Isolate spill and stop leak where safe. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet.

Storage Information Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Product has a shelf life of 36 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), AS/NZS 1715, or equivalent respirator when using this product.

Hand Protection Chemical-resistant protective gloves (EN 374) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Nitrile gloves. (>= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced. Manufacturer's directions for use should be observed because of great diversity of types.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Yellow to brown
Odor:	Mild
pH:	9-10
Specific Gravity @ 20 C (Water=1):	Not Determined
Density @ 20 C (lbs./gallon):	11.58
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined Min: > 212
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined

Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Insoluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	None anticipated
Incompatibility (Materials to Avoid)	Strong oxidizers.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure

Acute Toxicity

Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact

May cause eye irritation

Skin Contact

May cause mild skin irritation. May cause an allergic skin reaction.

Ingestion

Aspiration into the lungs may cause chemical pneumonitis including coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal.

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Prolonged or repeated application of a similar product to the skin of laboratory mice without washing between applications resulted in increased incidence of skin tumors. It is suspected that tumors may be due in part to severely irritated conditions from continuous contact with the product.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (Fischer-Tropsch), C8-26-branched and linear	848301-67-7	> 5000 mg/kg (Rat) (similar substance)	> 3160 mg/kg (Rabbit) (similar substance)	> 5266 mg/m ³ (Rat, 4h) (similar substance)
Barium sulfate	7727-43-7	> 307,000 mg/kg (Rat) > 2000mg/kg (Rat) (similar substance - barium dichloride)	> 2,000 mg/kg (Rabbit)	No data available
Calcium chloride	10043-52-4	> 1000 mg/kg (Rat) 2301 mg/kg (Rat)	2630 mg/kg (Rat) > 5000 mg/kg (Rabbit)	No data available
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	> 2020 mg/kg (Rat)	> 2000 mg/kg (Rat)	No data available
Crystalline silica, quartz	14808-60-7	> 5000 mg/kg (Rat)	No data available	No data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	TLM48: > 50000 mg/l (Acartia tonsa)
Acute Algae Toxicity:	Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
------------	------------	-------------------	------------------	----------------------------	---------------------------

Distillates (Fischer-Tropsch), C8-26-branched and linear	848301-67-7	EL50(72h): > 10000 mg/L (Skeletonema costatum) (similar substance)	LL50(96h): > 1028 mg/L (Scopththalmus maximus) (similar substance)	No information available	LL50(48h): > 3193 mg/L (Acartia tonsa) (similar substance)
Barium sulfate	7727-43-7	EC50(72h): (growth rate) > 61.1 mg/L (Pseudokirchnerella subcapitata) EC50(72h): > 34.31 mg/L (Pseudokirchnerella subcapitata) (elemental Barium)	TLM96: 7500 ppm (Oncorhynchus mykiss) LC50(96h): > 174 mg/L (Danio rerio) LC50(96h): > 97.5 mg/L (Danio rerio) (elemental Barium) LC50(28d): 42700 ug/L (Oncorhynchus mykiss) (elemental Barium)	EC50(3h): (respiration rate) >1000 mg/L (activated sludge)	TLM96: > 1,000,000 ppm (Mysidopsis bahia) LC50(48h): 14500 ug/L (Daphnia magna) (elemental Barium) EC16(3wk): 5800 ug/L (Daphnia magna) (elemental Barium) EC16(3wk): 4800 ug/L (Daphnia magna)
Calcium chloride	10043-52-4	EC50(72h): 2900 mg/L (Pseudokirchnerella subcapitata)	LC50(96h): 4630 mg/L (Pimephales promelas)	No information available	EC50(48h): 2400 mg/L (Daphnia magna) EC50(21d) 610 mg/L (reproduction) (Daphnia magna)
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	EC50(72h): > 100 mg/L (growth rate) (Pseudokirchnerella subcapitata)	LC50(96h): > 100 mg/L (Danio rerio)	EC50(3h): > 100 mg/L (respiration rate) (Activated sludge)	IC50(48h): > 100 mg/L (Daphnia magna)
Crystalline silica, quartz	14808-60-7	No information available	LL0(96h): 10000 mg/L (Danio rerio) (similar substance)	No information available	LL50(24h): > 10000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Distillates (Fischer-Tropsch), C8-26-branched and linear	848301-67-7	Readily biodegradable (74% @ 28d) (similar substances)
Barium sulfate	7727-43-7	The methods for determining biodegradability are not applicable to inorganic substances.
Calcium chloride	10043-52-4	The methods for determining biodegradability are not applicable to inorganic substances.
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Readily biodegradable (71% @ 28d)
Crystalline silica, quartz	14808-60-7	The methods for determining biodegradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Distillates (Fischer-Tropsch), C8-26-branched and linear	848301-67-7	No information available
Barium sulfate	7727-43-7	BCF: 1.2 - 74.4 L/kg (Lepomis macrochirus)
Calcium chloride	10043-52-4	No information available
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	2.4
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

Substances	PBT and vPvB assessment
Crystalline silica, quartz	Not PBT/vPvB

12.6. Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

US DOT

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

US DOT Bulk

DOT (Bulk) Not Applicable

Canadian TDG u10

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

IMDG/IMO

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

IATA/ICAO

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard

EPA SARA (313) Chemicals This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.
California Proposition 65	The California Proposition 65 regulations apply to this product.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	Product contains one or more components not listed on the inventory.
WHMIS Hazard Class	D2B Toxic Materials D2A Very Toxic Materials Crystalline silica

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****