

SAFETY DATA SHEET.

Issuing date 02-Aug-2016 Revision Date 05-May-2021 Version 2.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name BATTERY CLEANER

Recommended use of the chemical

and restrictions on use

Product code 80-473

Product Type Non-flammable aerosol

Synonyms None

Supplier's details

Recommended Use Battery Cleaner.

Uses advised against No information available

Manufactured For: Kimball Midwest 4800 Roberts Rd. Columbus, OH 43228 800-233-1294

Emergency telephone number

Chemical Emergency Phone CHEMTREC: 1-800-424-9300

Number

Company Emergency Phone 800-233-1294

Number

2. HAZARDS IDENTIFICATION

Classification

Acute Toxicity - Oral	Category 4
Acute Toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

Warning

Hazard Statements

Harmful if swallowed

Harmful in contact with skin

Harmful if inhaled

Causes skin irritation.

Causes serious eye irritation.

Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Mild

Precautionary Statements - Prevention

Wash hands thoroughly after handling

Wear protective gloves, protective clothing, eye protection, face protection.

Do not eat, drink or smoke when using this product.

Avoid breathing fumes, gas, mist, vapors, spray.

Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

Specific treatment (see first aid on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice, attention

IF ON SKIN: Wash with plenty of soap and water.

Call a POISON CENTER or doctor, physician if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get Medical advice, attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor, physician if you feel unwell.

If SWALLOWED :Call a POISON CENTER or doctor, physician if you feel unwell.

Rinse mouth

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0.02099322% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
SODIUM BICARBONATE	144-55-8	1-10
TRIETHANOLAMINE	102-71-6	1-10
DIETHANOLAMINE	111-42-2	<0.1
ETHYLENE OXIDE	75-21-8	<0.1
1,4-DIOXANE	123-91-1	<0.1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove

any contact lenses and continue flushing. Seek immediate medical attention, advice.

Skin contact Wash off with soap and plenty of water. Remove and wash contaminated clothing before

re-use. Rinse immediately with plenty of water for 15 minutes and seek medical advice if

skin irritation persists.

Inhalation Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped,

contact emergency medical services immediately.

Ingestion Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to

unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Harmful if swallowed, in contact with skin, or if inhaled. Causes skin and eye irritation. May

cause respiratory irritation.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Propellant is flammable. Container may burst in fire. .

Explosion Data

Sensitivity to Mechanical Impact No.
Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventiliation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do

not allow material to contaminate ground water system. Prevent product from entering

drains. Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate

ground water system. Prevent product from entering drains.

Methods for cleaning up

Use personal protective equipment. Dam up. Cover liquid spill with sand, earth, or other

noncombustible absorbent material. Take up mechanically and collect in suitable container

for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such

as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep containers tightly closed in a dry and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition .Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m ³	TWA: 1000 ppm
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	106-97-8:TWA: 800 ppm
		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m ³

		ppm (vacated) TWA: 1900 mg/m ³	75-28-5:TWA: 800 ppm TWA: 1900 mg/m³
TRIETHANOLAMINE 102-71-6	TWA: 5 mg/m ³	-	-
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
ETHYLENE GLYCOL 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m³	-
DIETHANOLAMINE 111-42-2	TWA: 1 mg/m³ inhalable fraction and vapor Skin - potential significant contribution to overall exposure by the cutaneous route	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m³	TWA: 3 ppm TWA: 15 mg/m³
1,4-DIOXANE 123-91-1	TWA: 20 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 100 ppm TWA: 360 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 90 mg/m³ (vacated) S* S*	IDLH: 500 ppm Ceiling: 1 ppm 30 min Ceiling: 3.6 mg/m³ 30 min
ETHYLENE OXIDE 75-21-8	TWA: 1 ppm	TWA: 1 ppm STEL: 5 ppm see 29 CFR 1910.1047	IDLH: 800 ppm Ceiling: 5 ppm 10 min/day Ceiling: 9 mg/m³ 10 min/day TWA: 0.1 ppm less than stated value TWA: 0.18 mg/m³ less than stated value

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Exposure controls

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol Appearance Clear

AppearanceClearOdorMild

Color Amber Odor Threshold

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

pH 8.95

Melting/freezing point No information available

Boiling point/boiling range

Flash Point -91 °C / -132 °F Based on propellant

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limits in Air upper flammability limit lower flammability limit

Vapor pressure Vapor density

Specific Gravity 0.972

Water solubility Practically insoluble

Partition coefficient: n-octanol/water

Autoignition temperature No information available

Decomposition temperature

Viscosity No information available

Explosive properties

Other information

VOC Content(%) 16.96

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides, Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory

system.

Eye contact Irritating to eyes.

Skin contact Harmful if in contact with skin.

Ingestion Harmful and may be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
SODIUM BICARBONATE 144-55-8	= 4220 mg/kg (Rat)	-	-
TRIETHANOLAMINE 102-71-6	= 4190 mg/kg (Rat)	> 20000 mg/kg (Rabbit)	-
DIETHANOLAMINE 111-42-2	= 780 mg/kg (Rat)	= 11.9 mL/kg (Rabbit)	-
ETHYLENE OXIDE 75-21-8	= 72 mg/kg(Rat)	-	= 800 ppm (Rat) 4 h
1,4-DIOXANE 123-91-1	= 5170 mg/kg (Rat)	= 7600 mg/kg (Rabbit)	= 46 mg/L (Rat) 2 h

Information on toxicological effects

Symptoms Harmful if swallowed, in contact with skin, or inhaled.. Causes eye and skin irritation. May

cause respiratory irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation. Eye damage/irritation Irritating to eyes.

Irritation Causes skin and eye irritation. May cause respiratory irritation.

Sensitization No information available.

Germ cell mutagenicity There are no known mutagenic chemicals in this product.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Ethanolamine, Ethylene Oxide, 1,4-Dioxane are all in the product at <0.1 % reportable

levels.

Chemical Name	ACGIH	IARC	NTP	OSHA
TRIETHANOLAMINE 102-71-6	-	3	-	-
DIETHANOLAMINE 111-42-2	-	Group 2B	-	-
ETHYLENE OXIDE 75-21-8	A2	Group 1	Known	X
1,4-DIOXANE 123-91-1	A3	Group 2B	Reasonably Anticipated	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2B - Possibly Carcinogenic to Humans

Group 1 - Carcinogenic to Humans NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

This product does not contain a chemical(s) which is a known or suspected reproductive

hazard.

Specific target organ systemic toxicity (single exposure)

Specific target organ systemic toxicity (repeated exposure)

Chronic toxicity

No information available.

No information available.

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest. No information available.

Aspiration hazard No information available

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.02099322% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 24732 mg/kg

 ATEmix (dermal)
 74195 mg/kg

ATEmix (inhalation-dust/mist) 123.9 mg/l ATEmix (inhalation-vapor) 1282 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates
SODIUM BICARBONATE	-	8250 - 9000 mg/L LC50	-	2350 mg/L EC50 Daphnia
144-55-8		Lepomis macrochirus 96h		magna 48h
		static		
TRIETHANOLAMINE	169 mg/L EC50	10600 - 13000 mg/L LC50	-	-
102-71-6	Desmodesmus subspicatus	Pimephales promelas 96h		
	96h 216 mg/L EC50	flow-through 450 - 1000		
	Desmodesmus subspicatus	mg/L LC50 Lepomis		
	72h	macrochirus 96h static 1000		
		mg/L LC50 Pimephales		
		promelas 96h static		
DIETHANOLAMINE	2.1 - 2.3 mg/L EC50	1200 - 1580 mg/L LC50	-	55 mg/L EC50 Daphnia
111-42-2	Pseudokirchneriella	Pimephales promelas 96h		magna 48h
	subcapitata 96h 7.8 mg/L	static 4460 - 4980 mg/L		_
	EC50 Desmodesmus	LC50 Pimephales promelas		
	subspicatus 72h	96h flow-through 600 - 1000		
		mg/L LC50 Lepomis		
		macrochirus 96h static		
ETHYLENE OXIDE	-	73 - 96 mg/L LC50	-	137 - 300 mg/L LC50
75-21-8		Pimephales promelas 96h		Daphnia magna 48h
1,4-DIOXANE	-	10306 - 14742 mg/L LC50	=	163 mg/L EC50 water flea
123-91-1		Pimephales promelas 96h		48h Static
		static 9850 mg/L LC50		
		Pimephales promelas 96h		
		9850 mg/L LC50		
		Pimephales promelas 96h		
		flow-through 10000 mg/L		
		LC50 Lepomis macrochirus		
		96h semi-static 10000 mg/L		
		LC50 Lepomis macrochirus		
		96h static		

Persistence and degradability

.

Bioaccumulation

.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	
TRIETHANOLAMINE	-2.53
102-71-6	
DIETHANOLAMINE	-2.18
111-42-2	
ETHYLENE OXIDE	-0.3
75-21-8	
1,4-DIOXANE	-0.42
123-91-1	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in

accordance with federal, state, and local regulations. Dispose of in accordance with local

regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground LIMITED QUANTITY

IATA UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, LTD. QTY

IMDG UN1950, AEROSOLS, 2.2,LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Not listed	X	Х	Х	Х
SODIUM BICARBONATE	Х	Х	Х	Х	Х	Х	Х	Х
TRIETHANOLAMINE	Х	X	Х	Х	X	Х	Х	Х
DIETHANOLAMINE	Х	X	Х	X	X	Х	Х	Х
ETHYLENE OXIDE	Х	X	Х	Х	Х	Х	Х	Х
1,4-DIOXANE	Х	Х	Х	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical which is subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS-No	CAS-No Weight %*	
			Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	0.830403	1.0
ETHYLENE GLYCOL - 107-21-1	107-21-1	0.008387909	1.0
DIETHANOLAMINE - 111-42-2	111-42-2	<0.1	1.0
1,4-DIOXANE - 123-91-1	123-91-1	<0.1	0.1
ETHYLENE OXIDE - 75-21-8	75-21-8	<0.1	0.1

SARA 311/312 Hazard Categories

·

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
		RQs	
DIETHANOLAMINE	100 lb		RQ 100 lb final RQ
111-42-2			RQ 45.4 kg final RQ
ETHYLENE OXIDE	10 lb	10 lb	RQ 10 lb final RQ
75-21-8			RQ 4.54 kg final RQ
1,4-DIOXANE	100 lb		RQ 100 lb final RQ
123-91-1			RQ 45.4 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethylene Glycol CAS # 107-21-1) is considered a Proposition 65 chemical for developmental only when ingested. The purpose of this product is not for ingestion. NO warning for Ethylene Glycol is required for this product.



Chemical Name	California Prop. 65		
ETHYLENE GLYCOL - 107-21-1	Developmental (ingested)/<0.1%		
DIETHANOLAMINE - 111-42-2	Cancer / <0.1%		
1,4-DIOXANE - 123-91-1	Cancer < 0.1%		
ETHYLENE OXIDE - 75-21-8	Carcinogen		
	Developmental		
	Female Reproductive		
	Male Reproductive		
	<0.1%		

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
DEIONIZED WATER			X
7732-18-5			
TRIETHANOLAMINE	X	X	X
102-71-6			
2-BUTOXYETHANOL	X	X	X
111-76-2			
ETHYLENE GLYCOL	X	X	X
107-21-1			
DIETHANOLAMINE	X	X	X
111-42-2			
1,4-DIOXANE	X	X	X
123-91-1			
ETHYLENE OXIDE	X	X	X

75-21-8		

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 2 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2 Flammability 2 Physical Hazard 1 Personal protection B

Prepared By Regulatory Affairs Issuing date 02-Aug-2016 Revision Date 05-May-2021

Revision Note

(M)SDS sections updated 2 3 11 15

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet