

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BREAK-FREE PCL NC AEROSOL		DATE: October 12, 2011
PRODUCT NUMBER: 1010037 (PCLA-12-12)		
TRADE NAME: BREAK-FREE PCL NC, Aerosol		
GENERAL USE: Preservative, cleaner, lubricant		
CHEMICAL FAMILY: Solvent Blend.		
PRODUCT DESCRIPTION: Light amber colored liquid - aerosol.		
MANUFACTURER: Safariland LLC	DATE PREPARED: October 12, 2011	SUPERSEDES: July 16, 2008
ADDRESS (NUMBER, STREET, P.O. BOX) 13386 International Parkway		TELEPHONE NUMBER FOR INFORMATION / Customer Service 800-347-1200
(CITY, STATE AND ZIP CODE) Jacksonville, FL. 32218	COUNTRY USA	CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER  1-800-255-3924 01-813-248-0585 North America Toll Free International

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
 Note: All components are in full compliance with the Toxic Substances Control Act (TSCA) Inventory Regulations. All SARA Title III requirements have been complied with.

POTENTIAL HEALTH EFFECTS

INHALATION:
 Respiratory irritation and discomfort may be experienced if mists of materials resembling mineral oils are breathed at air concentrations exceeding recommended exposure levels. Excessive inhalation can cause respiratory irritation, central nervous system effects including dizziness, weakness, fatigue, nausea, headaches and possible unconsciousness.

SKIN:
 Possible slight to moderate redness may occur with extended daily exposure. Not classified as a primary skin irritant or corrosive.

EYES:
 Possible transient irritation. Not classified as a primary irritant.

INGESTION:
 Single dose oral toxicity is considered very low. Small amounts swallowed incidental to handling operations are not likely to cause injury. Swallowing large amount may cause injury and if aspirated (liquid enters the lung) may be rapidly absorbed through the lungs and result in injury to other body systems.

CARCINOGENICITY:
 NTP? **No** IARC MONOGRAPHS? **No** OSHA REGULATED? **No**
 CALIFORNIA, Prop.65? **No**

SECTION 3 - HAZARDOUS INGREDIENTS

Hazardous Components	% (by Weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)
Polyalphaolefin Synthetis Oil	40-60	68037-01-4	500-183-1	None	None
Synthetic Rust Inhibitors & lubrication additives	15-25	Not Reported	Not Reported	NA	NA
2-Ethylhexyl acetate	10-20	103-09-3	203-079-1	None	None
Dibasic Ester #1	3-8	Not Reported	Not Reported	None	None
Petroleum Distillates, Hydrotreated	1-5	64742-48-9	265-150-3	T+	R45
Carbon Dioxide Propellant	1-5	124-38-9	204-696-9	None	None

Notes: All SARA Title III materials have been reported. All ingredients contained in this formula are listed on the Toxic Substances Control Act (TSCA) chemical inventory.

SECTION 4 - FIRST AID MEASURES

INHALATION:
 If inhaled, move to fresh air. Anesthetic or narcotic effects could occur from overexposure to vapors, so call a physician; if available, give oxygen. If breathing stops, give mouth-to-mouth resuscitation. Follow good industrial hygiene practices.

EYES:
 Flush for at least 15 minutes with potable water, contact a physician if irritation persists.

SKIN:
 Wash with plenty of soap and water.

INGESTION:
 If swallowed, do not induce vomiting. If conscious, drink large quantities of water and seek immediate medical attention.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	BREAK-FREE PCL NC AEROSOL	DATE:	October 12, 2011
PRODUCT NUMBER:	1010037 (PCLA-12-12)		

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:

Flash Point: 94°C (201°F) PMCC

EXTINGUISHING MEDIA:

Carbon Dioxide, Dry Chemical, Foam.

FIRE FIGHTING PROCEDURES:

Firefighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus to avoid exposure from decomposition products. Proper eye and skin protection should be used. If a spill has not ignited, use water spray to disperse vapors and keep container cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

After ignition, the use of water can scatter the liquid thereby possibly spreading the fire. Ignition may also produce dense black smoke.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon Monoxide, Carbon Dioxide.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

For small spills, vacuum into waste containers or absorb with dry sand or absorbent cloth. For large spills immediately evacuate the area and shut off potential ignition sources. Only personnel equipped with proper respiratory and skin/eye protection should be permitted in the area. Dike the area to contain the spill. Take precautions as necessary to prevent contamination of ground or surface waters. Recover with a wet vacuum or absorb spilled material in sawdust or vermiculite and sweep into closed containers for disposal. After all visible traces have been removed, thoroughly wet vacuum area again. DO NOT FLUSH INTO SEWER.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from open flame or other ignition sources. Do not store above 120°F. Maintain adequate ventilation and keep from children. Note that some vapors are heavier than air and can displace air in low areas or confined spaces such as pits or tanks. Do not enter those areas where large quantities of vapors are suspected of collecting until exchanging the air or using special breathing apparatus with an observer present for possible assistance.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH		OSHA	
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TLV/TWA ppm	TWA mg/m3	TWA ppm	PEL mg/m3
Polyalphaolefin Synthetis Oil	NA	5	NA	NA	5	NA	NA	NA
Synthetic Rust Inhibitors & lubrication additives	NA	5	NA	NA	5	NA	NA	NA
2-Ethylhexyl acetate	NA	NA	NA	NA	NA	NA	NA	NA
Dibasic Ester #1	NA	NA	NA	NA	NA	NA	NA	NA
Petroleum Distillates, Hydrotreated	NA	5	NA	NA	5	NA	NA	NA
Carbon Dioxide Propellant	5000	NE	10000	NE	5000	NE	5000	NE

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Not required for normal work situations where adequate ventilation is provided. Use NIOSH European EN-149 approved self contained, positive pressure respirators for emergencies and in situations where air may be displaced by vapors. Follow OSHA Std. 29CFR 1910.134.

PROTECTIVE GLOVES:

Use gloves and full protective clothing if there is prolonged or repeated contact of liquid with skin. Solvex gloves recommended.

EYE PROTECTION:

For normal conditions wear safety glasses. Where there is reasonable probability of liquid contact, wear splash proof goggles. Contact lenses should not be worn under such conditions. If vapor exposure causes eye discomfort, use a full-face respirator.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Safety shower and eye-wash fountain in manufacturing areas. Personal protective clothing and use of equipment must be in accordance with 29CFR 1910.132 and 29CFR 1910.133.

WORK / HYGIENIC PRACTICES:

Do not smoke, eat or drink while using the product. Wash hands with soap and water before smoking, eating, drinking or using toilet facilities. Launder contaminated clothing before re-use.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: BREAK-FREE PCL NC AEROSOL
PRODUCT NUMBER: 1010037 (PCLA-12-12) **DATE:** October 12, 2011

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Light amber colored liquid with a mild odor.	VAPOR PRESSURE NA
pH NA	SPECIFIC GRAVITY (WATER = 1) 0.88
BOILING POINT / BOILING RANGE 190.5°C (375°F) Initial	SOLUBILITY IN WATER Nil
FLASH POINT 94°C (201°F) PMCC	VISCOSITY NA
FLAMMABLE LIMITS LEL: NE UEL: NE	VAPOR DENSITY (AIR = 1) NA
AUTO-IGNITION TEMPERATURE NE	EVAPORATION RATE >1 (Ether = 1) VOC- 21% 25.6% Volatile by weight

SECTION 10 - STABILITY AND REACTIVITY

STABILITY STABLE X	CONDITIONS TO AVOID: Sources of ignition such as sparks, hot spots, welding, flames, and cigarettes.
INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon Monoxide, carbon dioxide.	
HAZARDOUS POLYMERIZATION: Will not occur.	CONDITIONS TO AVOID: None related to polymerization.

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Polyalphaolefin Synthetis Oil	68037-01-4 500-183-1	>5000 mg/kg (ORAL, RAT)	NR
Synthetic Rust Inhibitors & Lubrication additives	Not Reported Not Reported	NR	NR
2-Ethylhexyl acetate	103-09-3 203-079-1	3200 mg/kg (ORAL, RAT)	NR
Dibasic Ester #1	Not Reported Not Reported	NR	NR
Synthetic Isoparaffinic Hydrocarbon	64742-48-9	>5000 mg/kg (ORAL, RAT)	NR
	265-150-3		
Carbon Dioxide Propellant	124-38-9	>5000 mg/kg (ORAL, RAT)	NR
	204-696-9		

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product, however it is known that organic compounds can be persistent pollutants. Do not release product in waterways or sewer systems.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:
 Recovered liquids may be reprocessed, or incinerated, or treated in a permitted hazardous waste management facility. Care must be taken when using or disposing of chemical materials and/or their containers to prevent environmental contamination. Dispose of chemical materials and/or their containers in accordance with the Clean Air Act, the Clean Water Act, the Resource Conservation and Recovery Act, as well as any other Federal, State, or local laws and regulations regarding disposal.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosol, Non-Flammable	
DOT HAZARD CLASS / Pack Group: 2.2	IATA HAZARD CLASS / Pack Group: 2.2
REFERENCE: 49CFR	IMDG HAZARD CLASS: 2.2
UN / NA IDENTIFICATION NUMBER: UN1950	RID/ADR Dangerous Goods Code: 2.2
LABEL: Non-Flammable	TDG Class / Pack Group: 2.2
HAZARD SYMBOLS:	Hazard Identification Number (HIN): 20



Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	BREAK-FREE PCL NC AEROSOL	DATE:	October 12, 2011
PRODUCT NUMBER:	1010037 (PCLA-12-12)		

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act): **All components are listed.**

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):

Acute Health: Yes	Chronic Health: Yes
Fire: Yes	Sudden Release of Pressure: Yes
Reactive: No	

313 REPORTABLE INGREDIENTS: **None**

CERCLA (USA - Comprehensive Response Compensation and Liability Act): **No**

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: **No**

CPR (Canadian Controlled Products Regulations): **Referenced.**

IDL (Canadian Ingredient Disclosure List): **Listed.**

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): **Listed on DSL.**

EINECS (European Inventory of Existing Commercial Chemical Substances): **Proprietary ingredients not referenced.**

WGK Water Quality Index: **2**

RISK PHRASES:	SYMBOL(S) REQUIRED FOR EU LABEL	SAFETY PHRASES:
R 45: May cause cancer.	 T+Toxic	S 45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S 53: Avoid exposure - obtain special instructions before use.

SECTION 16 - OTHER INFORMATION

Legend: NA = Not Available, NE = Not Established, ND = Not Determined, C = Carcinogen, NTP = National Toxicology Program

HMIS HAZARD RATINGS	HEALTH:	1	0 = INSIGNIFICANT
	FLAMMABILITY:	1	1 = SLIGHT
	PHYSICAL HAZARD:	0	2 = MODERATE
	PERSONAL PROTECTIVE EQUIPMENT:	C	3 = HIGH
			4 = EXTREME

REVISION SUMMARY:
 Revised to GHS/E.U. protocols 10/12/2011 supersedes 7/16/2008 issue.LB

MSDS Prepared by:
 ChemTel Inc.
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
 Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.