

1. Product and Company Identification

Product Code: C85
Product Name: Energized Circuit & Contact Cleaner
Company Name: CYCLO INDUSTRIES, INC.
902 SOUTH US HIGHWAY 1
JUPITER, FL 33477
Phone Number: (800)843-7813

Web site address: www.cyclo.com
Email address: ehs@cyclo.com

Emergency Contact: First Aid Emergency (800)752-7869
CHEMTREC (703) 527-3887 (800)424-9300

Information: First Aid Emergency (Outside U.S.) (312)906-6194

2. Hazards Identification

Serious Eye Damage/Eye Irritation, Category 2A

Carcinogenicity, Category 2

Toxic To Reproduction, Category 1B

Specific Target Organ Toxicity (single exposure), Category 3

Specific Target Organ Toxicity (repeated exposure), Category 2

Aquatic Toxicity (Chronic), Category 2



GHS Signal Word: Danger

GHS Hazard Phrases: H315: Causes skin irritation.
H319: Causes serious eye irritation.
H351: Suspected of causing cancer.
H360: May damage fertility or the unborn child.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure.
H411: Toxic to aquatic life with long lasting effects.
H280: Contents under pressure. May explode if heated.

GHS Precaution Phrases: P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P271: Use only outdoors or in a well-ventilated area.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P273: Avoid release to the environment.

GHS Response Phrases: P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P363: Wash contaminated clothing before reuse.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

GHS Storage and Disposal Phrases: P501: Dispose of contents/container in accordance with local/regional/national/international regulation.
P403+233: Store container tightly closed in well-ventilated place.



SAFETY DATA SHEET

Energized Circuit & Contact Cleaner

Page: 2

Revision: 07/08/2015
Supersedes Revision: 05/05/2014

Potential Health Effects (Acute and Chronic): No data available.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
127-18-4	Tetrachloroethylene	85.0 -100.0 %
124-38-9	Carbon dioxide	0.0 -15.0 %

4. First Aid Measures

Emergency and First Aid Procedures: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact, wash with soap and water for 15 minutes. Remove contaminated clothing and shoes and launder before reuse. Call physician immediately if adverse reaction occurs.

5. Fire Fighting Measures

Flammability Classification: NFPA Level 1 Aerosol
Flash Pt: NP Method Used: TAG Closed Cup
Explosive Limits: LEL: N.D. UEL: N.D.
Autoignition Pt: No data.
Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Use water spray to keep containers cool that are exposed to heat or flames.
Fire Fighting Instructions: Wear approved positive-pressure self-contained breathing apparatus and protective clothing. Avoid skin contact.
Flammable Properties and Hazards: No data available.
Hazardous Combustion Products: Hydrogen chloride, phosgene, chlorine.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Wear appropriate protective clothing and equipment to prevent skin and eye contact. Avoid breathing vapor. When airborne exposure limits are exceeded use NIOSH approved respiratory protection equipment; appropriate to the material and/or its components. Contain any liquid from leaking containers. Ventilate spill area. Soak up material with absorbent and place in chemical waste container. Leaking containers should be removed to an isolated, well-ventilated area and transferred to other suitable containers. Do not allow to enter sanitary drains, sewer or surface and subsurface waters. Keep out of lakes, ponds or streams.

7. Handling and Storage

Precautions To Be Taken in Handling: Caution: contents under pressure. Use only in a well ventilated area. Avoid breathing vapors. If exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Keep out of the reach of children.
Precautions To Be Taken in Storing: Do not puncture, incinerate or store above 120 degrees F. Exposure to high temperatures may cause bursting. Do not store in the passenger compartment of an automobile. Keep away from heat and open flame. This material or its vapors in contact with flames or hot glowing surfaces may form corrosive acid fumes.



SAFETY DATA SHEET

Energized Circuit & Contact Cleaner

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
127-18-4	Tetrachloroethylene	PEL: 100 ppm STEL: 300 ppm/(5min/3hr) CEIL: 200 ppm	TLV: 25 ppm STEL: 100 ppm	No data.
124-38-9	Carbon dioxide	PEL: 5000 ppm	TLV: 5000 ppm STEL: 30,000 ppm	No data.

Respiratory Equipment (Specify Type):	Do not breathe mist or vapor. Use in a well-ventilated area. Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure.
Eye Protection:	Chemical goggles; also wear a face shield if splashing hazard exists.
Protective Gloves:	Avoid skin contact. Wear protective clothing and gloves.
Other Protective Clothing:	Avoid skin contact. Wear protective clothing and gloves.
Engineering Controls (Ventilation etc.):	Use in a well-ventilated area. Local exhaust ventilation as necessary to maintain exposure to within applicable limits.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas <input checked="" type="checkbox"/> Liquid <input type="checkbox"/> Solid
Appearance and Odor:	Clear, colorless liquid. Faint sweet odor.
Melting Point:	No data.
Boiling Point:	250.00 F (121.1 C)
Flash Pt:	NP Method Used: TAG Closed Cup
Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or mm Hg):	~ 13mmHg@20C
Vapor Density (vs. Air = 1):	~ 4.1
Specific Gravity (Water = 1):	1.62@25/25C
Solubility in Water:	> 65%
Percent Volatile:	No data.
Autoignition Pt:	No data.

10. Stability and Reactivity

Stability:	Unstable <input type="checkbox"/> Stable <input checked="" type="checkbox"/>
Conditions To Avoid - Instability:	Do not expose to heat or store at temperatures above 120 degrees F. Avoid contact with open flame, electric arcs, or other hot surfaces that could cause thermal decomposition.
Incompatibility - Materials To Avoid:	Nitric acid. Sulfuric acid. Strong acids. Contact with oxidizing agents. Chlorine compounds. Chloroform. Alkalis. Potassium t-butoxide. Strong bases.
Hazardous Decomposition or Byproducts:	Carbon monoxide. The thermal decomposition products of this material are categorized as very toxic by the University of Pittsburgh toxicity of combustion products test method.
Possibility of Hazardous Reactions:	Will occur <input type="checkbox"/> Will not occur <input checked="" type="checkbox"/>
Conditions To Avoid - Hazardous Reactions:	No data available.



SAFETY DATA SHEET

Energized Circuit & Contact Cleaner

Revision: 07/08/2015
Supersedes Revision: 05/05/2014


CAS #	Hazardous Components (Chemical Name)
127-18-4	Tetrachloroethylene
124-38-9	Carbon dioxide

International Regulatory Lists
 Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes - 063-01
 Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA: Yes

16. Other Information

Revision Date: 07/08/2015

Hazard Rating System:



Additional Information About This Product: Not for sale in CA.

Company Policy or Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.