HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: CEMENT - CLASS G LAFARGE

03-Jan-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: Synonyms: Chemical Family: Application:	CEMENT - CLASS G LAFARGE None Cement Cement
Manufacturer/Supplier	Halliburton Energy Services P.O. Box 1431 Duncan, Oklahoma 73536-0431 Emergency Telephone: (281) 575-5000
Prepared By	Chemical Compliance Telephone: 1-580-251-4335 e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Portland cement	65997-15-1	60 - 100%	1 mg/m ³	15 mg/m ³
Crystalline silica, quartz	14808-60-7	<3	0.025 mg/m ³	<u>10 mg/m³</u> %SiO2 + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

3. HAZARDS IDENTIFICATION

Hazard Overview

Revision Date:

CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

4. FIRST AID MEASURES

Inhalation

If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult. CEMENT - CLASS G LAFARGE

CEMENT - CLASS G LAFARGE Page 1 of 7

Skin	Wash with soap and water. Get medical attention if irritation persists.
Eyes	In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.
Ingestion	Under normal conditions, first aid procedures are not required.
Notes to Physician	Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F): Flash Point/Range (C): Flash Point Method: Autoignition Temperature (F): Autoignition Temperature (C): Flammability Limits in Air - Lowe Flammability Limits in Air - Upper	· · ·	Not Determined Not Determined Not Determined Not Determined Not Determined Not Determined
Fire Extinguishing Media	None - does not burn.	
Special Exposure Hazards	Not applicable.	
Special Protective Equipment for Fire-Fighters	Not applicable.	
NFPA Ratings: HMIS Ratings:	Health 1, Flammability Health 1*, Flammabilit	

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary
MeasuresNone known.Procedure for Cleaning /
AbsorptionCollect using dustless method and hold for appropriate disposal. Consider possible
toxic or fire hazards associated with contaminating substances and use appropriate
methods for collection, storage and disposal.

7. HANDLING AND STORAGE

Handling PrecautionsAvoid contact with eyes, skin, or clothing. This product contains quartz, cristobalite,
and/or tridymite which may become airborne without a visible cloud. Avoid breathing
dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep
exposure below recommended exposure limits. Wear a NIOSH certified, European
Standard En 149, or equivalent respirator when using this product. Material is
slippery when wet.Storage InformationUse good housekeeping in storage and work areas to prevent accumulation of dust.
Close container when not in use. Product has a shelf life of 24 months. Store in a
cool, dry location.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits listed in Section 2.

CEMENT - CLASS G LAFARGE Page 2 of 7

Respiratory Protection	Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product.
Hand Protection	Normal work gloves.
Skin Protection	Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.
Eye Protection	Wear safety glasses or goggles to protect against exposure.
Other Precautions	Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Color: Odor: pH: Specific Gravity @ 20 C (Water=1): Density @ 20 C (Ibs./gallon): Bulk Density @ 20 C (Ibs/ft3): Boiling Point/Range (F): Boiling Point/Range (C): Freezing Point/Range (C): Freezing Point/Range (C): Vapor Pressure @ 20 C (mmHg): Vapor Density (Air=1): Percent Volatiles: Evaporation Rate (Butyl Acetate=1): Solubility in Water (g/100ml): Solubility in Solvents (g/100ml): VOCs (Ibs./gallon): Viscosity, Dynamic @ 20 C (centipoise): Viscosity, Kinematic @ 20 C (centistrokes):	Solid Gray Odorless 12.4 3.15 Not Determined 94 Not Determined Not Determined Not Determined Not Determined Not Determined 0 Not Determined 0.5 Not Determined Not Determined Not Determined Not Determined Not Determined Not Determined
Viscosity, Kinematic @ 20 C (centistrokes): Partition Coefficient/n-Octanol/Water: Molecular Weight (g/mole):	

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from any contact with water.
Incompatibility (Materials to Avoid)	Hydrofluoric acid.
Hazardous Decomposition Products	Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

CEMENT - CLASS G LAFARGE Page 3 of 7

Inhalation	Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A). Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).
Skin Contact	Can dry skin. May cause an allergic skin reaction. May cause alkali burns with confined contact.
Eye Contact	May cause severe eye irritation.
Ingestion	None known
Aggravated Medical Conditions	Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to quartz dust.
Chronic Effects/Carcinogenicity	 Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis. Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2). There is some evidence that breathing respirable crystalline silica or the disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.
Other Information	For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).
Toxicity Tests	
Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	Not determined
Primary Irritation Effect:	Not determined

CEMENT - CLASS G LAFARGE Page 4 of 7

Carcinogenicity	Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997).
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)	Not determined
Persistence/Degradability	Not applicable
Bio-accumulation	Not determined

Ecotoxicological Information

Acute Fish Toxicity: Acute Crustaceans Toxicity: Acute Algae Toxicity:	Not determined Not determined Not determined
Chemical Fate Information	Not determined
Other Information	Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method Bury in a licensed landfill according to federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT Not restricted

Canadian TDG Not restricted

ADR Not restricted

Air Transportation

ICAO/IATA Not restricted

Sea Transportation

IMDG Not restricted

Other Transportation Information

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.
EPA SARA Title III Extremely Hazardous Substances	Not applicable
EPA SARA (311,312) Hazard Class	Acute Health Hazard Chronic Health Hazard
EPA SARA (313) Chemicals	This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).
EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.
California Proposition 65	The California Proposition 65 regulations apply to this product.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	E Corrosive Material D2A Very Toxic Materials Crystalline silica

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS Not applicable

Additional Information	For additional information on the use of this product, contact your local Halliburton representative.
	For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.
Disclaimer Statement	This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

CEMENT - CLASS G LAFARGE Page 6 of 7

CEMENT - CLASS G LAFARGE Page 7 of 7

END OF MSDS