HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: CHARGE SDP, 4", 4SPF HMX, MILLENNIUM

Revision Date:

27-Mar-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: Synonyms: Chemical Family: Application:	CHARGE SDP, 4", 4SPF HMX, MILLENNIUM None Explosive Explosive Charge
Manufacturer/Supplier	Halliburton Energy Services P.O. Box 1431 Duncan, Oklahoma 73536-0431 Emergency Telephone: (281) 575-5000
Prepared By	Chemical Compliance Telephone: 1-580-251-4335 e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Cyclotetramethylenetetranitramin e (HMX)	2691-41-0	0-10	Not applicable	Not applicable
Lead	7439-92-1	NF	0.05 mg/m ³	0.05 mg/m ³
Copper	7440-50-8	NF	1 mg/m ³	1 mg/m ³
Tin	7440-31-5	NF	2 mg/m ³	2 mg/m ³
Antimony	7440-36-0	NF	0.5 mg/m ³	0.5 mg/m ³
Corrosion resistant steel	Mixture	NF	Not applicable	Not applicable
Desensitizing wax	Mixture	NF	Not applicable	Not applicable
Aluminum	7429-90-5	NF	1 mg/m ³	15 mg/m ³
Iron oxide	1309-37-1	NF	5 mg/m ³	10 mg/m ³

3. HAZARDS IDENTIFICATION

Hazard Overview

Explosive. May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed.

4. FIRST AID MEASURES	
Inhalation	If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.
Skin	Wash with soap and water. Get medical attention if irritation persists.
Eyes	In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.
Ingestion	Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F): Flash Point/Range (C): Flash Point Method: Autoignition Temperature (F): Autoignition Temperature (C): Flammability Limits in Air - Lowe Flammability Limits in Air - Uppe		
Fire Extinguishing Media	None. Do NOT fight fire. Isolate area and evacuate personnel to a safe area. Guard against intruders. Allow fire to burn itself out.	
Special Exposure Hazards	May detonate with impact or on heating. May explode and throw fragments 1 mile or more in fire. Evacuate all persons, including emergency responders.	
Special Protective Equipment for Fire-Fighters	Not applicable.	
NFPA Ratings: HMIS Ratings:	Health 1, Flammability 3, Reactivity 4 Health 1, Flammability 3, Reactivity 4	

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Use only competent persons for cleanup.

Environmental Precautionary Measures	Prevent from entering sewers, waterways, or low areas.
Procedure for Cleaning / Absorption	Isolate area and remove sources of friction, impact, heat, low level electrical current, and RF energy. Remove ignition sources and work with non-sparking tools.

7. HANDLING AND STORAGE

Handling Precautions	Do NOT consume food, drink, or tobacco in contaminated areas. Avoid contact with eyes, skin, or clothing. Wash hands after use. Launder contaminated clothing before reuse.
Storage Information	Store only in ATF approved magazines. Keep away from friction, impact, and heat.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- **Engineering Controls** Use in a well ventilated area.
- **Respiratory Protection** Dust/mist respirator. (N95, P2/P3)
- Hand Protection Cloth gloves.
- Skin Protection Cotton coveralls, undergarments, and socks. Conductive soled shoes.
- **Eye Protection** Wear safety glasses or goggles to protect against exposure.
- Other Precautions None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

9. PHYSICAL AND CHEMICAL PROPERTIES

	_
Color:	Metallic
Odor:	Odorless
pH:	Not Determined
Specific Gravity @ 20 C (Water=1):	Not Determined
Density @ 20 C (lbs./gallon):	Not Determined
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Insoluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	May detonate with friction, impact, heat, and low level electrical current.
Incompatibility (Materials to Avoid)	Strong acids. Strong alkalis.
Hazardous Decomposition Products	Shrapnel. Oxides of nitrogen. Metal oxides. Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation. Product does not present exposures health hazards during normal handling and use. However, this product is an explosive material and uncontrolled detonation may cause severe physical injury including death. All explosives are dangerous and must be handles carefully and used following approved safety procedures under the direction of competent, experience persons in accordance with all applicable regulations and ordinances.
Inhalation	May cause effects to the blood and blood system. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness. May cause damage to the nervous, urinary, and reproductive systems. Nitrogen oxides generated during use are irritating to the respiratory system.
Skin Contact	May be absorbed through the skin and contribute to the symptoms listed under ingestion. Nitrogen oxides generated during use are skin irritants.
Eye Contact	May cause eye irritation.
Ingestion	May cause abdominal pain, vomiting, nausea, and diarrhea.

CHARGE SDP, 4", 4SPF HMX, MILLENNIUM Page 3 of 6

Aggravated Medical Conditions	None known.
Chronic Effects/Carcinogenicity	Prolonged or repeated exposure may cause blood forming system, nervous, urinary tract and reproductive system damage. Prolonged or repeated exposure may cause embryo and fetus toxicity.
Other Information	None known.
Toxicity Tests	
Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	Not determined
Primary Irritation Effect:	Not determined
Carcinogenicity	Not determined
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)	Not determined	
Persistence/Degradability	Not applicable	
Bio-accumulation	Not determined	
Ecotoxicological Information		
Aguta Figh Taxiaitur	Not determined	

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity	:Not determined
Acute Algae Toxicity:	Not determined
Chemical Fate Information	Not determined
Other Information	Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
Contaminated Packaging	Do NOT reuse container. Store only in ATF approved magazines.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN0440,Charges, Shaped, 1.4D, II EX1996080028 NAERG 114 Canadian TDG Charges, Shaped, 1.4D, UN0440, II EX1996080028

ADR

UN0440, Charges, Shaped, 1.4D, II EX1996080028

Air Transportation

ICAO/IATA

UN0440,Charges, Shaped, 1.4D, II EX1996080028

Sea Transportation

IMDG

UN0440,Charges, Shaped, 1.4D, II EX1996080028 EmS F-B, S-X

Other Transportation Information

Labels:

Explosive 1.4D

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.	
EPA SARA Title III Extremely Hazardous Substances	Not applicable	
EPA SARA (311,312) Hazard Class	Acute Health Hazard Fire Hazard Sudden Release of Pressure Hazard	
EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Lead//7439-92-1 Copper//7440-50-8	
EPA CERCLA/Superfund Reportable Spill Quantity	EPA Reportable Spill Quantity is 400 Pounds based on Lead (CAS: 7439-92-1).	
	If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:	
	Reactivity D003	
California Proposition 65	The California Proposition 65 regulations apply to this product.	
CHARGE SDP, 4", 4SPF HMX, MILLENNIUM		

MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	F Dangerously Reactive Material

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS Not applicable

Additional InformationFor additional information on the use of this product, contact your local Halliburton
representative.For questions about the Material Safety Data Sheet for this or other Halliburton
products, contact Chemical Compliance at 1-580-251-4335.Disclaimer StatementThis information is furnished without warranty, expressed or implied, as to accuracy
or completeness. The information is obtained from various sources including the
manufacturer and other third party sources. The information may not be valid under
all conditions nor if this material is used in combination with other materials or in any
process. Final determination of suitability of any material is the sole responsibility of
the user.

END OF MSDS