SAFETY DATA SHEET

M47011 - ANSI - EN





CHLOROFORM (ALL GRADES)

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Identification: Occidental Chemical Corporation

5005 LBJ Freeway P.O. Box 809050 Dallas, TX 75380-9050 1-800-752-5151

24 Hour Emergency Telephone

Number:

1-800-733-3665 or 1-972-404-3228 (USA); CANUTEC (Canada): 1-613-996-6666; CHEMTREC (within USA and Canada): 1-800-424-9300; CHEMTREC (outside USA and Canada): +1 703-527-3887; CHEMTREC Contract No: CCN16186

To Request an SDS: MSDS@oxy.com or 1-972-404-3245

Customer Service: 1-800-752-5151 or 1-972-404-3700

Product Identifier: CHLOROFORM; CHLOROFORM TECHNICAL GRADE; CHLOROFORM

FLUOROCARBON GRADE; CHLOROFORM ALCOHOL STABILIZED GRADE

Trade Name: Chloroform: Chloroform Technical Grade: Chloroform Fluorocarbon Grade:

Chloroform Alcohol Stabilized Grade

Synonyms: METHYL TRICHLORIDE, FORMYL TRICHLORIDE, METHANE TRICHLORIDE,

METHENYL TRICHLORIDE, TRICHLOROFORM, TRICHLOROMETHANE

Product Use: Refrigerant, Dyes, Plastic and resin manufacturing

Uses Advised Against: None identified

Note: The Alcohol Stabilized Grade contains small amounts of ethanol as a

stabilizer. The Technical and Fluorocarbon Grades do not.

SDS No.: M47011

CHLOROFORM (ALL GRADES)

SDS Revision Date: 27-Jun-2016

SECTION 2. HAZARDS IDENTIFICATION

OSHA REGULATORY STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

EMERGENCY OVERVIEW:

Color: Colorless Appearance: Clear

Odor: Mildly sweet odor

Signal Word: DANGER

MAJOR HEALTH HAZARDS: TOXIC IF INHALED. MAY CAUSE DROWSINESS OR DIZZINESS. HARMFUL IF SWALLOWED. CAUSES SKIN IRRITATION. CAUSES EYE IRRITATION. SUSPECTED OF CAUSING CANCER. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. CAUSES DAMAGE TO RESPIRATORY SYSTEM, KIDNEY, LIVER, CENTRAL NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENTS: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapors, or spray. Use only outdoors or in a well-ventilated area. Use respiratory protection as required. Wear gloves, protective clothing, eye, and face protection. Wash skin and contaminated clothing thoroughly after handling. Do not eat, drink or smoke when using this product.

GHS CLASSIFICATION:

GHS: CONTACT HAZARD - SKIN:	Category 2 - Causes skin irritation
GHS: CONTACT HAZARD - EYE:	Category 2B - Causes eye irritation
GHS: ACUTE TOXICITY - INHALATION:	Category 3 - Toxic if inhaled
GHS: ACUTE TOXICITY - ORAL:	Category 4 - Harmful if swallowed
GHS: ACUTE TOXICITY - DERMAL:	No data available
	Not classified
GHS: TARGET ORGAN TOXICITY (SINGLE	Category 3 - May cause drowsiness or dizziness
EXPOSURE):	
GHS: TARGET ORGAN TOXICITY (REPEATED	Category 1 - Causes damage to Respiratory System,
EXPOSURE):	Kidney, Liver, Central Nervous System (CNS) through
	prolonged or repeated exposure
GHS: TARGET ORGAN TOXICITY (REPEATED	Category 2 - May cause damage to kidney and liver
EXPOSURE):	through prolonged or repeated exposure
GHS: CARCINOGENICITY:	Category 2 - Suspected of causing cancer
GHS: REPRODUCTION TOXIN:	Category 2 - Suspected of damaging fertility or the unborn
	child

2 of 15

SDS No.: M47011 SDS Revision Date: 27-Jun-2016

UNKNOWN ACUTE TOXICITY: Not applicable. This product was tested as a whole. This information only pertains to untested mixtures.

GHS SYMBOL: Health hazards, Skull and Crossbones, Exclamation mark







GHS SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

GHS - Health Hazard Statement(s)

- Toxic if inhaled
- · Harmful if swallowed
- Causes skin irritation
- Causes eye irritation
- May cause drowsiness or dizziness
- · Suspected of causing cancer
- · May damage fertility or the unborn child
- Causes damage to organs through prolonged or repeated exposure : (Respiratory System, Kidneys, Liver, Central Nervous System)

GHS - Precautionary Statement(s) - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Do not breathe dust, fume, gas, mist, vapors, or spray
- · Use only outdoors or in a well-ventilated area
- Wear protective gloves, protective clothing, eye, and face protection
- · Wash thoroughly after handling
- Do not eat, drink or smoke when using this product

GHS - Precautionary Statement(s) - Response

- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Call a POISON CENTER or doctor/physician
- Specific treatment (see First Aid information on product label and/or Section 4 of the SDS)
- IF ON SKIN: Wash with plenty of water
- If skin irritation occurs: Get medical advice/attention
- Take off contaminated clothing and wash it before reuse
- Specific treatment (see Section 4 of the safety data sheet and/or the First Aid information on the product label)
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF exposed or concerned: Get medical advice/attention

GHS - Precautionary Statement(s) - Storage

Store in a well-ventilated place. Keep container tightly closed

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

· Store locked up

GHS - Precautionary Statement(s) - Disposal

• Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations

Hazards Not Otherwise Classified (HNOC)

None identified

See Section 11: TOXICOLOGICAL INFORMATION

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: METHYL TRICHLORIDE, FORMYL TRICHLORIDE, METHANE TRICHLORIDE, METHENYL TRICHLOROFORM, TRICHLOROMETHANE

Component	Percent [%]	CAS Number
Chloroform	> 99	67-66-3
Ethyl Alcohol (Alcohol Stabilized Grade	< 1	64-17-5
Only)		

SECTION 4. FIRST AID MEASURES

INHALATION: If inhaled and adverse effects occur, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. See Notes to Physician below and Section 11 for more information.

SKIN CONTACT: If on skin or hair, wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Treat any skin irritation symptomatically.

EYE CONTACT: If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

INGESTION: If swallowed, rinse mouth with water (only if the person is conscious). Contact a poison center or doctor/physician if you feel unwell.

Most Important Symptoms/Effects (Acute and Delayed):

Acute Symptoms/Effects: Listed below.

Inhalation (Breathing): Respiratory System Effects: Inhalation of this material may cause acute respiratory depression with central nervous system (CNS) depression, resulting in lightheadedness to possibly rapid loss of consciousness. Moderate to severe exposures may cause cardiac arrhythmias.

Skin: Skin Irritation: Exposure to skin may cause redness, dryness, localized edema, ulcerations.

Eye: Eye Irritation. Eye exposure may cause irritation, tearing, conjunctivitis, corneal edema, cornea epithelial damage.

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

Ingestion (Swallowing): Gastrointestinal System Effects: May be fatal if swallowed.

Delayed Symptoms/Effects:

- Respiratory System Effects: Chemical pneumonitis and delayed pulmonary edema
- Skin: Repeated and prolonged skin contact may cause a chronic dermatitis
- May cause delayed hepatotoxicity
- Acute renal toxicity has been rarely reported
- Suspected of causing cancer
- Suspected of damaging fertility or the unborn child

Interaction with Other Chemicals Which Enhance Toxicity: Alcohol may enhance toxic effects. May potentiate other agents that cause central nervous system (CNS) and respiratory system depression, such as alcohol, opiates. Liver toxicity may be enhanced by other agents that cause liver damage, such as alcohol, acetaminophen. Catecholamines may potentiate arrhythmias.

Medical Conditions Aggravated by Exposure: May increase potential for cardiac arrhythmia. Persons with alcoholism, kidney disorders, liver disorders, or central nervous system disorders may be more susceptible to toxicity.

Protection of First-Aiders: Protect against vapor/gas exposure. Do not breathe gas, fumes, vapor, mist, or spray. Protect against liquid contamination/frostbite. Avoid contact with skin and eyes. Use personal protective equipment. Refer to Section 8 for specific personal protective equipment recommendations.

Notes to Physician: For ingestion, nasogastric aspiration is recommended if volume ingested is of sufficient volume to aspirate. Protect the airway, onset of respiratory depression may be rapid. Consider EKG monitoring to detect cardiac arrhythmias. Monitor blood pressure for hypotension. Avoid catecholemines, especially in the presence of arrhythmias. For very high exposures, (intentional, solvent abuse), oxygen, advanced cardiac life support, intubation and volume support may be required. For skin exposures, wash the area with soap and water, and treat any irritation symptomatically. Thorough decontamination of the eye is important. See section 11 for additional toxicology information.

SECTION 5. FIRE-FIGHTING MEASURES

Fire Hazard: Negligible fire hazard.

Extinguishing Media: Use media appropriate for surrounding fire

Fire Fighting: Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Flood with fine water spray. Do not scatter spilled material with high-pressure water streams. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Keep water runoff out of water supplies and sewers (see Section 6 of the MSDS).

Component	Immediately Dangerous to Life/ Health (IDLH)
Chloroform	500 ppm IDLH
67-66-3	
Ethyl Alcohol (Alcohol Stabilized Grade Only) 64-17-5	3300 ppm IDLH

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

Hazardous Combustion Products: Thermal decomposition or combustion products: hydrogen chloride, chlorine,

phosgene, oxides of carbon

Sensitivity to Mechanical Not sensitive.

Impact:

Sensitivity to Static Discharge: Not sensitive.

Lower Flammability Level (air): Not flammable

Upper Flammability Level (air): Not flammable

Flash point: None

Auto-ignition Temperature: >1832 °F (>1000 °C)

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Keep unnecessary and unprotected persons away. Isolate hazard area and deny entry. Evacuation of surrounding area may be necessary for large spills. Do not get in eyes, on skin or on clothing. Do not breathe dust, fume, gas, mist, vapors, or spray. Most vapors are heavier than air and will spread along ground and collect in low or confined areas (drains, basements, tanks). Ventilate closed spaces before entering. Wear appropriate personal protective equipment recommended in Section 8, Exposure Controls / Personal Protection, of the SDS.

Methods and Materials for Containment and Cleaning Up:

Stop leak if possible without personal risk. Shut off ventilation system if needed. Ventilate closed spaces before entering. Completely contain spilled materials with dikes, sandbags, etc. Remove contaminated soil or collect with appropriate absorbent and place into suitable container. Keep container tightly closed. Liquid material may be removed with a properly rated vacuum truck. Dispose of in accordance with all applicable regulations. See Section 13, Disposal considerations, for additional information.

Environmental Precautions:

Avoid discharge into drains, surface water or groundwater. Keep out of water supplies, sewers and soil. Releases should be reported, if required, to appropriate agencies.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Most vapors are heavier than air and will spread along ground and collect in low or confined areas (drains, basements, tanks). Avoid breathing vapor or mist. Avoid contact with skin, eyes and clothing. Do not taste or swallow. Wash thoroughly after handling. When using, do not eat, drink or smoke.

Safe Storage Conditions:

Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Store in a cool, dry area. Store in a well-ventilated area. Prevent water or moist air from entering storage

SDS No.: M47011 SDS Revision Date: 27-Jun-2016

tanks or containers. Do not enter confined spaces without following proper confined space entry procedures. Do not store in aluminum container or use aluminum fittings or transfer lines. Do not reuse drum without recycling or reconditioning in accordance with any applicable federal, state or local laws. Do not use cutting or welding torches, open flames or electric arcs on empty or full containers. Keep separated from incompatible substances (see Section 10 of SDS).

Incompatibilities/ Materials to Avoid:

bases, reactive metals, metallic fines or powders, oxidizing materials, halogens, acetone, aluminum, disilane, magnesium, potassium, sodium

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Regulatory Exposure Limit(s): Listed below for the product components that have regulatory occupational exposure limits (OEL's).

Component	OSHA Final PEL TWA	OSHA Final PEL STEL	OSHA Final PELCeiling
Chloroform 67-66-3			50 ppm 240 mg/m³
Ethyl Alcohol (Alcohol Stabilized Grade Only) 64-17-5	1000 ppm 1900 mg/m³		

OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit

NON-REGULATORY EXPOSURE LIMIT(S): Listed below for the product components that have non-regulatory occupational exposure limits (OEL's).

occupational exposure	(/					
Component	ACGIH TWA	ACGIH STEL	ACGIH Ceiling	OSHA TWA	OSHA STEL	OSHA Ceiling
				(Vacated)	(Vacated)	(Vacated)
Chloroform	10 ppm			2 ppm		
				9.78 mg/m ³		
Ethyl Alcohol (Alcohol		1000 ppm		1000 ppm		
Stabilized Grade				1900 mg/m ³		
Only)				•		

⁻ The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).

- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

Component	OXY REL	OXY REL	OXY REL
	8 hr TWA	STEL	Ceiling
Chloroform 67-66-3 (> 99)	2 ppm		50 ppm

Additional Advice:

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

1. SEE SECTION 11 FOR ADDITIONAL TOXICOLOGICAL INFORMATION

ENGINEERING CONTROLS: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear chemical safety goggles with a face-shield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear chemical resistant clothing to prevent skin contact. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods.

Hand Protection: Wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove.

Protective Material Types:

Viton®, Polyvinyl alcohol (PVA), Polyethylene (PE)

Respiratory Protection: Where vapor concentration exceeds or is likely to exceed applicable exposure limits, a NIOSH approved respirator is required. A NIOSH approved self-contained positive pressure breathing apparatus with full-face piece or airline respirator is required for spills, emergencies and/or IDLH concentrations. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

Component	Immediately Dangerous to Life/ Health (IDLH)
Chloroform	500 ppm IDLH
67-66-3	
Ethyl Alcohol (Alcohol Stabilized Grade Only)	3300 ppm IDLH
64-17-5	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Colorless

Odor: Mildly sweet odor

Odor Threshold [ppm]: 200 ppm (causes olfactory fatigue).

Molecular Weight: 119.37 Molecular Formula: CHCl3

Decomposition Temperature:No data availableBoiling Point/Range:142 ° F (61.1 ° C)Freezing Point/Range:-83 ° F (-63.9 ° C).Vapor Pressure:160 mmHg @ 20° C

Vapor Density (air=1): 4.1

Relative Density/Specific Gravity 1 4 @ 25 ° C

(water=1):

Density: No data available Water Solubility: No data available 0.8% @ 25 ℃

SDS No.: M47011 SDS Revision Date: 27-Jun-2016

pH: Not applicable

Volatility: 100% Evaporation Rate (ether=1): 0.56

Partition Coefficient log Kow = 1.97

(n-octanol/water):

Flash point: None

Flammability (solid, gas):

Lower Flammability Level (air):

Upper Flammability Level (air):

Auto-ignition Temperature:

Viscosity:

Not flammable

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal temperatures and pressures.

Chemical Stability: Stable at normal temperatures and pressures.

Possibility of Hazardous Reactions: Keep away from heat. Containers may rupture or explode if exposed to heat. Will attack some forms of plastics, rubber, and coatings. Avoid contact with incompatible substances and conditions due to generation of phosgene and other toxic and irritating substances.

Conditions to Avoid: (e.g., static discharge, shock, or vibration) -. None known.

Incompatibilities/ Materials to Avoid: bases, reactive metals, metallic fines or powders, oxidizing materials, halogens, acetone, aluminum, disilane, magnesium, potassium, sodium

Hazardous Decomposition Products: Thermal decomposition or combustion products: hydrogen chloride, chlorine, phosgene, oxides of carbon

Hazardous Polymerization: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

IRRITATION DATA: 10 mg/24 hour(s) open skin-rabbit mild; 500 mg/24 hour(s) skin-rabbit mild; 148 mg eyes-rabbit; 20 mg/24 hour(s) eyes-rabbit moderate

TOXICITY DATA:

PRODUCT TOXICITY DATA: CHLOROFORM

LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
908-1336 mg/kg oral-rat LD50	> 20 gm/kg skin-rabbit LD50	8000-9770 mg/m³ (4 hr - Rat)

COMPONENT TOXICITY DATA:

Note: The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given.

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

Component	LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
Chloroform		20 g/kg (Rabbit)	47702 mg/m³ (4 hr-Rat)
67-66-3			

POTENTIAL HEALTH EFFECTS:

Eye contact: Eye contact may cause irritation, conjunctivitis, tearing, swelling, eye pain, corneal

edema, blurred vision, cornea epithelial damage.

Skin contact: Skin contact may cause irritation, redness, dryness, localized edema, ulcerations

after significant long-term exposure.

Inhalation: Not a pulmonary irritant. May cause respiratory depression. May cause slightly

sweet odor on breath. May cause central nervous system (CNS) depression resulting in lightheadedness to rapid loss of consciusness. Moderate to severe

exposures may cause cardiac arrhythmias.

Ingestion: May cause gastrointestinal effects, liver damage, kidney damage,

unconsciousness and death.

Chronic Effects: Increased irritability and decreased concentration was reported in female workers

exposed to levels of 77 ppm or greater in the workplace. Deliberate abuse has been associated with depression, hallucinations, delirium and degenerative changes in central and peripheral nervous system tissues. May be excreted in breast milk. Repeated exposure has been associated with liver and kidney damage in humans and animals. In addition, nasal cavity changes were observed in rats and mice exposed for 7 days. Long-term ingestion may cause liver

damage, reproductive effects and cancer. Interstitial pneumonitis was observed in male rats and in rabbits exposed to this material for six months. This effect was

not observed in other species.

SIGNS AND SYMPTOMS OF EXPOSURE:

Listed below.

Inhalation (Breathing): Respiratory System Effects: Inhalation of this material may cause acute respiratory depression with central nervous system (CNS) depression, resulting in lightheadedness to possibly rapid loss of consciousness. Moderate to severe exposures may cause cardiac arrhythmias.

Skin: Skin Irritation: Exposure to skin may cause redness, dryness, localized edema, ulcerations.

Eye: Eye Irritation. Eye exposure may cause irritation, tearing, conjunctivitis, corneal edema, cornea epithelial damage.

Ingestion (Swallowing): Gastrointestinal System Effects: May be fatal if swallowed.

TOXICITY:

Chloroform was used as an anesthetic for humans (10,000 - 22,500 ppm), but is no longer recommended for this use due to liver and kidney damage. Intentional abuse can result in significant toxicity. Respiratory depression, with central nervous system depression and delayed hepatotoxicity are indicative of chloroform poisoning. Symptoms of central nervous system depression have been reported in workers at concentrations of 80-240 ppm. Dizziness,

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

vertigo, fatigue, and headache have been reported from exposure to 920 ppm for approximately 3 minutes. Exposure to levels of 1500-2000 ppm have been reported to cause slight anesthesia. Irregular heartbeat may occur from exposure to levels of 8000 ppm or higher. This material is likely to be fatal after 5-10 minutes of 25.00 ppm.

Interaction with Other Chemicals Which Enhance Toxicity: Alcohol may enhance toxic effects. May potentiate other agents that cause central nervous system (CNS) and respiratory system depression, such as alcohol, opiates. Liver toxicity may be enhanced by other agents that cause liver damage, such as alcohol, acetaminophen. Catecholamines may potentiate arrhythmias.

GHS HEALTH HAZARDS:

GHS: CONTACT HAZARD - EYE: Category 2B - Causes eye irritation

Skin Absorbent / Dermal Route? No.

GHS: CARCINOGENICITY:

Category 2 - Suspected of causing cancer.

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure):

Category 3 - Narcotic Effects

SPECIFIC TARGET ORGAN TOXICITY (Repeated or Prolonged Exposure):

Category 1 - Liver, Kidneys, Central Nervous System (CNS)

MUTAGENIC DATA:

Not classified as a mutagen per GHS criteria. This material has tested positive in one or more in vitro mutagenicity studies. However, the majority genotoxicity data have demonstrated a pattern of negative results.

REPRODUCTIVE TOXICITY:

Category 2 - Suspected of damaging fertility or the unborn child.

DEVELOPMENTAL TOXICITY:

Category 2 - Suspected of damaging fertility or the unborn child. This material may cause harm to the human fetus based on tests with laboratory animals. Studies of workers have not shown any association between exposure and adverse effects on reproduction or pregnancy outcome. This material crosses the placenta rapidly and enters fetal circulation. Developmental studies in experimental animals have produced a variety of results, some indicating fetotoxicity and weak teratogenicity. Animal studies indicate that inhalation exposure may cause reproductive effects in rodents.

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

FATE AND TRANSPORT:

BIODEGRADATION: Slow but substantial biodegradation apparently can occur when the proper microbial populations exist and are acclimated to the chemical.

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

PERSISTENCE: AIR: This material released to the atmosphere will degrade by reaction with hydroxyl radicals with a half-life of 151 days. SOIL: On land is expected to evaporate rapidly into the atmosphere due to its high vapor pressure. It is poorly adsorbed to soil and can leach into the groundwater. WATER: Primary loss will be by evaporation into the atmosphere. Laboratory experiments have measured the half-life for evaporation to be several hours to days. This material has a negligible rate of hydrolysis.

BIOCONCENTRATION: Bioconcentration potential in aquatic organisms is low with BCF of 2.9-10.35.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from material:

Reuse or reprocess, if possible. Keep out of water supplies, sewers and soil. Dispose in accordance with all applicable regulations.

Container Management:

Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

SECTION 14. TRANSPORT INFORMATION

LAND TRANSPORT

U.S. DOT 49 CFR 172.101:

UN NUMBER: UN1888
PROPER SHIPPING NAME: Chloroform

HAZARD CLASS/ DIVISION: 6.1
PACKING GROUP: III
LABELING REQUIREMENTS: 6.1

RQ (lbs): RQ 10 Lbs. (Chloroform)

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

UN NUMBER: UN1888 SHIPPING NAME: Chloroform

CLASS OR DIVISION: 6.1
PACKING/RISK GROUP: III
LABELING REQUIREMENTS: 6.1

MARITIME TRANSPORT (IMO / IMDG) :

UN NUMBER: UN1888

PROPER SHIPPING NAME: Chloroform

HAZARD CLASS / DIVISION: 6.1

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

Packing Group: III
LABELING REQUIREMENTS: 6.1

SECTION 15. REGULATORY INFORMATION

U.S. REGULATIONS

OSHA REGULATORY STATUS:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

If a release is reportable under CERCLA section 103, notify the state emergency response commission and local emergency planning committee. In addition, notify the National Response Center at (800) 424-8802 or (202) 426-2675.

Component	CERCLA Reportable Quantities:
Chloroform	10 lb (final RQ)

SARA EHS Chemical (40 CFR 355.30)

If a release is reportable under EPCRA, notify the state emergency response commission and local emergency planning committee. If the TPQ is met, facilities are subject to reporting requirements under EPCRA Sections 311 and 312.

Component	EPCRA RQs	Section 302 Threshold Planning Quantity (TPQs)
Chloroform	10 lb (EPCRA RQ)	10000 lb TPQ

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):

Acute Health Hazard, Chronic Health Hazard, Extremely Hazardous

EPCRA SECTION 313 (40 CFR 372.65):

The following chemicals are listed in 40 CFR 372.65 and may be subject to Community Right-to Know Reporting requirements

Component	Status:
Chloroform	Listed

OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):

Not regulated

NATIONAL INVENTORY STATUS

U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA): All components are listed or exempt

TSCA 12(b): This product is not subject to export notification.

Canadian Chemical Inventory: All components of this product are listed on either the DSL or the NDSL.

SDS No.: M47011 SDS Revision Date: 27-Jun-2016

STATE REGULATIONS

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer, and/or birth defects, and/or other reproductive harm.

Component	Proposition 65 Cancer	Proposition 65 CRT List - Male reproductive	Proposition 65 CRT List - Female	Right to Know Hazardous	Hazardous	New Jersey Special Health Hazards Substance List
Chloroform 67-66-3	Not Listed			Listed	0388	carcinogen
Ethyl Alcohol (Alcohol Stabilized Grade Only) 64-17-5				Listed	0844	

Component	Environmental	to Know Hazardous Substance List	to Know Special Hazardous	to Know	Rhode Island Right to Know Hazardous Substance List
Chloroform 67-66-3		Listed	Present	Present	Listed
Ethyl Alcohol (Alcohol Stabilized Grade Only) 64-17-5		Listed	Not Listed	Not Listed	Not Listed

CANADIAN REGULATIONS

• This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations

Component	Canadian Chemical Inventory:	NDSL:	WHMIS - Classifications of Substances:
Ethyl alcohol	Listed Present (that participate in atmospheric photochemical reactions except those under item number 65 on the Toxic Substances List source)		B2,D2B
Chloroform	Listed Present (that participate in atmospheric photochemical reactions except those under item number 65 on the Toxic Substances List source)		D1B,D2A,D2B

SECTION 16. OTHER INFORMATION

Prepared by: OxyChem Corporate HESS - Product Stewardship

SDS No.: M47011 **SDS Revision Date**: 27-Jun-2016

Rev. Date: 27-Jun-2016

Health Rating: 2 Flammability: 0 Reactivity Rating: 0

Reason for Revision:

Product Identifier has been added or updated: SEE SECTION 1

• Product Name and/or Trade Name(s) has been revised: SEE SECTION 1

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees

End of Safety Data Sheet