

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : CalCoat-127®

Manufacturer or supplier's details

Company : Johns Manville

Address : P.O. Box 5108
Denver, CO USA 80127

Telephone : 303-978-2000 8:00AM-5:00PM M-F

Emergency telephone number : 1-800-424-9300 (Chemtrec, in English)

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin corrosion : Category 1

Serious eye damage : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS Label element

Hazard pictograms



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H350 May cause cancer.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust or mist.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

shower.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous components**

Chemical Name	CAS-No.	Concentration (%)
cement, portland, chemicals	65997-15-1	>= 30 - < 50
synthetic calcium silicate	1344-95-2	>= 30 - < 50
Continuous Filament Glass Fibers	Not Assigned	>= 20 - < 30
Crystalline silica	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended.
If inhaled	: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

Hazardous combustion products	: No hazardous combustion products are known
-------------------------------	--

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid dust formation.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Keep in a dry, cool place.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
cement, portland, chemicals	65997-15-1	TWA (Respirable fraction)	1 mg/m ³	ACGIH
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA
		TWA (respirable fraction)	5 mg/m ³	OSHA
		TWA (Total dust)	10 mg/m ³	OSHA
		TWA (respirable)	5 mg/m ³	OSHA

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

		dust fraction)		
		TWA (Dust)	50 Million particles per cubic foot	OSHA
synthetic calcium silicate	1344-95-2	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA
		TWA (respirable fraction)	5 mg/m3	OSHA
		TWA	10 mg/m3	ACGIH
Continuous Filament Glass Fibers	Not Assigned	TWA (Total dust)	10 mg/m3	ACGIH
		TWA (Total dust)	15 mg/m3	OSHA
		TWA (Respirable dust)	5 mg/m3	OSHA
		TWA (Respirable dust)	5 mg/m3	ACGIH
Crystalline silica	14808-60-7	TWA (Respirable fraction)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO ₂ +2	OSHA
		TWA (respirable)	10 mg/m3 / %SiO ₂ +2	OSHA
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA
		TWA (Respirable dust)	0.05 mg/m3	NIOSH REL
		TWA (Respirable fraction)	0.1 mg/m3	OSHA

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
 Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

Skin and body protection	: If used and stored as directed, no special protective equipment is necessary.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: solid
Colour	: yellow
Odour	: not significant
Odour Threshold	: No data available
pH	: Not applicable
	: Not applicable
	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: No data available
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Relative density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Stable under recommended storage conditions.
No hazards to be specially mentioned.

Conditions to avoid : No data available

SECTION 11. TOXICOLOGICAL INFORMATION**IARC** Group 1: Carcinogenic to humans
Crystalline silica 14808-60-7**ACGIH** Suspected human carcinogen
Crystalline silica 14808-60-7**OSHA** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.**NTP** Known to be human carcinogen
Crystalline silica 14808-60-7**STOT - single exposure****Components:****synthetic calcium silicate:**

Target Organs: Eyes, Lungs

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Contaminated packaging

: Empty containers should be taken to an approved waste handling site for recycling or disposal.
Packaging that can not be reused after cleaning must be disposed or recycled in accordance with all federal, national and local regulations.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

These products are not classified as dangerous goods according to international transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: Not relevant

Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302

: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Insulating Cement

Version 1.1

Revision Date 01/16/2015

Print Date 08/02/2015

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Crystalline silica

14808-60-7

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 01/16/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.