



PRODUCT DATA

Castrol Transmax™ Type F Automatic Transmission Fluid (ATF)

Castrol Transmax™ Type F Automatic Transmission Fluid is for use in older Ford vehicles that require Type F transmission fluid.

Features and Benefits

- Provides excellent lubrication to gears and bushings allowing for smooth transmission operation
- Effectively resists fluid oxidation
- Approved for all transmissions calling for a Type F transmission fluid. May be used in other hydraulic applications calling for a Type F fluid such as power steering and shock systems. Not for use where any MERCON® fluid is required. Check owners manual for details.

Warranty and Protection Requirements

- Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a Ford Type F ATF is specified.

Industry Specifications and OEM Approvals

- Meets or exceeds Ford Type F ATF requirements
- Meets or exceeds Ford ESW-M2C33-F/G

Typical Properties*

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	37.0
Viscosity at 100°C, cSt	ASTM D-445	7.4
Viscosity Index	ASTM D-2270	167
Color, Typical	ASTM D-1500	7.0
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	55,000
Pour Point, °C (°F)	ASTM D-97	-40 (-40)
Flash Point, °C (°F)	ASTM D-92	175 (347)
Specific Gravity, 60°F	ASTM D-1298	0.862
Pounds per Gallon	ASTM D-287	7.25

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



Part Numbers and UPCs

Packaged Goods

Case Size	6/1 Qt
Case Part No.	06816
Bottle/ Unit UPC	0-79191-00438-8
Case UPC	0-79191-06816-8

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: 1,800.462.0835
Email: contactus@bp.com
©2011 BP Lubricants USA Inc. All rights reserved.

www.castrol.com/us