Material Safety Data Sheet

Provided by:

PO Box 24600

DPC Industries, Inc.

DX Systems Company

Houston, Tx 77229-4600 281-457-4888

DPC Enterprises, LP

DX Terminals

888-647-7717

DXI Industries, Inc.

www.dxgroup.com

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name

CHLORINE

Synonyms

NONE

Chemical Name

CHLORINE

281-457-4888

Date of Issue:

10/1/00

Emergency phone:

Reviewed / Revision Date:

Chemtrec:

800-424-9300

03/27/2007

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	PERCENT	CAS NO.
CHLORINE	> 99%	7782-50-5

SECTION 3 - HAZARDS IDENTIFICATION

Potential Health Effects

ACGIH - TLV:

0.5 ppm

Eye Contact

CONTACT MAY CAUSE EYE BURNS.

Skin Contact

CONTACT MAY CAUSE BURNS AND TISSUE DESTRUCTION.

Ingestion

NOT A LIKELY ROUTE OF EXPOSURE.

Inhalation

COUGHING, BURNING, CHEST PAIN, VOMITING, HEADACHE, ANXIETY AND FEELING OF SUFFOCATION. SEVERE EXPOSURE MAY CAUSE PNEUMONITIS AND PULMONARY EDEMA.

Carcinogenicity:

NTP NO

IARC NO

OSHA NO

SECTION 4 - FIRST AID PROCEDCURES

Eve Contact:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

Skin Contact:

IMMEDIATELY REMOVE CONTAMINATED CLOTHING OR SHOES, WIPE EXCESS FROM SKIN AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. USE SOAP IF AVAILABLE OR FOLLOW BY WASHING WITH SOAP AND WATER. DO NOT REUSE CLOTHING UNTIL THOROUGHLY CLEANED. GET MEDICAL ATTENTION.

Inhalation:

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GET MEDICAL ATTENTION.

Ingestion:

DO NOT INDUCE VOMITING. RINSE MOUTH WITH WATER. IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER OR MILK AND GET IMMEDIATE MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON!

SECTION 5 -FIRE FIGHTING MEASURES

Flash Point (°F)

NOT APPLICABLE

Extinguishing Media

USE MEDIA FOR SURROUNDING MATERIALS.

Special Firefighting Procedures/Precuations WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. AVOID BREATHING FUMES OR VAPORS. USE WATER TO COOL CONTAINERS BUT AVOID GETTING WATER INTO CONTAINERS. DOES NOT BURN, BUT IS A STRONG OXIDIZER AND SERIOUS FIRE RISK.

SECTION 6 -ACCIDENTAL RELEASE MEASURES

For Spill:

EVACUATE UNNECESSARY PERSONNEL UPWIND OF SPILL AREA. CONTAIN LIQUIDS AND PREVENT DISCHARGES INTO WATERWAYS AND SEWERS. CONTROL OR STOP THE LOSS OF VOLATILE MATERIAL TO THE ATMOSPHERE. DO NOT APPLY WATER TO THE LEAK. REACTS WITH WATER TO FORM CORROSIVE, ACIDIC SOLUTION. CHLORINE CAN BE ABSORBED INTO AN ALKALI.

SECTION 7 - HANDLING AND STORAGE

Keep container tightly closed when not in use. Store in a cool, dry, well-ventilated area, away from heat and incompatible materials. Protect containers from physical damage.

FOLLOW SAFETY PROCEDURES FOR CONTAINERS OF COMPRESSED GASES. PROVIDE SPECIAL TRAINING TO WORKERS HANDLING CHLORINE. LEAKS SHOULD BE STOPPED WITH PROMPTLY. VAPORS ARE HEAVIER THAN AIR. STORE IN WELL-VENTILATED AREA OF LOW FIRE POTENTIAL AND AWAY FROM INCOMPATIBLE MATERIALS. DO NOT USE STAINLESS STEEL EQUIPMENT. REGULARLY TEST AND INSPECT PIPING AND CONTAINMENT. HEATING COULD MELT PLUGS ON CYLINDERS AND TON CONTAINERS AND CAUSE SAFETY VALVES ON TANK CARS TO VENT, CAUSING LEAKS. MOISTURE (MORE THAN 150 PPM OF WATER) AND CHLORINE CAN FORM HYDROCHLORIC AND HYPOCHLOROUS ACIDS, WHICH ARE CORROSIVE. NEVER PLACE A LEAKING CONTAINER IN WATER OR SPRAY LEAKING CONTAINER WITH WATER. NEVER TAMPER WITH FUSIBLE PLUGS OR SAFETY DEVICES ON CONTAINERS; NEVER MANIFOLD CONTAINERS FROM LIQUID VALVES. THIS PRODUCT IS TOXIC TO FISH. KEEP OUT OF WATERWAYS AND SEWERS.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection

USE A NIOSH/MSHA APPROVED RESPIRATOR FOLLOWING MANUFACTURER'S

RECOMMENDATIONS WHEN CONCENTRATIONS EXCEED PERMISSIBLE EXPOSURE LIMITS.

Ventilation

LOCAL AND MECHANICAL RECOMMENDED.

Protective Gloves

CHEMICAL IMPERVIOUS GLOVES.

Eye/Face Protection

CHEMICAL SAFETY GOGGLES AND/OR FULL-FACE SHIELD.

Other Protection

CHEMICAL RESISTANT CLOTHING SUCH AS COVERALLS/APRON, BOOTS, ETC. EMERGENCY

SHOWER AND EYEWASH FACILITY SHOULD BE IN CLOSE PROXIMITY.

Work Practices

USE GOOD PERSONAL HYGIENE PRACTICES. WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. PROMPTLY REMOVE SOILED CLOTHING AND WASH THOROUGHLY BEFORE REUSE. SHOWER AFTER WORK USING PLENTY OF SOAP AND WATER.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (°F): -29.3

Vapor Pressure (mmHg):

5830 (@ 20 C)

Freezing Point (°F): -150

Vapor Density (Air=1):

2.49

Solubility (H2O):

NEGLIGIBLE

Specific Gravity (H2O=1):

pH

Evaporation Rate:

NOT APPLICABLE

NOT AVAILABLE

Appearance/Odor:

AMBER COLOR LIQUID. GREENISH-YELLOW GAS. PUNGENT IRRITATING ODOR.

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:

YES

Incompatible Material:

AVOID CONTACT WITH REDUCING AGENTS. KEEP AWAY FROM MATERIALS SUCH AS ACETYLENE, TURPENTINE & OTHER HYDROCARBONS, AMMONIA, HYDROGEN,

ETHER, METALS, SULFUR, & ALUMINUM.

Hazardous Polymerization:

WILL NOT OCCUR.

Decomposition Products:

REACTS WITH HYDROGEN SULFIDE AND WATER FORMING HYDROCHLORIC ACID. COMBINES WITH CARBON MONOXIDE AND SULFUR DIOXIDE FORMING

PHOSGENE AND SULFURYL CHLORIDE

SECTION 11 - TOXICITY INFORMATION

LC50 (rat) = 293 ppm (1-HR), 690 ppm (30-MINUTE) LC50 (mouse) = 70 ppm (4-HR), 137 ppm (1-HR)

SECTION 12 - ECOLOGICAL INFORMATION

LC50/96HR/RAINBOW TROUT/14-291 UG/L LC50/48HR/WATER FLEA/30-150 UG/L LOEC PGR/5-10 DAY/GREEN ALGAE/760-1520 UG/L

HIGHLY TOXIC TO AQUATIC ORGANISMS. THIS MATERIAL IS NOT SUBJECT TO BIODEGRADATION AND DOES NOT BIOACCUMULATE.

SECTION 13 - DISPOSAL CONSIDERATIONS

DO NOT DISCHARGE INTO WATERWAYS OR SEWER SYSTEMS WITHOUT PRIOR APPROVAL. CHLORINE CAN BE ABSORBED IN ALKALINE SOLUTIONS. COMMON ONES ARE CAUSTIC SODA AND SODA ASH. PLACE NEUTRALIZED MATERIAL IN CONTAINER FOR DISPOSAL.

DISPOSE OF WASTE MATERIALS ACCORDING TO ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 14 - TRANSPORT INFORMATION

USA DOT Shipping Name: CHLORINE

Hazard Class:

2.3 (POISON--INHALATION HAZARD, ZONE B)

UN/NA Number:

UN1017

Packing Group:

NOT APPLICABLE

Subsidiary Hazard:

(8) CORROSIVE

Marine Pollutant:

YES

SECTION 15 - REGULATORY INFORMATION

CERCLA RQ (lbs): 10

SARA Title III Section 312:

✓ Acute

✓ Chronic

Flammable

✓ Sudden Release of Pressure

✓ Reactive

0

SARA Title III Section 313:

Yes

SARA Extremely Hazardous Substance:

0 - Least

HMIS HAZARD RATING

Health:

Fire:

0

Reactivity:

1 - Slight

2 - Moderate

3 - High

4 - Extreme

SECTION 16 - OTHER INFORMATION

EPA Pesticide Registration Number:

813-10

NSF Maximum Use Level for Potable Water (Standard 60):

30 mg/l

TSCA (Toxic Substance Control Act), 40 CFR 710:

Sources of the raw materials used in this mixture assure that all chemical ingredients present are in compliance with Section 8(b) Chemical Substance Inventory, or are otherwise in compliance with TSCA.

DISCLAIMER

THE DATA PRESENTED IS TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE AND BELIEF; HOWEVER, NEITHER SELLER NOR PREPARER MAKES ANY WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE INFORMATION PRESENTED. THE USER IS CAUTIONED TO PERFOM HIS OWN HAZARD EVALUATION AND TO RELY UPON HIS OWN DETERMINATIONS.