



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 011-003
Product name Disinfectant Spray for Hospital Use
Effective date 02-Sep-2011
Company information Claire Manufacturing Co.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 01

2. Hazards Identification

Emergency overview Aerosol. FLAMMABLE
CONTENTS UNDER PRESSURE.
Will be easily ignited by heat, spark or flames. Contact with eyes may cause irritation.
Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Skin contact. Ingestion.

Eyes Moderately irritating to the eyes.

Skin Harmful if absorbed through the skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.
Components of the product may be absorbed into the body by ingestion.

Target organs Blood. Central nervous system. Lungs.

Chronic effects Unconsciousness. Cyanosis (blue tissue condition, nails, lips, and/or skin). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing. Jaundice. Defatting of the skin. Skin irritation. Corneal damage.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Ethyl Alcohol	64-17-5	40 - 50
n-Butane	106-97-8	15 - 20
Propane	74-98-6	5 - 8
Methanol	67-56-1	1 - 3
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or Poison Control Center immediately.

Skin contact Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Inhalation Move to fresh air. Get medical attention if symptoms persist.

Ingestion
Notes to physician

In the unlikely event of swallowing contact a physician or poison control center.
Keep victim under observation.

5. Fire Fighting Measures

Flammable properties Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Foam. Dry chemical. Carbon dioxide (CO2).

Protection of firefighters

Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin.

Storage Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 2 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Methanol	67-56-1	200 ppm	250 ppm	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Methanol	67-56-1	200 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Do not get in eyes. Chemical goggles are recommended.

Skin protection Chemical resistant gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas.

Boiling point 136.4 °F (57.8 °C) estimated

Color	colorless
Density	0.7516 g/cm ³ estimated
Flammability (HOC)	25.0491 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	fruity alcoholic
pH	9.5 - 10.5
Physical state	Liquid.
Pressure	75 - 90 psig @ 70F
Solubility	Partially
Specific gravity	0.7517

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include oxides of nitrogen.

11. Toxicological Information

Acute effects Acute LC50: 81 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Ethyl Alcohol	64-17-5	Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h
Methanol	67-56-1	Inhalation LC50 Rat 83.2 mg/L 4 h; Inhalation LC50 Rat 64000 ppm 4 h; Oral LD50 Rat 5628 mg/kg; Dermal LD50 Rabbit 15800 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol	64-17-5	Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [in preparation] (in alcoholic beverages)
---------------	---------	--

Teratogenicity Animal experiments showed mutagenic and teratogenic effects.

12. Ecological Information

Ecotoxicity	LC50 1730 mg/L, Fish, 96.00 Hours, EC50 931 mg/L, Daphnia, 48.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
--------------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	None
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Pesticides are exempt from TSCA.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Methanol	67-56-1	1.0 % de minimis concentration
----------	---------	--------------------------------

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical	Yes
-------------------------------------	-----

CERCLA (Superfund) reportable quantity

Methanol: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - Yes
	Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl Alcohol	64-17-5	Present
Methanol	67-56-1	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 3
Physical hazard: 0
Personal protection:

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Prepared by

Regulatory Compliance