SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL NAME: Methacrylate Polymer

PRODUCT NAME: **COMPETITORS PINK**

Manufacturer's Name : EZ Flow Nail Systems Address: 13720 Rosecrans Ave

City, State, Zip : Santa Fe Springs, CA 90670 Business Telephone : 562-229-0337

Emergency Telephone : 800-535-5053

PREPARATION/UPDATE DATE: 10/04/00 PRINT DATE: 8/16/02

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

FOR POLYMER:

ITEM	CHEMICAL NAME	CAS NUMBER:	WT/WT %
01	Particulates Not Otherwise Classified	NE	60.0-100.0
02	Residual Monomers	NA	0.5-5.0
03	Benzoyl Peroxide	94-36-0	0.5-1.5
04	Azo Dye	59487-23-97	0.5-1.5

	ACG	IH	OSH	A	Company	
ITEM	TLV-TWA	TLV-STEL	PEL TWA	PEL CEILING	Recommendation	SKIN
01	10 mg/m ³	NE	15 mg/m ³	NE	NE	NE
02	NA	NA	NA	NA	NA	NA
03	5 m/m ³	NE	5 m/m ³	NE	NE	NE
04	NE	NE	NE	NE	NE	NE

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS CONTINUED

FOR DECOMPOSITION PRODUCTS:

ITEMCHEMICAL NAMECAS NUMBER:WT/WT %05Ethyl Methacrylate Monomer97-63-260.0-100.0

ACGIH OSHA Company

ITEMTLV-TWATLV-STELPEL TWAPEL CEILINGRecommendationSKIN05100 ppmNE100 ppmNE100 ppmNE

See Section 16 for Abbreviations.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

WARNING: For Polymer: May irritate eyes, skin and respiratory tract.

For Polymer:

OSHA classifies this material as Particulates, Not

Otherwise Classified.

Eyes: May be irritated by gross overexposure, no matter how

generated. Keep dust out of eyes.

Skin May be irritated by gross overexposure, no matter how

generated. May cause dryness.

Respiratory Tract May be irritated by gross overexposure, no matter how

generated.

For Benzoyl Peroxide: Eyes: May cause irritation or damage.

Skin: Prolonged and/or repeated skin contact may cause

irritation, defatting, dermatitis and sensitization.

Inhalation: May cause irritation of nose, throat and lungs.

Ingestion: May produce muscular weakness.

For Azo Dye: Eyes: May cause mechanical irritation, although found to be non-

irritating when tested on the eyes of rabbits.

Ingestion: Extreme quantities may cause discomfort to the digestive

ract.

Respiratory Tract: May cause mechanical irritation.

Skin: Found to be non-irritating when tested on the skin of

rabbits.

SECTION 3 - HAZARDS IDENTIFICATION CONTINUED

For Decomposition Products:

Ethyl Methacrylate:

Acute Hazards: Eyes: Eye contact may cause irritation with discomfort, tearing, or

blurring of vision.

Respiratory Tract: Inhalation may cause irritation of the respiratory tract with

coughing, of nonspecific discomfort, such as nausea,

headache and or weakness.

Skin: Effects in humans include skin irritation with discomfort or

allergic skin rashes.

Digestive Tract: Ingestion may cause anesthetic effects such as dizziness,

headache, confusion, incoordination, and loss of

consciousness

Symptoms: May include burning sensation, coughing, wheezing,

laryngitis, shortness of breath, headache, nausea and

vomiting.

Chronic Hazards: Skin: May cause allergic skin rashes.

Animal Studies: Administered lethal oral doses include weakness, labored

and irregular respiration, drop in arterial blood pressure and

coma.

CARCINOGENICITY: IARC lists Benzoyl Peroxide as not classifiable as to

carcinogenicity to humans. None of the other components of this material are listed by IARC, NTP, OSHA, or ACGIH

as carcinogens.

PRIMARY ROUTES OF ENTRY: Inhalation, Skin or Eyes.

SECTION 4 - FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Get medical help if discomfort persists.

EYES: Flush with water for 15 minutes, including under eyelids. Get medical help if

discomfort persists.

SKIN: Wash with soap and water. Get medical help if discomfort persists.

INGESTION: Rinse mouth out with water. Call doctor if amount was large.

CLOTHING: Wash thoroughly before reuse.

TREATMENT: Treat symptoms after thorough decontamination.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 304 °C, 580 °F

FLAMMABLE LIMIT, AIR VOL% LOWER: NA

UPPER: NA

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHER METHOD: Water, carbon dioxide, dry chemical.

FIRE AND EXPLOSION HAZARDS: Polymer dust is combustible. The explosive limits of the polymer

particles suspended in air are approximately those of coal dust.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid extinguishing methods which may generate dust clouds.

Water stream can disperse dust into air, producing a fire hazard and possible explosion hazard if exposed to ignition source.

EXPLOSION HAZARD: Firefighters should wear self-contained breathing apparatus.

SENSITIVE TO MECHANICAL IMPACT: For Polymer: No. For Benzoyl Peroxide Component: Yes

SENSITIVE TO STATIC DISCHARGE: For Polymer: No. For Benzoyl Peroxide Component: Yes

SECTION 6 - ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE: Sweep up to avoid slipping hazard. Keep airborne particulates at a

minimum when cleaning up spills.

SECTION 7- HANDLING AND STORAGE

PRECAUTIONS FOR HANDLING: Use in well ventilated areas. Wear gloves when handling powder.

PRECAUTIONS FOR STORAGE: Store in cool dry place. Keep container closed to prevent water

absorption and contamination.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

VENTILATION: Use good, local exhaust at processing equipment, including buffers,

sanders, grinders and polishers.

RESPIRATORY PROTECTION: Use type for Particulates Not Otherwise Classified, if needed.

EYE PROTECTION: Safety glasses or chemical splash goggles.

PROTECTIVE GLOVES: Impervious, nitrile, if hot plastic is handled.

OTHER PROTECTIVE EQUIPMENT: Provide eyewash, safety shower and impervious clothing are

recommended. High temperature processing equipment should be

well ventilated.

INDUSTRIAL HYGIENE PRACTICES: Wash face and hands thoroughly with soap and water after use and

before eating, drinking, smoking or applying cosmetics.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Fine white powder.

ODOR: Faint odor in bulk.

:Ha ND **ODOR THRESHOLD:** ND **BOILING POINT:** NA FREEZING POINT: ND VISCOSITY: NA **SPECIFIC GRAVITY** (H₂O=1): 1.25 **VAPOR PRESSURE:** NA **PERCENT VOLATILE W/W%:** NA **VAPOR DENSITY** (AIR=1): NA **EVAPORATION RATE** (BuAc =1): 3.0

SOLUBILITY IN WATER: Insoluble.

COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Heating above 240 °C, 464 °F.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Methacrylate Monomer and Oxides of Carbon when burned.

HAZARDOUS POLYMERIZATION: MAY OCCUR: WILL NOT OCCUR: X

STABILITY: UNSTABLE: STABLE: X

SECTION 11- TOXICOLOGICAL PROPERTIES

TARGET ORGANS:

For Polymer; None Listed.
For Benzoyl Peroxide: Skin and eyes.
For Azo Dye: None Listed.

For Decomposition Products:

Ethyl Methacrylate: None Listed.

MUTAGENICITY DATA:

For Polymer: None Listed.

For Benzoyl Peroxide:

SECTION 11- TOXICOLOGICAL PROPERTIES CONTINUED

MUTAGENICITY DATA CONTINUED:

For Decomposition Products:

Ethyl Methacrylate: None Listed.

REPRODUCTIVE TOXICITY DATA:

For Polymer: None Listed.

For Decomposition Products: None Listed.

Ethyl Methacrylate:

Intraperitoneal Rat TD_{Lo}: 735 mg/kg, 5-15D pregnant. Intraperitoneal Rat TD_{Lo}: 366 mg/kg, 5-15 D pregnant.

TUMOROGENIC DATA:

For Polymer: None Listed.

For Benzoyl Peroxide:

Skin Mouse TD_{Lo}: 24 gm/kg/30W.

TOXICITY DATA:

For Polymer: None Listed.

For Benzoyl Peroxide:

For Azo Dye:

Oral Rat LD_{50} : >10,000 mg/kg.

Ames Test Negative

For Decomposition Products:

Ethyl Methacrylate:

Inhalation Rat LC₅₀: 8300 ppm/4H. Intraperitoneal Mouse LD₅₀: 1369 mg/kg. Intraperitoneal Rat 1223 mg/kg. LD₅₀: Oral Mouse LD₅₀: 7836 mg/kg. 14800 mg/kg. Oral Rat LD₅₀: Oral Rabbit 3630 mg/kg. LD₅₀: Subcutaneous Rat 25 gm/kg. LD_{Lo:}

SECTION 12 - ECOLOGICAL INFORMATION

AQUATIC TOXICITY:

For Polymer: None Listed.

For Decomposition Products:

Ethyl Methacrylate: None Listed.

ECOLOGICAL TOXICITY:

For Polymer: Not Known. For Benzoyl Peroxide: Not Known.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose in a landfill or incinerate according to Federal, State, and

Local regulations.

DISPOSAL OF EMPTY CONTAINERS: Reuse of empty drums or containers is not recommended.

Employees should be advised of the potential hazards, due to residual material, associated with empty containers. It is our policy to discourage the reuse of empty containers and to dispose of all empty containers properly, in accordance with Federal, State and

Local regulations.

SECTION 14 - TRANSPORTATION

DOT/UN SHIPPING NAME: SYNTHETIC GUM RESIN GRANULAR, NOIBN

DOT/UN CLASS: NA/UN NUMBER: PACKING GROUP:

NAERG: LABEL:

NMFC ITEM #: 46030

SCHEDULE B: 3906.90.6000

IMDG CLASS:
IMDG PG:

CERLA RQ: For Decomposition Products:

Ethyl Methacrylate Monomer: 1000 lb.

SECTION 15 - REGULATORY INFORMATION

ITEM 04	TSCA X	EINECS X	CERCLA	313	CAA	RCRA
05	X	X	Χ	Χ	X	U 118
ITEM 05	CWA	PA X	NJ X	CA 65	WHMIS X	DAK

TSCA: FOR USE IN FDA REGULATED PRODUCTS ONLY

CANADIAN WHMIS: This product has been classified in accordance with the hazardous criteria of the CPR and the MSDS contains all the information required by the CPR.

All of the components of this material are listed on the Canadian DSL.

SECTION 16 - OTHER INFORMATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0

PERSONAL PROTECTIVE EQUIPMENT: Gloves and Safety Glasses or Chemical Splash Goggles.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0

ABBREVIATIONS:

NA NE ppm mg gm kg mm	Not Applicable Not Established parts per million Milligram Gram Kilogram Millimeter	ND CPR G L mol µ P	Not Determined Controlled Products Regulation Gallon Liter Mole Micro Pico
LC TC BOD Lo TLm	Lethal Concentration Toxic Concentration Biological Oxygen Demand Lowest Threshold Limit	LD TD COD ThOD	Lethal Dose Toxic Dose Chemical Oxygen Demand Theoretical Oxygen Demand

SECTION 16 - OTHER INFORMATION CONTINUED

ABBREVIATIONS CONTINUED:

H D W	Hours Days Weeks	M Y	Months Years
ACGIH IARC TLV	Occupational Safety and Health Administration American Conference of Governmental Industrial International Agency for Research for Cancer Threshold Limit Value Permissible Exposure Limit	Hygienist	t
Prepare	ed By:	Health,	Safety and Environment
Reviewe	ed By:	Technic	al Review
Reviewe	ed By:	Senior (Company Officer
Issue Da	ate:		

THIS MATERIAL SAFETY DATA SHEET IS PREPARED IN COMPLIANCE WITH FEDERAL REGULATIONS (29 CFR 1910.1200), THE COMMONWEALTH OF PENNSYLVANIA REGULATIONS (TITLE 34. CHAPTERS 301-323) AND CANADIAN WHMIS REGULATIONS, ANY APPLICABLE STATE AND LOCAL REGULATIONS SHOULD BE CONSULTED. THE ABOVE INFORMATION MAY BE BASED IN PART ON INFORMATION PROVIDED BY COMPONENT SUPPLIERS AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE OF THE MATERIAL, OR THE HAZARDS CONNECTED WITH SUCH USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE ASSUME NO RESPONSIBILITY FOR THE RESULT OF ITS USE. THIS INFORMATION AND MATERIAL IS FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION AS TO THE SUITABILITY OF THE MATERIAL FOR HIS/HER PARTICULAR PURPOSE AND ON THE CONDITION THAT HE/SHE ASSUME THE RISK OF HIS/HER USE THEREOF.